

Filmfoam^{C6} 911 FP AFFF 1%

Description

Filmfoam^{C6} 911 FP is a superior quality synthetic Aqueous Film-Forming Foam (AFFF) concentrate for extinguishing and securing flammable hydrocarbon liquid fires.

Filmfoam^{C6} 911 FP is a unique combination of hydrocarbon and fluorochemical surface active agents. It produces a vapour-sealing aqueous film that spreads rapidly over the fuel surface to provide rapid control and extinguishment.

- Film-forming for fast flame knockdown and extinguishment.
- Burnback resistance and post-fire security.
- Foam blanket reseals when ruptured by personnel or equipment.

Applications

Filmfoam^{C6} 911 FP is used in high risk situations where hydrocarbons (such as crude oil, diesel and aviation kerosene) are stored, processed, or transported. It is used extensively on Rapid Intervention Vehicles (RIV) where fast extinguishment with limited quantities of foam is essential for saving life. Other applications include hydrocarbon storage tanks, process areas, warehouses, power stations and offshore platforms.

Filmfoam^{C6} 911 FP provides a vapour suppressing foam blanket on unignited hydrocarbon spills.

Approvals and Listings

Filmfoam^{C6} 911 FP is independently tested and certified to EN1568:2008 part 3.

Performance exceeds ICAO Level B fire performance and is certified to this performance level.

Filmfoam^{C6} 911 FP is audited and approved to Underwriters Laboratories UL162 (7th Edition).

Equipment

Filmfoam^{C6} 911 FP is intended for use at 1% (1 part concentrate to 99 parts water). Filmfoam^{C6} 911 FP is readily proportioned using conventional foam proportioning equipment.

Filmfoam^{C6} 911 FP can be used with air aspirating discharge devices and non-aspirating. Devices include low expansion branchpipes, monitors, top pourers, rimseal pourers, as well as water and foam sprinklers. Filmfoam^{C6} 911 FP is also suitable for base injection or sub-surface application systems.

Non-aspirated foam is suitable for shallow fuel fires and spill fires. Where a major fuel fire is involved, Kerr Fire always recommends the use of aspirated foam where a stable foam blanket is essential.

Compatibility

Filmfoam^{C6} 911 FP is suitable for use in combination with:

- Soft or hard, fresh, brackish or sea water.
- Dry powder extinguishing agents either separately or as twin agent systems due to the C6 content.
- Expanded protein-based or synthetic foams for application to a fire in sequence or simultaneously.

Environment

The C6 surfactants balance high performance and low environmental impact. Filmfoam^{C6} 911 FP demonstrates low aquatic toxicity.

C6 Fluorosurfactants

These are the most effective agents currently available to tackle serious flammable liquid fires, providing firefighter safety and asset protection. Kerr foams containing C6 surfactants utilise the very latest in firefighting foam technologies, developed and refined specifically to lower the environmental impact without reducing performance.

Filmfoam^{C6} 911 FP AFFF 1%

Storage

Filmfoam^{C6} 911 FP is exceptionally stable in long-term storage. A shelf-life of at least ten years can be expected if it is stored properly.

Disposal

Please refer to Kerr Fire's Foam Disposal Guide and MSDS for more information.

Product Quality

Filmfoam^{C6} 911 FP production is closely controlled and is audited by UL in accordance with their approval system.

Kerr Fire operates a quality management system which complies with the requirements of BS EN ISO 9001.

Typical Physico-Chemical Properties

Appearance		Amber liquid
Specific gravity @ 20°C (68°F)		1.025 - 1.045
pH @ 20°C (68°F)		6.6 - 7.6
Viscosity @ 20°C (68°F)	mm ² sec ⁻¹	6.0
Viscosity @ 0°C (32°F)	mm ² sec ⁻¹	15.0
Maximum continuous storage temperature	°C (°F)	60 (140)
Effect of freeze/thaw		None
Lowest use temperature	°C (°F)	-17.8 (0)
Sediment as shipped	% v/v	≤ 0.1
Sediment after ageing	% v/v	≤ 0.1

Typical Foam Properties


These vary depending on the performance characteristics of the foam.

When tested in accordance with UK Defence Standard 42-40 it gives the following properties:

Expansion Ratio	≥8:1
25% Drainage Time	≥2 minutes 45 seconds

Typical Packing Specification

	Plastic Square	Plastic Square	Plastic Cylindrical	Plastic Cylindrical	Ecobulk MX
Capacity	25 litres	5 US gallons	200 litres	55 US gallons	1000 litres
Empty weight (kg)	1.2	0.8	9.0	9.0	70
Filled weight (kg)	27	21	217	225	1110
Dimensions (mm)	448 x 286 x 286	402 x 293 x 240	580 D x 922 H	580 D x 922 H	1200 L x 1000 W x 1160 H



EMERGENCY FOAM SERVICE Call +44 (0) 15242 61166 – 24 hours a day, every day

Page 2/2

Kerr Fire

Station Road, Bentham, Lancaster, LA2 7NA, UK

Tel: +44 (0)1524 264037 • Fax: +44 (0)1524 264180 • Email: info@kerrfire.co.uk • Web: www.kerrfire.co.uk

© Kerr Fire. The right is reserved to modify any specification without prior notice. 6745/3 10.16



FM 595473

EMS 576644