

QUALITY IS
MORE THAN WHAT
MEETS THE EYE.

EXPERIENCE
IN EVERY VALVE





Pressed for time?

JUST PRESS, CRIMP AND TRIPLE YOUR PRODUCTIVITY¹.

Reduce installation time up to 68% with Milwaukee Valve's extensive new line of UltraPress press-connection valves. Perfect for potable water, HVAC and inert gas systems, UltraPress valves quickly install without brazing, soldering or special tools. With no open flame required, water service connections can be made wet or dry for faster, easier repairs. Plus, UltraPress eliminates heat-installation costs like solder, flux, propane torches, oxygen/gas bottles and "hot" work permits.

Available in fully annealed brass, bronze and lead-free² UltraPure® alloys—in ball, gate, globe and check styles—you're sure to find the valves you need. Accessories, too, like extension, INSULATOR/MS™ and lockout handles.

See the full line of UltraPress products, additional features, full specifications, and a downloadable brochure at www.UltraPressValves.com.

¹ Estimate based on MCAA's WebLEM (Web-based Labor Estimating Manual).

² Lead content less than 0.25%, defined as lead-free by US Senate Bill S.3874.

© 2016, Milwaukee Valve Company.

ULTRAPRESS



16550 West Stratton Drive • New Berlin, WI 53151
262.432.2700 • Fax 262.432.2701
www.MilwaukeeValve.com • www.UltraPressValves.com



CONTENTS

BALL VALVES SECTION 1, PAGE 4-10

BUTTERFLY VALVES SECTION 2, PAGE 11-13

- C Series Commercial Construction
- M Series Standard Industrial
- UltraPure® Commercial Construction For Potable Water
- H Series High-Pressure
- U Series Low-Pressure
- HP Series High-Performance
- Bronze Butterball® Butterfly

ACTUATION SECTION 3, PAGE 14-15

BRONZE VALVES SECTION 4, PAGE 16-20

- Gate, Page 16-17
- Globe & Angle, Page 18-19
- Check, Page 19-20

CAST STEEL VALVES SECTION 5, PAGE 21

- Gate
- Globe
- Check

IRON VALVES SECTION 6, PAGE 22-23

- Gate & Clip-Gate, Page 21
- Globe, Page 21
- Check Valves, Page 22

FIRE PROTECTION VALVES SECTION 7, PAGE 24-25

ULTRAPURE® LEAD-FREE VALVES FOR POTABLE WATER SERVICE . . SECTION 8, PAGE 26-29

TANK AND TRAILER VALVES SECTION 9, PAGE 30-31

SAMPLER VALVES SECTION 10, PAGE 32

FLOW CONTROL, MEDICAL GAS AND SPECIALTY VALVES SECTION 11, PAGE 32

ENGINEERING & DESIGN CAPABILITIES PAGE 34-35

Rev. 4/19

The information presented on this sheet is correct at time of publication. Milwaukee Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.milwaukeevalve.com. State of California Prop 65 ⚠️ WARNING: Cancer and Reproductive Harm. For more information visit www.p65warnings.ca.gov.

BALL VALVES



BA-100TIH



BA-100 P2



BA-150H

2-PIECE BRONZE

Standard Port

BA-100 / BA-100S

600 WOG 150 SWP, MSS SP-110, Threaded, BA-100S with Stainless Steel Ball and Stem 1/4" thru 3"

BA-100ELD

125 psig, MSS SP-110, Latch Lock Handle, Threaded with Exhaust Port 1/4" thru 2"

BA-100M

600 WOG 150 SWP, MSS SP-110, Male x Female 1/4" thru 2"

BA-100 P2 / BA-100S P2

200 psig @ 250°F, MSS SP-110, Press X Press, BA-100S P2 with Stainless Steel Ball and Stem 1/2" thru 2"

BA-150 / BA-150S

600 WOG 150 SWP, MSS SP-110, Solder, BA-150S with Stainless Steel Ball & Stem 3/8" thru 3"

Full Port

BA-100H

600 WOG, MSS SP-110, Threaded With Hose, Cap and Chain 1/2" and 3/4"

BA-150H

600 WOG, MSS SP-110, Solder With Hose, Cap and Chain 1/2" and 3/4"

BA-100H P1 / BA-100SH P1

200 psig @ 250°F, MSS SP-110, Press X Hose, BA-100SH P1 with Stainless Steel Ball & Stem 1/2" and 3/4"



BA-450



UPBA-100 P2 XH



BA-100 P2 TIH

continued

2-PIECE BRONZE

Full Port

BA-400 / BA-400S

600 WOG 150 SWP, MSS SP-110, Threaded, BA-400S with Stainless Steel Ball & Stem 1/4" thru 2"

BA-400 P2 / BA-400S P2

200 psig @ 250°F, MSS SP-110, Press X Press, BA-400S with Stainless Steel Ball & Stem 1/2" thru 2"

BA-400S3

600 WOG, 250 SWP, MSS SP-110, Stainless Steel Ball & Stem, Threaded, Steam Seats 1/2" thru 2"

BA-450 / BA-450S

600 WOG, 150 SWP, MSS SP-110, Solder, BA-450S with Stainless Steel Ball & Stem 3/8" thru 2"

2-PIECE BRONZE LEAD-FREE BRONZE BALL VALVES FOR POTABLE WATER SERVICE*



Standard Port

UPBA-100 / UPBA-100S

600 WOG, MSS SP-110, Threaded, UPBA-100S with Stainless Steel Ball & Stem 1/4" thru 3"

UPBA-100 P2 / UPBA-100S P2

200 psig @ 250°F, MSS SP-110, Press X Press, UPBA-100S with Stainless Steel Ball and Stem 1/2" thru 3"

Options/Accessories

BA-100/150 / UPBA-100/150
INSULATOR Handle (TIH)
Oval Handle (OH)
Locking Oval Handle (LO)
Stainless-Steel Handle (SH)
Tee Handle (TH)
Locking Handle (LD)
Extension Handle (XH)
Extension Handle w/Memory Stop (XM)
Memory Stop (MS)
Chain Lever (CL)

Options/Accessories

BA-100/150 / UPBA-100/150
BA-400/450 / UPBA-400/450
INSULATOR Handle (TIH)
Oval Handle (OH)
Locking Oval Handle (LO)
Stainless-Steel Handle (SH)
Tee Handle (TH)
Locking Handle (LD)
Extension Handle (XH)
Extension Handle w/Memory Stop (XM)
Memory Stop (MS)
Chain Lever (CL)



UPBA-100H



UPBA-400 P2 TIH



UPBA-450S

Options/Accessories

BA-100/150 / UPBA-100/150
 BA-400/450 / UPBA-400/450
 INSULATOR Handle (TIH)
 Oval Handle (OH)
 Locking Oval Handle (LO)
 Stainless-Steel Handle (SH)
 Tee Handle (TH)
 Locking Handle (LD)
 Extension Handle (XH)
 Extension Handle w/Memory Stop (XM)
 Memory Stop (MS)
 Chain Lever (CL)

continued
**2-PIECE
 BRONZE LEAD-FREE
 BRONZE BALL VALVES
 FOR POTABLE
 WATER SERVICE***

**Standard Port**

UPBA-150 / UPBA-150S
 600 WOG, MSS SP-110, Solder,
 UPBA-150S with Stainless Steel
 Ball & Stem
 3/8" thru 3"

Full Port

UPBA-100H
 600 WOG, MSS SP-110, Threaded
 With Hose, Cap and Chain
 1/2" and 3/4"

UPBA-150H
 600 WOG, Solder with Hose,
 Cap and Chain
 1/2" and 3/4"

UPBA-400 / UPBA-400S
 600 WOG, MSS SP-110, Threaded,
 UPBA-400S with Stainless Steel
 Ball & Stem
 1/4" thru 2"

UPBA-100H P1
 200 psig @ 250°F, MSS SP-110,
 Press X Hose
 1/2" and 3/4"

UPBA-400 P2 / UPBA-400S P2
 200 psig @ 250°F, MSS SP-110,
 Press X Press, UPBA-400S with
 Stainless Steel Ball and Stem
 1/2" thru 2"

UPBA-450 / UPBA-450S
 600 WOG, MSS SP-110, Solder,
 UPBA-450S with Stainless Steel
 Ball & Stem
 1/2" thru 2"



BA-200



BA-475B



BA-480S

Options/Accessories

BA-200/250,
 BA-475B/485B / UPBA-475B/485B
 BA-480B/490B / UPBA-480B/490B
 INSULATOR Handle (TIH)
 (Except BA-200/250)
 Oval Handle (OH)
 Stainless-Steel Handle (SH)
 Tee Handle (TH)
 Extension Handle (XH)
 Extension Handle with Memory Stop (XM)
 Memory Stop (MS)

2-PIECE FORGED BRASS

Standard Port

BA-200
 400 WOG 150 SWP, Threaded
 1/4" thru 4"

BA-250
 400 WOG 150 SWP, Solder
 3/8" thru 3"

Full Port

BA-475B
 600 WOG (1/4" thru 3"), 400 WOG
 (4"), CSA/UL/FM/CGA Approved
 to 2", Threaded
 1/4" thru 4"

BA-485B
 600 WOG (1/2" thru 3"), 400 WOG
 (4"), Heavy Pattern, Solder
 1/2" thru 4"

BA-480B / BA-480S
 200 psig @ 250°F, Press X
 Press, BA-480S with
 Stainless Steel Ball & Stem
 1/2" thru 3"

BA-490B / BA-490S
 200 psig @ 250°F, Press X
 Threaded, BA-490S with
 Stainless Steel Ball & Stem
 1/2" thru 2"

BA-480BH / BA-480SH
 200 psig @ 250°F, Press X Hose,
 BA-480SH with Stainless Steel
 Ball & Stem,
 1/2" thru 3/4"

BA-481B
 200 psig @ 250°F, Press X
 Press, Extension Stem with
 Memory stop,
 1/2" thru 3"

BA-491B
 200 psig @ 250°F, Press X
 Threaded, Extension stem with
 Memory Stop,
 1/2" thru 2"

BALL VALVES



UPBA-475B



UPBA-480



UPBA-481B

Options/Accessories

BA-475B/485B / UPBA-475B/485B
 BA-480B/490B / UPBA-480B/490B
 INSULATOR Handle (TIH)
 (BA-480B/BA-490B only)
 Oval Handle (OH)
 Stainless-Steel Handle (SH)
 Tee Handle (TH)
 Extension Handle (XH)
 Extension Handle with Memory
 Stop (XM)
 Memory Stop (MS)

2-PIECE LEAD-FREE FORGED BRASS BALL VALVES FOR POTABLE WATER SERVICE

Full Port

UPBA-475B *

600 WOG (1/4" thru 2") 400 WOG (2-1/2" thru 3") MSS SP-110, UL/CSA Rated to 2", Threaded 1/4" thru 3"

UPBA-485B *

600 WOG (1/2" thru 2") 400 WOG (2-1/2" thru 3"), MSS SP-110, Solder 1/2" thru 3"

UPBA-480B / UPBA-480S*

200 psig @ 250°F, MSS SP-110, Press X Press, UPBA-480S with Stainless Steel Ball and Stem 1/2" thru 4"

UPBA-480BH / UPBA-480SH *

200 PSIG @ 250°F, Press X Hose, BA-480SH with Stainless Steel Ball & Stem, 1/2" and 3/4"

UPBA-481B / UPBA-481S *

200 psig @ 250°F, MSS SP-110, Press X Press, Extension Stem With Memory Stop, UPBA-481S with Stainless Steel Ball and Stem 1/2" thru 3"

UPBA-490B / UPBA-490S *

200 psig @ 250°F, MSS SP-110, Press X Threaded, UPBA-490S with Stainless Steel Ball and Stem 1/2" thru 2"

UPBA-491B / UPBA-491S *

200 psig @ 250°F, MSS SP-110, Press X Threaded, Extension Stem With Memory Stop, UPBA-491S with Stainless Steel Ball and Stem 1/2" thru 2"



BA-500



BA-300TIH



BA-350TE

Options/Accessories

BA-300/350 / UPBA-300/350
 INSULATOR Handle (TIH)
 Oval Handle (OH)
 Locking Oval Handle (LO)
 Stainless-Steel Handle (SH)
 Tee Handle (TH)
 Locking Handle (LD)
 Extension Handle (XH)
 Extension Handle w/Memory Stop (XM)
 Memory Stop (MS)
 Chain Lever (CL)

2-PIECE BRASS CIRCULATOR-FLANGE

BA-500

600 WOG, 150 SWP, Full Port, Sold in Pkg. of 2, Threaded 3/4" thru 1-1/4"

BA-550

600 WOG, 150 SWP, Full Port, Sold in Pkg. of 2, Solder 3/4" thru 1-1/4"

3-PIECE BRONZE BALL VALVES

Full Port

BA-300 / BA-300S

600 WOG, 150 SWP, MSS SP-110, Threaded, BA-300S with Stainless Steel Ball & Stem 1/4" thru 3" *

BA-300SB / BA-300SBS

600 WOG, 150 SWP Silbrazed, BA-300SBS with Stainless Steel Ball & Stem 3/4" thru 2"

BA-350 / BA-350S

600 WOG, 150 SWP, MSS SP-110, Solder, BA-350S with Stainless Steel Ball and Stem 3/8" thru 3"

BA-300 P2 / BA-300S P2

200 psig @ 250°F, MSS SP-110, Press X Press, BA-300S P2 with Stainless Steel Ball and Stem 1/2" thru 2"

BA-350TE / BA-350STE **

600 WOG, 150 SWP, Solder, BA-350STE with Stainless Steel Ball and Stem, Tube End 1/2" thru 3"



UPBA-350

3-PIECE LEAD-FREE BRONZE BALL VALVES FOR POTABLE WATER



Full Port

UPBA-300 / UPBA-300S

600 WOG, MSS SP-110, Threaded,
UPBA-300S with Stainless Steel
Ball & Stem
1/4" thru 3"

UPBA-350 / UPBA-350S

600 WOG, MSS SP-110, Solder,
UPBA-350S with Stainless Steel
Ball & Stem
3/8" thru 3"

UPBA-300 P2 / UPBA-300S P2

200 psig @ 250°F, MSS SP-110,
Press X Press, UPBA-300S P2
with Stainless Steel Ball & Stem
1/2" thru 2"



F90SS300R-N1



F90CS150R-N1



F91CS150R-N1

UNIBODY, FLANGED-END

Standard Port

F90CS150R-N1

Class 150, TEFLON[®] NXT-75
Seats, Carbon Steel Body,
Stainless Steel Ball & Stem,
Actuator Mounting Pads
1/2" thru 6"

F90CS300R-N1

Class 300, TEFLON[®] NXT-75
Seats, Carbon Steel Body,
Stainless Steel Ball & Stem,
Actuator Mounting Pads
1/2" thru 6"

F90SS150R-N1

Class 150, TEFLON[®] NXT-75
Seats, Stainless Steel Body,
Stainless Steel Ball & Stem,
Actuator Mounting Pads
1/2" thru 6"

F90SS300R-N1

Class 300, TEFLON[®] NXT-75
Seats, Stainless Steel Body,
Stainless Steel Ball & Stem,
Actuator Mounting Pads
1/2" thru 6"

UNIBODY, FLANGED-END, FIRE-SAFE

Standard Port

F91CS150R-N1

Class 150, TEFLON[®] NXT-75
Seats, Carbon Steel Body,
Stainless Steel Ball & Stem,
Fire-Safe to API 607, Actuator
Mounting Pads
1/2" thru 6"

F91CS300R-N1

Class 300, TEFLON[®] NXT-75
Seats, Carbon Steel Body,
Stainless Steel Ball & Stem,
Fire-Safe to API 607, Actuator
Mounting Pads
1/2" thru 6"

Options/Accessories

BA-300/350 / UPBA-300/350

INSULATOR Handle (TIH)
Oval Handle (OH)
Locking Oval Handle (LO)
Stainless-Steel Handle (SH)
Tee Handle (TH)
Locking Handle (LD)
Extension Handle (XH)
Extension Handle w/Memory Stop (XM)
Memory Stop (MS)
Chain Lever (CL)

Options/Accessories

F90/91

Stainless Oval Handle (OS)
Carbon Oval Handle (OH)
Extended Handle (XH)
Extended Locking Handle (XLH)
Gear Operator (GO)
Pneumatic Actuator
Electric Actuator
Assemble Dry (AD)
Chlorine Cleaned (CC)
Oxygen Cleaned (OC)
Grounded Ball (GB)
Vented Ball (VB)

BALL VALVES



F91SS150R-N1



10SSOD-02-LL

continued UNIBODY, FLANGED- END, FIRE-SAFE

Standard Port

F91SS150R-N1

Class 150, TEFLON[®] NXT-75 Seats, Stainless Steel Body, Stainless Steel Ball & Stem, Fire-Safe to API 607, Actuator Mounting Pads 1/2" thru 6"

F91SS300R-N1

Class 300, TEFLON[®] NXT-75 Seats, Stainless Steel Body, Stainless Steel Ball & Stem, Fire-Safe to API 607, Actuator Mounting Pads 1/2" thru 6"



F201CSN2



F201SSN2

2-PIECE, FLANGED- END, FIRE-SAFE

F201CSN2

Class 150, TEFLON[®] NXT-75 Seats, Carbon Steel Body, Stainless Steel Ball & Stem, Full Port, Live Loaded Graphite Packing, Actuator Mounting Pads, Fire-Safe to API 607 1" thru 12"

F203CSN2

Class 300, TEFLON[®] NXT-75 Seats, Carbon Steel Body, Stainless Steel Ball & Stem, Full Port, Live Loaded Graphite Packing, Actuator Mounting Pads, Fire-Safe to API 607 1" thru 12"

F201SSN2

Class 150, TEFLON[®] NXT-75 Seats, Stainless Steel Body, Stainless Steel Ball & Stem, Full Port, Live Loaded Graphite Packing, Actuator Mounting Pads, Fire-Safe to API 607 1" thru 12"

F203SSN2

Class 300, TEFLON[®] NXT-75 Seats, Stainless Steel Body, Stainless Steel Ball & Stem, Full Port, Live Loaded Graphite Packing, Actuator Mounting Pads, Fire-Safe to API 607 1" thru 12"

UNIBODY, THREADED, FIRE-SAFE

Reduced Port

10CSOD-02-LL

2000 WOG, Carbon Steel Body, Stainless Steel Ball & Stem, RPTFE Seats, Fire-Safe to API 607, Threaded 1/4" thru 2"

10SSOD-02-LL

2000 WOG, Stainless Steel Body, Stainless Steel Ball & Stem, RPTFE Seats, Fire-Safe to API 607, Threaded 1/4" thru 2"



BA3WDSLH

Options/Accessories

F91

Stainless Oval Handle (OS)
Carbon Oval Handle (OH)
Extended Handle (XH)
Extended Locking Handle (XLH)
Gear Operator (GO)
Pneumatic Actuator
Electric Actuator
Assemble Dry (AD)
Chlorine Cleaned (CC)
Oxygen Cleaned (OC)
Grounded Ball (GB)
Vented Ball (VB)

Options/Accessories

F20

Lever Handle (2)
Gear Operator (3)
Pneumatic Actuator
Electric Actuator
Assemble Dry (A)
Chlorine Cleaned (C)
Oxygen Cleaned (O)
Vented Ball (V)
Flat-Faced Flange (F)
PTFE Packing (T)

DIVERTER VALVE

Standard Port

BA3WDSLH

1000 WOG, Stainless Steel Body, Stainless Steel Ball & Stem, RPTFE Seats, 3-Way Port Diverter, Threaded Ends 1/4" thru 2"



20BSOR-02



20SSOR-N1



BA-260

Options/Accessories**20 series**

Stainless Oval Handle (OS)
 Stainless Latch Lock Handle (LL)
 Stainless-Steel Spring-Loaded Oval Handle (LO)
 Extended Handle (XH)
 Stainless Spring Latch-Lock Handle (LS)
 Pneumatic Actuator
 Electric Actuator
 Assemble Dry (AD)
 Grounded Ball (GB)
 Grounded Stem (GS)
 Vented Ball (VB)

2-PIECE, THREADED**Standard Port****20BSOR-02**

600 WOG, Bronze Body, Stainless Steel Ball & Stem, RPTFE Seats, Actuator Mounting Pads, Threaded 1/4" thru 2"

20BBOR-02

600 WOG, Bronze Body, Chrome Plated Ball, Bronze Stem, RPTFE Seats, Actuator Mounting Pads, Threaded 1/4" thru 2"

20CSOR-N1

Carbon Steel Body, Stainless Steel Ball & Stem, TEFLON® NXT-75 Seats, Actuator Mounting Pads, Threaded 2000 WOG 1/4" thru 1", 1500 WOG 1-1/4" thru 2"

20SSOR-N1

Stainless Steel Body, Stainless Steel Ball & Stem, TEFLON® NXT-75 Seats, Actuator Mounting Pads, Threaded 2000 WOG 1/4" thru 1", 1500 WOG 1-1/4" thru 2"

Full Port**BA-260**

1000 WOG, Stainless Steel Body and Ball, RPTFE Seats, Locking Handle, Threaded 1/4" thru 3"



41CSOF-02-LL



41SSOF-02-LL



22SSOR-N1

Options/Accessories**22 series**

Stainless Oval Handle (OS)
 Stainless Latch Lock Handle (LL)
 Stainless-Steel Spring-Loaded Oval Handle (LO)
 Extended Handle (XH)
 Stainless Spring Latch-Lock Handle (LS)
 Pneumatic Actuator
 Electric Actuator
 Assemble Dry (AD)
 Grounded Ball (GB)
 Grounded Stem (GS)
 Vented Ball (VB)

41 Series

Stainless Handle (SH)
 Stainless Oval Handle (OS)
 Stainless Latch Lock Handle (LL)
 Carbon-Steel Oval Handle (OH)
 Locking Spring-Return Stainless-Steel Oval Handle (LO)
 Extended Handle (XH)
 Stainless Spring Latch Lock Handle (LS)

HIGH-PRESSURE, SEAL-WELDED, FIRE-SAFE**Full Port****41CSOF-02-LL**

Carbon Steel Body, Stainless Steel Ball & Stem, Available with Socket-Weld, Extended Butt-Weld Ends and 3,000-lb. Configuration (Consult Factory), Actuator Mounting Pads, Threaded Class 900 1/2" thru 1-1/2" Class 600 2"

41SSOF-02-LL

Stainless Steel Body, Stainless Steel Ball & Stem, Available with Socket-Weld, Extended Butt-Weld Ends and 3,000-lb. Configuration (Consult Factory), Actuator Mounting Pads, Threaded Class 900 1/2" thru 1-1/2" Class 600 2"

2-PIECE, SEAL-WELDED**Standard Port****22CSOR-N1**

Carbon Steel Body, Stainless Steel Ball & Stem, TEFLON® NXT-75 Seats, Actuator Mounting Pads, Threaded 2000 WOG 1/4" thru 1", 1500 WOG 1-1/4" thru 2"

22SSOR-N1

Stainless Steel Body, Stainless Steel Ball & Stem, TEFLON® NXT-75 Seats, Actuator Mounting Pads, Threaded 2000 WOG 1/4" thru 1", 1500 WOG 1-1/4" thru 2"

BALL VALVES



30SSOF-02



30BSOF-02



30CSOF-02



30SSOF-02-LO

Options/Accessories

30 Series

- Stainless Latch Lock Handle (LL)
- Locking Stainless-Steel Oval Handle (LO)
- Stainless-Steel Latch Lock Spring-Loaded Handle (LS)
- Stainless-Steel Oval Handle (OS)
- Extended Handle 2" (XH)
- Extended Handle 4 1/2" (XLH)
- Extended Handle (XH)
- Pneumatic Actuator
- Electric Actuator
- Assemble Dry (AD)
- Grounded Ball (GB)
- Grounded Stem (GS)
- Vented Ball (VB)

3-PIECE, THREADED

Full Port

30BBOF-02

600 WOG, Bronze Body, Chrome Plated Ball & Stem, RPTFE Seats, PTFE V-Ring Packing, Threaded, Available with Solder, Actuator Mounting Pads 1/4" thru 2"

30BSOF-02

600 WOG, Bronze Body, Stainless Steel Ball & Stem, RPTFE Seats, PTFE V-Ring Packing, Actuator Mounting Pads, Threaded, Available with Solder 1/4" thru 2"

30CSOF-02

1000 WOG, Carbon Steel Body, Stainless Steel Ball & Stem, RPTFE Seats, PTFE V-Ring Packing, Actuator Mounting Pads, Threaded, Available with Socket-Weld 1/4" thru 2"

30SSOF-02

1000 WOG, Stainless Steel Body, Stainless Steel Ball & Stem, RPTFE Seats, PTFE V-Ring Packing, Actuator Mounting Pads, Threaded, Available with Socket-Weld 1/4" thru 2"



35RCSO-LL



35RCSO-LL

3-PIECE, ENCLOSED-BOLT, FIRE-SAFE

Standard Port

35RCSO-LL

2000 WOG, Carbon Steel Body, Stainless Steel Ball & Stem, TEFLON® NXT-75 Seats, Fire-Safe to API 607, Live Loaded Graphite Packing, Actuator Mounting Pads, Threaded, Available with Socket-Weld 1/4" thru 2"

35RSSO-LL

2000 WOG, Stainless Steel Body, Stainless Steel Ball & Stem, Live Loaded Flexible Graphite Packing, TEFLON® NXT-75 Seats, Fire-Safe to API 607, Actuator Mounting Pads, Threaded, Available with Socket-Weld 1/4" thru 2"

Full Port

35FCSO-LL

2000 WOG, Carbon Steel Body, Stainless Steel Ball & Stem, TEFLON® NXT-75 Seats, Fire-Safe to API 607, Live Loaded Graphite Packing, Actuator Mounting Pads, Threaded, Available with Socket-Weld 1/4" thru 2"

35FSSO-LL

2000 WOG, Stainless Steel Body, Stainless Steel Ball & Stem, TEFLON® NXT-75 Seats, Fire-Safe to API 607, Live Loaded Graphite Packing, Actuator Mounting Pads, Threaded, Available with Socket-Weld 1/4" thru 2"

Options/Accessories

35 series

- Latch Lock Handle (LL)
- Locking Stainless-Steel Oval Handle (LO)
- Extended Handle (XH)
- Pneumatic Actuator
- Electric Actuator
- Assemble Dry (A)
- Chlorine Cleaned (Stainless Only) (C)
- Oxygen Cleaned (O)



CL323E



CW323E

C SERIES — COMMERCIAL BUTTERFLY

Concentric valve to MSS SP-67, Available in lug or wafer body. CL Series IAPMO tested and certified against NSF/ANSI 372 for lead-free* compliance. Body: Cast Iron ASTM A126 Class B
Disc: ALBr (Aluminum Bronze)
Stem: 416 Stainless Steel
Liner: EPDM
2" thru 12" rated at 200 WOG
14" thru 48" rated at 150 WOG

These valves are based on our M Series, but intended for commercial applications in HVAC and similar systems. The valves feature a phenolic-backed rubber seat with optimized disc and stem design for reliable sealing, low torque, and long life. C Series valves from 2" thru 12" are approved by the U.S. Coast Guard for Category A service. Lug butterfly valves 2" thru 12" are bi-directional dead-end service to 200 psig max. Valves 14" thru 24" are rated for uni-directional dead-end service to 150 psig. The valves are available with 10-position locking-lever handles (up to 12 inch) and gear operators.



MW323E



ML323E



ML223E

M SERIES — INDUSTRIAL BUTTERFLY*

Concentric valve to MSS SP-67, Available in lug or wafer body. Disc: Ni-plated Ductile Iron, ALBr, or Stainless Steel, nylon and epoxy-coated optional. Stem: 416 or 316 Stainless Steel. Liner: EPDM, Buna, FDA Neoprene, PTFE, Hypalon, and many other options. Body: Cast iron ASTM A126 Class B or Ductile Iron ASTM A536 65-45-12
2" thru 12" rated at 200 WOG
14" thru 48" rated at 150 WOG

These valves feature a phenolic-backed rubber seat with optimized disc and stem design for reliable sealing, low torque, and long life. 2" thru 12" are approved by the U.S. Coast Guard for Category A service. Lug butterfly valves 2" thru 12" are bi-directional dead-end service to 200 psig max. BUNA and EPDM only. All others 150 psig uni-directional field repairable. Valves 14" thru 24" rated for uni-directional dead-end service to 150 psig. The valves are available with on-board actuation direct from the factory, 10 position locking lever handles (up to 12 inch), gear operators, or other options — consult the factory.

- Available in Low Lead
ML133E/233E/333E
2" thru 12"
ML133E/333E
14" thru 24"

BUTTERFLY VALVES



ML133E/233E/333E



LEAD-FREE COMMERCIAL BUTTERFLY

ML133E/233E/333E

Cast Iron Body, Lug Style, Aluminum Bronze Disc, EPDM Liner, Bi-Directional Dead-End Service 200 psig Max, IAPMO Tested and certified against NSF/ANSI 372 for "Lead-free" compliance. 2" thru 12"

ML133E/333E

Cast Iron Body, Lug Style, Aluminum Bronze Disc, EPDM Liner, Bi-Directional Dead-End Service 200 psig Max 2" thru 12", Uni-Directional Dead-End Service 150 psig Max, 14" thru 24", IAPMO Tested and certified against NSF/ANSI 372 for "Lead-free" compliance.

CL Series

Cast Iron Body, Lug Style, Aluminum Bronze Disc, EPDM Liner, Bi-Directional Dead-End Service 200 psig Max 2" thru 12", Uni-Directional Dead-End Service 150 psig Max, 14" thru 24", IAPMO Tested and certified against NSF/ANSI 372 for "Lead-free" compliance.



CL323E



HPILCS WITH LEVER HANDLE



HPILCS WITH GEAR OPERATOR



HPILSS WITH GEAR OPERATOR

HP SERIES HIGH PERFORMANCE BUTTERFLY

Double offset valve designed to MSS SP-68, ASME B16.34, and API 609, Category B. Available in lug or wafer body, ANSI Class 150 and 300 in sizes 2-1/2" thru 36"

Body: A216 WCB carbon steel or ASTM A351 CF8M Stainless Steel
Disc: ASTM A351 CF8M Stainless Steel
Stem: 17-4PH or 316 Stainless Steel
Seats: RTFE standard, Virgin PTFE, UHMWPE and other options.

These valves feature a double offset seat and disc design for superior sealing with no leakage and minimal seat contact and wear. The valves are available with on-board actuation direct from the factory, 10 position locking lever handles (up to 8 inch), gear operators on all valves, for other actuation options or accessories, consult the factory.



HL123E

H SERIES — HIGH-PRESSURE INDUSTRIAL BUTTERFLY

Concentric valve to MSS SP-67,
Available in lug or wafer body.

Body: Ductile iron ASTM A536
65-45-12

Disc: Ni Plated DI, AlBr, or
Stainless Steel.

Stem: 416 or 316 Stainless Steel
Liner: EPDM, Buna, Viton.

2" thru 12" rated at 250 WOG
14" thru 24" rated at 200 WOG

The H Series is tested and rated
for higher-pressure services.

H Series Valves from 2" thru 12"
are approved by the U.S. Coast
Guard for Category A service.

Lug butterfly valves 2" thru 12"
are uni-directional dead-end
service to 200 psig max. BUNA
and EPDM only. Valves 14" thru
24" are rated for uni-directional
dead end service to 150 psig.



HL323E



UL123E

U SERIES — LOW-PRESSURE BUTTERFLY

Concentric Valve to MSS SP-67,
Available in lug or wafer body
2" thru 12" rated at 50 WOG

The U Series is a low pressure
version of our M Series valve,
with a reduced interference seat
to reduce torque. These valves
are available with a special low
friction coating on the liner as
an option to further reduce
torque and wear in dry bulk
services. The valves are available
with on-board actuation direct
from the factory, 10 position
locking lever handles (up to 12
inch), gear operators, or other
options — consult the factory.



BB2-100



BB2-350

BRONZE BUTTERBALL® BUTTERFLY

BB2-100

175 psig, Threaded
1/4" thru 2" (1/2" thru 2" UL/CSA)

BB2-350

175 psig, Solder
3/8" thru 2"

BB1-10A0

175 psig, Threaded, Actuator
Mounting Pads
1" thru 2"



35 SERIES BALL VALVE WITH PNEUMATIC ACTUATOR



F20 SERIES BALL VALVE WITH PNEUMATIC ACTUATOR WITH LIMIT SWITCH

PNEUMATIC ACTUATION

2-Piece Ball Valves

Available on Threaded-End Valves. Available on Bronze, Carbon-Steel and Stainless-Steel Valves. Available on 1/2" thru 2" Valves.

3-Piece Ball Valves

Available on Threaded-End and Socket-Weld-End Valves. Available on Bronze, Carbon-Steel and Stainless-Steel Valves. Available on 1/2" thru 2" Valves.

Flanged-End Ball Valves

Available on 150 and 300 lbs. Class Valves. Available on 1/2" thru 12" Valves.

PNEUMATIC BALL VALVE PACKAGE

2-Piece Full Port Stainless Steel Ball Valve

with stainless ball and stem. 1000 psig rated @ 100° F Temperature Range: -20° to 450° F 50 psi SWP for on/off service Factory Assembled and tested Available on 1/4" to 3" valves.

BA260LDA

Spring Return (fail closed) actuator sized for 80 psi air supply 120V three-way Nema 4/4X NAMUR mounted solenoid.

BA260LDB

Double -acting actuator sized for 80 psi air supply 120V four-way Nema 4/4X NAMUR mounted solenoid.-



ML SERIES BUTTERFLY VALVE WITH PNEUMATIC ACTUATOR



HP SERIES LUG BUTTERFLY VALVE WITH PNEUMATIC ACTUATOR

continued PNEUMATIC ACTUATION

Butterfly Valves

Available on HP Series High-Performance Butterfly Available in Wafer and Lugged Patterns. Available on 2" thru 48" Valves. Available on Class 150 2-1/2" thru 36". Available on Class 300 2-1/2" thru 36". Available on C and M Series Butterfly Valves. Available on Wafer and Lugged Patterns. Available on 2" thru 48".

PNEUMATIC BUTTERFLY PACKAGE

Cast Iron Lug Butterfly

200 WOG with Aluminum Bronze Disc and EPDM Liner for on/off service. Temperature Range: 0° to 250° F for HVAC Service Factory assembled and tested Available on 2" to 12" valves.

CLA23E

Double-acting actuator sized for 80 psi air supply. 120V four-way Nema 4/4x Namur mounted solenoid.

CLB23E

Spring return fail closed actuator. 120V three-way Nema 4/4x Namur mounted solenoid.

Pneumatic Actuation and Ball Valve Package Options

- Double-Acting Actuators
- Spring-Return Actuators
- Solenoid Valves
- Actuator Brackets
- Limit Switches
- Valve Positioners
- Modulating Positioners



BA-260 BALL VALVE WITH
ELECTRIC ACTUATOR



35 SERIES BALL VALVE WITH
ELECTRIC ACTUATOR

ELECTRIC ACTUATION

2-Piece Ball Valves

Available on Threaded-End Valves.
Available on Bronze,
Carbon-Steel and Stainless-
Steel Valves.
Available on 1/2" thru 2" Valves.

3-Piece Ball Valves

Available on Threaded-End
and Socket-Weld-End Valves.
Available on Bronze,
Carbon-Steel and Stainless-
Steel Valves.
Available on 1/2" thru 2" Valves.

Flanged-End Ball Valves

Available on 150 and 300 lbs. Class
Valves
Available on 1/2" thru 12" Valves

ELECTRIC BALL VALVE PACKAGE

2-Piece Full Port Stainless Ball Valve

with stainless ball and stem.
1000 psig rated @ 100° F
Temperature Range: -20° to 450° F
50 psi SWP for on/off service
Factory Assembled and tested
Available on 1/4" to 3" valves.

BA260LDC

120VAC Nema 4 rated electric
actuator
25% duty cycle with 2 limit switches/
remote light indicator,
Manual override, visual position
indicator.



CL SERIES BUTTERFLY VALVE WITH
ELECTRIC ACTUATOR



HP SERIES LUG BUTTERFLY VALVE
WITH ELECTRIC ACTUATOR

continued ELECTRIC ACTUATION

Butterfly Valves

Available on C and M Series Iron
Butterfly Valves and HP Series
High-Performance Butterfly
Valves.
Available in Wafer and Lugged
Patterns.
Available on 2" thru 48" valves.
Available on Class 150 2-1/2" thru
36".
Available on Class 300 2-1/2" thru
36".
Available on C and M Series
Butterfly Valves.
Available on Wafer and Lugged
Patterns.
Available on 2" to 48" valves

ELECTRIC BUTTERFLY VALVE PACKAGE

Cast Iron Lug Butterfly

200 WOG with Aluminum Bronze
Disc and EPDM Liner for on/off
service.
120V four-way Nema 4/4x Namur
mounted solenoid.
Temperature Range: 0° to 250° F
for HVAC Service
Factory Assembled and tested
Available on 2" to 12" valves.

CLC23E

120VAC Nema 4 rated electric
actuator
25% duty cycle with 2 limit
switches
Manual override and visual
position indicator.

**Electric Actuation and Butterfly
Valve Package Options**
120 Volt AC and DC Voltages
NEMA 4 and 7 Housings
4-20 maDC Valve Positioners
Actuator Brackets
Extra Limit Switches
Reversing Actuators
Limit Switches
Modulating Positioners

BRONZE VALVES



105

BRONZE GATE VALVES, NON-RISING STEM

Threaded End

105
125 SWP-200 WOG, MSS SP-80,
Threaded Bonnet
1/4" thru 4"

1140
150 SWP-300 WOG, MSS SP-80,
Threaded Bonnet
1/4" thru 4"

1141
150 SWP-300 WOG, MSS SP-80,
Union Bonnet
1/4" thru 2"

1176
200 SWP-400 WOG,
Stainless-Steel Seats,
MSS SP-80, Union Bonnet
1/4" thru 2"

1186
300 SWP-1000 WOG,
Stainless-Steel Seats,
MSS SP-80, Union Bonnet
1/4" thru 2"

UP105 *
UltraPure Lead Free Bronze,
Threaded, 300 WOG, MSS SP-80,
Threaded Bonnet
1/4" thru 2"

UP667 *
UltraPure Lead Free Brass,
Threaded, 200 WOG, Threaded
Bonnet
1/4" thru 2"

Solder End

115
125 SWP-200 WOG, MSS SP-80,
Threaded Bonnet
3/8" thru 4"



UP115

UP115 *
UltraPure Lead-Free Bronze, 300
WOG, MSS SP-80, Threaded Bonnet
3/8" thru 2"

UP668 *
UltraPure Lead-Free Brass, Solder,
200 WOG, Threaded Bonnet
1/4" thru 2"

Press x
Press Ends



105 P2
200 psig @ 250°F,
MSS SP-80, Threaded Bonnet
1/2" thru 2"

1141 P2
200 psig @ 250°F,
MSS SP-80, Union Bonnet
1/2" thru 2"

UP105 P2 *
UltraPure Lead-Free Bronze,
200 psig @ 250°F,
MSS SP-80, Threaded Bonnet
1/2" thru 2"



115



105 P2



1186



148

BRONZE GATE VALVES, RISING STEM

Threaded End

148
125 SWP-200 WOG,
MSS SP-80, Threaded Bonnet
1/4" thru 4"

1150
150 SWP-300 WOG,
MSS SP-80, Threaded Bonnet
1/4" thru 4"

Press x
Press Ends



148 P2
125 SWP-200 psig @ 250°F,
MSS SP-80, Threaded Bonnet
1/2" thru 2"



UP667



148 P2



UP 148

continued
**BRONZE GATE
 VALVES, RISING STEM**

Threaded End

UP148 *

UltraPure Lead-Free Bronze,
 300 WOG, MSS SP-80,
 Threaded Bonnet
 1/4" thru 2"

1152

125 SWP-200 WOG,
 MSS SP-80, Union Bonnet
 1/4" thru 3"

1151

150 SWP-300 WOG, MSS SP-80,
 Union Bonnet
 1/4" thru 3"

1153

200 SWP-400 WOG, Bronze
 Seats, MSS SP-80, Union Bonnet
 1/4" thru 3"

1156

200 SWP-400 WOG, Cu-Ni Seat
 Ring, MSS SP-80, Union Bonnet
 1/4" thru 2"

1174

200 SWP-400 WOG, Stainless-
 Steel Seat Ring, MSS SP-80,
 Union Bonnet
 1/4" thru 3"

1182

300 SWP-1000 WOG, Cu-Ni Seat
 Ring, MSS SP-80, Union Bonnet
 1/4" thru 2"

1184

300 SWP-1000 WOG,
 Stainless-Steel Seat Ring,
 MSS SP-80, Union Bonnet
 1/4" thru 3"

Solder End

149

125 SWP-200 WOG, MSS SP-80,
 Threaded Bonnet
 3/8" thru 4"



1169

continued
**BRONZE GATE
 VALVES, RISING STEM**

Solder End

1169

150 SWP-300 WOG,
 MSS SP-80, Union Bonnet
 3/8" thru 3"

UP149 *

UltraPure Lead-Free Bronze,
 300 WOG, MSS SP-80,
 Threaded Bonnet
 3/8" thru 2"

Press x Press Ends

148 P2

200 psig @ 250°F,
 MSS SP-80, Threaded Bonnet
 1/2" thru 2"



1152 P2

200 psig @ 250°F,
 MSS SP-80, Union Bonnet
 1/2" thru 2"

UP148 P2 *

UltraPure Lead-Free Bronze,
 200 psig @ 250°F, MSS SP-80,
 Threaded Bonnet
 1/2" thru 2"

**QUICK-OPENING
 GATE VALVES**

Threaded Ends

P900

150 WSP-300 WOG, Spring-
 Loaded Handle
 1" thru 3"

P901

150 WSP-300 WOG, Quick-Open
 Lever Handle
 1/2" thru 4"

902

150 WOG O-Ring Seal,
 Quick-Open Lever with Springs
 3/4" and 1-1/4"



1174



149



UP149



UP148 P2



P901



502



570



593A

BRONZE GLOBE VALVES

Threaded Ends

502
125 SWP-200 WOG, MSS SP-80,
Bronze Disc, Threaded Bonnet
1/8" thru 3"

600
200 SWP-400 WOG, MSS SP-80,
Needle Disc, Threaded Bonnet
1/8" thru 3/4"

590T
150 SWP-300 WOG, MSS SP-80,
PTFE Disc, Union Bonnet
1/8" thru 3"

591A
150 SWP-300 WOG, MSS SP-80,
SS Seat & Disc, Union Bonnet
1/4" thru 2"

570
200 SWP-400 WOG, MSS SP-80,
Bronze Disc, Union Bonnet
1/8" thru 3"

572
300 SWP-1000 WOG, MSS SP-80,
Bronze Disc, Union Bonnet
1/4" thru 2"

592A
200 SWP-400 WOG, MSS SP-80,
SS Seat & Disc, Union Bonnet
1/4" thru 2"

593A
300 SWP-1000 WOG, MSS SP-80,
SS Seat & Disc, Union Bonnet
1/4" thru 2"

UP502 *
UltraPure Lead-Free Bronze,
300 WOG, MSS SP-80, Bronze
Disc, Threaded Bonnet
1/8" thru 2"



1590T



UP1502



502 P2

continued BRONZE GLOBE VALVES

Solder Ends

1502
125 SWP-200 WOG, MSS SP-80,
Bronze Disc, Threaded Bonnet
3/8" thru 2"

1590T
150 SWP-300 WOG, MSS SP-80,
PTFE Disc, Union Bonnet
1/2" thru 3"

UP1502 *
UltraPure Lead-Free Bronze,
300 WOG, MSS SP-80,
Bronze Disc, Threaded Bonnet
3/8" thru 2"

Press x 
Press Ends

502 P2
200 psig @ 250°F, MSS SP-80,
Bronze Disc, Threaded Bonnet
1/2" thru 2"

590T P2
200 psig @ 250°F, MSS SP-80,
PTFE Disc, Union Bonnet
1/2" thru 2"

UP502 P2 *
UltraPure Lead-Free Bronze,
200 psig @ 250°F, MSS SP-80,
Bronze Disc, Threaded Bonnet
1/2" thru 2"



504

BRONZE ANGLE VALVES

Threaded Ends

504
125 SWP-200 WOG, MSS SP-80,
Bronze Disc, Threaded Bonnet
1/4" thru 2-1/2"

582
300 SWP-600 WOG, MSS SP-80,
Bronze Disc, Union Bonnet
1/4" thru 2"

595T
150 SWP-300 WOG, MSS SP-80,
PTFE Disc, Union Bonnet
1/4" thru 2"



595T

BRONZE CHECK VALVES HORIZONTAL SWING CHECK

Threaded Ends

509
Bronze, 125 SWP-200
WOG, MSS SP-80, Brass Disc
(1/4" - 1-1/2"), Bronze Disc (2" - 3")
1/4" thru 3"

509T
Bronze, 125 SWP-200 WOG,
MSS SP-80, PTFE Disc
1/4" thru 2"

510T
Bronze, 150 SWP-300 WOG,
MSS SP-80, PTFE Disc
1/4" thru 2"

515
Bronze, 150 SWP-300 WOG,
MSS SP-80, Bronze Disc
1/4" thru 2"

UP509 *
UltraPure Lead-Free Bronze, 300
WOG (1/4" thru 2"), 200 WOG
(2-1/2" thru 3"), MSS SP-80,
Bronze Disc, Threaded
1/4" thru 3"



509T



1509



969



UP509 P2

continued

BRONZE CHECK VALVES HORIZONTAL SWING CHECK

UP967 *
UltraPure Lead Free Brass,
Brass Disc, 200 WOG
3/8" thru 3"

Solder Ends

1509
Bronze, 125 SWP-200 WOG,
MSS SP-80, Bronze Disc
3/8" thru 3"

1509T
Bronze, 125 SWP-200 WOG,
MSS SP-80, PTFE Disc
3/8" thru 2"

1510T
Bronze, 150 SWP-300 WOG,
MSS SP-80, PTFE Disc
(Also available w/Bronze Disc)
1/2" thru 2"

UP1509 *
UltraPure Lead-Free Bronze,
300 WOG, MSS SP-80, Bronze Disc
3/8" thru 3"

UP968 *
UltraPure Lead-Free Brass,
200 WOG, Brass Disc
3/8" thru 3"

Press x Press Ends

509 P2 
Bronze, 200 psig @ 250°F, MSS
SP-80, Brass Disc
1/2" thru 2"

969
Brass, 200 psig @ 250°F, Brass
Disc, Integral Seat
1/2" thru 2"

UP509 P2 *
UltraPure Lead-Free Bronze, 200 psig
@ 250°F, Brass Disc, MSS SP-80
1/2" thru 2"

BRONZE VALVES



UP969

continued
BRONZE CHECK VALVES HORIZONTAL SWING CHECK

UP969 *
 UltraPure Lead-Free Brass,
 Brass Disc, 200 psig @ 250°F
 1/2" thru 2"



509Y

HORIZONTAL SWING CHECK – Y PATTERN

Threaded Ends

507
 Bronze, 300 SWP-600 WOG,
 MSS SP-80, Bronze Disc
 1/4" thru 3"

508
 Bronze, 200 SWP-400 WOG,
 MSS SP-80, Bronze Disc
 1/4" thru 3"

509Y
 Bronze, 125 SWP-200 WOG,
 MSS SP-80, Bronze Disc
 1/4" thru 3"

515Y
 Bronze, 150 SWP-300 WOG,
 MSS SP-80, Bronze Disc
 1/4" thru 3"

Press x 
Press Ends

509Y P2
 Bronze, 200 psig @ 250°F, MSS
 SP-80, Bronze Disc
 1/2" thru 2"



UP548T

SPRING-LOADED LIFT CHECK

Threaded Ends

548B
 Bronze, 250 WOG, MSS SP-80,
 BUNA Disc
 3/8" thru 2"

548T
 Bronze, 250 WOG, MSS SP-80,
 PTFE Disc
 3/8" thru 2"

UP548T *
 UltraPure Lead-Free Bronze,
 PTFE Disc, 250 WOG, MSS SP-80
 3/8" thru 2"



1548T

Solder Ends

1548T
 Bronze, 250 WOG, MSS SP-80,
 PTFE Disc
 3/8" thru 2"

1548B
 Bronze, 250 WOG, MSS SP-80,
 BUNA Disc
 3/8" thru 2"



UP548T P2

UP1548T *
 UltraPure Lead-Free Bronze,
 PTFE Disc, 250 WOG, MSS SP-80
 3/8" thru 2"

Press Ends 

548B P2
 Bronze, 200 psig @ 250°F,
 MSS SP-80, Buna Disc
 1/2" thru 2"

548T P2
 Bronze, 200 psig @ 250°F,
 MSS SP-80, PTFE Disc
 1/2" thru 2"

UP548T P2 *
 UltraPure Lead-Free Bronze,
 200 psig @ 250°F, PTFE Disc,
 MSS SP-80
 1/2" thru 2"



1550

CAST STEEL GATE

1550CB2
 Class 150, Flanged, API 600,
 ASME B16.34 Design, API 598
 Tested, Available in Butt-weld,
 Consult Factory.
 2" thru 24"

3050CB2
 Class 300, Flanged, API 600,
 ASME B16.34 Design, API 598
 Tested, Available in Butt-weld,
 Consult Factory.
 2" thru 24"

6050CB2
 Class 600, Flanged, API 600,
 ASME B16.34 Design, API 598
 Tested, Available in Butt-weld,
 Consult Factory.
 2" thru 12"



1560

CAST STEEL GLOBE

1560CB2
 Class 150, Flanged, API 600,
 ASME B16.34 Design, API 598
 Tested, Available in Butt-weld,
 Consult Factory.
 2" thru 12"

3060CB2
 Class 300, Flanged, API 600,
 ASME B16.34 Design, API 598
 Tested, Available in Butt-Weld,
 Consult Factory.
 2" thru 10"

6060CB2
 Class 600, Flanged, API 600,
 ASME B16.34 Design, API 598
 Tested, Available in Butt-Weld,
 Consult Factory.
 2" thru 8"



1570

CAST STEEL CHECK

1570CB2
 Class 150, Flanged, API 600,
 ASME B16.34 Design, API 598
 Tested, Available in Butt-Weld,
 Consult Factory.
 2" thru 24"

3070CB2
 Class 300, Flanged, API 600,
 ASME B16.34 Design, API 598
 Tested, Available in Butt-Weld,
 Consult Factory.
 2" thru 12"

6070CB2
 Class 600, Flanged, API 600,
 ASME B16.34 Design, API 598
 Tested, Available in Butt-Weld,
 Consult Factory.
 2" thru 12"



F2882M

IRON GATE

2882A or 2882M

125 SWP 200 WOG, Non-Rising Stem, IBBM, MSS SP-70
A Available 2" thru 12"
M Available 2" thru 24"

2882A26 or 2882M26

125 SWP 200 WOG, Non-Rising Stem, All Iron, MSS SP-70
A Available 2" thru 12"
M Available 2" thru 24"

2885A or 2885M

125 SWP 200 WOG, OS & Y, IBBM, MSS SP-70
A Available 2" thru 12"
M Available 2" thru 24"

2885M26*

125 SWP 200 WOG, OS & Y, All Iron, MSS SP-70
M Available 2" thru 12"

UP2885A or UP2885M

UltraPure Lead-Free Iron
125 SWP 200 WOG, OS & Y, All Iron, MSS SP-70
A Available 2" thru 12"
M Available 2" thru 12"

2885M13

3% Nickel Iron, OS & Y, Iron Body, SS Trim, MSS SP-70
2" thru 12"

2894A or 2894M

250 WSP 500 WOG, OS & Y, IBBM, MSS SP-70
A Available 2" thru 12"
M Available 2" thru 12"



2887M

IRON CLIP GATE

2887M

150 SWP 225 WOG, Bronze Trim, Threaded
1/4" thru 2"
125 SWP 175 WOG, Bronze Trim, Threaded
2" thru 4"

2888M

150 SWP 225 WOG, All Iron, Threaded
1/4" thru 2"
125 SWP 175 WOG, All Iron, Threaded
2-1/2" thru 4"



2894M



2981A

IRON GLOBE

2981A or 2981M

125 SWP 200 WOG, MSS SP-85
A Available 2" thru 10"
M Available 2" thru 10"

2983A or 2983M

250 SWP 500 WOG, IBBM, MSS SP-85
A Available 2-1/2" thru 6"
M Available 2-1/2" thru 6"

2986M

Angle Globe, 125 SWP, 200 WOG, MSS SP-85
2" thru 8"

2986M-SC

Angle Stop Check, Globe Style, 125 SWP, 200 WOG, MSS SP-85
2" thru 8"



2974M

IRON CHECK

2974A or 2974M

125 SWP 200 WOG, IBBM, MSS SP-71

A Available 2" thru 12"
M Available 2" thru 24"

2974MLW

125 SWP 200 WOG, IBBM, MSS SP-71, Lever and Weight, 2" thru 12"

2974A26 or 2974M26*

125 SWP 200 WOG, All Iron, A Available 2" thru 12"
M Available 2" thru 24"

UP2974A or UP2974M

UltraPure Lead-Free Iron
125 SWP 200 WOG, All Iron, A Available 2" thru 12"
M Available 2" thru 24"

2974M13

3% Nickel Iron, 125 SWP, 200 WOG Iron Body, Stainless-Steel Trim, MSS SP-71
2" thru 12"

2970M

250 SWP 500 WOG, IBBM, MSS SP-71
2-1/2" thru 6"



2974MLW



2970



1400



1800

SILENT CHECK

1400

Class 125, Wafer-Style Cast-Iron Body, Stainless-Steel Disc, Stainless-Steel Spring, Meets Senate Law S3874
2" thru 10"
(Also Available Class 250)

1800

Class 125, Globe-Style Cast-Iron Body, Stainless-Steel Disc, Stainless-Steel Spring, Meets Senate Law S3874
2-1/2" thru 42"
(Also Available Class 250)

NON-SLAM CHECK

8800

Class 125, Wafer-Style Cast-Iron Body, Stainless-Steel Double Disc
2" thru 16"



UPBBTSCS02



LEAD-FREE BRONZE SLO-CLOSE SPRINKLER-CONTROL VALVE INDOOR/ OUTDOOR*

UPBBTSC

175 psig, UL/FM, Slo-Close with Position Indicator, IAPMO Tested and Certified, Less Tamper Switch, NPT-Threaded Ends 1" - 2"

UPBBTSCS02

NPT-Threaded Ends, 175 psig, UL/FM, Slo-Close with Position Indicator, Tamper Switch 1" thru 2"



BBVSC100

SLO-CLOSE SPRINKLER-CONTROL VALVE INDOOR/ OUTDOOR

BB-SC100

175 psig, UL/FM, Slo-Close w/Position Indicator, Less Tamper Switch, Indoor/Outdoor, Threaded 1" thru 2-1/2"

BB-SCS02

175 psig, UL/FM, Slo-Close w/Position Indicator, With Tamper Switch, Indoor/Outdoor, Threaded 1" thru 2-1/2"

BBVSC100

175 psig, UL/FM, Slo-Close w/Position Indicator, Less Tamper Switch, Indoor/Outdoor, Grooved 2" and 2-1/2"

BBVSCS02

175 psig, UL/FM, Slo-Close w/Position Indicator, With Tamper Switch, Indoor/Outdoor, Grooved 2" and 2-1/2"



2885-FP

IRON GATE

2885-FP
OS & Y Bronze Trim, 175 WOG
UL/FM
2-1/2" thru 8"

IRON CHECK VALVE

2974-FP
175 WOG, UL/FM, Rubber Disc
2-1/2" thru 8"



2974-FP



118-FP

BRONZE GATE VALVE WITH UL/FM TRIM

118-FP
OS & Y, UL/FM, NPT Threaded
1" thru 2"

HIGH-RISE SPRINKLER-CONTROL VALVE

BBHSC100
350 psig, Less Tamper Switch,
Threaded
1" thru 2-1/2"

BBHSC02
350 psig, With Tamper Switch,
Threaded
1" thru 2-1/2"

BVHSC100
350 psig, Less Tamper Switch,
Grooved
2" and 2-1/2"

BVHSC02
350 psig, With Tamper Switch,
Grooved
2" and 2-1/2"



BBHSC02



BB2FP

BUTTERBALL TRIM VALVES UL/FM

BB2FP
175 psig, Quarter Turn, UL-Listed,
FM-Approved,
NPT Threaded Ends
1/2" thru 2"



LEAD-FREE* VALVES FOR POTABLE WATER SERVICE



UPBA-100TIH



UPBA-150H

2-PIECE LEAD-FREE BRONZE BALL VALVES

Standard Port

UPBA-100 / UPBA-100S *

600 WOG, MSS SP-110, Threaded, UPBA-100S with Stainless Steel Ball & Stem
1/4" thru 3"

UPBA-150 / UPBA-150S *

600 WOG, MSS SP-110, Solder, UPBA-150S with Stainless Steel Ball & Stem
3/8" thru 3"

UPBA-100 P2 / UPBA-100S P2 *

200 psig @ 250°F, MSS SP-110, Press X Press, UPBA-100S P2 with Stainless Steel Ball and Stem
1/2" thru 3"

Full Port

UPBA-100H *

600 WOG, Threaded with Hose-End, Cap and Chain
1/2" and 3/4"

UPBA-150H *

600 WOG, Solder with Hose-End, Cap and Chain
1/2" and 3/4"

UPBA-400 / UPBA-400S *

600 WOG, MSS SP-110, Threaded, UPBA-400S with Stainless Steel Ball & Stem
1/4" thru 2"

UPBA-450 / UPBA-450S *

600 WOG, MSS SP-110, Solder, UPBA-450S with Stainless Steel Ball & Stem
1/2" thru 2"

UPBA-100H P1 *

200 psig @ 250°F, MSS SP-110, Press X Hose-End
1/2" and 3/4"

Options/Accessories

UPBA-100/150
UPBA-400/450
INSULATOR Handle (TIH)
Oval Handle (OH)
Locking Oval Handle (LO)
Stainless-Steel Handle (SH)
Tee Handle (TH)
Locking Handle (LD)
Extension Handle (XH)
Extension Handle w/Memory Stop (XM)
Memory Stop (MS)
Chain Lever (CL)



UPBA-400 P2 XH



UPBA-475B



UPBA-481BXH

Options/Accessories

UPBA-400/450
INSULATOR Handle (TIH)
Oval Handle (OH)
Locking Oval Handle (LO)
Stainless-Steel Handle (SH)
Tee Handle (TH)
Locking Handle (LD)
Extension Handle (XH)
Extension Handle w/Memory Stop (XM)
Memory Stop (MS)
Chain Lever (CL)

UPBA-475B/485B

UPBA-480B/490B
INSULATOR Handle (TIH)
Oval Handle (OH)
Stainless-Steel Handle (SH)
Tee Handle (TH)
Extension Handle (XH)
Extension Handle with Memory Stop (XM)
Memory Stop (MS)

continued



2-PIECE LEAD-FREE BRONZE BALL VALVES

UPBA-400 P2 / UPBA-400S P2 *

200 psig @ 250°F, MSS SP-110, Press X Press, UPBA-400S P2 with Stainless Steel Ball and Stem
1/2" thru 2"

2-PIECE LEAD-FREE BRASS BALL VALVES*

UPBA-475B **

600 WOG (1/2" thru 2"), 400 WOG (2-1/2" thru 3"), MSS SP-110, UL/CSA Rated to 2", Threaded
1/4" thru 3"

UPBA-485B **

600 WOG (1/2" thru 2"), 400 WOG (2-1/2" thru 3"), MSS SP-110, Solder
1/2" thru 3"

Full Port

UPBA-480B / UPBA-480S **

200 psig @ 250°F, MSS SP-110, Press X Press, UPBA-480S with Stainless Steel Ball and Stem
1/2" thru 4"

UPBA-480SH **

200 psig @ 250°F, MSS SP-110, Press X Hose-End
1/2" thru 3/4"

UPBA-481B / UPBA-481S **

200 psig @ 250°F, MSS SP-110, Extension Stem With Memory Stop, Press X Press, UPBA-481S with Stainless Steel Ball and Stem
1/2" thru 3"



UPBA-490B



UPBA-491B



UPBA-350

Options/Accessories

UPBA-480B/490B

UPBA-300/350

INSULATOR Handle (TIH)

Oval Handle (OH)

Stainless-Steel Handle (SH)

Tee Handle (TH)

Extension Handle (XH)

Extension Handle with Memory Stop (XM)

Memory Stop (MS)

Chain Lever (CL)

continued

2-PIECE LEAD-FREE BRASS BALL VALVES

**UPBA-490B / UPBA-490S ***

200 psig @ 250°F, MSS SP-110, Press X Threaded, UPBA-490S with Stainless Steel Ball and Stem
1/2" thru 4"

UPBA-490SH *

200 psig @ 250°F, MSS SP-110, Press X Hose
1/2" and 3/4"

UPBA-491B / UPBA-491S *

200 psig @ 250°F, MSS SP-110, Extension Stem with Memory Stop, Press X Threaded, UPBA-491S with Stainless Steel Ball and Stem
1/2" thru 2"

3-PIECE LEAD-FREE BRASS BALL VALVES

**Full Port****UPBA-300 / UPBA-300S ***

600 WOG, MSS SP-110, Threaded, UPBA-300S with Stainless Steel Ball & Stem
1/4" thru 3"

UPBA-350 / UPBA-350S *

600 WOG, MSS SP-110, Solder, UPBA-350S with Stainless Steel Ball & Stem
3/8" thru 3"

UPBA-300 P2 / UPBA-300S P2 *

200 psig @ 250°F, MSS SP-110, Press X Press, UPBA-300S P2 with Stainless Steel Ball & Stem
1/2" thru 2"



UP105



UP105 P2



UP667



LEAD-FREE BRASS GATE VALVES

Non-Rising Stem**UP105 ***

300 WOG, MSS SP-80, Threaded Bonnet, Threaded
1/4" thru 2"

UP115 *

300 WOG, MSS SP-80, Threaded Bonnet, Solder
3/8" thru 2"

UP105 P2 *

200 psig @ 250°F, MSS SP-80, Threaded Bonnet, Press X Press
1/2" thru 2"

Rising Stem**UP148 ***

300 WOG, MSS SP-80, Threaded Bonnet, Threaded
1/4" thru 2"

UP149 *

300 WOG, MSS SP-80, Threaded Bonnet, Solder
1/2" thru 2"

UP148 P2 *

200 psig @ 250°F, MSS SP-80, Threaded Bonnet, Press X Press
1/2" thru 2"



LEAD-FREE BRASS GATE VALVES

Non-Rising Stem**UP667 ***

200 WOG, Threaded Bonnet, Threaded
1/4" thru 2"

UP668 *

200 WOG, Threaded Bonnet, Solder
1/2" thru 2"

* Meets Senate law S3874. IAPMO tested and certified to NSF/ANSI 372 for "lead-free" compliance.

** Meets Senate Law S3874. Tested and Certified by IAPMO R & T to NSF/ANSI 61 and NSF/ANSI 372 for "Lead Free" compliance.



LEAD-FREE* VALVES FOR POTABLE WATER SERVICE



UP502 P2



LEAD-FREE BRONZE GLOBE VALVES

UP502 *
300 WOG, MSS SP-80, Threaded
Bonnet, Threaded
1/8" thru 2"

UP1502 *
300 WOG, MSS SP-80, Threaded
Bonnet, Solder
3/8" thru 2"

UP502 P2 *
200 psig @ 250°F, Press X
Press, MSS SP-80, Threaded
Bonnet, Press X Press
1/2" thru 2"



UP1502



UP509



LEAD-FREE BRONZE CHECK VALVES

Horizontal Swing Check

UP509 *
300 WOG, Bronze Disc,
MSS SP-80, Threaded
1/4" thru 3"

UP1509 *
300 WOG, Bronze Disc,
MSS SP-80, Solder
3/8" thru 3"

UP509 P2 *
300 WOG, Bronze Disc,
MSS SP-80, Press X Press
1/2" thru 2"



UP968



UP969



UP548T P2

continued



LEAD-FREE CHECK VALVES

UP967 *
Brass, 200 WOG, Brass Disc,
Threaded
3/8" thru 3"

UP968 *
Brass, 200 WOG, Brass Disc,
Solder
3/8" thru 3"

UP969 *
Bronze, 200 psig @ 250°F, Brass
Disc, Press x Press
1/2" thru 2"



LEAD-FREE SPRING LOAD LIFT CHECK VALVES

UP548T *
PTFE Disc, 250 WOG, MSS SP-80,
Threaded
3/8" thru 2"

UP1548T *
PTFE Disc, 250 WOG, MSS SP-80,
Solder
3/8" thru 2"

UP548T P2 *
200 psig @ 250°F, PTFE Disc,
MSS SP-80, Press X Press
1/2" thru 2"



UPBBTSCS02W



1400



1800



LEAD-FREE BRONZE SLO-CLOSE SPRINKLER-CONTROL VALVE INDOOR/ OUTDOOR

UPBBTSCW

175 psig, UL/FM, Slo-Close with Position Indicator, IAPMO Tested and Certified, Less Tamper Switch, NPT-Threaded Ends 1" - 2"

UPBBTSCS02W

NPT-Threaded Ends, 175 psig, UL/FM, Slo-Close with Position Indicator, Tamper Switch 1" thru 2"

SILENT CHECK

1400

Class 125, Wafer-Style Cast-Iron Body, Stainless-Steel Disc, Stainless-Steel Spring, Meets Senate Law S3874 2" thru 10" (Also Available Class 250)

1800*

Class 125, Globe-Style Cast-Iron Body, Stainless-Steel Disc, Stainless-Steel Spring, Meets Senate Law S3874 2-1/2" thru 42" (Also Available Class 250)

LEAD-FREE NON-SLAM CHECK

8800

Class 125, Wafer-Style Cast-Iron Body, Stainless-Steel Double Disc 2" thru 16"



ML133E



CL323E



LEAD-FREE COMMERCIAL BUTTERFLY

ML133E/233E/333E

Cast Iron Body, Lug Style, Aluminum Bronze Disc, EPDM Liner, Bi-Directional Dead-End Service 200 psig Max 2" thru 12"

ML133E/333E

Cast Iron Body, Lug Style, Aluminum Bronze Disc, EPDM Liner, Bi-Directional Dead-End Service 200 psig Max 2" thru 12", Uni-Directional Dead-End Service 150 psig Max 14" thru 24"

CL Series

Cast Iron Body, Lug Style, Aluminum Bronze Disc, EPDM Liner, Bi-Directional Dead-End Service 200 psig Max 2" thru 12", Uni-Directional Dead-End Service 150 psig Max 14" thru 24"

LEAD-FREE IRON GATE

2885M26

125 SWP 200 WOG, OS & Y, All Iron, MSS SP-70 M Available 2" thru 12"

LEAD-FREE IRON CHECK

2974A26 or 2974M26

125 SWP 200 WOG, All Iron, A Available 2" thru 12" M Available 2" thru 24"



P-2056

HOSE NOZZLE

P-202

Bronze, Overwing Aircraft Refueling, Tank Trucks, Bronze Internal Parts, 2 Stage Fulcrum Lever, Balanced Dashpot Control, Dual Disc, Less Strainer, Cap, and Cable
1-1/2", 2", 2-1/2" x 2"

P-2056

Aluminum, Aircraft Refueling, Cushion Close, Tank Trucks, 135 GPM 25 psig
Inlet Nozzle Pressure, Aluminum & Stainless Internal Parts, Conforms to MIL-N-87963 Type MD-3
2"



P-2855E

BUTTERFLY

P-2855E

Aluminum, EPDM Liner, Tank Trucks, Bulk Plants, Dry Bulk Plants, 90° Arc, Quick Open, Available with Ductile Iron or Stainless Disc
2" thru 6"

P-2855H

Aluminum, Hydrin Liner, Tank Trucks, Bulk Plants, Dry Bulk Plants, 90° Arc, Quick Open, Available with Ductile Iron or Stainless Disc
2" thru 6"

P-2860H

Aluminum, Tank Trucks, Bulk Plants, Dry Bulk Plants, 90° Arc, Quick Open, Hydrin Liner for Air Lines and a Wide Variety of Chemicals to 300°F, Discs are Stainless Steel
2" thru 4"



C-35551

GATE

C-35551 / 5551

Aluminum, Bronze Trim, Tank Trucks, Bulk Plants, Filling Stations, Rising Stem, Double Disc, Bolted Bonnet, Round Flange Ends
3" thru 6"

P-2699RF

Aluminum, Transport Tank, Bulk Plants, Filling Stations, Rising Stem, Split Wedge Disc, Bolted Bonnet, Round Flange Ends
4"

P-2671

Bronze, Tank Trucks, Bulk Plants, Filling Stations, Rising Stem, Double Disc, Threaded Bonnet, Flange Ends
2"

P-900

Bronze, Quick Opening, Hazardous Liquid, 150 SWP, Lever Operated, Double Disc, Gland Packed
1" thru 3"

P-901

Bronze, Quick Opening, Double Disc, Gland Packed, 150 SWP, 300 lb. WOG, Lever Operated
1/2" thru 4"

902

Bronze, Quick Opening, Tank Trucks, Bulk Plants, 150 WOG, Lever Operated, Double Disc, O-Ring Stem Packed
3/4" and 1-1/4"



P-900



P-902



P-509

CHECK

P-509

Bronze, Horizontal Swing, Tank, Dry Bulk Trucks, Bronze Disc, Threaded Cap, Threaded Ends
1/4" thru 3"

P-509S

Bronze, Horizontal Swing, Tank, Dry Bulk Trucks, Composition Disc, Threaded Cap, Threaded Ends
1/4" thru 2"

P-2519A

Swing Check, Aluminum, Dry Bulk Transports, Tank Truck, Aluminum Disc with Viton Seat, 150 WOG
3"

P-717F

Angle Lift Check, Aluminum, 125 psig WOG at 100°F, 25 psig WOG at 350°F, Square Bolted Cap, Square Flange, Viton Disc
2-1/2"

P-717S

Angle Check, Bronze, 125 psig, WOG at 100°F, 25 psig WOG at 350°F, Threaded Cap, Viton Disc, Threaded Ends,
2"

P-728

Lift Check, Aluminum, Dry Bulk Transports, Tank Trucks, 125 psig WOG at 100°F, 25 psig at 350°F, Spring Loaded, Viton Disc, Threaded Ends
3"

P-729

Lift Check, Aluminum, Dry Bulk Transports, Tank Trucks, 125 psig WOG at 100°F, 25 psig at 350°F, Spring Loaded, Viton Disc, Flanged Ends
3"



P-717



P-728



P-612A

RELIEF

P-612A

Aluminum, Bulk Tank Truck, Pneumatic Conveyor Systems, Railroad Dry Bulk Tanks, NPT Threaded Inlet, Settings from 6 psig to 30 psig
2"



505-001

GLOBE SAMPLER VALVES

505-001
Bronze Body, 200 WOG, Threaded Ends, Teflon Disc, 1/2", 3/4", 1", 1-1/2", 2"

505-202
Bronze Body, 200 WOG, Teflon Disc, Threaded Ends, Complete with 3/8" Sampling Device 1", 1-1/2", 2"

506-202
Bronze Body, Offset Flange Inlet, Threaded Outlet, Teflon Disc, 300 WOG, Complete with 3/8" Sampling Device 1" and 2"



P-2641

GATE SAMPLER VALVE

P-2641
Bronze Body, 300 WOG, Flanged Ends, Solid Wedge, Screwed Bonnet, Non-Rising Stem With Gland Packing, Available with 3/8" Sampling Device P2641B3 2"



FC200

CONTROL VALVES

FC200 Series, Brass, 2-Way, 600 WOG, Linear Characteristics, Integral Mounting Pads, Sizes 1/2" - 2"

FC300 Series, Brass, 3-Way, 600 WOG, Linear Characteristics, Integral Mounting Pads 1/2" - 2"



FC300



MG SERIES

MEDICAL GAS VALVES*

MG Series, 3-Piece Bronze Ball Valve with Extended Copper-Tube Ends, customized to meet individual requirements 1/2" - 2"

PREVENTS CONDENSATION

Do you need an insulating valve handle that **DOES IT ALL?**



EASY-ADJUST MEMORY STOP



THE INSULATOR/MS™
A Milwaukee/Hammond Valve Product

NO SWEAT.

INSULATOR/MS™ from Milwaukee Valve is the only insulating ball valve handle that does it all – controls condensation, has reliable memory stop, and saves time since there's no need to disassemble for adjustments.

INSULATOR creates a heat transfer barrier between the piping system and the exposed portion of a valve handle and surrounding air. This eliminates or reduces condensation, and keeps damaging moisture from infiltrating insulated systems. And its operating range of +15° F to +250° F lets you spec multiple project types with one versatile product.

INSULATOR's unique memory stop adjusts easily with a few quick turns of a hex wrench, while competitive handles require time-consuming disassembly to perform stop adjustments.

INSULATOR is available on all 1/2" thru 2" bronze, brass and UltraPure ball valves, including solder, threaded and UltraPress press-fit ends. For specs and other info, visit MilwaukeeValve.com, HammondValve.com or UltraPureNoLeadValves.com.



QUALITY IS MORE THAN WHAT MEETS THE EYE.

For the most part, engineering is invisible. Engineers or contractors know what a valve looks like, and knows what it does, but typically, they can't see the superiority designed into each and every Milwaukee Valve product. Milwaukee Valve demands excellence in our engineering department, with groups operating in each of our facilities to support the manufacturing of all products. These engineers provide design services as well, translating the critical specifications and processes into manufactured items – a key step where other suppliers, without our depth of experience, often fall flat.




Milwaukee Valve's well-staffed engineering department is supported by state-of-the-art computer tools, from 3D design using Solidworks, to finite element analysis (FEA) using COSMOS, to computational fluid dynamics (CFD) using CF Design software, to automated data acquisition in our laboratories using Labview. We operate our own fire-test facility to help us achieve and maintain the most advanced fire-safe designs to the latest API and other standards. We translate our 3D designs directly to tool paths, both on our shop floor and in our pattern shop, which supports our in-house foundry operation. These capabilities also service our engineering and contracting customers, who use these models in their equipment and building designs.

In addition, Milwaukee Valve has extensive experience in the development of products for specific OEMs or demanding service conditions. Some are minor modifications to existing products. Others are turnkey product-development projects designed to meet the demanding safety needs or harsh application requirements of a specific user.

Milwaukee Valve's background in the Commercial, Industrial, and very specialized Marine business for the United States Navy should provide you with confidence to entrust your most difficult engineering applications to our experienced staff, helping you grow your business and providing you with the great service you deserve.

If you have a service that is constantly causing you concern, give us a call. Our application engineering and technical service teams stand ready to help.



For more information on our capabilities or assistance with a specific problem, contact your Milwaukee Valve sales representative (<http://www.milwaukeevalve.com/index.php/reps>).

Their experience and industry knowledge will simplify finding a solution to your product and application requirements.

This condensed catalog is not a complete depiction of Milwaukee Valve's products or capabilities. Please contact the factory for special service conditions or additional accessories and options.

WEBSITE REDUCES ERRORS AND SAVES TIME

Simplify your projects and reduce ordering errors by building your own valves, courtesy of Milwaukee Valve's online Advanced Search feature.



You know the service, and Milwaukee Valve has the valves and the options to solve your service issues. Found at www.MilwaukeeValve.com, the Advanced Search function acts as an online configurator, laying out all available options in one easy-to-use format. You select the type of valve you require, and choose the available materials, sizes, options, etc. Once all options are selected, you are given the model numbers for the valves that meet your criteria. When you know exactly what you are ordering, the result is fewer returns, lower shipping costs, and all-around time savings. The Advanced Search is especially beneficial in selecting Butterfly and Industrial valves, which both offer thousands of different valve and option combinations.

In addition, the website contains specification data for virtually every Milwaukee Valve product, and has the capacity to produce product submittals, access 2D and 3D CAD files, and is a repository for a wide variety of product information, including price lists, literature downloads, technical service bulletins, competitive cross reference and even provides links to YouTube instruction and installation videos.

And if you require assistance in selecting a valve, ball, seat, actuation or any of many other options, assistance is available from your Milwaukee Valve sales representative. Try it out at www.MilwaukeeValve.com.



16550 West Stratton Drive,
New Berlin, WI 53151
Phone 262-432-2700 • Fax 262-432-2701
www.MilwaukeeValve.com