LONFOAM

LONSEAL

In addition to its stylish color choices, LONFOAM features an added layer of closed-cell foam to enhance long-term comfort and significantly reduce impact noise. It provides a durable, low-maintenance and smooth-textured flooring, and is a perfect fit for interior multi-purpose fitness room environments, healthcare facilities, commercial and institutional use.

STANDARD SIZES (nominal)


Overall thickness: 0.120" (3.0 mm)
Wear layer thickness: 0.030" (0.70 mm)
Roll size: 6' (1.8 m) wide X 60' (18.3 m) long

Weight: 0.7 lbs./sq.ft., 235 lbs./roll

Colors: Ten available

GREEN FEATURES

- GreenMedic™: Formulated for microbial resistance
- GreenAir™: Formulated for low VOCs
- FloorScore[®] Indoor Air Quality Certified
 Conforms to CA Specification 01350
- · LEED Low Emitting Materials
- Adhesives and Sealants: LEED IEQ Credit 4.1
- Flooring Systems: LEED IEQ Credit 4.3



10-YEAR WARRANTY

Lonseal offers a 10-year limited warranty.

TECHNICAL DATA

Sheet Vinyl Floor Covering with Backing, ASTM F1303	Type 1, Grade1, Class C
Flexibility, ASTM F137	Pass
Hardness, ASTM D2240	85
James Machine, SCOF, ASTM D2047	Neolite: 0.61; Neolite w/ Finish: 0.64
Abrasion Resistance, ASTM D3884	0.08%, 1,000 cycles
Static Load (max 0.005"), ASTM F970	750 psi
Short-term Indentation, ASTM F1914	0.001" residual indentation @ 75 lbs.
Castor Chair Test, ISO TR4918	25,000 cycles - Wear: 4.5, Color: 4.0, Change: 4.5
Dimensional Stability, ASTM F2199	0.17% loss
Heat Stability, ASTM F1514	Pass
Light Stability, ASTM F1515	Pass
Critical Radiant Flux, ASTM E648	Class 1 ≥0.45 watts/cm ²
Chemical Resistance, ASTM F925	Slight Surface Dulling: 5% Ammonia; Slight Color Change:
	5% Phenol

For detailed technical information, please refer to www.lonseal.com.







LONSEAL, INC.
928 E. 238th Street, Carson, CA 90745 USA
800.832.7111 toll free | 310.830.7111 ph
www.lonseal.com

Updated: 04.14.14