

Frames		Rigid					Coupled	
		Monobar			Monoblock			
Length of bar		3 m 00		4 m 50	6 m 10		3 m 00	9 m 00
Transport width		-		-	3 m 00		-	3 m 00
Number of metering units		4	6	6	8	12	6	12 18
Inter-row spacings (cm)		70-80	45/50	70-80	70-80	45/50	50	70/75 45/50
Turbofan		Drive by PTO – 540 rpm in standard version, 450 or 1000 rpm on option - universal joint on option						
Tyres		2 x (500x15)		2 x (6,5x80x15)	4 x (500x15)		2 x (6,5x80x15)	8 x (6,5x80x15) 8 x (500x15)
Metering box (16 settings)		● 1		● 1	● 1		● 1	● 2
Hydraulic row markers		○	○	●	●		○	●
Fertilizer	Standard	○ 2 x 175 L		○ 2 x 270 L	○ 4 x 175 L		○ 2 x 270 L	○ 4 x 270 L ○ 5 x 175 L + 1 x 270 L
	Front-mounted Standard	○	○	○	○	○	○	○
	Front-mounted DUO	-	-	-	-	-	-	○
Microsem	Insecticide	○	○	○	○	○	○	○
	Helicide	○	○	○	○	○	○	○
Hectare counter		○	○	○	○	○	○	○
Seed monitors		○	○	○	○	○	○	○
Row cut-off system		○	○	○	○	○	○	○
Lighting kit		○	○	○	○	○	○	○
Weight planter only		600 kg	800 kg	800 kg	1200 kg	1700 kg	850 kg	2800 kg 3600 kg

## MAIN NC SEED DISCS

Type of seed	Standard discs delivered	Number of holes	Diameter of holes	Distances on the row (standard seed spacing gearbox)	Other possibilities, number and Ø of holes
Maize	DC 3050	30	5 mm	7 to 21,5 cm	18 - 24 and ø 4,5 - 6 mm
Sunflower	DC 2425 DC 1825	24 18	2,5 mm	9 to 26,5 cm 12 to 35,5 cm	
Sugarbeet	DC 3020	30	2 mm	7 to 21,5 cm	24
Beans	DC 6045 DC 6035	60	4,5 mm 3,5 mm	3,5 to 11 cm	ø 2,5 mm
Soya - Peas	DC 6045	60	4,5 mm	3,5 to 11 cm	
Rapeseed	DC 7212	72	1,2 mm	3 to 9 cm	36 - 60 - 120
Cotton	DC 3635	36	3,5 mm	6 to 18 cm	
Sorghum	DC 7222	72	2,2 mm	3 to 9 cm	36
Kidney beans	DC 3060	30	6 mm	7 to 21,5 cm	ø 5 - 6,5 mm
Peanut	DC 3065	30	6,5 mm	7 to 21,5 cm	36 and ø 5,5 - 6 mm

# FEATURES



The precision Planter specialist

Coupled		Single telescopic			Folding		
		Monobar	Monoblock 125	Monoblock 260	Double-bar		CRT
12 m 00		4 m 50	4 m 50	4 m 50	6 m 00		9 m 00
3 m 00		3 m 15	3 m 50	3 m 15	3 m 00	3 m 00	3 m 00
16	24	6	8	6	8	12	12
70	45	75/80	35/45/49	75/80	75/80	45/50	70/75/76,2/80
Drive by PTO – 540 rpm in standard version, 450 or 1000 rpm on option - universal joint on option							
8 x (6,5x80x15)	8 x (500x15)	2 x (6,5x80x15)			4 x (6,5x80x15)	4 x (500x15)	4 x (6,5x80x15)
● 2		● 1			● 3		● 3 (Wheel unit gearbox)
●		●			●		●
-	-	○ 2 x 270 L	○ 2 x 270 L	○ 2 x 270 L or 1 x 980 L	○ 4 x 175 L		○ 4 x 270 L
-	-	○	○	○	○	○	○
○	○	-	-	-	-	-	○
○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○
3500 kg	4200 kg	900 kg	1200 kg	1000 kg	1800 kg	2200 kg	3000 kg

\*According to equipment  
 ● : Standard  
 ○ : On option  
 - : Not possible  
 For other models, special inter-row spacings and other crops, please consult us.

## NC METERING UNIT EQUIPMENT

Metering unit type		NC Classic V1	NC Classic V2	NC Classic V3	NC Technic Maize	NC Technic Sugarbeet	NC Technic Beans
40L hopper		●	●	●	●	○	●
20L hopper		○	○	○	○	●	○
Front assembled equipment	Clod removers	●	●	●	●	●	●
	300 x 100 front wheel 2)	-	-	-	○	●	●
	Double-discs openers	○	○	○	○	-	-
	Double discs and 285 x 65 wheel 2)	-	-	-	○	○	○
Balancing system 3)		-	-	-	○	●	●
Additional adjustable spring 1)		○	○	○	○	○	○
Maize shoe + 4 cm		●	●	●	●	-	-
Low maize shoe		-	-	-	○	○	●
Sugarbeet shoe		-	-	-	-	●	-
Scrapers		●	●	●	-	-	-
Stainless press wheel 3)		-	-	-	○	●	○
Supple intermediate press wheel 3)		-	-	-	○	○	○
Rear assembled equipment	Steel V-wheels	●	○	○	-	-	-
	Wheel 370 x 170 Farmflex	○	●	○	○	○	○
	Wheel 500 x 175 Farmflex	○	○	●	-	-	-
	2" press wheel	-	-	-	●	●	●
	Crumbler kit	-	-	-	-	○	-

1) Please consult us 2) Only with balancing system 3) Only compatible with low maize shoe and sugarbeet shoe