



Product Bulletin



DOUBLE CUT™

Product Description:

Double Cut™ is an aggressive low swirl, correcting compound designed to remove heavy surface imperfections. Fast removal of 1000-1200 grit sand scratches, severe swirls, holograms and heavy oxidation. May be applied by D/A or a variable speed polisher. Works well with wool or foam cutting pads. Leaves a clean, glossy surface ready for polishing. For machine use. CONTAINS NO WAX OR SILICONE. BODY SHOP SAFE. VOC COMPLIANT.

Product Details:

VOC Compliant
Body Shop Safe
NPE Free
Phosphate Free
pH: 9.3
Color: White
Fragrance: Floral

Packaging:

Quart: P-16-Q



Features & Benefits:

Removes Heavy Surface Imperfections, Holograms, & 1000-1200 Grit Wet Sand Scratches
Designed for DA Compound Correction
Uses High Purity Aluminum Oxide Abrasive System
Low Dust, Silica-Free Formula
Great for Marine Gel Coat & Fiberglass Surfaces
Body Shop Safe – Contains No Wax or Silicone

Application: *Shake well before using. Read label before use. See SDS for more information.*

D/A Polisher: Use a PRO® BU-7-C Blue Compound Pad. Apply product to pad. Set D/A polisher speed to 4-6. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants. Follow with a PRO® YU-7-C Yellow Polish Pad and P-5 Reflect-It™.

High Speed Buffer: Use a PRO® VC-80-C Wool Pad or VF-85-C Yellow Foam Compound Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure at 1200-1800 rpm. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants. Follow with a PRO® RV-85-C Charcoal Foam Polish Pad and P-21 Swirl Eliminator™.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Safety glasses and NIOSH approved dust mask are recommended while machine buffing this product. Do not apply in direct sunlight or onto a hot surface. Polish one section at a time.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

