



TEC-GUARD

ARMOR

TEC-GUARD DEX-MERC AUTOMATIC TRANSMISSION FLUID



TEC-GUARD® Armor Dex/Merc Automatic Transmission Fluid is formulated with selected Group II base oils and additives to meet demands of an automotive transmission environment and to provide excellent oxidation control and low-temperature performance required in passenger car and light truck transmissions.

Meets or exceeds the following performance requirements and industry specifications: DEXRON® III H, DEXRON® III G, DEXRON® IIE, MERCON®, or Type A, M2C138-CJ or M2C 166-H Fluids, Allison® C-4, Caterpillar® TO-2. In Chrysler® transmissions, except where Chrysler® MS-9602, MS-7176 or ATF+4 are required. In 1979 or newer transmissions built by Ford®, except Ford® FMX and pre-1980 C-4 transmissions and where MERCON® V is required. It is not recommended for Ford® Type F, Continuously Variable Transmissions (CVT), Dual Clutch Transmissions (DCT), or in transmissions requiring DEXRON® VI automatic transmission fluid.

Always consult your owner's manual for specific recommendations.

- Designed to provide smooth shift performance where DEXRON® III or a MERCON® transmission fluid is required
- Provides excellent high temperature oxidation resistance
- Protects against rust, corrosion, and wear

Test Method		Product Numbers	
ASTM D1298 - API Gravity	32	Bulk	10411205200ATF
ASTM D93 - Flash Point, °C	185	Drum	10411215200ATF
ASTM D97 - Pour Point, °C	-48	Pail	10411245200ATF
ASTM D445 - Viscosity @ 40° C, cST	32.8	Tote	10411205200ATF
ASTM D445 - Viscosity @ 100° C, cST	7.2	12/1 Quart	10411265200ATF
ASTM D2270 - Viscosity Index	179		
Color	Red		

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.