

ACETONE

Page: 1

Compilation date: 13/09/2012

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ACETONE

REACH registered name: ACETONE

REACH registered number(s): 01-2119471330-49

CAS number: 67-64-1

EINECS number: 200-662-2

Index number: 606-001-00-8

Product code: \$106

Synonyms: 2-PROPANONE

DIMETHYL KETONE

PROPAN-2-ONE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Solvents With Safety Ltd

Units 1 - 4

Plumtree Farm Ind Est

Harworth Doncaster

DN11 8EW United Kingdom

Tel: 01302 711733

Fax: 01302 711744

Email: sales@solventswithsafety.co.uk

1.4. Emergency telephone number

Emergency tel: 07976024391

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R36; -: R66; -: R67

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066

Most important adverse effects: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or

cracking. Vapours may cause drowsiness and dizziness.

ACETONE

Page: 2

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS09: Environmental







Label elements under CHIP:

Hazard symbols: Highly flammable.

Irritant.

Dangerous for the environment.







Risk phrases: R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S46: If swallowed, seek medical advice immediately and show this container or label.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: ACETONE

Section 4: First aid measures

ACETONE

Page: 3

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing

becomes bubbly, have the casualty sit and provide oxygen if available. Move to fresh air

in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness.

Ingestion: Headaches or general malaise may result. Nausea and stomach pain may occur.

Inhalation: Drowsiness or mental confusion may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water spray. Dry chemical powder. Alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Vapour may travel considerable distance to source of ignition and flash back. Forms

explosive air-vapour mixture. In combustion emits toxic fumes of carbon dioxide / carbon

monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition. Do not attempt to take action without suitable protective clothing - see section 8

of SDS.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks. Mix with sand or vermiculite.

ACETONE

Page: 4

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container

tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic charge in the immediate area. The floor of the storage room must be impermeable to

prevent the escape of liquids.

Suitable packaging: Steel drums. Stainless steel. Polyethylene. Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure all engineering measures

mentioned in section 7 of SDS are in place.

Respiratory protection: Not applicable.

Hand protection: Protective gloves. Gloves (solvent-resistant).

Eye protection: Tightly fitting safety goggles.

Skin protection: Solvent resistant protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Moderate

ACETONE

Page: 5

Solubility in water: Soluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Boiling point/range°C: 55.8-56.6 Melting point/range°C: -94.7

Flammability limits %: lower: 2.5 upper: 14.3

Flash point°C: -17 Autoflammability°C: 465

Vapour pressure: 24.1 kPa 20 Relative density: 0.79 20

pH: 5-6 **VOC g/I**: 790

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Amines. Strong reducing agents. Bases. Alkalis.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORL	RAT	LD50	5800	mg/kg
ORL	MUS	LD50	3000	mg/kg
IVN	RAT	LD50	5500	mg/kg

ACETONE

Page: 6

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Based on test data
STOT-single exposure	-	Based on test data

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness.

Ingestion: Headaches or general malaise may result. Nausea and stomach pain may occur.

Inhalation: Drowsiness or mental confusion may occur.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Solvent reclamation/regeneration.

Waste code number: 140603

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

ACETONE

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN1090

14.2. UN proper shipping name

Shipping name: ACETONE

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Tunnel code: D/E **Transport category:** 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has been carried out for the substance or the mixture by

the supplier.

Section 16: Other information

Other information

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

R11: Highly flammable. R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.