



Owensboro Specialty Polymers, Inc.

Chemistry that Connects, People that Care

Owensboro Specialty Polymers, Inc.

5529 Highway 2830

Owensboro, KY 42303

www.onssp.com

Everflex[®] Versaflex[®]

Paint/Coating Emulsions

Product Comparison Chart

Description	% Total Solids	Viscosity ¹ (cps)	pH	Particle Size (microns)	Clarity	Water Resistance	Tg°C
Everflex Vinyl Paint/Coatings Emulsions							
G A high molecular weight permanently flexible vinyl acetate copolymer emulsion. It offers excellent flow, holdout, flexibility and machining properties. Widely used in primers, sealers, and specialty coating applications.	52	300-700	4.0-6.5	1.5	Excellent	Very Good	-7
GT A unique vinyl copolymer emulsion designed for high solids mastic compounds, caulks, sealants and joint cements. Its outstanding chemical and mechanical stability enables the formulator to develop highly loaded compounds with excellent rheological characteristics.	55	1,500-3,000	4.0-6.5	1.0	Excellent	Excellent	6
SP1084 A high molecular weight vinyl acetate copolymer emulsion. Widely used as concrete additive to improve adhesion and compressive strength.	53	300-700	4.5-5.5	1.5	Good	Good	14
Versaflex Acrylic Paint/Coatings Emulsions							
9 A vinylidene chloride acrylate emulsion polymer with excellent adhesion to glass, metal and some engineering plastics in either clear or pigmented coatings.	48-50	10-40	2.5-3.5	0.1	Excellent	Excellent	5

¹ Brookfield LVF, 25°C

Literature Code OSP_PCC_Everflex_Versaflex_Rev4
Issue Date: April 28, 2015

The information presented herein is based on the best available data and is believed to be true and accurate. Please read all statements, recommendations, or suggestions in conjunction with our conditions of sale which apply to all goods supplied by us. No responsibility for the use of these statements, recommendations, or suggestions is assumed by the supplier, nor are they intended as a recommendation for any use which would infringe any patent or copyright. The buyer bears sole responsibility for determining suitability of the product for their application.