

L Range of Low resistance Weather Louvres

FEATURES:

- 90% Free Vent Area
- Two Way Venting
- Steel Welded Construction
- Life Time Guaranty
- Third Party Tested
- Certified Compliance
- Simple to Install
- Conforms to FIA guidance
- Fast Delivery on standard sizes
- Made in the UK




The L range of weather louvres for the Flow² Pressure Vents is designed to give the lowest level of resistance and a free vent area that equals the Flow² Pressure Vent of 90%. It achieves this with a unique louvre blade system that provides a high level of weather proofing with a high level of free vent area.

When used with the Flow² Pressure vent there is no reduction in free vent area (FVA).

The units are finished in a RAL9006 Silver Grey Powder Coated finish that has high resistance to rusk and salt ingress . The installation could not be samplers are the louvre screw directly to the outer wall sleeve of the pressure vent and a simple sealant on the sides and top fully water proofs the system.

Special colours are available in request.

Louvre Size	L150	L300	L500	L700	L1000
A	280	420	700	930	1230
B	430	430	630	920	1220
Unit Weight	4kg	8kg	12kg	15kg	22kg
FVA @ M ² 100Pa	0.045/0.045	0.083/0.083	0.27/0.27	0.45	0.9
Unit Finish	-	RAL9066 Silver Grey			



LinkedIn

Find us on:
facebook