



The UK's largest distributor of **marstair** cellar coolers...



CX(E) cellarator refrigeration R407c

THE INNOVATIVE CX(E) CELLARATOR SPLIT SYSTEM IS DESIGNED TO HELP THE LICENSED TRADE MAINTAIN A COOLED ENVIRONMENT MORE EFFECTIVELY THAN EVER BEFORE.

With its revolutionary one piece moulded body, impregnated with an anti-bacterial additive, the CX(E) is ideal for cellar cooling, food preparation areas and any areas requiring controlled temperatures down to 4°C.

The Cellarator provides consistent temperature control with economy, ease of maintenance, flexible positioning, hygiene, safety and reliability.



The Cellarator is available in 2 versions:

- CX ELECTROMECHANICAL (optional digital temperature display)
- CX(E) with electronic control

SPECIFICATION

- Capacity range from 2.3 - 6.8kW
- Long pipe runs up to 80m (50m for CKC DCU+ 20 & 30)
- The unit controls temperatures down to 4°C (dependent upon system match)
- De-ice stat is standard on CXE electronic units
- Antibacterial agent added to the chassis during the moulding process for complete mould protection throughout the material
- 6 fins-per-inch brewery specification heat exchanger
- Mounting brackets suitable for both wall and ceiling mounting and a waterproof power switch
- Direct access to the electrics at the front of the unit
- ABS drain tray incorporating standard 22mm OD fitting drain stub
- Easy to install field electric heater kit with factory fit option
- Outdoor condensing units incorporating a low pressure switch, HP switch and low ambient start as standard
- Ducted condensing units for where external installations are not an option
- Stylish design chassis and rounded corners for safety

R410a cellar cooling

COMPETITIVE RANGE OF R410A CELLAR COOLERS

BASED ON THE SAME HIGH SPECIFICATION INDOOR UNITS
AS OUR SUCCESSFUL CX(E)/CKC RANGE

SPECIFICATION

- Designed with a high impact resistant moulded polymer cabinet impregnated with an anti-bacterial additive to help prevent mold growth
- 6 fins-per-inch brewery specification heat exchanger
- Rounded corners, mounting brackets suitable for both wall and ceiling mounting and a waterproof power switch
- Direct access to the electrics at the front of the unit
- ABS drain tray incorporating standard 22mm OD fitting drain stub
- Up to 15m pipe runs
- Easy to install field fit electric heater kit with factory fit option
- Air throws to suit all applications

FEATURES

- LP Switch
- 3 minute timer
- Random start contactor
- De-ice stat as standard
- Electronic Control ('E' units only)



CX(E) Indoor Unit



CKA Outdoor Unit

Available
in 3
capacities
2.3 to 4.5KW



Need Advice?

Call ICE Refrigeration Services Ltd for more information or to price a cellar cooler unit:
01747 352440 or 07708 969572 or email info@iceref.co.uk