



---

---

[www.butcherblock.com](http://www.butcherblock.com)

Submittal Data:

Material: Hard Maple, Kiln Dried to 6 to 8% Moisture Content.

Fabrication: Fabricated from wood strips not more than 1 7/8" wide. Finger joint material may be used for sizes over 7 foot. Tops over 12 feet in length will be manufactured in sections and joined in the field with mechanical fasteners.

Glued under pressure using radio frequency.

Size tolerance: Length, +/- 1/8"  
Width, +/- 1/8"  
Thickness, +/- 1/16"

Sanded with 120 grit paper.

Finish: "Durakryl 102" U.V. Cured Polyurethane. "Durakryl 102" Meets or Exceeds the K.C.M.A. ANSI A161.1-1995 Performance and Construction Standard

Curbs: Solid Hard Maple, 4x3/4 with Durakryl 102 Finish.

Tops over 1 3/4" in thickness and over 72" in length will have finger joints appear in the face.

Woodwelded Companies do not select for color. We use the full log run. Natural occurring variations in color, grain, and mineral marks are not considered defects. Butcher block products are real wood, and just as no two trees in nature are alike, no two butcher block tops are alike.



---

---

**Bally Block Company**

Post Office Box 188 30 South Seventh Street Bally, PA. 19503 {Telephone} 610-845-7511 {Facsimile} 610-845-3910

**Michigan Maple Block Company**

1420 Standish Ave. Petoskey, MI. 49770 {Telephone} 231-347-4170 {Facsimile} 800-447-7975