

# DURAGLAZE

## Description

A clear, non-yellowing chemical resistant glaze which forms a hard, easy cleaned transparent membrane. Ideally suited for overcoating warehouse markings where a clear glaze is required.

## Typical Uses

- An overglaze for acrylic coatings subject to constant wear and handling.
- For sealing and sand retention on newly laid pavers and cobblestones, concrete, unglazed tiles and brickwork.
- For building exteriors subject to constant wear and handling.

## **Properties**

	~
Resin System	Acrylic (solvent based)
Pigmentation	None
Finish	Gloss
Colour	Clear
Dilution Rate	Use as supplied. If required, use Damar Toluene.
Theoretical Coverage	12m <sup>2</sup> per litre for over glazing. 3-4m <sup>2</sup> per litre for porous pavers and bricks first coat and up to 8m <sup>2</sup> if a second or third coat is applied.
Dry Time @ 25°C	l hour. Recoat 24 hours.
Number of Coats	2 (generally), 3 on porous pavers.
Clean Up	Toluene

## **Performance / Limitations**

- Not suitable for use over glazed and/or ceramic tiles.
- Designed for use in situations where a hard wearing, clear and glossy surface is required irrespective of the immediate undercoat or substrate.

- Application to concrete is problematic due to large variations in drying agents and surface finishes available, plus surface contaminations.
- For application to concrete surfaces please refer to concrete application sheet
- Can be used over existing paint work but its compatibility needs to evaluated. (Look for the wrinkling of the film.)
- This product is not recommended as a finish for particle board or any manufactured product having a high wax content.

------

## Preparation

• Substrate must be in clean and dry condition, free from dirt, grease, and loose material.

## **Application**

• Can be applied by brush, roller or spray. (Conventional or airless.)

#### -----

-----

## Health and Safety

- For detailed information refer to the MSDS and label for this product.
- Provide adequate ventilation during use.
- Avoid breathing vapour.
- Wear eye protection when handling as splashed to the eye may cause irritation.
- If swallowed or eyes become contaminated, seek medical attention.
- When spraying, wear a quality mask with an approved vapour cartridge.
- Product is FLAMMABLE

NEW ZEALAND: Eastgate Business Park, 800 Te Ngae Road, Rotorua PO BOX 7084, Te Ngae, Rotorua 3042, New Zealand P: 0800 33 44 75 F: 0800 33 44 76 E: orders@damarindustries.co.nz www.damarindustries.co.nz AUSTRALIA: 25 Hargraves Place, Wetherill Park, NSW, 2164 PO BOX 6599, Wetherill Park 2164, Australia P: +61 2 9756 4511 | F: +61 2 9756 0985 www.damarindustries.com.au

DISCLAIMER: This information is not a specification and is given in good faith. Since conditions of use are beyond the manufacturers control, all information given is without warranty, implied or otherwise, and is not intended to be exhaustive. Final determination for sustainability of the product for the use contemplated is the sole responsibility of the user. It is also the users responsibility to ensure that all information is current prior to using the product.