

Description: The ILSG (In-Line Sight Glass) Provides product viewing for process or safety reasons, whilst the hose assembly is connected. The FEP material coupled with the Series 7000 coupling provides a hygienic assembly.

Note : As standard the assembly will be provided with approximately 100mm visible length.



Approvals: FDA 21CFR177.1550

Features:

- 316 Stainless steel or FEP in contact with product, using hygienic fittings
- Shatterproof sight tube for maximum safety
- Uses the series 7000 swaging system for crevice free fitting connection
- Available with or without guard
- Materials of construction for hygienic use
- Detergent or caustic (CIP) cleanable
- Steam cleanable (short duration) SIP

Dimensions			
NB inches	DN mm	Id mm	Wall Thickness
1/2	15	12.7	2.5
3/4	20	19.1	3.2
1	25	21.7	3.2
1 1/2	40	34.4	3.2
2	50	47.1	3.2
2 1/2	65	58.8	3.7
3	80	72.5	4.5
4	100	97.9	5.5

- Options:**
- 1) End fittings - Hygienic end connections RJT, IDF/ISS, DIN, SMS, Tri-clamp etc.
 - 2) Elbows - fixed.
 - 3) Fittings Materials - Hastelloy C22, C276.
 - 4) Guarding—None, mesh or slotted stainless steel.

Please consult Flexrite for Working Pressures and Temperatures.

Website : www.flexrite.co.uk

E-mail: enquiry@flexrite.co.uk

Tel : +44 (0)1933 673699

Fax : +44 (0)1933 675819

19 The Trinity Centre
Park Farm Industrial Estate,
Wellingborough, NN8 6ZB