

THE WEATHER-TITE™ M2 LIFTGATE ASSEMBLY

THE ONLY DUAL POLE
PLUG CONNECTION WITH
**SUPERIOR
CORROSION
PROTECTION**



AVOID DOWNTIME DUE TO CORROSION AND KEEP
YOUR LIFTGATE CYCLING FOR ON-TIME DELIVERIES.



Weather-Proof Plug

Unbreakable, non-corrosive housing
which is completely molded to the
electrical cable to combat against
corrosion



Moisture Blocking Seal

The WEATHER-TITE™ seal adds additional
corrosion protection at the front of the plug
by blocking moisture and contaminants from
entering the electrical system through the
coupled connection

Heavy Duty Jacketing

Flexible from - 82°F to 195°F (- 63°C to 91°C)
with chemical and abrasion resistance



Common Standard Connection

Will work with any standard J3082
dual pole liftgate socket



WE MAKE PRODUCTS THAT MAKE A DIFFERENCE®

12070 BURKE STREET, SANTA FE SPRINGS, CA 90670
800.423.4512 FAX 800.597.7757

PHILIPS

WEATHER-TITE™ M2 Liftgate Assemblies

- For dual pole liftgate applications utilizing a trailer battery pack
- Features plugs that are unbreakable with non-corrosive housing which are completely molded to the electrical cable to combat against corrosion
- The WEATHER-TITE™ seal adds additional corrosion protection at the front of the plug by blocking moisture and contaminants from entering the electrical system through the coupled connection
- 100 amp continuous capacity, 200 amp intermittent capacity
- Flexible from - 82°F to 195°F (- 63°C to 91°C)
- Meets J3082 standards

COILED DUAL POLE WEATHER-TITE™ M2 - 4 GA.



2/4 ga. Fine Stranded Copper

23-23276 12', 1 ground, 1 hot, 4 ga.

23-26276 15', 1 ground, 1 hot, 4 ga.

23-29276 15' with 48" lead, 1 ground, 1 hot, 4 ga.

- Excellent recoil memory, chemical and abrasion resistance

COILED DUAL POLE WEATHER-TITE™ M2 - 2 GA.



2/2 ga. Fine Stranded Copper

25-23276 12', 1 ground, 1 hot, 2 ga.

25-26276 15', 1 ground, 1 hot, 2 ga.

25-29276 15' with 48" lead, 1 ground, 1 hot, 2 ga.

- Excellent recoil memory, chemical and abrasion resistance

STRAIGHT DUAL POLE WEATHER-TITE™ M2 - 4 GA.



2/4 ga. Fine Stranded Copper

23-22576 12', 1 ground, 1 hot, 4 ga.

23-22776 15', 1 ground, 1 hot, 4 ga.

- Good chemical and abrasion resistance

STRAIGHT DUAL POLE WEATHER-TITE™ M2 - 2 GA.



2/2 ga. Fine Stranded Copper

25-22576 12', 1 ground, 1 hot, 2 ga.

25-22776 15', 1 ground, 1 hot, 2 ga.

- Good chemical and abrasion resistance

WE MAKE PRODUCTS THAT MAKE A DIFFERENCE®

12070 BURKE STREET, SANTA FE SPRINGS, CA 90670

800.423.4512 FAX 800.597.7757

PHILIPS