



Features

- Intel® Core™ J1900, 2.42GHz
- Two independent display
- 9-36V DC wide range power
- Fanless design

System

CPU	Intel® Core™ Processor J1900
Model	Intel® Core™ J1900, 2.42GHz
Core Number	4
Max Speed	2.42GHz
L3 Cache	2 MB
BIOS	UEFI

I/O

LAN	2 (+2 optional)
HDMI	1
USB 3.0	2
USB 2.0	2
Serial	3 RS232 + 1 RS232/422/485
VGA	1
Audio	1 (Line-out)

Storage Space

Max Data Transfer Rate	SATA2 (3.0GB/s)
------------------------	-----------------

Expansion Slot

PCIe	0
PCI	0
Mini-PCIe	1 (half-size)
mSATA	1 (full-size) shared with SATA2
Cfast Card Socket	1 (optional)

Environment

Operating temperature	0 ~ 50 °C
Storage temperature	-30 ~ 70 °C
Storage humidity	10 to 90% @ 40 °C - non condensing
Certification	CE

Display

Display type	10.4" XGA - 4:3
Max. resolution	1024 x 768
Max. color	16,7 M
Luminance (cd/m ²)	500
View angle (H°/V°)	88 / 88 (H) 88 / 88 (V)
Contrast	1000 : 1

Touch Screen

Type	Resistive zero bezel Projected Capacitive
Interface	USB
Light transmission	Projected capacitive: 90% Resistive: 80%

Mechanical

Construction	Aluminum front bezel optional INOX 316
IP Rating	Front bezel IP66
Mounting	Panel/VESA mounting
Dimension (mm)	297(W) x 222(H) x 95.09(D)
Net weight	3 Kg

Power

Power input	9-36V DC in using 4-pin ATX PWR Con
Power consumption	10W
Power On	AT/ATX supported

Supported Operating System

Windows® 7 Ultimate (32bit)
Windows® 7 Professional (32/64bit) Ita/Eng
Windows® 7 Embedded (32bit) Eng/ML
Windows® 10 Professional (32/64bit)
Windows® 10 IoT Enterprise

