





# WE CALL IT A DRILL. YOU CALL IT YOUR GO-TO MONEYMAKER.



A comfortable operator is a more productive operator, which is why we've equipped the JT25 Horizontal Directional Drill operator's station with a cutting-edge design. It features:

- Choice of single-handled control or dual joysticks for easy control of thrust and rotation.
- Excellent view of the tool joint when making up and breaking out pipe; open-top vise wrenches are angled toward the operator.
- Exceptionally comfortable, new supportive seat design with high armrests.
- LCD display provides engine diagnostics and informational messages.
- Optional climate-controlled cab, for maximum comfort and productivity in any weather condition.

## JT25 HORIZONTAL DIRECTIONAL DRILL SPECIFICATIONS

	U.S.	METRIC
PERATION		
Spindle speed, max	220 rpm	
Spindle torque, max	4,000 ft·lb	5420 N⋅m
Carriage thrust travel speed	182 fpm	55 m/min
Carriage pullback travel speed	190 fpm	58 m/min
Thrust force	27,000 lb	120 kN
Pullback force	27,000 lb	120 kN
Ground travel speed		
Forward	2.8 mph	4.6 km/h
Reverse	2.8 mph	4.6 km/h
OWER		
Engine	Cummins® QSB4.5	
Fuel	Diesel	
Cooling medium	Liquid	
Injection	Direct	
Aspiration	Turbocharged & charge air cooled	
Number of cylinders	4	
Displacement	275 in <sup>3</sup>	4.5 L
Bore	4.21 in	107 mm
Stroke	4.88 in	124 mm
Gross horsepower Tier 3/Tier 4	130 hp	97 kW
Rated speed Tier 3/Tier 4	2,500 rpm	
Emissons compliance Tier 3	EPA Tier 3	EU Stage IIIA
Emissions compliance Tier 4	EPA Tier 4	EU Stage IV
IMENSIONS (*FULL RACK, 55 PIPE)		
Transport length	232.5 in	5.9 m
Width	87 in	2.21 m
Width w/cab	87 in	2.21 m
Transport height	93 in	2.36 m
Transport height w/cab	99.5 in	2.53 m
Weight	20,760 lb	9417 kg
Weight w/cab	21,360 lb	9689 kg
Ground clearance	5.7 in	145 mm
Entry angle	9-20°	
Entry angle, tracks on ground	9-17°	

	U.S.	<b>METRIC</b>
DRILLING FLUID SYSTEM (ON BOARD)		
Pressure, max	1,200 psi	83 bar
Flow, max	50 gpm	189 I/min
FLUID CAPACITIES		
Fuel tank	48 gal	182 L
Engine lubrication oil w/filter	13.7 qt	13 L
Hydraulic reservoir	27 gal	102 L
Engine cooling system	24 qt	22.7 L
Antifreeze tank	8 gal	30 L
Diesel exhaust fluid tank	5 gal	18.9 L
POWER PIPE® HD		
Length	118 in	3 m
Joint diameter	2.75 in	70 mm
Pipe diameter	2.38 in	60 mm
Bend radius, min	123 ft	37.5 m
Weight of drill pipe, lined	88 lb	40 kg
Weight of lined drill pipe & large box (55 pipe)	5,647 lb	2562 kg
Weight of lined drill pipe & small box (25 pipe)	2,770 lb	1154 kg
POWER PIPE FORGED		
Length	120 in	3.05 m
Joint diameter	2.63 in	66.7 mm
Pipe diameter	2.38 in	60 mm
Bend radius, min	108.2 ft	33 m
Weight per drill pipe, forged	73 lb	33 kg
Weight w/drill pipe & large box (55 pipe)	4,522 lb	2187 kg
Weight w/drill pipe & small box (25 pipe)	2,395 lb	1086 kg
BATTERY (2 USED)		
SAE reserve capacity rating	195 min	
SAE cold crank rating @ 0°F (-18°F)	950 amps	
NOISE LEVEL		
Operator sound	86 dBA	
Operator sound w/cab	80 dBA	
Exterior sound power	104 dBA	

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.





### THE DITCH WITCH HDD SYSTEM INCLUDES:



#### **HDD TOOLING**

For your directional drill, we offer a complete line of genuine Ditch Witch drill bits, HD backreamers, drill pipe, and beacon housings, the most reliable and durable in the horizontal directional drilling industry.



#### **MUD MIXERS**

Ditch Witch fluid-management systems include the innovative FM13V, a fluid-mixing system that features a pump that lubricates itself during mixing and works so efficiently that it delivers 20 percent more fluid than other models.



#### **VACUUM EXCAVATORS**

Ditch Witch vacuum excavators are designed for a tremendous range of soft-excavation and cleanup tasks, including all manner of non-hazardous spills in and around the directional drilling jobsite. They're the most powerful, efficient and quiet vac systems on the market.

