



flexiform  
credenzas

Crown  
Commercial  
Service  
*Supplier*

**office /domestic  
sleek and smooth credenzas  
with 2, 3 or 4 doors**

**introducing the  
flexiform credenza.**

**flexiform**



Credenzas are available with 2, 3 and 4 door units with a choice of hubless castors or A frame legs



# credenza

Our credenzas are available in a powder coated paint with 2, 3 or 4 compartments with various leg styles available, internal components included as standard.

## FEATURES & BENEFITS

- 2, 3 or 4 door credenzas.
- Hubless castor feet available on 2 and 3 door powder coated units with overall height of 620mm.
- Optional angled 'A' leg feet on all units raising the height to 740mm.
- Push-to-open mechanism on powder coated units.
- Soft close hinges.
- Complete with internal shelf (1 per door compartment).
- Powder coated paint finish available in a wide range of finishes including white, pale grey, silver, graphite grey and black.
- Curved decorative end panels with optional contrasting finish.
- Inset 25mm MFC top with 2mm ABS edge in a choice of white, grey, oak, walnut, beech or maple. Contrasting edge strips available on request.



Above top: Ferro gooseneck handle doors  
Above bottom: castor foot option



# lets get a little technical

---

## **CREDENZA UNIT**

14swg to 20swg depending upon structural requirements of selected cabinet. Non-locking doors with soft close hinges. A choice of 2 legs styles; angled (bringing the unit up to 740mm high) and hubless castors. Angled legs are constructed using 14swg 60mm x 30mm steel tube with feet levellers. Door compartments are complete with a central shelf.

---

## **WARRANTY**

Credenza storage comes with a minimum warranty of 10 years from the date of installation.

## **DIMENSIONS**

All credenzas are 515mm deep, and either 620mm high (castors) or 740mm (angled 'A' legs). The 2 compartment credenzas are 1088mm wide. 3 compartment credenzas are 1600mm wide and 4 compartment credenzas are 2216mm wide.

---

## **WORKSURFACES**

FSC®-C015991 certified. Our credenza worksurfaces are 25mm melamine faced chipboard (MFC) with 2mm ABS matching edging as standard. Tops can be supplied with contrast edging. Our tops meet British standard 476 class 1 surface spread of flame, and E1 European standards on Formaldehyde emissions. Alternative tops including laminate can also be supplied, please contact a Flexiform representative on 01274 706206 for more information.

---

## **AFTERCARE**

Due to their resistant surfaces, our worktops do not require any special maintenance. For light soiling, clean with a paper towel, soft clean cloth (dry/damp) or sponge. If using a damp cloth, dry the surface with an absorbent paper towel or microfiber cloth. For normal soiling, clean with warm water, a clean rag, microfiber cloth, soft sponge or soft brush. Use non-abrasive domestic cleaners, remove all traces of cleaning agent with fresh water, and dry the surface with an absorbent cloth or paper towel. Please ensure no liquid accesses the power modules during cleaning. If this occurs, isolate from the electrical supply immediately and consult a qualified electrician.







#### YORKSHIRE HQ

Flexiform  
1392 Leeds Road  
Bradford  
West Yorkshire  
BD3 7AE

t: 01274 706206

#### LONDON

Flexiform  
1st Floor  
45 Gee Street  
London  
EC1V 3RS

t: 02033 010436

#### SCOTLAND

Flexiform  
2B Young Square  
Brucefield Industry Park  
Bellsquarry, Livingston  
EH54 9BX

t: 01506 416410

Find us online:



Company Registration Number: 02542123

**flexiform**  
[www.flexiform.co.uk](http://www.flexiform.co.uk)