

# TEC-GUARD

# ARMOR

## TEC-GUARD SYNTHETIC BLEND FULL SYNTHETIC PASSENGER CAR MOTOR OILS



TEC-GUARD® Armor Full Synthetic 0W-20 is an advanced synthetic engine oil designed to maximize engine protection and enhance fuel economy. It is backward compatible with earlier API/ILSAC performance levels.

Meets or exceeds the following performance requirements and industry specifications: FORD® WSS-M2C947-A, FORD® WSS-M2C947-B1, ILSAC GF-5, ILSAC GF-4, ILSAC GF-3, API SN PLUS, API SN, GM® 6094M, GM® 4718M, CHRYSLER® MS-6395, GM® Dexos1™ Gen 2. Always consult your owner's manual for specific recommendations.

- Low viscosity, for gasoline engines
- Excellent thermal and oxidation stability
- Excellent low temperature capabilities

Test Method		Product Numbers	
NOVACK Volatility	<13%	Bulk	10425204900W20
ASTM D93 - Flash Point, °C	200	Drum	10425214900W20
ASTM D97 - Pour Point, °C	-51	Pail	10425244900W20
ASTM D445 - Viscosity @ 40° C, cST	42.7	Tote	10425204900W20
ASTM D445 - Viscosity @ 100° C, cST	8.1	4/1 Gallon	10425114900W20
ASTM D2270 - Viscosity Index	168	12/1 Quart	10425264900W20
ASTM D896 - TBN	7.3		

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.

TEC-GUARD

1320 1st Street • Rock Island, IL 61201 309-788-5631 • [www.tec-guard.com](http://www.tec-guard.com)