

## Elastomeric Bitumen Sealant

Adawall Elastomeric Bitumen Sealant is a bituminous rubber sealant for sealing line drainage units and general jointing/waterproofing of construction products. It is in a ready to use cartridge and applied with a sealant gun.

### CHARACTERISTICS

- Good adhesion on bituminous surfaces
- Easy to apply
- Can be applied on wet surfaces (even under water)
- Excellent slump resistance
- Accommodates movement up to 10%

### APPLICATION EXAMPLES

- sealing of gaps and cracks and connection joints between drains
- sealing line drainage joints in concrete and steel drainage units

**PACKAGING** Cartridge of 310 ml

**COLOURS** Black

**SHELF LIFE** 1 year in unopened packaging in a cool and dry storage place.

### TECHNICAL DATA

**Base** : Bituminous Elastomere

**Consistency** : Stable Paste

**Curing sytem** : Physical Drying

**Skin formation** : Surface Dryness after 20 min.

**Curing rate** : Does not apply

**Hardness** : Does not apply

**Shrinkage** : ca 11 %

**Specific gravity** : ca 1.25 g/ml

**Temperature resistance** : - 35°C until +130°C

**Maximum allowed movement** : 10 %

### INSTRUCTIONS FOR USE

**Surface preparation** : Clean, free of dust and grease. May be wet.

**Application method** : Mastic gun

**Application temperature** : +1°C until + 30°C

**Clean with** : White Spirit immediately after application

### JOINT DESIGN

**Minimum width** : 5 mm

**Maximum width** : 30 mm (3 pass method on larger joints)

**Minimum depth** : 5 mm

**Recommendation** : Joint Depth = Joint Width

**SAFETY RECOMMENDATIONS** Apply the usual industrial hygiene.