

QUIET ZONE

Laminate and Wood Products

- ◆ Improves the comfort of all laminate and engineered wood products
- ◆ Reduces foot fall noise IIC 70 STC 71
- ◆ MB protects flooring products from water damage
- ◆ Includes lip & tape
- ◆ CRI Certification
- ◆ Made in Canada/North America



ACOUSTICAL UNDERLAYMENT

SPECIFICATIONS

THICKNESS	2.2 mm
DENSITY	14 lbs /ft ³
CONTENT	100% Virgin SBR Synthetic Rubber
FILM	Moisture Block with lip & tape (0.076 mm)
ROLL WIDTH	3 FT
ROLL LENGTH	33 FT
ROLL WEIGHT	13.5 LBS
AREA / ROLL	100 SQ FT
PALLET	48 ROLLS 4,800 SQ FT
TOLERANCE	+/- 10%



FEATURES & BENEFITS

GREEN FEATURE

Made with 100% virgin SBR synthetic rubber

SUITABILITY

Quiet Zone is suitable for all floating laminate and engineered wood floors. It is ideal for concrete and other subfloors as well as below-grade installations.

SOUND ABSORPTION

Quiet Zone will significantly diminish impact sound. Sound transmission class: (STC): 71
Impact Insulation Class (IIC): 70

WATER RESISTANCE Zero moisture penetration

RECYCLABLE Quiet Zone is 100% recyclable

EASY INSTALLATION

Superior density allows the Quiet Zone to lay flat during installation. Quiet Zone features our Moisture Block Seam Lock which makes it easy to seam joints. A vapor barrier poly strip along one edge is coupled with a strip of two-sided tape along the other edge. Expose the tape by removing the protective strip, overlap and press.

SUBFLOOR IMPERFECTIONS

With a minimum density of 14 lbs/ft³ (224 kg/m³) Quiet Zone supports the laminate floor and is flexible enough to handle any minor subfloor imperfections.

WARRANTY 27 Year limited warranty
3 Year commercial warranty