



















LED Surface-mount Cylindrical Downlight						CE / RoHs / TUV / SAA Certification	
Picture	Item	Model.No	Technology Specification			Size Picture	Lifud+ CREE
	LED Surface-mount Downlight	SL-SM-B10R	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w	
			Power:	10W	Size:	Φ90*H90mm	
			LED Chips:	CREE 1pcs	Install:	Surface Mounted	
			CCT:	3000K / 4000K / 5000K	CRI:	>90	
			Beam Angle:	50°	IP:	20	
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI	
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM	18Pcs/Ctn 16KG/Ctn
	LED Surface-mount Downlight	SL-SM-B15R	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w	
			Power:	15W	Size:	Φ110*H120mm	
			LED Chips:	CREE 1pcs	Install:	Surface Mounted	
			CCT:	3000K / 4000K / 5000K	CRI:	>90	
			Beam Angle:	50°	IP:	20	
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI	
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM	18Pcs/Ctn 20KG/Ctn
	LED Surface-mount Downlight	SL-SM-B25R	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w	
			Power:	25W	Size:	Φ130*H152mm	
			LED Chips:	CREE 1pcs	Install:	Surface Mounted	
			CCT:	3000K / 4000K / 5000K	CRI:	>90	
			Beam Angle:	50°	IP:	20	
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI	
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM	18Pcs/Ctn 24KG/Ctn

	LED Surface-mount Downlight	SL-SM-B35R	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w	
			Power:	35W	Size:	Φ170*H185mm	
			LED Chips:	CREE 1pcs	Install:	Surface Mounted	
			CCT:	3000K / 4000K / 5000K	CRI:	>90	Packaging : 38*38*40cm
			Beam Angle:	50°	IP:	20	
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI	
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM	
	LED Surface-mount Downlight	SL-SM-B45R	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w	
			Power:	45W	Size:	Φ193*H193mm	
			LED Chips:	CREE 1pcs	Install:	Surface Mounted	
			CCT:	3000K / 4000K / 5000K	CRI:	>90	Packaging : 38*38*40cm
			Beam Angle:	50°	IP:	20	
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI	
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM	
	LED Surface-mount Downlight	SL-SM-B10S	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w	
			Power:	10W	Size:	Φ90*H90mm	
			LED Chips:	CREE 1pcs	Install:	Surface Mounted	
			CCT:	3000K / 4000K / 5000K	CRI:	>90	Packaging : 32*32*22cm
			Beam Angle:	50°	IP:	20	
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI	
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM	
	LED Surface-mount Downlight	SL-SM-B20S	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w	
			Power:	20W	Size:	Φ110*H120mm	
			LED Chips:	CREE 1pcs	Install:	Surface Mounted	
			CCT:	3000K / 4000K / 5000K	CRI:	>90	Packaging : 37*37*28cm
			Beam Angle:	50°	IP:	20	
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI	
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM	

	LED Surface-mount Downlight	SL-SM-B30S	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w		
			Power:	30W	Size:	Φ130*H135mm		
			LED Chips:	CREE 1pcs	Install:	Surface Mounted		
			CCT:	3000K / 4000K / 5000K	CRI:	>90		
			Beam Angle:	50°	IP:	20		
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI	Packaging : 44*44*36cm	
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM	18Pcs/Ctn 24KG/Ctn	
	LED Surface-mount Downlight	SL-SM-B40S	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w		
			Power:	40W	Size:	Φ165*H165mm		
			LED Chips:	CREE 1pcs	Install:	Surface Mounted		
			CCT:	3000K / 4000K / 5000K	CRI:	>90		
			Beam Angle:	50°	IP:	20		
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI	Packaging : 35*35*35cm	
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM	8Pcs/Ctn 12KG/Ctn	