## OVERLIGHT

### **OTG**

OVERLIGHT is the new generation of OTG (over the glasses). Compact and attractive, they guarantee maximum safety for all, including wearers of prescription glasses.







- **+ PIVOTING TEMPLES**
- + DESIGN



# OVERLIGHT

**OTG** 

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
OVERLIGHT	Clear - L	OVLITLPSI	2C-1,2 😭 1 FT €€	<b>≅</b> EN166 FT <b>C€</b>	Anti-scratch/anti-fog

#### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

- **F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

#### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- **F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

#### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE				
	OVLITLPSI			
Individual plastic bag	3660740006495			
10 safety spectacles per box	3660740106492			
180 safety spectacles per outer pack	3660740206499			
300 safety spectacles per outer pack	-			

CHARACTERISTICS				
LENSES	PC - 2,4 mm - Curve 4			
FRAME	PC			
TEMPLES	PC			
STRAP	Non applicable			
FOAM	Non applicable			
SPARE LENSES	No			











04/11/2015

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

