

# GÖLZ®



**Hand-Held Power Tools  
for Diamond Tool Operation**

[www.golzgroup.com](http://www.golzgroup.com)

## Powerful Wall Chaser - Designed for your safety and comfort.

Operates with 2 diamond blades up to a max. cutting width of 46 mm and a max. cutting depth of 45 mm.

### Quick and easy to use in

- Sandstone
- Soft bricks
- Poroton
- Hard bricks
- Limestone
- Clinker
- Concrete

### Features

- Softstart electronic
- Thermal overload
- Overload LED
- Easy cutting depth adjustment
- Easy tool change
- 35 mm vacuum hose connector

### Advantages

- Cuts 15mm close to a wall
- Ergonomical Handles
- Easy handling
- Steppless cutting depth adjustment
- Easy handling by big switches and buttons
- Perfect dust absorbtion



Specifications	GÖLZ SF150
Operation	Dry only
Motor	230 V, 50 Hz
Power	2,3 kW
RPM	4.300 min <sup>-1</sup>
max. Blade Ø	150 mm
Arbor hole Ø	22,23 mm
Max cutting depth	45 mm
Max cutting width	46 mm
Weight	5,8 kg
<b>Order number</b>	<b>SF 150</b>

Accessories	Order number
Dry Vac Starmix 1625	0295 100 1000

## Electrical Cut Off Saw for wet an dry operation - Vacuum adaptor for slurry and dust control - the allround saw for most of your sawing requirements up to a cutting depth of 130 mm (5 inch)

Powerful 2,7 kW Electri-Cut Off Saw - 350 mm (14 inch) blade and blade guard with integrated vacuum adaptor. The anti-clockwise rotating blade guarantees best dust and slurry control by connecting a vacuum cleaner.

### Quick and easy to use in

- All kinds of openings in concret or brick walls
- Cutting pipes, concrete, stone, clinker and brick

### Features

- 2,7 kW electric motor with soft start electronic
- Thermal overload protection
- Easy cutting depth adjustment
- Easy tool change
- 35 mm vacuum hose connector
- Adjustable blade guard and handles
- Easy to operate by extra wide guiding wheels



Specifications	GÖLZ ES350
Operation	Dry and Wet
Motor	230 V, 50 Hz
Power	2,7 kW
RPM	2.200 min <sup>-1</sup>
max. Blade Ø	350 mm
Arbor hole Ø	25,4 mm
Max cutting depth	130 mm
Weight	12,5 kg
<b>Order number</b>	<b>ES350</b>

Accessories	Order number
Cutting depth limiter	0295 150 1310
Close to wall cutting adapter	0295 150 1311

## Powerful Handsaw for various cutting applications in the general construction business up to a max cutting depth of 158 mm (6 inch)

Powerful, 3 kW Handsaw with 400 mm Diamond blade. The perfect and safe solution for your convenience.

### Quick and easy to use in

- Wall cutting jobs for doors and windows, in brick and concrete, soft and sandstone, tiles and natural stone

### Features

- 3 kW-Electric motor with softstart electronic, Electronic overload protection and PRCD for operators safety
- Allows precise cutting by guiding wheels
- Cutting depth adjustable
- Individually adjustable handles
- Only for wet cut applications



Specifications	GÖLZ HE160	GÖLZ HE160F
Operation	Standard	Flush cutting
Motor	230 V, 14 A, 50 Hz	
Power	3,0 kW	
RPM	1.770 min <sup>-1</sup>	
max. Blade Ø	400 mm	
Arbor hole Ø	25,4 mm	
max cutting depth	158 mm	
Weight	11 kg	
<b>Order number</b>	<b>0295 150 1087</b>	<b>0295 150 1088</b>

Accessories	Order number
Blade guard with flange for flush cutting	0295 150 1090
Carrying case	0295 150 1091
Cutting depth limiter	BD505101



## Robust and powerful - perfect for your grinding and polishing requirements for small jobs. Easy polishing - grinding - cleaning

### Perfect surface preparation in concrete

### Features

- Softstart and surface speed control
- Thermal overload protection and LED
- 125 mm dust collector cover, front can be opened to operate direct against a wall
- 35 mm vacuum hose connector
- Handles adjustable for your comfort.



Specifications	GÖLZ SM125
Motor	230 V, 50 - 60 Hz
Power	1.800 Watt
RPM	10.000 min <sup>-1</sup>
Cup Grinder Ø	125 mm
Arbor hole Ø	22,23 mm
Weight	5,4 kg
<b>Order number</b>	<b>SM 125</b>

Accessories	Order number
Dry Vac Starmix 1625	0295 100 1000

## Single Speed Dry Drilling Hand Held Core Drill. Dry drilling with and without dust collection for switches and junction boxes.

- Easy to use single speed drill for holes up to 160 mm with damond core bits
- No vibrations, no impact drilling
- Dry drilling in soft bricks and blocks, poroton, porous concrete, sand-lime bricks
- Thermal overload protection
- Accessories: Dry core bits, Dustcollector, see Diamondtools catalogue (page 29)



Specifications	GÖLZ TB10S
Operation	Dry
Style	D-handle
Motor	Single phase, 230 V, 50 Hz
Power	1,8 kW (1,2 kW)
RPM	1200 min <sup>-1</sup>
Gears	1
Bit-ø in Brickwork (Dry)	Ø up to 160 mm
Drill bit connection	M18 male
Water connection	---
Ring collar Ø	53 mm
Dimensions (LxWxH)	460x95x320 mm
Weight	5,7 kg
<b>Order number</b>	<b>0295 007 6050</b>

## 2-Speed Heavy Duty Hand Held Core Drill. Compact Core Drill for anchor and installation holes

- 2-Speed Gearbox
- Drill Bit connection 1 1/4" UNC + R 1/2" oder R1/2"
- PRCD integrated in the power cord
- Electronic softstart and overload protection
- FB23P - wet & dry use up to ø200 mm
- FB25P- wet use, up to ø70 mm
- Horizontal & Vertical Bubble Levels
- Toolset SW32 & SW41 inclusive



Specifications	GÖLZ FB23P	GÖLZ FB25P
Operation	Wet & Dry	Wet
Style	Pistol-handle	
Motor	Single phase, 230 V, 50 Hz	
Power	2,2 kW (1,5 kW)	
RPM	520/1400 min <sup>-1</sup>	1400/2900 min <sup>-1</sup>
Gears	2	
Bit-ø in Concrete (Wet)	10 - 110 mm – Hand held 10 - 160 mm – Stand mounted	10 - 70 mm - Hand held 10 - 70 mm - Stand mounted
Bit-ø in Brickwork (Dry)	20 - 200 mm - Hand held, (Optional dust collector)	
Drill bit connection	1 1/4"UNC + R1/2"	R1/2"
Water connection	Gardena	
Ring collar Ø	60 mm	
Dimensions (LxWxH)	396x100x295 mm	337x100x295 mm
Weight	5,9 kg	5,6 kg
<b>Order number</b>	<b>0295 007 5020</b>	<b>0295 007 5025</b>

Accessories	Order number
Carrying Case	<b>B802223</b>
Drill Stand DS160S	<b>0295 110 9010</b>
Drill Stand KB125	<b>0295 125 6000</b>



## 3-Speed Heavy Duty Hand Held Core Drill. Powerful core drill with full metal housing for hand held or drill stand operation

- 3-Speed Gearbox
- Drill Bit connection 1 1/4" UNC + R 1/2"
- PRCD integrated in the power cord
- Softstart and thermal overload protection
- FB33P - wet use up to ø160 mm
- FB33S - wet & dry use up to ø200mm
- Horizontal & Vertical Bubble Levels
- Toolset SW32 & SW41 inclusive



Specifications	GÖLZ FB33P	GÖLZ FB33S
Operation	Wet	Wet & Dry
Style	Pistol-handle	D-handle
Motor	Single phase, 230 V, 50 Hz	
Power	2,2 kW (1,5 kW)	
RPM	520/1400/2900 min <sup>-1</sup>	
Gears	3	
Bit-ø in Concrete (Wet)	20 - 110 mm - Hand held 20 - 160 mm - Stand mounted	20 - 110 mm - Hand held 20 - 160 mm - Stand mounted
Bit-ø in Brickwork (Dry)	20 - 200 mm - Hand held (Optional dust collector)	20 - 200 mm - Hand held, Dust collector integrated
Drill bit connection	1 1/4" UNC + R1/2"	
Water connection	Gardena	Geka-coupling
Ring collar Ø	60 mm	
Dimensions (LxWxH)	422x100x295 mm	562x100x150 mm
Weight	6,5 kg	
<b>Order number</b>	<b>0295 007 5064</b>	<b>0295 007 5073</b>

Accessories	Order number
Carrying Case	<b>B802223</b>
Drill Stand DS160S	<b>0295 110 9010</b>
Drill Stand KB125	<b>0295 125 6000</b>



## 3-Speed Hand Held Core Drill. For hand held or drill stand operation

- 3-Speed Gearbox
- Drill Bit connection 1 1/4" UNC + R 1/2"
- PRCD integrated in the power cord
- Thermal overload protection
- Wet & Dry use in Concrete and Brickwork
- Horizontal & Vertical Bubble Levels
- Toolset SW32 & SW41 inclusive



Specifications	GÖLZ FB20P
Operation	Wet & Dry
Style	Pistol-handle
Motor	Single phase, 230 V, 50 Hz
Power	2,2 kW (1,5 kW)
RPM	450/1200/2500 min <sup>-1</sup>
Gears	3
Bit-ø in Concrete (Wet)	20 - 110 mm - Hand held 20 - 160 mm - Stand mounted
Bit-ø in Brickwork (Dry)	20 - 200 mm - Hand held
Drill bit connection	1 1/4" UNC + R1/2"
Water connection	Gardena
Ring collar Ø	60 mm
Dimensions (LxWxH)	432 x 119 x 272 mm
Weight	6,7 kg
<b>Order number</b>	<b>0295 007 5080</b>

Accessories	Order number
Carrying Case	<b>B802223</b>
Drill Stand DS160S	<b>0295 110 9010</b>
Drill Stand KB125	<b>0295 125 6000</b>





**GÖLZ® - Group**

**GÖLZ GmbH**

**Dommersbach 51 | 53940 Hellenthal-Blumenthal**

**Telefon +49 2482 12-0 | Fax +49 2482 12-222**

**info@goelz.de | www.goelz.de**

**ÖSTERREICH**

**Gölz Ges.m.b.H.**

**Samstr. 52 | A-5020 Salzburg**

**Telefon +43 662 438175 | Fax +43 662 430734**

**info@goelz.at | www.goelz.at**

**FRANKREICH**

**Gölz S.A.S.**

**Espace Laiterie | 1, rue de la Mairie | F-67370 Berstett**

**Telefon +33 3 88 59 43 00 | Fax +33 3 88 59 47 77**

**info@golz.fr | www.golz.fr**

**GROSSBRITANNIEN**

**Golz (UK) Ltd.**

**Unit A5 | Springhead, Enterprise Park**

**Northfleet | Kent DA 11 8HB**

**Telefon +44 1 474 321 679 | Fax +44 1 474 321 477**

**info@goelz.co.uk | www.golzuk.com**

**BENELUX**

**Gölz Benelux N.V. Belgien**

**Eupener Straße 61 | B-4731 Raeren-Eynatten**

**Telefon +32 87 55 23 49 | Fax +32 13 78 33 28**

**benelux@goelz.de | www.golzgroup.com**

**USA**

**Golz L.L.C.**

**5860 East Osage Ridge Lane | Columbia MO 65203-6018**

**info@golzusa.com | www.golzgroup.com**



**Your GÖLZ dealer**

