UPRIGHT CATERING CHILLERS

Upright Solid Door Catering Chillers







High capacity single and double door catering chillers.

Key Features of Catering Chillers

- Available as a single door (SDCC1) or double door (SDCC2) chiller
- Temperature range: -2/+10°C
- Fully automatic operation
- Digital temperature display
- Fan assisted cooling
- Fully adjustable shelving
- Interior light
- Suitable for fresh meat
- Refrigerant: R134A
- 2/1 gastronorm size
- Type of defrost: Electric
- Number of shelves: 3 per door Operating range: Up to 40°C ambient
- Exterior Finish: Attractive stainless Steel
 - interior/exterior
- Power required: 13 amp supply
- Lock fitted as standard

Technical specifications for Catering Chillers

Product Code	SUC1 (Single Door)	SUC2 (Double Door)
Total Width	740 mm	1480 mm
Total Depth	850 mm	850 mm
Total Height (Inc Castors)	2010 mm	2010 mm
Storage Capacity	650 ltr	1410 Ltr
Power Supply Required	13 amp	13 amp
Nominal Power Consumption	350 Watts	650 Watts
Temperature Range	-2°C/+10°C	-2°C/+10°C
Interior/Exterior finish	Stainless Steel	Stainless Steel
Number of shelves	3 shelves per door	3 shelves per door
Refrigerant Type	R134A	R134A