

SLIM 617



System

- CPU	Intel® Atom™ D2550 i processor
- Chipset	Intel® NM10
- Memory type	Dual Channel DDR3 800MHz SDRAM MAX 4GB
- Ethernet	GbE LAN1: Intel® 82574L; LAN2: Intel® 82853V

I/O

- Serial ports	2 x RS232 - RS232/422/485
- USB ports	4 USB 2.0
- Audio	3 (Mic-in, Line-out, Line-in)
- Video input	1 HDMI - 1 DVI - 2 PS/2
- Ethernet	2 x RJ45
- Power connection	1 x 4 pin DC terminal block 1 x 2 pin remote power switch 2 x LED light for power and HDD indication

Storage Space

- HDD	2 x 2,5" SATA3 (Support RAID 0,1) easily accessible design
- Mini-PCIe	1 x mSATA slot (full-size)
- M2	B key for SSD and 3G supported (type: 2242 ,2280mm)

Expansion Slot

-Mini-PCIe	1, F/S Mini-PCIe slot (with mSATA supported)
-PCIe	2 PCIe 8X or 3 PCI (optional)

Environment

Operating temperature	0 ~ 50 °C
Storage temperature	-30 ~ 70 °C
Storage humidity	10 to 90% @ 40 °C - non condensing
Certification	CE

Display

- Display type	17" TFT-LCD
- Max. resolution	1280 x 1024
- Max. color	16,7 M
- Luminance (cd/m2)	350
- View angle (H°/V°)	80 / 80 (H) 60 / 80 (V)
- Contrast	1000 : 1

Touch Screen

- Type	Project capacitive optional resistive
- Interface	USB
- Light transmission	Project capacitive: 90% resistive: 80%

Mechanical

- Construction	Aluminum front bezel optional INOX 316
- IP Rating	Front bezel IP66
- Mounting	Panel mounting
- Dimension (mm)	452 x 356 x 93.5
- Net weight	-

Supported Operating System

- Windows 7 Professional (32bit)
- Windows XP Professional (32/64bit)
- Windows 10 IOT Enterprise (32/64bit)

