

Tri-Flex[®] Wire Rope Slings

Composed 3 Parts of EIP Rope	Design Factor 5.1: Rated Loads in Tons			Finished Diameter	Weight per Ft. Lbs.
	Vertical	Choker	Vertical Basket		
1/4	1.7	1.3	3.4	1/2	0.44
5/16	2.6	1.9	5.2	5/8	0.68
3/8	3.6	2.7	7.2	3/4	0.99
7/16	4.9	3.7	9.8	7/8	1.33
1/2	6.4	4.8	12.8	1	1.75
9/16	8	6	16	1 1/8	2.24
5/8	9.9	7.4	19.8	1 1/4	2.73
3/4	14	10.5	28	1 1/2	3.9
7/8	19	14.3	38	1 3/4	5.4
1	24.8	18.6	49.6	2	7
1 1/8	31.2	23.4	62.4	2 1/4	8.9
1 1/4	38.4	28.8	76.8	2 1/2	10
1 3/8	46	34.5	92	2 3/4	13.3
1 1/2	55	41.2	110	3	15.8
1 3/4	73	54.8	146	3 1/2	21.5
2	95	71.2	190	4	28
2 1/4	118	88.5	236	4 1/2	35.6
2 1/2	145	109	290	5	44