Offering the world a better weld for over 80 years



RW Series High Production Ring Welders


4 Models: From .030" (.762mm) to .500" (12.7mm) diameter Steel

Micro's RW Series, a totally new generation of butt welders, is ideally suited for either high speed piece production butt welding or just welding wire from coil to coil. Micro Products, the leader in butt welding technology, has used every resource available in the development of the RW Series. We went back to the drawing board and solicited input from everyone involved - from production to maintenance, to engineers, to the operators themselves on what features they desired in an optimum butt welder - including:

- Superior repeatability
- Excellent weld integrity
- · A minimum of moving parts
- Straight slide welding platen
- A minimum of maintenance
- High speed

The result is a butt welder with exceptional speed and durability. Just "set it and forget it" for superior repeatability weld after weld after weld. High speed pneumatic clamping and upset mechanism with super smooth ball bearing straight slide shafts make this welder ideal for welding rings or other piece production jobs. But these same characteristics also make the RW series a perfect choice for butt welding from coil to coil.

For more information on our High Production Ring Welders or other butt welders, contact Micro-Weld.



RW Series Ring Welders - 4 Models See back for features & technical specifications

Phone: 1-800-872-1068 (in U.S.A.) or 630-406-9550 Email: info@micro-weld.com Web: www.micro-weld.com



Offering the world a better weld for over 80 years

High Production Ring Welders - 4 Models

Standard Features Include

4 Basic models with wire diameter ranges from .030" up to .500" steel wire, high speed clamping and upset mechanisms, super smooth ball bearing straight slide welding platen, Micro SCR Welding Control, heavy duty Micro-Weld welding transformer, fully enclosed heavy duty truck with swivel casters.

Micro-Weld's Welding Transformer

- · World famous for durability
- · Exceeds the most demanding specifications in the industry
- Extra heavy duty primary coil and secondary for long life and smooth delivery of power
- Extra capacity built in

Micro-Weld's SCR Welding Control Is the "Heart Of The System"

Provides pinpoint accuracy for the right amount of welding heat and welding cycle duration necessary to obtain high quality welds. Provides consistent repeatability weld after weld. Eliminates the mechanical heat selection switch and the mechanical contactor.

Micro-Weld's Dependability

The RW Series carries the Micro-Weld name, known worldwide for making the most durable, trouble-free, electric resistance welders on the market since 1928. Every possible advantage has been engineered "into it" so you get the most "out of it".

Micrometer Precision Electric Resistance Ring Welders

RW-1	RW-2	RW-3	RW-4
.030" to .187"	.080" to .250"	.187" to .375"	.250" to .500"
.762 to 4.749mm	2.032 to 6.35mm	4.749 to 9.525mm	6.35 to 12.7mm
230 Std. 460 Opt.	230 Std. 460 Opt.	460 Std. 230 Opt.	460 Std. 230 Opt.
60 Cycle	60 Cycle	60 Cycle	60 Cycle
16 KVA	46 KVA	75 KVA	150 KVA
Short Circuit Demand			
10 to 99%	10 to 99%	10 to 99%	10 to 99%
5 KVA	10 KVA	20 KVA	30 KVA
90 PSI	90 PSI	90 PSI	90 PSI
1 to 99 Cycles	1 to 99 Cycles	1 to 99 Cycles	1 to 99 Cycles
Pneumatic	Pneumatic	Pneumatic	Pneumatic
Enclosed	Enclosed	Enclosed	Enclosed
	.030" to .187" .762 to 4.749mm 230 Std. 460 Opt. 60 Cycle 16 KVA 10 to 99% 5 KVA 90 PSI 1 to 99 Cycles Pneumatic	.030" to .187" .080" to .250" .762 to 4.749mm 2.032 to 6.35mm 230 Std. 460 Opt. 230 Std. 460 Opt. 60 Cycle 60 Cycle 16 KVA 46 KVA Short Circuit De 10 to 99% 10 to 99% 5 KVA 10 KVA 90 PSI 90 PSI 1 to 99 Cycles 1 to 99 Cycles Pneumatic Pneumatic	.030" to .187" .080" to .250" .187" to .375" .762 to 4.749mm 2.032 to 6.35mm 4.749 to 9.525mm 230 Std. 460 Opt. 230 Std. 460 Opt. 460 Std. 230 Opt. 60 Cycle 60 Cycle 60 Cycle 16 KVA 46 KVA 75 KVA Short Circuit Demand 10 to 99% 10 to 99% 10 to 99% 5 KVA 10 KVA 20 KVA 90 PSI 90 PSI 90 PSI 1 to 99 Cycles 1 to 99 Cycles 1 to 99 Cycles

Dimensions & Weights Model **Height Overall** Welding Die Height Floor or Weight Bench Space **RW-1** 46" 44 1/2" 31" x 31" 280 lbs 113.03cm 78.74 x 78.74cm 127.27kg 116.84cm RW-2 44 1/2" 31" x 31" 46" 280 lbs 116.84cm 113.03cm 78.74 x 78.74cm 127.27kg **RW-3** 49" 44 1/2" 31" x 31" 550 lbs 78.74 x 78.74cm 113.03cm 124.46cm 250kg RW-4 49" 44 1/2" 31" x 31" 550 lbs 124.46cm 113.03cm 78.74 x 78.74cm 250kg



Visit Micro-Weld Website: www.micro-weld.com

Email: info@micro-weld.com


1886 E. Fabyan Parkway Batavia, Illinois 60510 USA Phone: 630-406-9550 • Fax: 630-406-9552

Features

- High speed clamping and upset mechanism
- · Choice of Micro SCR welding control
- Heavy duty welding transformer
 - Heavy duty cast headpiece
 - Straight slide welding platen
- Heavy duty fully enclosed truck with 4 swivel casters

Optional Features

- Special voltages
- 50 Hertz
- Pneumatic anneal mechanism
- Standard anneal mechanism
- Water cooling
- Bench mounting



Over 50 models of butt, flash & ring welders available
Excellent welds with consistency
Easy to operate

• Customer service & support worldwide

phone Toll-free: 1-800-872-1068 (U.S.A.) 630-406-9550

> email info@micro-weld.com

> web www.micro-weld.com

©2011 Micro Products Company



