

# XLE



The XLE makes your fun more fun and your work more productive. All your gear is locked up weather tight ready for the next challenge. Specifically engineered to be low on maintenance and high on reliability, the XLE's unique design delivers carefree towing and easy maneuverability. Top-notch components mean your XLE will provide years of service. Loaded with quality features not found on other trailers in its class, the XLE is an excellent value now and at resale time.

Trailers shown may feature optional equipment available at an additional charge.



Your Authorized United Trailers Dealer:

**BUILT FOR THE LONG HAUL**

# SPECIFICATIONS

## XLE

MODEL		XLE-46SA20	XLE-58SA3	XLE-510SA3	XLE-610SA3	XLE-612SA30
Body:	Length	6' 0"	8' 9"	10' 9"	10' 9"	12' 9"
	Width	4' 0"	5' 0"	5' 0"	6' 0"	6' 0"
Overall:	Length	9' 6"	11' 6"	13' 6"	13' 6"	15' 6"
	Width	5' 4"	6' 8"	6' 8"	7' 8"	7' 8"
	Height	5' 6"	7' 1"	7' 1"	7' 7"	7' 7"
Interior:	Length	5' 8"	8' 4"	10' 4"	10' 4"	12' 4"
	Width	3' 9"	4' 9"	4' 9"	5' 9"	5' 9"
	Height	3' 9-1/2"	5' 4-3/4"	5' 4-3/4"	5' 10-1/2"	5' 10-1/2"
Rear Door Opening:	Width	42"	54"	54"	66"	66"
	Height	42"	61"	61"	67"	67"
Platform Height		18"	18"	18"	18"	18"
Axles		Single	Single	Single	Single	Single
Axle Type		4" Drop	4" Drop	4" Drop	4" Drop	4" Drop
Suspension		Spring	Spring	Spring	Spring	Spring
Tire Size		ST145/R12	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Load Range		D	C	C	C	C
Wheel Bolt Pattern		5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5
Hitch Ball Size		2"	2"	2"	2"	2"
Hitch to Top of Ball		16"	16"	16"	16"	16"
Hitch Weight (% of Curb Weight)		10-15%	10-15%	10-15%	10-15%	10-15%
Avg Curb Weight (lbs.)		545	800	885	1015	1140
GVWR (lbs.)		2,000	2,990	2,990	2,990	2,990
GAWR (lbs.)		2,000	3,000	3,000	3,000	3,000
Avg. Payload Capacity		1455	2190	2105	1975	1850

Specifications and features subject to change without notice.

## STANDARD FEATURES

- Steel Unibody Construction
- Protective Undercoating
- Dexter Straight Axle w/ E/Z Lube Hubs (4' Wides)
- Dexter 4" Drop Spring Axles w/ E/Z Lube Hubs (5' & 6' Wides)
- 12" Radial Tires w/ White Mod Steel Wheels (4' Wides)
- 15" Radial Tires w/ White Mod Steel Wheels (5' & 6' Wides)
- 2" Coupler with Jack
- DOT Safety Chains
- 4-Way Trailer Plug
- 3" Tube Main Frame
- 24" On-Center Roof Tubes
- 24" On-Center Vertical Hat Posts
- 24" On-Center Crossmembers
- Clear LED Surface Mounted Tail & Clearance Lights
- 5.2mm Lauan Sidewall Liner
- 3/4" Engineered Wood Flooring
- (1) 12-Volt LED Dome Light w/ Switch
- .030 Smooth Aluminum Exterior (14 Colors Available)
- Screwed Exterior
- Smooth Aluminum Fenders
- 12" x .025 Aluminum Tread Plate Stoneguard
- Single Rear Door (4' and 5' Wides)
- Double Rear Doors (6' Wides)
- 1 Year Limited Warranty

