

GLASS MAINTENANCE

a guide for glass hygiene and maintenance

OTS

theservicecentre



BEFORE PLACING GLASSES INTO THE GLASSWASHER, PLEASE ENSURE TO

- MANUALLY REMOVE LIPSTICK - WE RECOMMEND ELIMINATOR
- POUR ANY DRINK RESIDUES DOWN THE SINK

CABINET GLASSWASHER OPERATION

1. Ensure that the machine is up to operating temperature.
2. Fill basket completely. **ONLY GLASSES.** No coffee cups or ashtrays.
3. Put in basket, close door and run cycle.
4. Visually check glasses at the end of cycle.
 - Is water running off glass as a sheet? if **YES** this is normal
 - Can you see droplets sticking to the surface? if **NO** this is not normal
 - Droplets indicate there is a problem. **Glasses require renovating**
5. Always use a specially formulated glass washing detergent and rinse aid.
6. Alternating chemical brands can cause crystallisation in the pump hoses.

RENOVATION

New glasses may be coated in lubricant used in glass manufacture. To remove this, **RENOVATE ALL NEW GLASSES BEFORE USE.**

Sugars, proteins, hop resins and detergent residues may gradually build up a film on the glass which may cause the beer foam to collapse.

TO PREVENT THIS GLASSES SHOULD BE RENOVATED REGULARLY

DAILY MAINTENANCE PROCEDURE

1. Switch off power.
2. Remove basket.
3. Remove plug and drain machine.
4. Remove and clean filters.
5. Top up chemicals.
6. Leave door open overnight.

WEEKLY MAINTENANCE PROCEDURE

1. Remove wash arms.
2. Remove and clean jets and nozzles.
3. Re-assemble.
4. Clean machine by running cycle with renovate.
5. Check water softener (if fitted)



“ new glasses may be coated in lubricant used in glass manufacture... ”

How to use Liquid Renovate

- Remove the detergent tube from the existing 5ltr container and replace the original screw cap.
- Place the detergent tube into the 5ltr container of Liquid Renovate.
- It may take up to 6 washes for Liquid Renovate to enter the wash tank.
- Load the glasses into the basket and wash in the normal manner. There may be an aroma of Chlorine (Bleach) in the atmosphere but there will not be any chemicals left on the glass as long as the glasswasher is operating properly.
- Renovate should be left on the machine until the glasses are clean and the water sheets off the glass (no raindrops). This will usually take about 2-3 days over busy periods (weekends).
- When renovation has been completed, the original glasswasher detergent should be re-installed.

If after renovating, your glasses are still poor and they look cloudy, then this could be down to minerals in your water drying on the glass. A suitable water softener with regular monitoring will remove the limescale and calcium deposits and reduce scale build up inside the machine. Both machine and glasses will need less maintenance and you will see noticeable differences. You may even have a fault with your machine, get your glasswasher regularly checked, it will save you money in the long run.

when quality matters...

to place an order for chemical or Liquid Renovate
www.omegatec.co.uk Tel. 01978 437 002