CASIO_®

TE-3000S TE-4000F TE-4500F

Stylish EPOS terminals with flexible keyboard programming and a 5-colour backlit LCD screen to suit your specific business needs









TE-3000S TE-4000F TE-4500F

Equipped with a full range of advanced features to complement and expand your business

System configuration

A maximum of 32 terminals can be connected to consolidate sales data. Shared check tracking by up to 4 terminals and printer sharing up to 3 external printers can be set up easily using CAT5 or CASIO inline cables. (Optional Arc-net communication board required.)

Operator display

5.2-inch LCD with 2 x 16 characters ensuring the operator a clear view of all transaction information.



10 digit, 7 segment display space for numeric entries.
5-colour backlight enabling the operator to select a display illumination colour to suit the store image. Scheduler function permitting switching among both backlight colours and menu levels to differentiate items or prices (between Lunch and Dinner menus, for example).

Tilt screen operator display

Tilt screen function allows the operator to adjust the display to the optimal angle for comfortable readability.



Printer

Silent 58mm thermal receipt and journal printer with fast line printing.
Receipt auto cutter installed. Drop-in paper loading for easy paper roll handling. Graphic/watermark logos presenting an affluent image.



Data storage

CF (Compact Flash) card interface for data back-up and installed as standard equipment.



PODIS RESCRIPPITE ASSAMENT PROBABILITY AND COURS OF THE PROBABILITY OF THE

Serial ports

3 x RS232c ports for direct communication with computer, modem and external and slip printers.

Com2 with +5v power provided for optional barcode scanner.

Scanning

Barcode scanning for quick, accurate registration available with optional barcode scanner.

Keyboards

TE-3000S: raised keyboard; TE-4000F: combination keyboard with reversible flat keyboard; TE-4500F; full flat keyboard.

Reports

- Financial
- Transaction
- Department, sub-department PLU
- Table analysis
- Open check
- Monthly
- · Hourly, hourly item
- Employee (time and attendance) •

Flash

- Group
- Clerk
- Scanning PLU
- Mix & match
- Not-found PLU

| 2 | 10-10-2010 SUNI | 21:10 | Mode symbol/date/time | K SMITH | MCW01 | C00045 | Clerk descriptor/Mo-No./consecutive No. | 2 | SCAN PLU | C0011-Report header/Title/reset counter/Z only/ 2001026 | Report header/Title/reset co

Options

Model No.	Product	
RK-3	1MB memory module	
I/O-PB-17	Arc-net communication board	
UP-360	External thermal printer	
SP-1300	Slip printer	

Specifications

Displays	Operator	5.2-inch LCD with color backlight 2 x 16 characters / 10 digits, 7 segments
	Customer	Pop-up 10-digit numeric LED
Printer	Printing method	Two-station thermal printer
	Printing speed	20 lines/sec. (max.)
	Paper width	58mm +0/-1mm x 83 Φ
	Receipt auto cutter	Yes
	Paper-loading	Drop-in paper-loading
Memory backup		90-day data back-up (vanadium lithium battery)
Power consumption	AC 120V	Operating 0.9A, Standby 0.2A
	AC 230V	Operating 0.5A, Standby 0.11A
Operating environment	Temperature	0 to 40 ℃
	Humidity	10 to 85%RH
Dimensions (W x D x H)		410 x 491 x 215(292)*mm
Weight		Approx. 9 kg



www.casio.co.



Retail Point services Ltd



