



SAFETY DATA SHEET
600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name 600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455
Product No. 600/V607/39

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses As a paint thinner/cleaner

1.3. Details of the supplier of the safety data sheet

Supplier TEAL & MACKRILL LIMITED
LOCKWOOD STREET
HULL
HU2 0HN
+44(0)1482 320194(T)
+44(0)1482 219266(F)
info@teamac.co.uk
Contact Person Technical Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

1.4. Emergency telephone number

+44 (0) 1482 320194 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Liq. 3 - H226
Human health Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; STOT SE 3 - H335; Asp. Tox. 1 - H304
Environment Not classified.

Classification (1999/45/EEC)

Xn; R20/21, R65. Xi; R36/37/38. R10.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Contains XYLENE, MIXED ISOMERS

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

Hazard Statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.

600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455

H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.

Precautionary Statements

P102 Keep out of reach of children.
 P101 If medical advice is needed, have product container or label at hand.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P313 Get medical advice/attention.
 P501 Dispose of contents/container in accordance with national regulations.

Supplementary Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing vapour/spray.
 P264 Wash contaminated skin thoroughly after handling.
 P321 Specific treatment (see medical advice on this label).
 P370+378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
 P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P302+352 IF ON SKIN: Wash with plenty of soap and water.
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P322 Specific measures (see ... on this label).
 P331 Do NOT induce vomiting.
 P332+313 If skin irritation occurs: Get medical advice/attention.
 P337 If eye irritation persists:
 P362 Take off contaminated clothing and wash before reuse.
 P363 Wash contaminated clothing before reuse.
 P403+233 Store in a well-ventilated place. Keep container tightly closed.
 P403+235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| | | |
|---|--|--|
| XYLENE, MIXED ISOMERS | | 60-100% |
| CAS-No.: 1330-20-7 | EC No.: 215-535-7 | Registration Number: 01-2119488216-32-xxxx |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 | Classification (67/548/EEC) Xn;R20/21,R65. Xi;R36/37/38. R10. | |

600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455

| | | |
|-------------------------------|-----------------------------|--------|
| 1-METHOXY-2-PROPANOL | | 10-30% |
| CAS-No.: 107-98-2 | EC No.: 203-539-1 | |
| Classification (EC 1272/2008) | Classification (67/548/EEC) | |
| Flam. Liq. 3 - H226 | R10 | |
| STOT SE 3 - H336 | R67 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES**4.1. Description of first aid measures**

General information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious.

Inhalation

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues. Place unconscious person on the side in the recovery position and ensure breathing can take place.

Ingestion

DO NOT induce vomiting. Get medical attention immediately. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position.

Skin contact

Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information

If adverse symptoms develop as described the casualty should be transferred to hospital as soon as possible.

4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media**

Extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

FLAMMABLE. Solvent vapours may form explosive mixtures with air.

Specific hazards

When heated and in case of fire, harmful vapours/gases may be formed.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Be aware of danger for fire to re-start. Cool containers exposed to flames with water until well after the fire is out. Do not allow runoff to sewer, waterway or ground.

Protective equipment for fire-fighters

Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455

Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Do not smoke, use open fire or other sources of ignition. Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Should be prevented from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

6.4. Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep upright. Store separated from: Oxidising material. Alkalis. Acids.

Storage Class

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 50 litres of liquids with a flashpoint below 32°C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage Description

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

| Name | STD | TWA - 8 Hrs | | STEL - 15 Min | | Notes |
|-----------------------|-----|-------------|-----------------------|---------------|-----------------------|-------|
| 1-METHOXY-2-PROPANOL | WEL | 100 ppm | 375 mg/m ³ | 150 ppm | 560 mg/m ³ | Sk |
| XYLENE, MIXED ISOMERS | WEL | 50 ppm | 220 mg/m ³ | 100 ppm | 441 mg/m ³ | Sk |

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455**XYLENE, MIXED ISOMERS (CAS: 1330-20-7)**

| DNEL | | | | |
|----------|-------------|------------|------------------|----------------|
| Consumer | Oral | Long Term | Systemic Effects | 12.5 mg/kg/day |
| Consumer | Dermal | Long Term | Systemic Effects | 1872 mg/kg/day |
| Consumer | Inhalation. | Long Term | Systemic Effects | 65.3 mg/m3 |
| Consumer | Inhalation. | Short Term | 260 | mg/m3 |
| Industry | Dermal | Long Term | Systemic Effects | 3182 mg/kg/day |
| Industry | Inhalation. | Long Term | Systemic Effects | 221 mg/m3 |
| Industry | Inhalation. | Short Term | 442 | mg/m3 |

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

No specific hygiene procedures noted, but good personal hygiene practices are always advisable, especially when working with chemicals.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

| | |
|-------------------------------|---------------------------------|
| Appearance | Clear liquid. |
| Odour | of solvents |
| Solubility | Immiscible with water |
| Relative density | 0.84 - 0.86 @ 25 C |
| Vapour density (air=1) | heavier than air |
| Vapour pressure | 7.5 mm Hg @ 20C |
| Viscosity | <30 seconds 3mm ISO cup s @25 C |
| Flash point (°C) | >21 CC (Closed cup). |
| Flammability Limit - Lower(%) | 0.8 |

9.2. Other information

| | |
|---------------------------------|-------------|
| Volatility Description | Volatile |
| Volatile By Vol. (%) | 100 |
| Volatile Organic Compound (VOC) | 860 g/litre |

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

No specific reactivity hazards associated with this product.

600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455**10.2. Chemical stability**

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Not determined.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with acids and oxidising substances.

10.5. Incompatible materials

Materials To Avoid

Strong alkalis. Strong acids. Strong oxidising substances.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Inhalation

Vapour from this chemical can be hazardous when inhaled. Vapour may irritate respiratory system or lungs.

Ingestion

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

Eye contact

May cause temporary eye irritation.

Health Warnings

This product has low toxicity. Only large volumes may have adverse impact on human health.

Route of entry

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

Medical Considerations

Skin disorders and allergies. Avoid vomiting and normal rinse of stomach because of risk of aspiration.

Toxicological information on ingredients.

600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455
XYLENE, MIXED ISOMERS (CAS: 1330-20-7)

Acute toxicity:

Acute Toxicity (Oral LD50)
4300 mg/kg Rat

Acute Toxicity (Dermal LD50)
> 1700 mg/kg Rabbit

Acute Toxicity (Inhalation LC50)
5000 ppmV (gas) Rat 4 hours

Serious eye damage/irritation:

Severe skin irritant; irritation of eyes is assumed. No testing is needed.

Respiratory or skin sensitisation:

Not sensitising.
Not Sensitising.

Carcinogenicity:

This substance has no evidence of carcinogenic properties.

Reproductive Toxicity:

This substance has no evidence of toxicity to reproduction.

Aspiration hazard:

Viscosity
Kinematic viscosity <= 20.5 mm²/s.
Inhalation
Harmful by inhalation.
Ingestion
Pneumonia may be the result if vomited material containing solvents reaches the lungs.
Skin contact
Harmful in contact with skin.
Eye contact
May cause severe irritation to eyes.
Central nervous system Liver

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product contains a substance which may cause long term adverse effects in the aquatic environment.

Ecological information on ingredients.

XYLENE, MIXED ISOMERS (CAS: 1330-20-7)

Ecotoxicity

The product is not expected to be hazardous to the environment.

12.1. Toxicity

Ecological information on ingredients.

XYLENE, MIXED ISOMERS (CAS: 1330-20-7)

LC 50, 96 Hrs, Fish mg/l
2.6
EC 50, 48 Hrs, Daphnia, mg/l
3.62
IC 50, 72 Hrs, Algae, mg/l
3.2

600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455**12.2. Persistence and degradability**

Degradability

The product is not expected to be biodegradable.

Ecological information on ingredients.

XYLENE, MIXED ISOMERS (CAS: 1330-20-7)

Degradability

The product is easily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential

The product contains potentially bioaccumulating substances.

Ecological information on ingredients.

XYLENE, MIXED ISOMERS (CAS: 1330-20-7)

Partition coefficient

log Kow 3.12 - 3.2

12.4. Mobility in soil

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Ecological information on ingredients.

XYLENE, MIXED ISOMERS (CAS: 1330-20-7)

Not Classified as PBT/vPvB by current EU criteria.

12.6. Other adverse effects

The product contains volatile, organic compounds which have a photochemical ozone creation potential.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Do not allow to enter drains, sewers or watercourses.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

Waste Class

When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

| | |
|----------------------|------|
| UN No. (ADR/RID/ADN) | 1263 |
| UN No. (IMDG) | 1263 |
| UN No. (ICAO) | 1263 |

14.2. UN proper shipping name

Proper Shipping Name PAINT

600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455**14.3. Transport hazard class(es)**

| | |
|---------------------|-----------------------------|
| ADR/RID/ADN Class | 1263 |
| ADR/RID/ADN Class | Class 3: Flammable liquids. |
| IMDG Class | 3 |
| ICAO Class/Division | 3 |
| Transport Labels | |

**14.4. Packing group**

| | |
|---------------------------|-----|
| ADR/RID/ADN Packing group | III |
| IMDG Packing group | III |
| ICAO Packing group | III |

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

| | |
|-------------------------|----------|
| EMS | F-E, S-E |
| Tunnel Restriction Code | (D/E) |

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

600/Q607 - 2 PACK ZINC PHOSPHATE THINNERS EVT-455**15.2. Chemical Safety Assessment**

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Update for CLP labelling.

| | |
|--------------------------|------------------------|
| Issued By | Technical Dept. (P.E.) |
| Revision Date | 14/05/2015 |
| Revision | 3 |
| Supersedes date | 15/03/2013 |
| SDS No. | 10977 |
| Safety Data Sheet Status | Approved. |
| Date | Date printed _____ |
| Signature | Initials _____ |

Risk Phrases In Full

| | |
|-----------|--|
| R10 | Flammable. |
| R20/21 | Harmful by inhalation and in contact with skin. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R36/37/38 | Irritating to eyes, respiratory system and skin. |
| R67 | Vapours may cause drowsiness and dizziness. |

Hazard Statements In Full

| | |
|------|--|
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H226 | Flammable liquid and vapour. |
| H332 | Harmful if inhaled. |
| H312 | Harmful in contact with skin. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs <<Organs>> through prolonged or repeated exposure if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H335 | May cause respiratory irritation. |

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.