

STANDARD AND SPECIALIST HOSE ASSEMBLIES

Product overview





Hose Ref	Minimum Bend Radius	Working Pressure at 20°C (BAR)	Working Pressure at 65°C (BAR)		Flow Rate at 3 BAR (lit/min)
DN8	35	12	6	18	28
DN10	50	12	6	18	40
DN13	50	12	6	18	57
DN20	80	12	6	18	135

WORKING

Pressure is stated as the continuous operating maximum pressure. Temperature is stated as maximum continuous operating temperature.

SECURITY

Pressure is stated as the peak pressure to be attained for short durations or transient pressure spikes. Installations where water hammer exceeds the limits stated will invalidate warranty.

BEND

Radius is the minimum by which the hose can be bent without causing excessive stress to the hose fabric.

HOSE SPECIFICATION DATA

The Qualflex range incorporates a non-toxic food grade and tested for aging under hot water conditions for 4800 cycles over 33 days.

Operating Temperature	0°C to 65°C Maximum
Identification	Printed with batch code and unique identification number
Inner Liner	Ethylene Propylene Diene Monomer (EPDM) elastomer
External Braid	Multi strand stainless steel AISI 304 EN 10204 3.1
Identification	Black polyester tracer

Qualflex end connections are manufactured using premium materials to ensure longevity in service and taint-free passage of potable water.

Brass End Connections Plastic End Connections EN12164/5 and tested to comply with ISO 6957 (Stress Cracking) BS6920 with hot water at 85°C

DISCOVER A RANGE OF HIGH QUALITY, FLEXIBLE HOSES

The Qualflex range is a family of high quality, flexible water hoses. Made exclusively in Britain, the range provides a safe and taint-free conveyance of potable water supplies in domestic and commercial applications. Qualflex hoses are independently assessed by third part UKAS accredited test houses to comply with Water Regulations Advisory Scheme (WRAS) certification and compliance to:

- •The Water Supply (Water Fittings) Regulations 1999,
- •The Water Byelaws 2004 Scotland,
- ·Water Supply (Water Fittings) Regulations Northern Ireland 2009.

Features

- Robust construction with excellent abrasion and crush resistance
- Excellent flexibility and kink resistance
- Wide selection of plumbing connections

Applications

- Bathroom appliances pumps and shower systems
- Commercial free standing appliances glass and dish washers
- Merchant plumbing domestic and commercial
- Brassware kitchen and bathroom taps
- Commercial plumbing potable water supplies.



ORDER TODAY:


Tel: 01942 603 351 Web: www.westco.co.uk



PRODUCT LIST

Pushfit Female Iron

	Part No	Description	In Stock	Pair
	28800	Pushfit 15mm x 1/2"Fl x 150mm x 10mm bore	Stock	Pair
	28801	Pushfit 15mm x 1/2"Fl x 300mm x 10mm bore	Stock	Pair
	28802	Pushfit 15mm x 1/2"Fl x 500mm x 10mm bore	Stock	Pair
	28112	Pushfit 15mm x 1/2"Fl x 900mm x 10mm bore	10 days	Single
	28113	Pushfit 15mm x 1/2"Fl x 1500mm x 10mm bore	10 days	Single
	28803	Pushfit 15mm x 1/2"Fl x 150mm x 12mm bore	Stock	Pair
	28804	Pushfit 15mm x 1/2"Fl x 300mm x 12mm bore	Stock	Pair
	28805	Pushfit 15mm x 1/2"Fl x 500mm x 12mm bore	Stock	Pair
	28117	Pushfit 15mm x 1/2"Fl x 900mm x 12mm bore	Stock	Single
1	28806	Pushfit 15mm x 3/4"Fl x 150mm x 12mm bore	Stock	Pair
	28807	Pushfit 15mm x 3/4"Fl x 300mm x 12mm bore	Stock	Pair
	28808	Pushfit 15mm x 3/4"Fl x 500mm x 12mm bore	Stock	Pair
	28120	Pushfit 15mm x 3/4"Fl x 900mm x 12mm bore	Stock	Single
	28809	Pushfit 15mm x 3/4"Fl x 150mm x 10mm bore	Stock	Pair
	28810	Pushfit 15mm x 3/4"Fl x 300mm x 10mm bore	Stock	Pair
	28811	Pushfit 15mm x 3/4"Fl x 500mm x 10mm bore	10 days	Pair
	28812	Pushfit 22mm x 3/4"Fl x 150mm x 12mm bore	10 days	Pair
	28813	Pushfit 22mm x 3/4"Fl x 300mm x 12mm bore	Stock	Pair
	28814	Pushfit 22mm x 3/4"Fl x 500mm x 12mm bore	Stock	Pair
	28126	Pushfit 22mm x 3/4"Fl x 900mm x 12mm bore	10 days	Single



Pushfit Female Iron 19mm Bore

	Part No	Description	In Stock	Pair
2	28815	Pushfit 22mm x 3/4"Fl x 300mm x 19mm bore	10 days	Pair
	28816	Pushfit 22mm x 3/4"Fl x 500mm x 19mm bore	10 days	Pair

Pushfit Compression

	Part No	Description	In Stock	Pair
	28817	Pushfit 15mm x 15mm x 150mm x 10mm bore	Stock	Pair
	28818	Pushfit 15mm x 15mm x 300mm x 10mm bore	Stock	Pair
	28819	Pushfit 15mm x 15mm x 500mm x 10mm bore	10 days	Pair
	28062	Pushfit 15mm x 15mm x 900mm x 10mm bore	10 days	Single
3	28820	Pushfit 15mm x 15mm x 150mm x 12mm bore	Stock	Pair
3	28821	Pushfit 15mm x 15mm x 300mm x 12mm bore	Stock	Pair
	28822	Pushfit 15mm x 15mm x 500mm x 12mm bore	Stock	Pair
	28066	Pushfit 15mm x 15mm x 900mm x 12mm bore	10 days	Single
	28823	Pushfit 22mm x 22mm x 300mm x 12mm bore	Stock	Pair
	28824	Pushfit 22mm x 22mm x 500mm x 12mm bore	Stock	Pair
	28070	Pushfit 22mm x 22mm x 900mm x 12mm bore	10 days	Single

4 | Qualflex

	Part No	Description	In Stock	Pair
	28826	Pushfit 15mm x 1/2"Fl x 300mm x 12mm bore ISO	Stock	Pair
	28827	Pushfit 15mm x 1/2"Fl x 500mm x 12mm bore ISO	Stock	Pair
4	28829	Pushfit 15mm x 3/4"Fl x 300mm x 12mm bore ISO	Stock	Pair
	28830	Pushfit 15mm x 3/4"Fl x 500mm x 12mm bore ISO	Stock	Pair
	28831	Pushfit 22mm x 3/4"Fl x 300mm x 12mm bore ISO	Stock	Pair
	28832	Pushfit 22mm x 3/4"Fl x 500mm x 12mm bore ISO	Stock	Pair

Pushfit Long & Short Pack

	Part No	Description	In Stock	Pair
5	28833	Pushfit 15mm x 300mm x 8mm x mono M10 L&S	Stock	Pair
	28834	Pushfit 15mm x 300mm x 10mm x mono M12 L&S	Stock	Pair

Female Iron Mono


	Part No	Description	In Stock	Pair
6	28836	Mono 1/2"Fl x 300mm x 8mm bore M10 L&S	Stock	Pair
	28835	Mono 1/2"Fl x 300mm x 10mm bore M12 L&S	Stock	Pair

Female Iron

	Part No	Description	In Stock	Pair
7	28838	1/2"Fl x 1/2"Fl x 300mm x 10mm bore	Stock	Pair
	28837	1/2"Fl x 1/2"Fl x 300mm x 12mm bore	Stock	Pair

Compression Mono Long & Short Pack

	Part No	Description	In Stock	Pair
8	28840	Mono 15mm x 300mm x 8mm bore M10 L&S	Stock	Pair
	28839	Mono 15mm x 300mm x 10mm bore M12 L&S	Stock	Pair



ORDER TODAY:

Tel: 01942 603 351 Web: www.westco.co.uk

$\ensuremath{\textbf{Qualflex}}$ standard and specialist hose assemblies from Westco \mid 5



PRODUCT LIST

Compression ISO

	Part No	Description	In Stock	Pair
	28849	Comp 15mm x 1/2"Fl x 300mm x 10mm bore ISO	10 days	Pair
	28848	Comp 15mm x 1/2"FI x 500mm x 10mm bore ISO	Stock	Pair
	28847	Comp 15mm x 3/4"Fl x 300mm x 10mm bore ISO	10 days	Pair
9	28846	Comp 15mm x 3/4"Fl x 500mm x 10mm bore ISO	Stock	Pair
	28845	Comp 15mm x 1/2"FI x 300mm x 12mm bore ISO	10 days	Pair
	28844	Comp 15mm x 1/2"Fl x 500mm x 12mm bore ISO	Stock	Pair
	28843	Comp 22mm x 3/4"Fl x 300mm x 12mm bore ISO	10 days	Pair
	28842	Comp 22mm x 3/4"Fl x 500mm x 12mm bore ISO	Stock	Pair

Compression


	Part No	Description	In Stock	Pair
	28858	Comp 15mm x 15mm x 150mm x 10mm bore	10 days	Pair
	28857	Comp 15mm x 15mm x 300mm x 10mm bore	10 days	Pair
	28856	Comp 15mm x 15mm x 500mm x 10mm bore	10 days	Pair
10	28855	Comp 15mm x 15mm x 150mm x 12mm bore	Stock	Pair
10	28854	Comp 15mm x 15mm x 300mm x 12mm bore	Stock	Pair
	28853	Comp 15mm x 15mm x 500mm x 12mm bore	10 days	Pair
	28852	Comp 22mm x 22mm x 150mm x 12mm bore	10 days	Pair
	28851	Comp 22mm x 22mm x 300mm x 12mm bore	Stock	Pair
	28850	Comp 22mm x 22mm x 500mm x 12mm bore	10 days	Pair

Compression Female Iron

	Part No	Description	In Stock	Pair
11	28873	15mm x 3/8"Fl x 300mm x 10mm bore	10 days	Pair
	28872	15mm x 1/2"Fl x 150mm x 10mm bore	Stock	Pair
	28871	15mm x 1/2"Fl x 300mm x 10mm bore	Stock	Pair
	28870	15mm x 1/2"Fl x 500mm x 10mm bore	10 days	Pair
	28413	15mm x 1/2"Fl x 900mm x 10mm bore	Stock	Single
	28414	15mm x 1/2"Fl x 1500mm x 10mm bore	10 days	Single
	28869	15mm x 3/4"Fl x 150mm x 10mm bore	Stock	Pair
	28868	15mm x 3/4"Fl x 300mm x 10mm bore	10 days	Pair
	28867	15mm x 3/4"Fl x 500mm x 10mm bore	10 days	Pair
	28866	15mm x 1/2" Fl x 150mm x 12mm bore	Stock	Pair
	28865	15mm x 1/2" Fl x 300mm x 12mm bore	Stock	Pair
	28864	15mm x 1/2" Fl x 500mm x 12mm bore	Stock	Pair
	28863	15mm x 3/4"Fl x 300mm x 12mm bore	Stock	Pair
	28862	15mm x 3/4"Fl x 500mm x 12mm bore	Stock	Pair
	28861	22mm x 3/4"Fl x 150mm x 12mm bore	10 days	Pair
	28860	22mm x 3/4"Fl x 300mm x 12mm bore	Stock	Pair
	28859	22mm x 3/4"Fl x 500mm x 12mm bore	10 days	Pair

Note: The estimate of 10 days for stock delivery refers to 10 working days.

6 | Qualflex



INSTALLATION



To ensure suitability, check the application does not exceed the rated temperature or pressure range as stated for both continuous and transient variations. The Qualflex range is not suitable for heating systems. Flexible hoses should always be installed by a competent plumber or engineer. An installation guide is available on the Hydralectric website – www.hydralectric.com.

TECHNICAL ASSISTANCE

For technical assistance and support, please contact the Hydralectric Technical Support team on **01932 334 200**, or visit **www.hydralectric.com**.

PLACE YOUR ORDER TODAY

For more information, or to place an order, speak to your local Westco representative or **visit www.westco.co.uk**.



Tel: 01942 603 351 Web: www.westco.co.uk

Unit C6 - William Way Moss Industrial Estate St. Helens Road Leigh Lancashire WN7 3PT



Telephone: 01942 603 351 Fax: 01942 607 780 enquiries@westco.co.uk www.westco.co.uk

Registered in England No. 1322734



