

Fujitsu recommends Windows.

Data Sheet

FUJITSU CELSIUS M730

Workstation

Your "Thoroughbred" Workstation

If you're looking for reliable performance when using demanding applications, the FUJITSU CELSIUS M730 single-processor workstation meets your needs. It can be individually configured, helping you to enhance your productivity. It features best-in-class noise emissions of only 20 dB for a quiet and efficient working environment. Comprehensive ISV certifications ensure your applications run smoothly. Finally, the convenient cold plug access at front simplifies subsequent expansion.



Performance

Higher productivity

- Future Intel® Xeon® processors, high performing graphics subsystems, quad-channel memory technology and high-speed hard disk drives

Ergonomics

Noise-reduced system engineered in Germany

- Optimized thermal management, low-noise chassis and silent fans

Reliability

System stability for the complete lifecycle

- High product standards thanks to top-quality components and comprehensive testing in certified in-house laboratories for 24/7 operation

Certification of workstation applications

Stability, compatibility and performance for the main workstation applications

- Comprehensive support for ISV applications and ease of integration into existing IT networks

Expandability

Excellent expandability for future demands

- Increased memory capacities of up to 128 GB



Components

Processor

| |
|---|
| Intel® Xeon® processor E5-2697v2 (12 cores, 2.70 GHz, 30 MB) |
| Intel® Xeon® processor E5-2695v2 (12 cores, 2.40 GHz, 30 MB) |
| Intel® Xeon® processor E5-2690v2 (10 Cores, 3.00 GHz, 25 MB) |
| Intel® Xeon® processor E5-2680v2 (10 Cores, 2.80 GHz, 25 MB) |
| Intel® Xeon® processor E5-2670v2 (10 Cores, 2.50 GHz, 25 MB) |
| Intel® Xeon® processor E5-2667v2 (8 Cores, 3.30 GHz, 25 MB) |
| Intel® Xeon® processor E5-2660v2 (10 Cores, 2.20 GHz, 25 MB) |
| Intel® Xeon® processor E5-2650v2 (8 Cores, 2.60 GHz, 20 MB) |
| Intel® Xeon® processor E5-2650Lv2 (10 Cores, 1.70 GHz, 25 MB) |
| Intel® Xeon® processor E5-2643v2 (6 Cores, 3.50 GHz, 25 MB) |
| Intel® Xeon® processor E5-2640v2 (8 Cores, 2.00 GHz, 20 MB) |
| Intel® Xeon® processor E5-2637v2 (4 Cores, 3.50 GHz, 15 MB) |
| Intel® Xeon® processor E5-2630v2 (6 Cores, 2.60 GHz, 15 MB) |
| Intel® Xeon® processor E5-2630Lv2 (6 Cores, 2.40 GHz, 15 MB) |
| Intel® Xeon® processor E5-2620v2 (6 Cores, 2.10 GHz, 15 MB) |
| Intel® Xeon® processor E5-2609v2 (4 Cores, 2.50 GHz, 10 MB) |
| Intel® Xeon® processor E5-2603v2 (4 Cores, 1.80 GHz, 10 MB) |
| Intel® Xeon® processor E5-1660v2 (6 Cores, 3.70 GHz, 15 MB) |
| Intel® Xeon® processor E5-1650v2 (6 Cores, 3.50 GHz, 12 MB) |
| Intel® Xeon® processor E5-1620v2 (4 Cores, 3.70 GHz, 10 MB) |
| Intel® Xeon® processor E5-1607v2 (4 Cores, 3.00 GHz, 10 MB) |
| Intel® Xeon® processor E5-1603 (4 Cores / 8 Threads, 2.80 GHz, 10 MB) |
| Intel® Xeon® processor E5 family featuring Intel® vPro™ Technology |

Operating systems

Operating system

Windows 8.1 Pro 64-bit
Windows 8 Pro 64-bit
Windows 7 Professional 64-bit

Operating system compatible

Windows® Server 2012
Windows 7 Professional 32-bit
Windows® XP Professional x64 Edition
Linux

Operating system notes

Certified for Red Hat® Enterprise Linux
Certified for SUSE Enterprise Desktop
Certified for SUSE Enterprise Server
For some configurations third party drivers are currently not available or configuration restrictions may apply.
SCU ports are not supported for Windows® XP 32bit (restriction by Intel®). Therefore an additional storage controller (D2607 or D2616) is necessary.
Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via <http://support.ts.fujitsu.com>

Memory modules

| |
|---|
| 4 GB (1 module(s) 4 GB) DDR3, ECC, 1,866 MHz, PC3-14900 |
| 4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1,600 MHz, PC3-12800 |
| 8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1,866 MHz, PC3-14900 |
| 16 GB (1 module(s) 16 GB) DDR3, registered, ECC, 1,866 MHz, PC3-14900 |

| | |
|---------------------------------------|---|
| Graphics | Ultra-high-end 3D: NVIDIA® Quadro® K6000, 12 GB, 2,880 cores, PCIe x16, 1x Dual Link DVI-I, 1x Dual Link DVI-D, 2x DisplayPort |
| | Ultra-high-end 3D: NVIDIA® Quadro® 6000, 6 GB, 448 cores, PCIe x16, 1x DVI-I, 2x DisplayPort |
| | Ultra-high-end 3D: NVIDIA® Quadro® K5000, 4 GB, 1,536 cores, PCIe x16, 1x Dual Link DVI-I, DVI-D, 2x DisplayPort |
| | High-end 3D: AMD FirePro™ W8000, 4 GB, 1,792 stream processors, PCIe x16, 4 x DisplayPort |
| | High-end 3D: AMD FirePro™ W7000, 4 GB, 1,280 stream processors, PCIe x16, 4 x DisplayPort |
| | High-end 3D: NVIDIA® Quadro® K4000, 3 GB, 768 cores, PCIe x16, 1x Dual Link DVI-I, 2x DisplayPort |
| | Midrange 3D: NVIDIA® Quadro® K2000D, 2 GB, 384 cores, PCIe x16, 2x Dual Link DVI-I |
| | Midrange 3D: NVIDIA® Quadro® K2000, 2 GB, 384 cores, PCIe x16, 1x Dual Link DVI-I, 2x DisplayPort |
| | Midrange 3D: AMD FirePro™ W5000, 2 GB, 768 cores, PCIe x16, 1x Dual Link DVI-I, 2x DisplayPort |
| | Entry 3D: AMD FirePro™ V4900, 1 GB, 480 stream processors, PCIe x16, 1x Dual Link DVI-I, 2x DisplayPort |
| | Entry 3D: NVIDIA® Quadro® K600, 1 GB, 192 cores, PCIe x16, 1x Dual Link DVI-I, 1x DisplayPort |
| | Entry 3D: AMD FirePro™ V3900, 1 GB, 480 stream processors, PCIe x16, 1x Dual Link DVI-I, 1x DisplayPort |
| | Entry 3D: NVIDIA® Quadro® 410, 512 MB, 192 cores, PCIe x16, 1x DVI-I, 1x DisplayPort |
| | Professional 2D: NVIDIA® NVS 510, 2 GB, 16 cores, PCIe 2.0 x16, 4x miniDP |
| | Professional 2D: NVIDIA® NVS 310, 512 MB, 16 cores, PCIe 2.0 x16, 2x DisplayPort |
| | Professional 2D: NVIDIA® NVS 300, 1 GB, 16 cores, PCIe 2.0 x16, 2x LFH59 (DP/DVI-I) |
| | Professional 2D: NVIDIA® NVS 300, 512 MB, 16 cores, PCIe 2.0 x16, 2x LFH59 (DP/DVI-I) |
| | GPU computing card: NVIDIA® Tesla™ K20, 5 GB, 2,496 cores, PCIe x16 |
| | Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2x miniDP, PCoIP |
| | Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4x miniDP, PCoIP |
| Personal Supercomputing | Coprocessor: Intel® Xeon Phi™ Coprocessor 3120A, PCIe x16 |
| Hard disk drives (internal) | SSD SATA III Premium, 512 GB, 2.5-inch |
| | SSD SATA III Premium, 256 GB, 2.5-inch |
| | SSD SATA III Premium, 128 GB, 2.5-inch |
| | SSD SATA III, 512 GB, 2.5-inch |
| | SSD SATA III, 256 GB, 2.5-inch |
| | SSD SATA III, 128 GB, 2.5-inch, SED |
| | SSD SATA III, 128 GB, 2.5-inch |
| | HDD SATA III, 10,000 rpm, 1,000 GB, 2.5-inch, business critical |
| | HDD SATA III, 10,000 rpm, 500 GB, 2.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 3,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch |
| | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch |
| | HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch |
| | HDD SAS, 15,000 rpm, 300 GB, 2.5-inch |
| | HDD SAS, 10,000 rpm, 900 GB, 2.5-inch |
| | HDD SAS, 10,000 rpm, 600 GB, 2.5-inch |
| HDD SAS, 10,000 rpm, 300 GB, 2.5-inch | |
| Hard disk notes | *Disk imaging software of the customer must be 4k sector size / advanced format ready One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. 24/7 ready (business critical HDDs required) |
| Drives (optional) | BD Triple Writer SATA slim (tray) |
| | DVD-ROM |
| | DVD Super Multi |
| | MultiCard Reader 24in1 USB 2.0 3.5" |

| | |
|---|--|
| SCSI / SAS Controller | RAID 5/6 Ctrl. 6 Gbit/s 8 ports int. 512 MB Cache |
| | RAID 0/1 Ctrl. 6 Gbit/s 8 ports int. |
| | RAID 0/1 Ctrl. 6 Gbit/s 8 ports ext. |
| Interface add on cards/components (optional) | |
| | WLAN 802.11 a/g/n (2x2), (dedicated regions only, not for Indonesia) |
| | USB 3.0 PCIe x1 |
| | Serial Interface FH |
| | Gigabit Ethernet PCIe x1, DS |
| | eSATA Interface |
| | Dual serial card PCIe x1 |
| | Dual 10 Gigabit Ethernet PCIe x8 |

Base unit

| Base unit | CELSIUS M730 | CELSIUS M730 power |
|--------------------------------|---|--------------------|
| Mainboard | | |
| Mainboard type | D3128 | |
| Formfactor | ATX | |
| Chipset | Intel® C602 | |
| Processor socket | Socket R | |
| Processor quantity maximum | 1 | |
| Memory slots | 8 DIMM (DDR3) ECC/non-ECC | |
| Supported capacity RAM (max.) | 128 GB | |
| Memory notes | In configurations with 4 GB and more the visible memory may be reduced to approximately 3.5 GB or less (for 32-bit operating systems) and configurations with 8 GB the visible memory may be reduced to approximately 7.5 GB or less (depending on system configuration). Large memory may lead to long boot times. When using a 32-bit operating system the maximum of memory might be 900 MB. | |
| LAN | Built-in 10/100/1,000 MBit/s Intel® 82579 LM | |
| BIOS version | AMI Aptio 4.6 | |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) | |
| Audio type | On board | |
| Audio codec | Conexant CX20642 | |
| Audio features | High Definition Audio | |
| I/O controller on board | | |
| Serial ATA total | 6 | |
| thereof SATA III | 2 | |
| SATA RAID support | 0, 1, 10, 5 | |
| SAS Controller type | optional upgrade to 4 ports, Intel C604 | |
| SAS RAID support | 0, 1, 10 | |
| Interfaces | | |
| Audio: in (rear) | 1 | |
| Audio: out (rear) | 1 | |
| Audio: in | 1 | |
| Audio: out | 1 | |
| Internal speakers | 1 | |
| USB 2.0 total | 11 | |

Interfaces

| | |
|-------------------------|----------------------------------|
| USB 3.0 total | 2 |
| USB front | 4 (2x USB 3.0) |
| USB rear | 6 |
| USB internal | 3, thereof 1 type A |
| Mouse / Keyboard (PS/2) | 1 / 1 |
| Ethernet (RJ-45) | 1 |
| Interface Module notes | Anytime USB charge functionality |

Input device / components

| | |
|--------------------------|--|
| | Optical USB tilt wheel mouse |
| Input devices (optional) | Optical USB/PS2 tilt wheel mouse Space Explorer USB Keyboard |

Drive bays

| | |
|-------------------------|----|
| Drive bays total | 12 |
| 2.5-inch internal bays | 8 |
| 3.5-inch internal bays | 4 |
| 3.5-inch external bays | 2 |
| 5.25-inch external bays | 2 |

Slots

| | |
|--------------------------------|---------------------------------------|
| PCI-Express 3.0 x4 (mech. x8) | 2 x (312 mm / 12.29 inch) Full height |
| PCI-Express 3.0 x16 | 2 x (312 mm / 12.29 inch) Full height |
| PCI-Express 2.0 x4 (mech. x16) | 1 x (312 mm / 12.29 inch) Full height |
| PCI (32-bit / 33 MHz) | 2 x (312 mm / 12.29 inch) Full height |

Electrical values

| | | |
|--------------------------------------|--|---|
| Power consumption note | 190 W depending on configuration | 250 W depending on configuration |
| Rated voltage range | 100 V - 240 V | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz | 50 Hz - 60 Hz |
| Operating voltage range | 100 V - 240 V | 100 V - 240 V |
| Operating line frequency range | 50 Hz - 60 Hz | 50 Hz - 60 Hz |
| Max. output of single power supply | 500 W up to 90% efficiency | 800 W up to 90% efficiency |
| Power factor correction/active power | active | |
| Power supply output | 1 graphics power rail (6pin connector / 17A@12V) | 2 graphics power rails (6pin connector / 17A@12V) |

Noise for standard configuration (HDD, ODD, FDD)

| | | |
|--|--|--|
| Related Processors for noise | Intel® Xeon® E5-1620v2 w/ Nvidia® NVS 300 | Intel® Xeon® E5-1620v2 w/ Nvidia® NVS 300 |
| Standard noise emission | 2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74 | 2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74 |
| Standard noise notes / description | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) |
| Standard noise operation mode: CPU 50% load | 3.5 B / 20 dB(A) Bystander position | 3.5 B / 20 dB(A) Bystander position |
| Standard noise operation mode: CPU 90% load | 3.5 B / 20 dB(A) Bystander position | 3.5 B / 20 dB(A) Bystander position |
| Standard noise operation mode: HDD load | 3.6 B / 20 dB(A) Bystander position | 3.6 B / 20 dB(A) Bystander position |
| Standard noise operation mode: Idle mode | 3.5 B / 20 dB(A) Bystander position | 3.5 B / 20 dB(A) Bystander position |
| Standard noise operation mode: ODD load | 4.5 B / 28 dB(A) Bystander position | 4.5 B / 28 dB(A) Bystander position |
| Standard noise operation mode: Office applications 2.0 | 3.5 B / 20 dB(A) Bystander position | 3.5 B / 20 dB(A) Bystander position |
| Blue angel noise emission according certification | According to ISO 7779:2010, ECMA-74 for max. possible configuration | According to ISO 7779:2010, ECMA-74 for max. possible configuration |

Noise for standard configuration (HDD, ODD, FDD)

| Blue angel noise notes / description | A-weighted sound power level L _{wad} (in B); 1B = 10dB | A-weighted sound power level L _{wad} (in B); 1B = 10dB |
|--|---|---|
| Blue angel noise operation mode: HDD load | 3.8 B = 38 dB (A) | 3.8 B = 38 dB (A) |
| Blue angel noise operation mode: Idle mode | 3.8 B = 38 dB (A) | 3.8 B = 38 dB (A) |
| Blue angel noise operation mode: ODD load | 4.6 B = 46 dB (A) | 4.6 B = 46 dB (A) |

Dimensions / Weight / Environmental

| | |
|-------------------------------|---|
| Dimensions (W x D x H) | 186 x 481 x 430 mm |
| Operating position | Vertical / horizontal |
| Weight | 18 kg |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) |
| Operating relative humidity | 5 - 85 % (relative humidity) |

Compliance

| | | |
|-----------------|---|--------------------|
| Product | CELSIUS M730 | CELSIUS M730 Power |
| Model | ETNA_S-D3128 | |
| Germany | GS depending on configuration | |
| Europe | CE | |
| USA/Canada | cCSAus FCC Class B | |
| Global | RoHS (EU & China) Medical EMC standard IEC60601-1-2 in combination with medical kit Microsoft Operating Systems (HCT / HCL entry / WHQL) WEEE (Waste electrical and electronic equipment) ENERGY STAR® 6.0 (dedicated regions, depending on configuration) EPEAT® Gold (dedicated regions) | |
| Compliance link | http://globalsp.ts.fujitsu.com/sites/certificates | |

Additional Software

| | |
|------------------------------------|--|
| Additional software (preinstalled) | Workplace Protect (secure authentication solution) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Microsoft Office (buy license to activate the pre-installed Microsoft Office) |
| Additional software (optional) | Drivers & Utilities DVD (DUDVD) Windows® 8 and Windows® 7 |

Security

| | |
|--------------------------|---|
| Physical Security | Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional) |
| System and BIOS Security | Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Dynamic USB security for full hardware USB protection Control of all USB interfaces Trusted platform module (TPM 1.2) EraseDisk |
| User Security | User and supervisor BIOS password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) |

Manageability

| | |
|--------------------------|--|
| Manageability technology | DeskUpdate Driver management iAMT 8.0 (depending on CPU) |
| Manageability software | DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform |

Manageability

| | |
|---------------------|---|
| DeskView components | Inventory Management BIOS Management Driver Management Security Management Alarm Management |
| Supported standards | WMI BootP (made4you) PXE WoL (Wake on LAN) |
| Manageability link | http://www.fujitsu.com/fts/manageability |

Miscellaneous

| | | |
|-------------------------|---------------------|---------------------|
| | Rack mountable (5U) | Rack mountable (5U) |
| Spare part availability | 5 years | 5 years |

Packaging information

| | | |
|----------------------------|---|---|
| Packaging dimension (mm) | 397 x 597 x 555 mm | 397 x 597 x 555 mm |
| Packaging dimension (inch) | 15.63 x 23.5 x 21.85 inch | 15.63 x 23.5 x 21.85 inch |
| Max. quantity / pallet | 16 | 16 |
| Packaging notes | printed user documentation is bleached in chlorine free process | printed user documentation is bleached in chlorine free process |

Warranty

| | |
|-----------------------------|---|
| Standard Warranty | 3 years (depending on country) |
| Service level | Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 3 years material warranty) |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |

Maintenance and Support Services - the perfect extension

| | |
|--------------------------|---|
| Recommended Service | 9x5, Response Time: Next Business Day |
| Spare Parts availability | 5 years after end of product life |
| Service Weblink | http://www.fujitsu.com/fts/services/support |

Recommended Accessories

MicroSaver Slim

The Fujitsu Kensington MicroSaver slim features the patented T-Bar locking mechanism with carbon tempered steel core cable and an external braided steel sheath. The MicroSaver slim is available with Kensington Master Access. This security solution allows you to manage and maintain a limitless number of locks with a master key.

Order Code:
S26361-F1650-L200

Display P23T-6 FPR 3D

If you're a pixel, color and performance-hungry professional using demanding 2D and 3D applications, FUJITSU Display P23T-6 FPR 3D is the perfect choice for you. The combination of the stunning IPS graphic panel with latest 3D FPR technology, unique energy efficiency features and sophisticated ergonomics make this display really unrivalled.

Order Code:
S26361-K1370-V170

Display P27T-7 LED

Enjoy perfect picture quality with 3.7 Mio pixels, outstanding ergonomics and usability as well as comfortable energy saving solutions of this 68.5 cm (27-inch) widescreen FUJITSU P Line Display.

Order Code:
S26361-K1442-V140

Mouse M440 ECO



Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.

Order Code:
S26381-K450-L200

SpaceMouse™ Pro



Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:
S26381-K459-L100

Keyboard KBPC PX ECO



Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1** (**: country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to the FUJITSU CELSIUS M730, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

To learn more about the FUJITSU CELSIUS M730, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

FORTUNA PS

Fortuna Power Systems Ltd

T: 01256 782030

E: sales@data-storage.co.uk

W: www.data-storage.co.uk

Contact

Fujitsu Technology Solutions
Website: www.fujitsu.com/fts
2014-07-09 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions