# **Chillers and Freezers**

#### **Features and Benefits**

- \* Switchable Interior Light
- \* Digital Temperature Display
- \* Lock Fitted
- \* Electronically Controlled
- \* Fan Assisted Cooling
- \* Fully Automatic Operation
- \* Chiller suitable for Fresh Meat
- \* Left-hand Hung Doors Available POA
- \* Stainless Steel Floor as Standard
- \* Suitable for use up to 32°C Ambient
- Pressure Release Valve Fitted on Freezer Rooms
- \* Heated Door Frames
- \* 75mm Insulation on all Rooms
- \* Integral Ladder Rack Shelving -4 Tier
- \* Deep Shelf 445mm
- \* Shallow Shelf 333mm
- \* Ladder Rack 1200mm high
- Coldroom Floors Not Suitable for Trolleys. Floorless Rooms Available POA

















## **Chillers and Freezers**

### **Technical Specifications**


**Temperature Ranges** 


Chiller ..... -2/+6°C -18/-22°C Freezer ... R404A Type of Defrost Hot Gas **Exterior Finish**. White White/ **Interior Finish** 


Stainless Steel

Power Required . . . . 20 Amp Supply

- External Height 2000mm
- Internal Height 1860mm








PC1512


£3554


£3849


Complete Chiller Room


Complete Freezer Room




















More Options Overleaf

## **Chillers and Freezers**


#### **Features and Benefits**


- Switchable Interior Light
- Digital Temperature Display
- Lock Fitted
- **Electronically Controlled**
- Fan Assisted Cooling
- **Fully Automatic Operation**
- Chiller suitable for Fresh Meat
- Left-hand Hung Doors Available POA
- Stainless Steel Floor as Standard
- Suitable for use up to 32°C Ambient
- Pressure Release Valve Fitted on Freezer Rooms
- **Heated Door Frames**
- 75mm Insulation on all Rooms
- Integral Ladder Rack Shelving -4 Tier
- Deep Shelf 445mm
- Shallow Shelf 333mm
- Ladder Rack 1200mm high
- Coldroom Floors Not Suitable for Trolleys. Floorless Rooms Available POA

#### **Technical Specifications Temperature Ranges**

Chiller . -2/+6°C **Freezer** -18/-22°C Refrigerant R404A Type of Defrost Hot Gas **Exterior Finish** White **Interior Finish** White/


Stainless Steel Power Required . . . . 20 Amp Supply























- External Height 2000mm





2400

2400



PC3024

£6344

£6607

Complete Chiller Room

Complete Freezer Room

150



#### Installation


#### Subject to:

- (a) Suitable single phase 20 amp fixed isolator to be provided by clients electrical contractor.
- (b) Flat prepared floor
- (c) Isolator to be within 1m of coldroom equipment.
- (d) Suitable ventilation if required
- (e) Suitable clear access to site for delivery and installation.
- (f) Prices assume normal working day Monday to Friday 0830 to 1700 hours.
- (g) Rooms are not suitable for outdoor installation.
- (h) Any subsequent visits to finish coldroom installation due to site delays or non site / incorrect site survey will incur additional costs.

#### **Site Survey**

A site survey option is available and recommended upon request for UK Mainland.

Multiple Installations would be price on application



## Coldroom Installations

Details below are for installation of packaged integral Coldrooms by Interlevin





