

Bitumen Rubber Sealant Strip

Extruded bitumen rubber sealants have been used in the construction industry for many years. They have established an excellent reputation for longevity and are often specified in traditional specifications. Advantages include:

- Low water absorption, high cohesion
- Good adhesion to dry concrete
- Immediate seal, no time needed for solvent evaporation
- One grade for winter and summer use
- Primer not required on horizontal surfaces
- Resistant to hardening after aging
- Permanent flexibility for joint movement
- Release paper for clean applications



Typical application sizes

Manhole dia.	Tongue & groove	Ogee	Box culverts
900	12 x 60	22 x 30	-
1050	12 x 60	22 x 30	-
1200	12 x 80	22 x 30	-
1350	12 x 80	22 x 30	-
1500	12 x 80	22 x 30	-
1800	12 x 80	22 x 30	-
2100	2 off 12x60	22 x 44	-
2400	2 off 12x60	25 x 40	-
2700	2 off 12x60	25 x 40	-
3000	2 off 12x60	25 x 40	-
Various	-	-	



Bitumen Sealant Strip order details

Code	Size (mm)	Roll length (mm)	Rolls/carton	Metres/carton
SE104	12 x 120	6	2	12
SE100	12 x 60	6	4	24
SE102	12 x 80	6	2	18
SE104	25 x 40	4	5	20

Primer also available – SE310 – 5 litre tins