

GO GO
ELITE TRAVELLER[®] LX

SLEEK STYLE AND
LUXURIOUS FEATURES.

GO-GO ELITE TRAVELLER[®] LX

The Go-Go Elite Traveller[®] LX delivers luxury and convenient features like a wraparound delta tiller with a high level charging port, LED kerb light and large storage basket together with a compact, easy to transport design. Sleek styling complements the Go-Go Elite Traveller LX's abundant features making it an exceptional travel mobility choice.



(Images are for illustration purposes only)

(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk

Pride[®]
Mobility Products Ltd.
— LIVE YOUR BEST[™] —

Go-Go Elite Traveller® LX	4-wheel
Weight capacity:	19 Stone 9 lbs. (125 kg)
Maximum speed ² :	Up to 4 mph (6.4 km/h)
Ground clearance ¹ :	6.35 cm (2.5") at midframe
Turning radius ¹ :	112 cm (44.125")
Overall length ¹ :	100.3 cm (39.5")
Overall width ¹ :	49.5 cm (19.5")
Tyres:	
Front:	5 cm x 17.78 cm (2" x 7") solid
Rear:	6.35 cm x 20.32 cm (2.5" x 8") solid
Anti-tips:	Rear
Transport weight:	
Total weight w/o battery pack ³ :	35.8 kg (79 lbs.)
Heaviest piece when disassembled:	15.2 kg (33.5 lbs.) (front section)
Drive system:	24-volt DC motor, sealed transaxle, rear-wheel drive
Dual braking system:	Regenerative and electromechanical
Standard seating:	Type: Foldable, compact, vinyl-covered molded plastic Weight: 10.2 kg (22.5 lbs.) Material: Black Vinyl Dimensions: 43 cm (17") width 43 cm (17") depth
Battery requirements ⁴ :	Two 12-volt, deep cycle (standard) Size: 2 x 12 AH (standard) 2 x 17 AH (optional) Weight ³ : 12 AH: 8.85 kg (19.5 lbs.) battery pack 17 AH: 13.4 kg (29.5 lbs.) battery pack
Battery charger:	Off-board, 2-amp

Colours:



Blue



Red

2 sets of colours with every scooter!

Features

- Feather-touch disassembly permits simple frame separation with only one hand
- Exclusive black, non-scuffing tyres
- Auto-connecting front to rear cable
- Front frame-mounted seat post offers maximum stability
- Frame design easily disassembles into 5 lightweight pieces for convenient transport and storage
- Includes 2 sets of easily changeable coloured panels in 2 exciting colours - Red and Blue
- Modular design for easy serviceability
- Microprocessor-based controller offers optimal power management and added safety features
- Front basket included
- Battery packs contain 2 x 12 volt batteries to power the 24 volt system
- Delta tiller with wraparound handles
- Charger XLR port incorporated in tiller allows charging without removing battery box
- LED kerb light
- Seat post suspension

Options

- 17 amp battery pack for increased range
- Additional 12 amp battery pack

¹ Due to manufacturing tolerances and continued product improvement, this specification is subject to a variance of +/- 3%.

² Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tyre type and tyre condition. This specification can be subject to a variance of +10%, -5%.

³ Battery weight may vary based on manufacturer.

⁴ AGM or gel cell type required.

⁵ Includes standard seat.

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.



32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk

DEALER INFO HERE

Pride[®]
Mobility Products Ltd.

UK_SC_GO-GO ET LX_SS_5-13-13



PRIDE[®]
PERFORMANCE MOBILITY
— LIVE YOUR BEST[®] —