



LED Surface-mount Cylindrical Light

No.	Item	Picture	Description	Beam	LED	Wattage	Size	CREE+KGP	Osram+AW	Epistar+AW
1	SLMD005-3F		Input: 200-240VAC, 50/60HZ; CRI: ≥80 Material::Alum.+PC IP54	45°	COB	10W	Size:83*108mm	Yes	/	/
2	SLMD005-4F			45°		20W	Size:115*117mm	Yes	/	/
3	SLMD005-6F			45°		30W	Size:150*139mm	Yes	/	/
4	SLMD005-8F			30°		40W	Size:190*156mm	Yes	/	/
9	SLMD001A-2.5F		Input: 200-240VAC, 50/60HZ; CRI: ≥80 Material:Alum.	110°	2835	5 W	Size:φ68*75mm	/	/	Yes
10	SLMD001A-3F					7 W	Size:φ88*75mm	/	/	Yes
11	SLMD001A-4F					9 W	Size:φ108*90mm	/	/	Yes
12	SLMD001A-5F					12 W	Size:φ128*105mm	/	/	Yes
13	SLMD001A-6F					18 W	Size:φ148*120mm	/	/	Yes
14	SLMD001B-2.5F		Input: 200-240VAC, 50/60HZ; CRI: ≥80 Material:Alum.	110°	2835	5 W	Size:φ68*88mm	/	/	Yes
15	SLMD001B-3F					7 W	Size:φ88*87mm	/	/	Yes
16	SLMD001B-4F					9 W	Size:φ108*108mm	/	/	Yes
17	SLMD001B-5F					12 W	Size:φ128*128mm	/	/	Yes
18	SLMD001B-6F					18 W	Size:φ148*148mm	/	/	Yes