



FT Plus

Pavement Protection

Uses:

"Wet Look" Colour Enhancement of Natural Stone and Concrete pavements, giving a consistent appearance and uniform coloration during both wet and dry conditions, also providing protection against staining by grease, oil, fats, fast food, tyre rubber, footwear marks and normal pavement grime combined with water repellency.

Advantages:

- enhanced and more consistent coloration
- long term effectiveness
- highly oil & water repellent
- no reduction in slip resistance


How it works:

FT Plus bonds tenaciously within the pores beneath a pavement surface, forming a breathable, highly resilient subsurface system which is resistant to staining and which reflects light in a way that masks the different appearance of wet and dry surfaces.

Regular cleaning using WEISS Grundreiniger then completes a sustainable regime.

The untreated surface (left) appears dark when damp.

The treated surface (right) is consistent



The untreated surface (left) appears light when dry.

The treated surface (right) is consistent

Directions:

Apply when surface is between 5-25°C and in dry weather conditions.

Do not dilute. Mix well before use. Ensure the surface is dry and clean.

Apply evenly using a spray, brush, roller or mop until no more is absorbed and the surface appears wet and glossy. If applying a second coat to a highly absorbent surface, do so within a maximum of 20 minutes.

Remove excess product with a cloth or squeegee before it dries on to the surface.

Treated surfaces may be walked on after 4-6 hours and protected against rain and soiling for 24 hours. Full protection will develop within 2-4 days.

Technical Data:

- Form fluid
- Colour clear
- Odour mild
- pH-value n.a.
- Density 1.0 g/cm³ at 20°C

Packaging Options:

- 1 litre plastic bottles
- 5 litre plastic bottles
- 10 litre plastic bottles
- 120 litre drums