

Technical Data Compact K3



Compact K3





Compact K3

Triple Convector Type 33

Height mm	Length mm	Henrad Code	Heat e Watts	missions Btu/hr	Henrad Price
600	400	2063304	956	3262	£142.48
	500	2063305	1195	4077	£165.36
	600	2063306	1433	4889	£183.04
	700	2063307	1672	5705	£199.68
	800	2063308	1911	6520	£211.12
	900	2063309	2150	7336	£228.80
	1000	2063310	2389	8151	£243.36
	1100	2063311	2628	8967	£268.32
	1200	2063312	2867	9782	£293.28
	1400	2063314	3345	11413	£377.52

Btu/hr @ ∆t50°C



Working pressure: Tested to withstand 8.0 bar

For technical and installation information visit our website www.henrad.co.uk/downloads







Technical Data Compact K3

Technical information

Testing and Operating Pressures

Henrad Compact K3 has been independently tested to ensure these radiators perform to a maximum working pressure of 8.0 bar.

Connections

Henrad Compact has $4 \times \frac{1}{2}$ " BSP connections as standard.

Paint Process

Two coat paint process, each Henrad radiator is subjected to a multi-stage cleaning and paint process.

The final powder coat is Traffic white (RAL 9016) which is stoved and cooled to give a perfect finish. All radiators are illustrated in Traffic white unless stated.

Water Treatment

Installation of the system should be properly flushed and fitted in accordance with the British Code of Practice for the Treatment of Water in Domestic Hot Water Central Heating Systems.


Warranty

Henrad Compact K3 comes with a 10 year manufacturer's warranty.

Henrad Compact K3

Wall Mounting Information


All dimensions in mm.




Mounting Bracket Information

All dimensions in mm.


Rear Elevation



Side Elevation








COMPACT K3 Lug Positions

All dimensions in mm.



Dimensions					
Α	133mm				
В	600mm				

Henrad (UK) Limited, Marriott Road, Mexborough, South Yorkshire S64 8BN. Telephone: 0844 543 6200 Facsimile: 0844 543 6300