



# TEC-GUARD

# ARMOR

## TEC-GUARD SYNTHETIC BLEND HIGH MILEAGE PASSENGER CAR MOTOR OILS



**TEC-GUARD® Armor High Mileage motor oils** are superior synthetic blend oils formulated to provide long engine life and premium protection for vehicles with more than 75,000 miles.

They meet modern engine performance demands for improved resistance to oxidation, deposit control, wear protection, prevent oil leakage, helps remove built up of sludge deposits and are backward compatible with earlier API/ILSAC performance levels.

**TEC-GUARD® Armor High Mileage Synthetic Blend 5W-20** meets or exceeds the following performance requirements and industry specifications: API SN PLUS, API SN, API SM, API SL, API SJ, ILSAC GF-5, ILSAC GF-4, ILSAC GF-3, FORD® WSS-M2C930-A, FORD® WSS-M2C945-A, FORD® WSS-M2C945-B1, GM® 6094M, CHRYSLER® MS-6395. Always consult your owner's manual for specific recommendations.

- Extended drain capabilities
- Reduces oil consumption
- Resists thermal breakdown
- Engine cleanliness
- Maximizes power output
- Extra protection for emission's systems
- Protects against rust, corrosion and wear

Test Method		Product Numbers	
NOVACK Volatility	<13%	Bulk	10425203305W20
ASTM D92 - Flash Point, °C	244	Drum	10425213305W20
ASTM D97 - Pour Point, °C	-48	Pail	10425243305W20
ASTM D445 - Viscosity @ 40° C, cST	49.21	Tote	10425203305W20
ASTM D445 - Viscosity @ 100° C, cST	8.59	4/1 Gallon	10425113305W20
ASTM D2270 - Viscosity Index	153	12/1 Quart	10425263305W20
ASTM D4052 - Density, ppg	7.14		

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.