



TEC-GUARD

ARMOR

TEC-GUARD SYNTHETIC BLEND PASSENGER CAR MOTOR OILS



TEC-GUARD® Armor Synthetic Blend 5W-30 is a synthetic blend engine oil that offers excellent oxidation stability, increases your engine's fuel economy, protects against deposits at all temperatures and it is backward compatible with earlier API/ILSAC performance levels.

TEC-GUARD® Armor Synthetic Blend 5W-30 meets or exceeds the following performance requirements and industry specifications:

ILSAC GF-5, ILSAC GF-4, ILSAC GF-3, API SN PLUS, API SN, FORD® WSS-M2C946-A, FORD® WSS-M2C946-B1, FORD® WSS-M2C929-A, GM® 6094M, CHRYSLER® MS-6395. Always consult your owner's manual for specific recommendations.

Test Method		Product Numbers	
NOVACK Volatility	<13%	Bulk	10425204805W30
ASTM D93 - Flash Point, °C	234	Drum	10425214805W30
ASTM D97 - Pour Point, °C	-48	Pail	10425244805W30
ASTM D445 - Viscosity @ 40° C, cST	60.1	Tote	10425204805W30
ASTM D445 - Viscosity @ 100° C, cST	10.2	4/1 Gallon	1042511805W30
ASTM D2270 - Viscosity Index	158	12/1 Quart	10425264805W30

- Excellent thermal oxidation control
- Industry leading high temperature deposit control
- Superior cold-cranking capabilities
- Enhanced anti-wear, anti-foam, bearing corrosion and anti-rust protection