
# **LINEAR LIGHT**



# by PolyBrite International, Inc.

# **CLLA Series**



CLLA is designed to replace up to 400W HPS lamps. Traditional in appearance while providing unmatched overhead lighting performance and energy savings.





#### **FEATURES & BENEFITS**

- Rugged extruded aluminum housing.
- Double wings enlarge heat dissipation area which provides exceptional thermal management.
- Corrosion resistant polyester powder painted 100μm thickness.
- Surface mount and suspension mount available.
- High quality LEDs, driver and components, e.g. MOLEX, WAGO connectors.
- Multiple lighting control options are available, e.g. motion sensor, 1-10V.
- 5 years limited warranty available.
- UL/CUL/DLC/LM79/CE/RoHS

Not all products are qualified on the DLC QPL. To view our DLC qualified products please consult the DLC Qualified Product List at www.designlights.org

### **TECHNICAL PARAMETERS**

Power	120/160/200W			
Input	90-305 VAC			
PF	>0.95			
THD	<15%			
L70	>50,000H			
Operating Temperature	-40°C ∼ +50°C			
Efficacy	110-130lm/W			
ANSI CCT	4000K/5000K			
Min CRI	80*			
IP Rating	IP43			
SPD	Optional			
DALI	/			
1-10V	Optional			
Photocell	/			
Smart Control	/			
Optic (IESNA)	Type V			
Color Options	White			

<sup>\*</sup> Standard

## ORDERING INFORMATION

Example : CLLA120-T5D-50K-WH-00

MODEL (Norminal Power) 90-305VAC	OPTIC LENS	CCT (ANSI)	OPTIONAL COLOR	LIGHTING CONTROL
CLLA120 CLLA160 CLLA200	T5D	40K ★ 50K	★ WH	00 Not required 02 Motion Sensor 05 1-10V dimming