



SS300

SS150

Proudly made in the UK, Precision's versatile all stainless steel space savers are perfect for space optimisation in commercial kitchens all around the world. This range of space saver counters and under counters offer high performance storage solutions in even the smallest of kitchens.

For example, our HSS 300 offers the same internal storage capacity as a traditional two door GN1/1 counter but with a 28% smaller footprint.




UC150

Key Features:

- Stainless Steel Interior & Exterior
- Designed To Operate In 43°C Ambient
- Front Breathing & Venting Refrigeration System
- GN 1/1 Shelving System
- R290 Hydrocarbon Refrigerant
- Zero ODP Injected Polyurethane Insulation - 60mm
- 1 / 4°C Refrigerator Temperature Range
- Electronic Controller With Easy Read LCD Screen
- Hot Gas Defrost
- Door / Drawer Locks Fitted As Standard
- Rifle Bore Coated Evaporators
- Integrated Flush Door Handle
- Gastronorm Shelving System - Anti Tilt Slides
- Hi / Lo Audio Visual Temperature Alarms
- Condensing Unit Safety System To Protect Compressor From Blocked Condensers
- Self Closing Doors
- Adjustable Levelling Feet At Front
- Rollers At Rear For Easy Positioning
- Waste Heat Recovery Condensate Vaporiser System

Options:

- Bank of 2 Drawers (150mm Depth)
- Bank of 2 Wide Drawers (150mm Depth) - SS300
- Countertop Pan Well - HSS300 - 4 x GN1/3 (150mm)
- Insulated Hinged Lid For Countertop Pan Well
- Castors - Increases Height by 62mm
- Adjustable Legs - Increases Height by 125mm
- Stainless Steel Back
- Extra Std Nylon Coated Shelves / Slides - GN1/1
- Stainless Steel Shelves / Slides - GN1/1
- Left Hang Hung Door (UC150 & SS150)



Model	HUC150	LUC150	HSS150	LSS150	HSS300	LSS300
Type	Refrigerator	Freezer	Refrigerator	Freezer	Refrigerator	Freezer
Material	ST/ST Int/Ext	ST/ST Int/Ext	ST/ST Int/Ext	ST/ST Int/Ext	ST/ST Int/Ext	ST/ST Int/Ext
Shelf Size	GN1/1	GN1/1	GN1/1	GN1/1	GN1/1	GN1/1
Number of Shelves	2	2	2	2	4	4
Max Number of Shelves (100mm Spacing)	4	4	4	4	8	8
Temperature Range	1 / 4°C	-18 / -22°C	1 / 4°C	-18 / -22°C	1 / 4°C	-18 / -22°C
Exterior WxDxH (mm)	650x620x815	650x620x815	445x745x860	445x745x860	865x745x860	865x745x860
Net Usable Volume (litres)	60	60	46	46	98	98
Weight (KG)	65	70	65	70	80	85
Refrigerant / GWP	R290 /3	R290 /3	R290 /3	R290 /3	R290 /3	R290 /3
Refrigeration Watts (+45°C Condensing)	405	208	405	208	375	449
Evaporating Temp	-10°C	-30°C	-10°C	-30°C	-10°C	-30°C
Heat Rejection Watts	608	312	608	312	559	674
Noise Output (dBa)	60	59	58	58	67	68
Power	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1
Running Amps	1.5	1.8	1.5	1.8	1.6	3.6
Energy Consumption / 24hrs - kWh*	1.06	5.48	0.77	4.41	1.3	7.45
Energy Consumption / Year (AEC) - kWh*	387	2000	280	1610	475	2720
Energy Efficiency Class*	A	D	A	D	A	F

*Tested to EN16825 Climate Test Class 4 - M1 Classification Test for Refrigerators / L1 Classification Test for Freezers

We are constantly innovating and improving our products. Please always check our website for the most up-to-date version of this spec sheet