

VALTEC



Aurora 150

ALL IN ONE POS TERMINAL



15inch Touch Display
Resolution: 1024x768



75x75mm
VESA-Compatible



Flexible Installation
For POS Peripheral



Aurora 150

Specifications

CPU : INTEL® Celeron™ J1900 (2.0 GHz) quad-core processor

I.O Chipset : INTEL IT8782F

Memory : 1*SO-DIMM slot Support DDR3L 1066/1333 1.35V

Max. capacity of system memory up to 8GB

Expansion Slots : 2 * MiniPCI-E connector slot

Ethernet LAN : Realtek® RTL8111F Chip PCI Express Gigabit LAN

Audio : ALC662 Audio CODEC HD Audio CODEC

Storage : 1* Serial ATA2 3Gb/s connector

1 * M-SATA Connector

Display

TFT LED Panel : 15" 250nits Typ., 1024 x 768 resolution

Touch Screen : Resistive or Capacitive type

Touch Control Board : USB interface

External I/O Ports

USB Port : 1* USB 3.0 port; 6* USB 2.0 ports

Network (LAN) : 1* RJ-45 port

Audio Port : 1* Line-out connector

Display Port : 1 * VGA port

Serial Port : 3 * COM port (D-SUB 9 PIN)

Power Input : 1* 12V DC in

Operation System

Windows 7, Linux (ubuntu, Fedora), POSReady, Windows 8, Windows 10