

2019 | AIR CONDITIONERS

AIR CONDITIONERS

2 0 1 9

LG HVAC SOLUTION



LG Electronics

<http://www.lg.com>
<http://partner.lge.com>

Copyright © 2019 LG Electronics. All rights reserved.



Distributed by



EUROPE SALES INFRASTRUCTURE

GLOBAL PRODUCTION SITE

-  Europe B2B Regional Head Office
-  National Sales Office
-  Air Conditioning Academy
-  European Distribution Center
-  Europe Energy Lab
-  Production Site



LG Energy Labs in Europe

LG Energy Labs are driven to fulfill the commitment of meeting all the requirements regarding energy efficiency and environmental demands. Each LG Energy Lab is an innovative site dedicated to provide essential commercial and residential products in heating, ventilation and the latest energy efficient air conditioning solutions. Additionally, as a showcase, the LG Energy Lab is equipped with complete monitoring and control systems. The performance of all products are tracked and analyzed by a team of Research and Development engineers based in France, Finland and Korea, ensuring maximum efficiency and reliability during the complete products' lifecycle.



European Air Conditioning Distribution Center

LG's European Air Conditioning Distribution Center is centralised in Oosterhout, the Netherlands. Supplying and delivering products to 15 countries in Europe, this Distribution hub has contributed to quick and seamless delivery, direct shipping for smaller orders and bespoke delivery to air conditioners. The hub tries to manage inventory efficiency by complying with the LG EU's established inventory pool.

TOTAL HVAC SOLUTION PROVIDER

Ever since manufacturing Korea's first exclusively home designed air conditioner in 1968, LG has remained as a pioneer and an epitome of air conditioning innovation. LG has been the world's best selling manufacturer of residential air conditioning solutions. In 2008, LG accomplished the target sales for more than 100 million air conditioners. Encouraged by its success rate and technological leadership in the residential air conditioning sector, LG has expanded its wings into system air conditioning as well.

LG has established itself as an inimitable / exemplary HVAC and energy solution provider, investing in new technologies and adding chillers, VRF systems, and building management systems (BMS) to its comprehensive product portfolio. Including a wide range of innovative solutions, LG delivers unparalleled customer service.

LG produces expert air conditioning professionals at its academic centers, of which there are nearly 80 worldwide. These academic centers provide workshops and training programs that offer excellent hands-on experience. Additionally, LG provides advanced and highly sophisticated tools for HVAC system engineers and installers,

including its time saving LG Air Conditioner Technical Solution (LATS) software. LG also operates several state-of-the-art R&D facilities all across the planet.

One such facility is the Energy Lab, a purpose-built R&D and testing center in northern France. Helping to keep the company ahead of the competition, the scientists and engineers at the Energy Lab study the ramifications of different environmental conditions on LG's products. This indepth research and analysis enables LG to tune its solutions to the specific environmental demands of each individual market. Combining the best technologies with the intellectual ideas, LG's high quality products have now earned the favoritism of customers in over 100 countries.

INDEX

008 - 119

RESIDENTIAL

012 - 061

WALL MOUNTED

062 - 119

MULTI SPLIT



120 - 203

COMMERCIAL

120 - 203

SINGLE SPLIT



204 - 238

HEATING

204 - 238

THERMA V



R32 REFRIGERANT

HIGHLY EFFICIENT GREEN REFRIGERANT

R32 is environment friendly and classified as a highly efficient 'Go Green' refrigerant.


Reducing Global Warming & Ozone Layer Depletion

The quantity of R32 refrigerant used is appreciably low as compared to the R410A refrigerant. Consequently, this results in decreasing the potential of global warming and minimal depletion of the ozone layer. Comparative case studies of the different refrigerants are indicated in the table and chart as below:

	R410A	R32
Composition	Blend of R32 50% + R125 50%	Pure R32 (No blend)
GWP (Global Warming Potential)	2087.5	675

High Refrigerant Compression Rate

High refrigerant compression rates lead to high capacity as compared to existing refrigerant R22, and R410A.



RESIDENTIAL

WALL MOUNTED

MULTI SPLIT



WALL MOUNTED

LINE-UP

INDOOR UNIT

MODEL	KBTU	5	7	9	12	15	18	24
	KW	1.5	2.1	2.6	3.5	4.2	5.3	7.0
Prestige				H09APNSM	H12APNSM			
ARTCOOL Gallery				A09FR.NSF	A12FR.NSF			
ARTCOOL Mirror			AM07BPNSJ	AC09BQ.NSJ	AC12BQ.NSJ	AC18BQ.NSK	AC24BQ.NSK	
Wall mounted				AC09SQ.NSJ	AC12SQ.NSJ	AC18SQ.NSK		
Deluxe			DM07RPNSJ	DC09RQ.NSJ	DC12RQ.NSJ	DC18RQ.NSK	DC24RQ.NSK	
Standard Plus		PM05SPNSJ	PM07SPNSJ	PC09SQ.NSJ	PC12SQ.NSJ	PM15SPNSJ	PC18SQ.NSK	PC24SQ.NSK
Standard				S09EQ.NSJ	S12EQ.NSJ	S18EQ.NSK	S24EQ.NSK	

○ Single Split Only ○● Compatible ● Multi Split Only

OUTDOOR UNIT

MODEL	KBTU	9	12	14	16	18	21	24	27	30
	KW	2.6	3.5	4.1	4.7	5.3	6.2	7.0	7.9	8.8
Prestige		H09APU24	H12APU24							
ARTCOOL Gallery		A09FR.UL2	A12FR.UL2							
ARTCOOL Mirror		AC09BQUA3	AC12BQUA3		AC18BQ.UL2		AC24BQU24			
Single		AC09BQUA3	AC12BQUA3		AC18BQ.UL2					
Deluxe		DC09RQUL2	DC12RQUL2		DC18RQUL2		DC24RQU24			
Standard Plus		PC09SQUA3	PC12SQUA3		PC18SQUUL2		PC24SQU24			
Standard		S09EQUA3	S12EQUA3		S18EQ.UL2		S24EQU24			

○ Single Split Only ○● Compatible ● Multi Split Only

* ARTCOOL Gallery is available in May, '19

※ Refer to multi split line up for 5, 7, 15KBTU indoor unit connection.

WALL MOUNTED

Prestige | Artcool | Deluxe | Standard Plus | Standard



PRESTIGE

DUAL Inverter



LG Prestige offers one of the most comprehensive air conditioning solutions with supreme energy efficiency and providing a tranquil environment.

ARTCOOL

Gallery DUAL Inverter



The design of LG air conditioners is fashionably elegant in such a way that it reigns supreme compared to others. Customise your space.

ARTCOOL DUAL Inverter



In addition to modern lines and classic style, LG ARTCOOL offers the most outstanding air conditioning solution in a complete and attractive package.

DELUXE DUAL Inverter



LG retains its leading position in supplying RACs, incorporating the essential and fundamental elements of air conditioner solutions.

STANDARD PLUS

DUAL Inverter



New Standard Plus is a compact size unit with powerful cooling performance and an intelligible and convenient design.

STANDARD




DUAL Inverter



Standard model displays all the sophisticated features of general RAC integrated with LG's more advanced technology.

WALL MOUNTED

FEATURE OVERVIEW

				CORE TECH		SMART		ENERGY EFFICIENCY	
				Dual Inverter Compressor	R32 Refrigerant	Embedded Wi-Fi	Smart Diagnosis	Active Energy Control	Energy Display
Prestige		9k	12k						
				●		●	●	●	●
ARTCOOL Gallery		9k	12k						
				●	●	● ³ (Ready)			
ARTCOOL		9k	12k	18k	24k				
				●	●	●	●	●	●
		7, 9, 12, 18, 24 kBtu							
		7k		●	●	●			
		Multi ⁴							
Deluxe		9k	12k	18k	24k				
				●	●	●	●	●	●
		A++ Cooling & A++ Heating							
		7k		●	●	●			
		Multi ⁴							
Standard Plus		9k	12k	18k	24k				
				●	●	●	●	●	●
		A++ Cooling & A+ Heating							
		5k		●	●	●			
		7k							
		15k							
		Multi ⁴							
Standard		9k	12k	18k	24k				
				●	●	●	●	●	●
		A++ Cooling & A+ Heating							

1. When connected to Multi Outdoor unit, Silent Mode 3dB is working by simply setting the dip switch on the PCB of the outdoor unit.
 2. When combines with 40kBtu, Cooling A+, Heating A
 3. Wi-Fi Ready : can be connected by using Wi-Fi controller (PWFMD200)
 4. Please refer to the specifications of Multi outdoor units.

DURABILITY	HEALTH	FAST COOLING & HEATING	COMFORT
			
Gold Fin™	Plasmaster™ Ionizer ²	Dual Protection Filter	Auto Cleaning
			Jet Cool
			4 Way Swing
			Fast Heating
			Comfort Air
			Low Noise 19dB
			Silent Mode 3dB
			Quick & Easy Installation

CORE TECH



Dual Inverter Compressor

- What is the Dual Inverter Compressor?


A compressor is the heart of an air conditioner, and monitoring whether it works properly, effectively, or noisily that can cause stress as well as cost more money. LG's Dual Inverter Compressor provides an effective solution, resulting in an air conditioner that cools faster, lasts longer, and operates quieter than conventional models.



- How it Works

Varied-Speed Dual Rotary

A compressor motor with a wider rotational frequency that is energy efficient and has a higher volumetric quick cooling capacity than any conventional compressors.



- Product Reliability Improvement

The Dual Inverter Compressor reduces the vibration and with it the sound pressure levels. The reduction in vibration reduces the possibility of fractures occurring in the the surrounding pipework.



R32 Refrigerant

- Pain Point

Due to accelerated global warming and the destruction of the ozone layer, various international conventions and meetings are held to enhance restrictions to the use of refrigerant or enforce the use of eco-friendly refrigerants. In order to reduce environmental destruction, refrigerant R32 is internationally acclaimed for being Eco-friendly. It has the unprecedented feature as a low volume refrigerant that is as efficient as any conventional refrigerant; thus qualifying as a green refrigerant.



- How it Works

Utilising a small amount of the R32 refrigerant also qualifies it to be a highly green efficient system.


Alleviate Global Warming & Ozone Layer Destruction

R32 efficiently works even in small volume compared to existing R410A refrigerant, which decreases potential hazard of global worming.

High Compressibility

R32's high compressibility rate gives more powerful cooling performance and efficiency compared to existing refrigerant R22 and R410A.

	R410A	R32
Composition	Blend of R32 50% + R125 50%	Pure R32 (No blend)
GWP (Global Warming Potential)	2087.5	675



- Benefit

Eco-friendly Refrigerants that can prevent environmental pollution.

High-Efficiency & High-Performance Refrigerant

Reduce refrigerant charge by 15% R410A Preparation for an increase in efficiency for both heating and cooling. R410A Preparation for easy install. (R410A blended refrigerant, R32 single refrigerant)

WALL MOUNTED KEY FEATURES

SMART**Embedded Wi-Fi**

Control your air conditioners by using Android or iOS based smartphones. This advanced technology provides you many benefits.

• LG Smart ThinQ

Download the 'LG SmartThinQ' app from the Google Downloads or the Appstore.



LG Smart ThinQ

• How it Works**Embedded Wi-Fi modem**


Enable "LG Smart ThinQ" on your air conditioner.



By using the embedded Wi-Fi modem, get ready for innovation without boundaries.

**Wi-Fi Connectivity**

Each individual member of your family can customise the air conditioner temperature and fan speed accordingly and then save the settings in their app to run it later. These settings can be saved for each air conditioner too.

Multiple Devices**Multi-Control**








* Can be controlled by multiple users, but not simultaneously

• Benefit**Simple operation for various functions**

On/Off, Current Temp

Mode, Set Temp

Vane Control

**Straight forward Management****Integrated Home Appliances Control**

Control / Monitor all your LG appliances from one place.



Access your air conditioner anytime and from anywhere with a Wi-Fi equipped device and LG's exclusive control app, Smart ThinQ.



WALL MOUNTED KEY FEATURES

SMART**Smart Diagnosis**

Smart Diagnosis allows you to check setup, installation, troubleshooting and other information conveniently from your smartphone.

* Specifications may vary for each model.

* When connected to Multi ODU, Smart Diagnosis function may not be supported.

• What is the Smart Diagnosis?

Smart Diagnosis allows users to conveniently check setup, installation, troubleshooting and other information directly from a smartphone.

* Builds upon widespread smartphone use and offers greater USP diversification


* Perfect for consumers who are unable to view information about their air conditioner via a display or remote control.

• How it works


By using "LG Smart ThinQ" App and clicking "Start Smart Diagnosis", monitor and check diagnosis results conveniently via Wi-Fi.



* When the model doesn't provide embedded Wi-Fi, diagnose by buzzer sound with the same app and remote controller.

**• Benefit**

Easily comprehensible error messages make detecting a solution and contacting the service center simple and convenient

For consumer**For Installer and SVC**

- Easily check operational status of a product without a display or one that provides limited information
- Save energy by monitoring key operational information and power consumption
- Using the Maintenance Guide helps to improve device performance and increase product life-span.

- Understand the product better by easily confirming operational status and information
- Intuitively diagnose problems by comparing current and past usage data
- Maintain installation capabilities and reduce installation errors by quickly confirming device operational status


WALL MOUNTED KEY FEATURES

SMART**SIMs**

By connecting SIMs chip, you can check the status of your air conditioner and diagnose problems from your smartphone.

* Specifications may vary for each model.

* When connected to Multi ODU, SIMs function may not be supported.

• What is the LG SIMs?

Monitor the status of your air conditioner and accurately diagnose problems by connecting it to a smartphone via a SIMs chip.

* SIMs : Smart Inverter Monitoring System

• How It Works**SIMS App**

1. Use a SIMs chip to connect a smartphone to an air conditioner.
2. Monitor and diagnose problems in real time using the SIMs app.

• Benefit**Easy Monitoring**

Diagnose problems anytime, anywhere with a SIMs chip.

Easy Diagnosis & Quick Response

Easily monitor IDU/ODU and diagnose problems.

Save and review diagnostic data.

Main	Current outdoor temperature Indoor temperature Inverter Comp frequency Operating opening Error code / Frequency limits Indoor. Outdoor fan speed
Indoor Unit	Indoor Unit Capacity / Operation Mode THM mode / REM mode FAN operating condition / EEV opening Room Temperature / Suction Temperature Intermediate Temperature Exit Temperature
Outdoor Unit	Frequency / Fan RPM DC Link / Input Current Input Voltage EEV operation mode Restart timer Compressor mode / EEV opening
Chart	Room Temperature Heat exchanger pipe temperature Compressor discharge temperature Frequency / Outdoor temperature Compressor suction temperature Electric current / Voltage

Certificate

* Smartphone Requirements (iOS : 6.1 or later, Android : 2.3 or later)

**Low Refrigerant Detection**

Early notification of low refrigerant protects your air conditioner from a risk of damage.

* Specifications may vary for each model.

* Depending on the experimental conditions.

* When connected to Multi ODU, Low Refrigerant Detection function may not be supported.


• How It Works**Early Detection of Low Refrigerant Levels**

The Air Conditioner is automatically shut down when low refrigerant level is detected.


3 Checkpoints for Low Refrigerant Level :

- 1) The heat exchanger temperature is comparatively cool
- 2) The outdoor unit is working properly
- 3) The energy consumption is working under a standard pattern

If any of the above conditions are not met, for a maximum of 4 times, after 15 minutes of Air Conditioner operation, a Low Refrigerant level is detected and the Air Conditioner is shut down.

Capacity and Effectiveness of the Refrigerant Levels

* This function only works under the following conditions:
- Indoor/Outdoor temperature is up to 20 degrees Celsius
- Cooling and dehumidification mode

• Benefit**Longer Lifespan for Air Conditioner**

* Some models show CH and 38 alternately on the display.

WALL MOUNTED KEY FEATURES

ENERGY EFFICIENCY

Supreme Energy Efficiency


LG's revolutionary Inverter technology boasts powerful yet quiet performance while minimising energy consumption. With world class energy efficiency, bask in the cosiness of the atmosphere surroundings whilst saving energy.

* Based on H09AL Model
* Specifications may vary for each model.


• High Efficient Compressor and Reversing Valve

Rotary Compressor and Motor Efficiency

The number of suction connections has been reduced from two to one to increase the efficiency of the refrigerant compression during low speed conditions. The DC motor in LG air conditioners remains unsurpassable incomparable to in the world's best efficiencies.


**Bi-Stable Reversing Valve**

The Input power of 4-way valve has been reduced to 0W by using a Bi-Stable type.



• Improved Inverter Drive Efficiency

Used to optimise the time of current flow by controlling the number of converter switching according to energy consumption status. Displays comparatively higher performance and advanced energy efficiency than conventional Inverter air conditioner by reducing power loss with an advanced material component called SiC.




Active Energy Control 4 - Step

LG's Active Energy Control adjusts the energy consumption level and cooling capacity by controlling maximum frequency of the compressor motor.


* Specifications may vary for each model.
* Depending on the experimental conditions.
* When connected to Multi ODU, Active Energy Control function may not be supported.

• Concept & Benefit

Cooling a home can come at a high cost particularly during the hot summer months. Avoid those costs and save energy by taking advantage of LG's 4-Step Energy Control System.



• How It Works



WALL MOUNTED KEY FEATURES

ENERGY EFFICIENCY**Energy Display**


LG's Energy Display panel monitors the amount of energy levels used. Save on energy consumption while enjoying the cooling by checking your energy level on the panel.

* Specifications may vary for each model.

* When connected to Multi ODU, Energy Display function may not be supported.

• How it Works**Magic Display & Remote Control**

With the push of a button on the remote control, indoor unit's LCD display shows the current and total energy use, thus making the users aware of reducing energy consumption.

**• Benefit****Normal Mode**

Current Setting Temp

**Electric Power**

Displays Current Energy Use

**• Additional Benefit****Fan Speed**

Display	Speed
F5	High
F4	Medium-High
F3	Medium
F2	Medium-Low
F1	Low

Sleep Mode

For example, setting 1hr

WALL MOUNTED KEY FEATURES

PERFECT HEALTHCARE**Plasmaster™ Ionizer^{PLUS}**


The powerful plasma ionizer protects you from bad odors and harmful and contagious particles in the air with over 3 million ions to sterilize not only the air passing through the air conditioner, but also surrounding surfaces for a safer, and cleaner environment.

* Specifications may vary for each model.


* Depending on the experimental conditions.

• How It Works**Sterilization and Deodorization (Utilizes Over 3 Million Ions)**

Plasmaster Ionizer+ reduces harmful and contagious microscopic particles by infusing the air passing through the air conditioner with over 3 million ions.

**• Test Result****Sterilization Performance Evaluations**


Sterilize Bacteria (E.coli colon bacillus) over 99.9% in 30 min.



* Test Conditions :
Space : 52m³ Chamber
Temperature & Humidity : Normal
Bacteria : Staphylococcus Aureus

2.1 odor strength decrease in 60 minutes

An odor measured as 2 European odor units (ouE/m³) or less indicates that the level of odor falls within permissible limits.



Odor strength reduce 3.6 → 1.5 / The Odor floating in the room as well as curtain and clothes.

WALL MOUNTED KEY FEATURES

PERFECT HEALTHCARE



Dual Protection Filter

The Dual Protection Filter collects dust.

* Specifications may vary for each model.
* Depending on the experimental conditions.

• What is the Dual Protection Filter?

The Dual Protection Filter, designed to capture dust particles over $10\mu\text{m}$ in size, is the first line of defense and hindrance against finer particles.



• Additional Benefit

Easy to Open

Easily detachable full surface cover helps clean the air conditioner flawlessly.

**Easy to Clean**

The filter is designed for easy handling and quick cleaning, which lengthens its lifespan.



Auto Cleaning

The interior of the air conditioner is maintained clean by drying off the heat exchanger, then sterilizing the interior once more.

* Specifications may vary for each model.

• Pain Point


The main cause of odor within air conditioners is mold and bacteria growing on the heat exchanger. These germs can spread when the heat exchanger is wet.




• How It Works

Cleans Filter with Regular Airflow

The comprehensive auto cleaning function prevents the formation of bacteria and mold on the heat exchanger, providing an enhancing environment.



By dehumidifying, the auto cleaning function eliminates substances that might be harmful.



The indoor environment remains odorless with the advanced deodorizing function.




By preventing polluting of the heat exchanger caused by various germs and bacteria, the performance and life span of the air conditioner do not wither away even after a period of 10 years.

• Benefit

Removes Harmful Particles

Auto Cleaning provides clean air by preventing bacteria, mold and odors that can otherwise accumulate in an indoor unit.



Bacteria
Prevention



Odor
Elimination



Mold
Elimination

WALL MOUNTED KEY FEATURES

FAST COOLING & HEATING



Fast Cooling

The cool airflow reaches all the corners of the room, keeping the space cool and comfortable.

* Specifications may vary for each model.
* Depending on the experimental conditions.


• How It Works

Bigger Skew Fan



A 25% larger skew fan emanates highly powerful blasts of air.

**Cooling Outlet**

A larger, optimally designed cooling outlet emanates to large areas and cools spaces faster.



• Test Result

Test Result**Changes in Temperature Over 30 Minutes**

* Test Conditions :
Outdoor temperature : 35°C, Indoor temperature : 33°C,
Humidity : 60%, Remote control : 24°C High

* Test Conditions :
: Indoor temperature 33°C, Outdoor temperature 35°C,
Relative humidity 60%, Setting temperature 24°C



Jet Cool

LG air conditioners provide optimized high-speed airflow, which can cool rooms faster while delivering cool air evenly in every direction.

* Specifications may vary for each model.
* Depending on the experimental conditions.

• How It Works


One Click "Jet Mode"

Reduces the temperature of outflowing air to 18°C for 30 minutes with just one click.



• More Powerful Performance

By reducing the second vortex, which decreases airflow within the air outlet, and enlarging the fan size, the amount of airflow is increased to 13.0 CMM.



WALL MOUNTED KEY FEATURES

FAST COOLING & HEATING



4-Way Swing

Cool air reaches out to the entire room regardless of where the air conditioner is installed

* Specifications may vary for each model.

• How It Works

6-Step Vane, Control up to 70°

The vertical vane, which moves up and down, has 6 different settings including full-auto swing.



* Angle can be different from each model and working mode.



5-Step Louver, Control up to 55°

The louver, which sways left and right, has 5 different settings including full auto-swing.



• Easy and Simple Control

Airflow direction can be changed by LG ThinQ Wi-Fi app.

Up/Down Swing**Left/Right Swing**

Fast Heating

LG Residential Air Conditioners satisfy your heating needs while consuming less energy, by heating a wider space in a shorter period of time to create a warm and comfortable living environment.


* Specifications may vary for each model.

* Depending on the experimental conditions.


• How It Works

4 way Auto Swing (Easy Airflow Control)


4 Way Auto Swing adjusts airflow based on the surrounding environment, allowing for optimal distribution of warm air to living areas and enabling quick heating.

**Vertical Airflow**


When heating, the vane sends heated air downwards to maintain a pleasant and balanced room temperature.



• Benefit & Test Result

22% Quick Heating

* Test Conditions :
Outdoor temperature : 7°C, Indoor temperature : 12°C,
Humidity : 87%, Remote control : 30°C Power

Changes in Temperature Over 20 Minutes

* Test Conditions :
Outdoor temperature : 7°C, Indoor temperature : 12°C,
Humidity : 87%, Remote control : 30°C Power

WALL MOUNTED KEY FEATURES

EXTREME DURABILITY




10-Year Inverter Compressor Warranty

LG, with confidence in product quality, preserves better lives for customers by providing 10 years warranty for Inverter Compressor of Air conditioners.

* Specifications may vary for each model.

• What is the 10 Year Warranty?

The compressors is for the Air Conditioner what the engine is to the vehicle. With the 10 year warranty on the compressor, users can avail of the benefits of LG air conditioner for a longer period of time.



• Benefit & Verification

Reliable Air Conditioner

Product safety is emphasized by offering a 10-year warranty on the compressor to reassure customers about product durability.



Verification

TUV Rheinland, Long Term Accelerated-reliability Test & High Marginal Test

- * Long Term Accelerated-Reliability test
LG's unique testing method with reinforced operating condition for a product life assurance to test and determine the product life cycle in a short period of time by accelerating the life cycle.
- * High Marginal Test
Test method to secure durability in various adverse conditions that may occur in the field by performing comp reliability test against higher pressure and temperature than the designed range of pressure and temperature which the comp operates in.
- * Verification obtained from TUV Rheinland for 10-year product life cycle



Gold Fin™


The Gold Fin™ coating protects the surface of the heat exchanger from unnecessary wear and corrosion.

- * Specifications may vary for each model.
- * Depending on the experimental conditions.

• How It Works

Crosscut View of Heat Exchanger

The gold-colored special coating on the fin of the heat exchanger prevents corrosion, extending the life of the unit.



• Test Result

Conventional Fin



* Test result 360 hrs. after being exposed to sodium chloride

Gold Fin™



WALL MOUNTED KEY FEATURES

COMFORT



Comfort Air

LG provides pure hygienic and temperature regulated atmosphere surrounding your living space. An automatic vane angle adjustment sets perfect vane angle and air volume.

* Specifications may vary for each model.

• Concept

If the air conditioner remains ON while asleep, it can lower body temperature or cause discomfort, especially if the outflow of cool air is directly close to the room's occupants. This can be eliminated by the Comfort Air vane angle thus providing a comfortable environment to the sleeping occupants.

• How It Works

Control Panel**Comfort Vane**

This option conveniently sets an AC's louvers to a preset position so that outflowing air is directed away from a room's occupants.

Scene 1: Inclines to a maximum 80° angle.

Sets vane angle to highest position : Optimized for gentle airflow cooling.

Indoor Unit Display**Remote Controller Display****Scene 2: Declines to a maximum 10° angle.**

Sets vane angle to lowest position : Optimized for gentle airflow heating.

Indoor Unit Display**Remote Controller Display**

Low Noise


LG Air Conditioners operate at 19dB low noise level, moreover provide healthy soft air by just 1 touch.

* Specifications may vary for each model.

• How It Works

LG's Unique Skew Fan


By minimizing the surface pressure of the fan blade when in contact with the air peak noise are reduced to a level that is among the lowest in the world.



**15%
Tilted
Stabilizer**

BLDC Fan Motor

With strong torque and powerful ND magnetism as well as precise speed control of 13 different steps for smooth operation, the BLDC motor provides substantial air volume and high static pressure, while keeping electrical and mechanical noise lower, and making high-speed operation available.




**Advanced
Motor**

- Low Efficiency.
- Heat Problem during overhauling.
- Difficult precise speed control.

- Low Electric and mechanical noise.
- Precise speed control durable.

ALVC (Active Low Vibration Control)

A speed-error component estimates the load to compensate for imbalances, which are the primary causes of vibration and noise, enabling the rotation of the motor without vibration at low Hz levels.



**40%
Cut Torque
Variation**

• Benefit



22dB
Conventional
Inverter



26dB
Forest



32dB
Conventional
On/Off



36dB
Library



WALL MOUNTED KEY FEATURES

COMFORT**Silent Mode**

Silent mode ensures a tranquil and serene experience for the user by reducing noise disturbances while you are resting.



* Specifications may vary for each model.

* Depending on the experimental conditions.

* When connected to Multi Outdoor unit, Silent Mode is working by simply setting the dip switch on the PCB of the outdoor unit.

• How It Works

In Silent Mode, the overall sound level of the outdoor unit drops by up to 3dB and the sound level of the indoor unit also decreases.

Press the Silent Button**Controls the Outdoor Compressor****• Test Result****Noise Comparison Graph**

* Test Conditions
Spec : Selecting Silent Mode reduces the noise of an outdoor fan unit by 3dB
Assessment : 36.2 dB emitted from center/side of unit at a distance of 1m.


**Quick & Easy Installation**

LG air conditioner is designed for an easy and efficient installation, making possible to install several units in a short period of time


* Specifications may vary for each model.

• Concept


By reducing the manpower and time required for installation, it is now possible to install more units in less time.

• How It Works**One Simple Packing Box****Installation Plate Improvement**


LG's installation plate is larger and customized to reduce installation time.

**Wider Tubing Space**


The space provided for tubing facilitates the whole installation process and hides the unorganized parts, making it appear clean and tidy.

**Detachable Bottom Cover**

The air conditioner's bottom cover is detachable for easier installation and access.

**Quick button for running test**

The test button is conveniently located and easy to find.



WALL MOUNTED SPECIFICATION
PRESTIGE



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification : www.eurovent-certification.com



• Single Combination

	UNIT		9K	12K
	INDOOR	OUTDOOR		
Capacity	Cooling Min / Rated / Max W		300 / 2500 / 4000	300 / 3500 / 4250
	Heating Min / Rated / Max W		300 / 3200 / 6900	300 / 4000 / 7320
Power Input	Cooling Rated W		4300	4700
	Heating -7°C W		490	833
EER			5.10	4.20
S.E.E.R.			9.4	9.1
P design C			2.5	3.5
COP			5.4	5.1
S.C.O.P.			5.2	5.1
P design H			3.2	3.8
Energy Label	Cooling (A+++ to D Scale)		A+++	A+++
	Heating (A+++ to D Scale)		A+++	A+++
Annual Energy Consumption	Cooling kWh		94	135
	Heating kWh		862	1045
Sound Pressure	Cooling S / L / M / H dBA		19 / 29 / 37 / 42	19 / 29 / 37 / 42
	Heating L / M / H dBA		29 / 37 / 42	29 / 37 / 42
Sound Power	Cooling High dBA		60	60
	Air Flow Rate Cooling S / L / M / H m³/min		6.6/8.7/11.1/12.4	6.6/8.7/11.1/12.4
	Max (Power) m³/min		15.5	15.5
	Heating L / M / H m³/min		8.7/11.1/14/3	8.7/11.1/14/3
Dehumidification Rate	Cooling I/h		1.5	1.7
Running Current	Cooling Rated/Max A		2.5/6.0	3.9/6.0
	Heating Rated/Max A		2.9/3.7	7.4/7.4
Starting Current	Cooling Rated A		2.5	3.9
	Heating Rated A		2.9	3.7
Power Supply		Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50
Circuit Breaker		A	15	15
Power Supply Cable	N x mm²		3 x 1.0	3 x 1.0
Power & Transmission Cable			4 x 1.0 (Including Earth)	4 x 1.0 (Including Earth)
Dimension	mm		875 x 295 x 235	875 x 295 x 235
Net Weight	kg		11.0	11.0
Fan Motor Output	W		30	30
OUTDOOR				
	H09AP.U24		H12AP.U24	
Operation Range	Cooling Min / Max °CDB		-10 / 48	-10 / 48
	Heating Min / Max °CDB		-25 / 24	-25 / 24
Sound Pressure	Cooling High dBA		48	48
	Heating High dBA		50	50
Sound Power	Cooling High dBA		65	65
	Air Flow Rate High m³/min		49	49
Piping	Length (Odu/ldu) Min / Max m		3 / 20	3 / 20
	Elevation (Odu/ldu) Max m		10	10
Piping Connection	Liquid OD(Outside) mm (inch)		6.35 (1/4)	6.35 (1/4)
	Gas OD(Outside) mm (inch)		9.52 (3/8)	9.52 (3/8)
	Drain OD(Outside) mm (inch)		21.5 (0.85)	21.5 (0.85)
	Type		R410A	R410A
Refrigerant	Charge at 7.5m g		1,150	1,150
	Additional charge t-CO₂ eq		2.40	2.40
	GWP		2087.5	2087.5
Fan Motor Output	Additional charge g/m		85	85
Compressor Type	GWP		Twin Rotary	Twin Rotary
Net Weight	kg		43	43
Dimension	mm		870 x 650 x 330	870 x 650 x 330

* This product contains Fluorinated greenhouse gases (R410A).

** S : Sleep / L : Low / M : Medium / H : High

*** Specification, design and feature are subject to change without prior notice.

WALL MOUNTED SPECIFICATION

ARTCOOL GALLERY



RESIDENTIAL



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification : www.eurovent-certification.com



• Single Combination

	UNIT		9K	12K
	INDOOR	OUTDOOR		
Capacity	Cooling Min / Rated / Max W		1300 / 2500 / 3500	1300 / 3500 / 4000
	Heating Capacity +7°C W		1300 / 3000 / 4000	1300 / 3500 / 4500
Power Input	Cooling Rated W		700	1090
	Heating +7°C W		930	1090
EER			3.57	3.21
S.E.E.R.			5.3	5.3
P design C			2.5	3.5
COP			3.22	3.21
S.C.O.P.			3.8	3.8
P design H			2.5	2.5
Energy Label	Cooling Energy Label		A	A
	Heating Energy Label		A	A
Annual Energy Consumption	Cooling kWh		165	231
	Heating kWh		921	921
Sound Pressure	Cooling S / L / M / H dBA		26 / 28 / 40 / 45	26 / 28 / 40 / 45
	Heating L / M / H dBA		28 / 40 / 46	28 / 40 / 46
Sound Power	Cooling H dBA		60	60
	Sleep Max (Power) m³/min		3.8 / 4.4 / 5.9 / 7.7	3.8 / 4.4 / 5.9 / 7.7
Air Flow Rate	Cooling Max (Power) m³/min		9.5	9.5
	Heating L / M / H m³/min		4.4 / 5.9 / 7.7	4.4 / 5.9 / 7.7
Dehumidification Rate	Cooling Rated A		1.2	1.4
Running Current	Cooling Current 6.0		3.5	4.5
	Heating Current 4.0		6.0	6.0
Starting Current	Cooling Current 7.0		5.0	5.0
	Heating Current 4.0		7.0	7.0
Power Supply	Cooling / Heating Rated A		3.5 / 4.0	4.5 / 5.0
	Ø / V / Hz 1 / 220-240 / 50		1 / 220-240 / 50	1 / 220-240 / 50
Circuit Breaker			A	15
Power Supply Cable	N x mm²		3 x 1.0	3 x 1.0
Power & Transmission Cable			4 x 1.0 (Including Earth)	4 x 1.0 (Including Earth)
Dimension	mm		600 x 600 x 146	600 x 600 x 146
Net Weight	kg		15.0	15.0
Fan Motor Output	W		16.7	16.7
OUTDOOR				
	H09FR.UJ2		A09FR.UJ2	
Operation Range	Cooling Min / Max °CDB		-10 / 48	-10 / 48
	Heating Min / Max °CDB		-10 / 24	-10 / 24
Sound Pressure	Cooling High dBA		49	49
	Heating High dBA		51	51
Sound Power	Cooling High dBA		65	65
	Air Flow Rate High m³/min		35	35
Piping	Length (Odu/ldu) Min / Max m		3 / 15	3 / 15
	Elevation (Odu/ldu) Max m		10	10
Piping Connection	Liquid OD(Outside) mm (inch)		6.35 (1/4)	6.35 (1/4)
	Gas OD(Outside) mm (inch)		9.52 (3/8)	9.52 (3/8)
	Drain OD(Outside) mm (inch)		21.5 (0.85)	21.5 (0.85)
	Type		R32	R32
Refrigerant	Charge at 7.5m g		800	800
	Additional charge t-CO₂ eq		0.540	0.540
	GWP		20	20
Fan Motor Output	Additional charge g/m		675	675
Compressor Type	GWP		43	43
Net Weight	kg		34.1	34.1
Dimension	mm		770 x 545 x 288	770 x 545 x 288

* This product contains Fluorinated greenhouse gases (R32).

** S : Sleep / L : Low / M : Medium / H : High

*** Specification, design and feature are subject to change without prior notice.

WALL MOUNTED SPECIFICATION

ARTCOOL MIRROR



- LG participates in the ECP programme for EUROVENT AC program.
- Check ongoing validity of certification : www.eurovent-certification.com



- Single Combination

UNIT		9K		12K		18K		24K	
INDOOR		AC09BQ.NSJ		AC12BQ.NSJ		AC18BQ.NSK		AC24BQ.NSK	
Capacity	Cooling	Min/Rated/Max	W	890 / 2500 / 3700	890 / 3500 / 4040	900 / 5000 / 5500	900 / 6600 / 7420	900 / 7500 / 8640	4850
	Heating +7°C	Min/Rated/Max	W	890 / 3300 / 4100	890 / 4000 / 5100	900 / 5800 / 6400	900 / 7500 / 8640		
Power Input	Heating -7°C	Rated	W	2600	3000	4200	4850	2164	2238
	Cooling	Rated	W	656	1080	1562	2164		
EER	Heating +7°C	Rated	W	800	1050	1611	2238	3.05	3.05
			W/W	3.81	3.24	3.20	3.05		
S.E.E.R.				7.0	6.6	7.0	6.9		
P design C			kW	2.5	3.5	5.0	6.6		
COP			W/W	4.13	3.81	3.60	3.35		
S.C.O.P.				4.0	4.0	4.3	4.2		
P design H			kW	2.5	2.5	3.9	5.0		
Energy Label	Cooling (A++ to E Scale)			A++	A++	A++	A++	A++	A++
	Heating (A++ to E Scale)			A+	A+	A+	A+		
Annual Energy Consumption	Cooling		kWh	125	186	250	335	31 / 34 / 42 / 47	31 / 34 / 42 / 47
	Heating		kWh	875	875	1270	1628		
Sound Pressure	Cooling	S / L / M / H	dBA	19 / 27 / 35 / 41	19 / 27 / 35 / 41	31 / 34 / 39 / 44	31 / 34 / 42 / 47	34 / 42 / 47	34 / 42 / 47
	Heating	L / M / H	dBA	27 / 35 / 41	27 / 35 / 41	34 / 39 / 44	34 / 42 / 47		
Sound Power	Cooling	H	dBA	59	59	60	65	20.0	20.0
	Cooling	S / L / M / H	m³/min	3.0 / 4.2 / 7.5 / 10.0	3.0 / 4.2 / 7.5 / 10.0	8.0 / 10.5 / 13.0 / 14.5	8.0 / 10.5 / 13.1 / 16.1		
Air Flow Rate	Max (Power)		m³/min	12.5	12.5	15.5		10.5 / 13.1 / 16.1	10.5 / 13.1 / 16.1
	Heating	L / M / H	m³/min	5.6 / 7.2 / 10.0	5.6 / 7.2 / 10.0	11.0 / 13.5 / 16.0			
Dehumidification Rate			l/h	1.1	1.3	1.8	2.5		
Running Current	Cooling	Rated	A	3.3	4.7	6.9	9.8	14.0	14.0
	Max	A		6.0	6.0	9.0			
Starting Current	Heating	Rated	A	4.0	4.7	7.1	10.4	14.0	14.0
	Max	A		7.0	7.0	9.5			
Power Supply	Cooling/Heating	Rated	A	3.3 / 4.0	4.7 / 4.7	6.9 / 7.1	9.8 / 10.4		
Circuit Breaker			Ø/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50		
Power Supply Cable			A	15	15	20	25		
Power & Transmission Cable			N x mm²	3 x 1.0	3 x 1.0	3 x 1.5	3 x 2.5	4 x 1.0	4 x 1.0
			N x mm²	4 x 1.0	4 x 1.0	4 x 1.0			
Dimension			(Including Earth)	(Including Earth)	(Including Earth)	(Including Earth)	(Including Earth)		
Net Weight			mm	837 x 308 x 192	837 x 308 x 192	998 x 345 x 212	998 x 345 x 212		
Fan Motor Output			kg	9.9	9.9	12.8	13.6		
			W	30	30	30	60		
OUTDOOR		AC09BQ.UA3		AC12BQ.UA3		AC18BQ.UL2		AC24BQ.U24	
Operation Range	Cooling	Min / Max	°CDB	-10 / 48	-10 / 48	-15 / 48	-15 / 48	-10 / 24	-10 / 24
	Heating	Min / Max	°CDB	-10 / 24	-10 / 24	-10 / 24	-10 / 24		
Sound Pressure	Cooling	High	dBA	48	48	53	53	54	54
	Heating	High	dBA	50	50	55			
Sound Power	Cooling	High	dBA	65	65	65	70	50	50
	Heating	High	m³/min	27	27	35			
Air Flow Rate	Length (Odu/ldu)	Min / Max	m	3 / 15	3 / 15	3 / 20	3 / 30	15	15
	Elevation (Odu/ldu)	Max	m	7	7	10			
Piping Connection	Liquid	OD(Outside)	mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	15.88 (5/8)	15.88 (5/8)
	Gas	OD(Outside)	mm (inch)	9.52 (3/8)	9.52 (3/8)	12.7 (1/2)	12.7 (1/2)		
	Drain	OD(Outside)	mm (inch)	21.5 (0.85)	21.5 (0.85)	21.5 (0.85)	21.5 (0.85)		
Refrigerant	Type			R32	R32	R32	R32		
	Charge at 7.5m		g	700	700	1000	1100		
	Additional charge	t-CO₂ eq		0.47	0.47	0.68	0.74		
	GWP	g/m		20	20	20	20		
Fan Motor Output			W	43	43	43	85		
Compressor Type				Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary		
Net Weight			kg	25.1	25.1	34.4	46.0		
Dimension			mm	717 x 483 x 230	717 x 483 x 230	770 x 545 x 288	870 x 650 x 330		

WALL MOUNTED SPECIFICATION

ARTCOOL SILVER



LG participates in the ECP programme
for EUROVENT AC program.
Check ongoing validity of certification :
www.eurovent-certification.com



- Single Combination

	UNIT		9K	12K	18K
	INDOOR		AC09SQ.NSJ	AC12SQ.NSJ	AC18SQ.NSK
Capacity	Cooling	Min/Rated/Max W	890 / 2500 / 3700	890 / 3500 / 4040	900 / 5000 / 5500
	Heating +7°C	Min/Rated/Max W	890 / 3300 / 4100	890 / 4000 / 5100	900 / 5800 / 6400
	Heating -7°C	Rated W	2600	3000	4200
Power Input	Cooling	Rated W	656	1080	1562
	Heating +7°C	Rated W	800	1050	1611
EER		W/W	3.81	3.24	3.20
S.E.E.R.			7.0	6.6	7.0
P design C		kW	2.5	3.5	5.0
COP		W/W	4.13	3.81	3.60
S.C.O.P.			4.0	4.0	4.3
P design H		kW	2.5	2.5	3.9
Energy Label	Cooling (A++ to E Scale)		A++	A++	A++
	Heating (A++ to E Scale)		A+	A+	A+
Annual Energy Consumption	Cooling	kWh	125	186	250
	Heating	kWh	875	875	1270
Sound Pressure	Cooling	S / L / M / H	dBA	19 / 27 / 35 / 41	19 / 27 / 35 / 41
	Heating	L / M / H	dBA	27 / 35 / 41	27 / 35 / 41
Sound Power	Cooling	H	dBA	59	59
					60
Air Flow Rate	Cooling	S / L / M / H	m³/min	3.0 / 4.2 / 7.5 / 10.0	3.0 / 4.2 / 7.5 / 10.0
		Max (Power)	m³/min	12.5	12.5
	Heating	L / M / H	m³/min	5.6 / 7.2 / 10.0	5.6 / 7.2 / 10.0
Dehumidification Rate			l/h	1.1	1.3
					1.8
Running Current	Cooling	Rated	A	3.3	4.7
		Max	A	6.0	6.0
	Heating	Rated	A	4.0	4.7
		Max	A	7.0	7.0
Starting Current	Cooling / Heating	Rated	A	3.3 / 4.0	4.7 / 4.7
Power Supply			Ø/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50
Circuit Breaker			A	15	15
Power Supply Cable	Power & Transmission Cable	N x mm²	N x mm²	3 x 1.0	3 x 1.0
					3 x 1.5
Dimension		mm		837 x 308 x 192	837 x 308 x 192
Net Weight		kg		8.7	8.7
Fan Motor Output		W		30	30

OUTDOOR			AC09BQ.UA3	AC12BQ.UA3	AC18BQ.UL2
Operation Range	Cooling	Min / Max	°CDB	-10 / 48	-10 / 48
	Heating	Min / Max	°CDB	-10 / 24	-10 / 24
Sound Pressure	Cooling	High	dBA	48	48
	Heating	High	dBA	50	50
Sound Power	Cooling	High	dBA	65	65
	Cooling	High	m³/min	27	27
Air Flow Rate	Length (Odu/ldu)	Min / Max	m	3 / 15	3 / 15
	Elevation (Odu/ldu)	Max	m	7	7
Piping	Liquid	OD(Outside)	mm (inch)	6.35 (1/4)	6.35 (1/4)
	Gas	OD(Outside)	mm (inch)	9.52 (3/8)	9.52 (3/8)
	Drain	OD(Outside)	mm (inch)	21.5 (0.85)	21.5 (0.85)
Refrigerant	Type			R32	R32
	Charge at 7.5m	g		700	700
	Additional charge	t-CO ₂ eq		0.47	0.47
	GWP	g/m		20	20
Fan Motor Output		W		43	43
Compressor Type			Twin Rotary	Twin Rotary	Twin Rotary
Net Weight		kg	25.1	25.1	34.4
Dimension		mm	717 x 483 x 230	717 x 483 x 230	770 x 545 x 288

* This product contains Fluorinated greenhouse gases (R32).

** S : Sleep / L : Low / M : Medium / H : High


*** Specification, design and feature are subject to change without prior notice.

* This product contains Fluorinated greenhouse gases (R32).

** S : Sleep / L : Low / M : Medium / H : High

*** Specification, design and feature are subject to change without prior notice.

WALL MOUNTED SPECIFICATION

DELUXE

LG participates in the ECP programme
for EUROVENT AC program.
Check ongoing validity of certification :
www.eurovent-certification.com

**• Single Combination**

	UNIT	INDOOR			
		9K	12K	18K	24K
Capacity	Cooling	Min/Rated/Max W	890 / 2500 / 3700	890 / 3500 / 4040	900 / 5000 / 5500
	Heating +7°C	Min/Rated/Max W	890 / 3200 / 5000	890 / 4000 / 6000	900 / 5800 / 6400
Power Input	Cooling	Rated W	3200	3500	4200
	Heating -7°C	Rated W	572	933	1562
EER	Cooling	Rated W/W	711	976	1611
	Heating +7°C	Rated W/W	4.37	3.75	3.20
S.E.E.R.			7.9	7.6	6.9
	P design C	kW	2.5	3.5	5.0
COP			4.5	4.1	3.60
	S.C.O.P.		4.6	4.6	4.3
P design H			2.8	2.9	3.9
	Energy Label	Cooling (A++ to E Scale)	A++	A++	A++
Annual Energy Consumption	Heating (A++ to E Scale)		A++	A++	A+
	Cooling	kWh	111	161	250
Sound Pressure	Heating	kWh	852	883	1270
	Cooling	S / L / M / H	19 / 27 / 37 / 42	19 / 27 / 37 / 42	31 / 34 / 39 / 44
Sound Power	Heating	L / M / H	27 / 37 / 42	27 / 37 / 42	34 / 39 / 44
	Cooling	dBA	60	60	60
Air Flow Rate	Cooling	m³/min	3.5 / 5.5 / 9.0 / 11.0	3.5 / 5.5 / 9.0 / 11.0	8.0 / 10.5 / 13.0 / 14.5
	Heating	m³/min	13.0	13.0	15.5
Dehumidification Rate	Cooling	m³/min	6.5 / 9.0 / 11.0	6.5 / 9.0 / 11.0	11.0 / 13.5 / 16.0
	Heating	m³/min	6.5 / 9.0 / 11.0	6.5 / 9.0 / 11.0	10.5 / 13.1 / 16.1
Running Current	Cooling	l/h	1.1	1.3	1.8
	Heating	l/h	2.5	4.0	6.9
Starting Current	Cooling	A	6.0	6.0	9.0
	Heating	A	3.2	4.3	7.1
Power Supply	Cooling	A	7.0	7.0	9.5
	Heating	A	7.0	7.0	14.0
Circuit Breaker	Cooling/Heating	Rated A	2.5 / 3.2	4.0 / 4.3	6.9 / 7.1
	Power Supply	Ø/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable	Cooling	A	15	15	20
	Heating	A	4 x 1.0	4 x 1.0	4 x 1.0
Power & Transmission Cable	Cooling	N x mm²	3 x 1.0	3 x 1.0	3 x 1.5
	Heating	N x mm²	(Including Earth)	(Including Earth)	(Including Earth)
Dimension	Cooling	mm	837 x 308 x 189	837 x 308 x 189	998 x 345 x 210
	Heating	mm	9.1	9.1	11.9
Net Weight	Cooling	kg	60	60	60
	Heating	kg	30	30	30
Fan Motor Output	Cooling	W	43	43	85
	Heating	W	675	675	675
	OUTDOOR	DC09RQ.UL2	DC12RQ.UL2	DC18RQ.UL2	DC24RQ.U24
	Cooling	Min/Max °CDB	-15 / 48	-15 / 48	-15 / 48
Operation Range	Heating	Min/Max °CDB	-15 / 24	-15 / 24	-10 / 24
	Cooling	High dBA	49	49	53
Sound Pressure	Heating	High dBA	51	51	55
	Cooling	High dBA	65	65	70
Sound Power	Heating	High m³/min	35	35	50
	Cooling	High m³/min	10	10	15
Piping	Length (Odu/ldu)	Min/Max m	3 / 20	3 / 20	3 / 20
	Elevation (Odu/ldu)	Max m	10	10	15
Piping Connection	Liquid OD(Outside)	mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas OD(Outside)	mm (inch)	9.52 (3/8)	9.52 (3/8)	12.7 (1/2)
	Drain OD(Outside)	mm (inch)	21.5 (0.85)	21.5 (0.85)	21.5 (0.85)
	Type		R32	R32	R32
Refrigerant	Charge at 7.5m	g	800	800	1000
	Additional charge	t-CO₂ eq g/m	0.54	0.54	0.68
Fan Motor Output	GWP		675	675	675
	Compressor Type		Twin Rotary	Twin Rotary	Twin Rotary
Net Weight	Net Weight	kg	34.1	34.1	46.0
	Dimension	mm	770 x 545 x 288	770 x 545 x 288	770 x 545 x 288

* This product contains Fluorinated greenhouse gases (R32).

** S : Sleep / L : Low / M : Medium / H : High

*** Specification, design and feature are subject to change without prior notice.

WALL MOUNTED SPECIFICATION

STANDARD PLUS

LG participates in the ECP programme
for EUROVENT AC program.
Check ongoing validity of certification :
www.eurovent-certification.com

**• Single Combination**

	UNIT	INDOOR			
		9K	12K	18K	24K
Capacity	Cooling	Min/Rated/Max W	890 / 2500 / 3700	890 / 3500 / 4040	900 / 5000 / 5500
	Heating +7°C	Min/Rated/Max W	890 / 3300 / 4100	890 / 4000 / 5100	900 / 5800 / 6400
Power Input	Cooling	Rated W	2600	3000	4200
	Heating -7°C	Rated W	656	1080	1562
EER	Cooling	Rated W/W	800	1050	1611
	Heating +7°C	Rated W/W	3.81	3.24	3.20
S.E.E.R.			7.0	6.6	6.9
	P design C	kW	2.5	3.5	5.0
COP			4.13	3.81	3.60
	S.C.O.P.		4.0	4.0	4.3
P design H			2.5	2.5	3.9
	Energy Label	Cooling (A++ to E Scale)	A++	A++	A++
Annual Energy Consumption	Heating (A++ to E Scale)		A++	A+	A+
	Cooling	kWh	125	186	250
Sound Pressure	Heating	kWh	875	875	1270
	Cooling	S / L / M / H	19 / 27 / 35 / 41	19 / 27 / 35 / 41	31 / 34 / 39 / 44
Sound Power	Heating	L / M / H	27 / 35 / 41	27 / 35 / 41	34 / 39 / 44
	Cooling	dBA	59	59	60
Air Flow Rate	Cooling	m³/min	3.0 / 4.2 / 7.5 / 10.0	3.0 / 4.2 / 7.5 / 10.0	8.0 / 10.5 / 13.0 / 14.5
	Heating	m³/min	12.5	12.5	20.0
Dehumidification Rate	Cooling	m³/min	5.6 / 7.2 / 10.0	5.6 / 7.2 / 10.0	11.0 / 13.5 / 16.0
	Heating	m³/min	1.1	1.3	1.8
Running Current	Cooling	l/h	3.3	4.7	6.9
	Heating	l/h	6.0	6.0	9.0
Starting Current	Cooling	l/h	4.0	4.7	7.1
	Heating	l/h	7.0	7.0	14.0
Power Supply	Cooling	Ø/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
	Heating	A	15	20	25
Circuit Breaker	Cooling	N x mm²	3 x 1.0	3 x 1.0	3 x 1.5
	Heating	N x mm²	4 x 1.0	4 x 1.0	4 x 1.0
Power & Transmission Cable	Cooling	(Including Earth)	(Including Earth)	(Including Earth)	(Including Earth)

WALL MOUNTED SPECIFICATION

STANDARD

LG participates in the ECP programme
for EUROVENT AC program.
Check ongoing validity of certification :
www.eurovent-certification.com



• Single Combination


	UNIT		9K	12K	18K	24K
	INDOOR	OUTDOOR	S09EQ.NSJ	S12EQ.NSJ	S18EQ.NSK	S24EQ.NSK
Capacity	Cooling Min / Rated / Max W		890 / 2500 / 3700	890 / 3500 / 4040	900/5000/5500	900 / 6600 / 7420
	Heating +7°C Min / Rated / Max W		890 / 3300 / 4100	890 / 4000 / 5100	900/5800/6400	900 / 7500 / 8640
Power Input	Cooling Rated W		2600	3000	4200	4850
	Heating -7°C Rated W		656	1080	1562	2164
EER	W/W		3.81	3.24	3.20	3.05
S.E.E.R.			7.0	6.6	7.0	6.9
P design C	kW		2.5	3.5	5.0	6.6
COP	W/W		4.13	3.81	3.60	3.35
S.C.O.P.			4.0	4.0	4.3	4.2
P design H	kW		2.5	2.5	3.9	5.0
Energy Label	Cooling (A++ to E Scale)		A++	A++	A++	A++
	Heating (A++ to E Scale)		A+	A+	A+	A+
Annual Energy Consumption	Cooling kWh		125	186	250	335
	Heating kWh		875	875	1270	1628
Sound Pressure	Cooling S / L / M / H dBA		19 / 27 / 35 / 41	19 / 27 / 35 / 41	31 / 34 / 39 / 44	31 / 34 / 42 / 47
	Heating L / M / H dBA		27 / 35 / 41	27 / 35 / 41	34 / 39 / 44	34 / 42 / 47
Sound Power	Cooling High dBA		59	59	60	65
	Heating L / M / H m³/min		3.0 / 4.2 / 7.5 / 10.0	3.0 / 4.2 / 7.5 / 10.0	8.0 / 10.5 / 13.0 / 14.5	8.0 / 10.5 / 13.1 / 16.1
Air Flow Rate	Cooling Max (Power) m³/min		12.5	12.5	15.5	20.0
	Heating L / M / H m³/min		5.6 / 7.2 / 10.0	5.6 / 7.2 / 10.0	11.0 / 13.5 / 16.0	10.5 / 13.1 / 16.1
Dehumidification Rate	I/h		1.1	1.3	1.8	2.5
Running Current	Cooling Rated A		3.3	4.7	6.9	9.8
	Max A		6.0	6.0	9.0	14.0
	Heating Rated A		4.0	4.7	7.1	10.4
	Max A		7.0	7.0	9.5	14.0
Starting Current	Cooling/Heating Rated A		3.3 / 4.0	4.7 / 4.7	6.9 / 7.1	9.8 / 10.4
Power Supply	Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Circuit Breaker	A		15	15	20	25
Power Supply Cable	N x mm²		3 x 1.0	3 x 1.0	3 x 1.5	3 x 2.5
Power & Transmission	N x mm²		4 x 1.0	4 x 1.0	4 x 1.0	4 x 1.0
Cable			(Including Earth)	(Including Earth)	(Including Earth)	(Including Earth)
Dimension	mm		837 x 308 x 189	837 x 308 x 189	998 x 345 x 210	998 x 345 x 210
Net Weight	kg		8.7	8.7	11.9	11.9
Fan Motor Output	W		30	30	30	60
OUTDOOR		S09EQ.UA3	S12EQ.UA3	S18EQ.UL2	S24EQ.U24	
Operation Range	Cooling Min / Max °CDB		-10 / 48	-10 / 48	-15 / 48	-15 / 48
	Heating Min / Max °CDB		-10 / 24	-10 / 24	-10 / 24	-10 / 24
Sound Pressure	Cooling High dBA		48	48	53	53
	Heating High dBA		50	50	55	54
Sound Power	Cooling High dBA		65	65	65	70
	Air Flow Rate Cooling High m³/min		27	27	35	50
Piping	Length (Odu/ldu) Min / Max m		3 / 15	3 / 15	3 / 20	3 / 30
	Elevation (Odu/ldu) Max m		7	7	10	15
Piping Connection	Liquid OD(Outside) mm (inch)		6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas OD(Outside) mm (inch)		9.52 (3/8)	9.52 (3/8)	12.7 (1/2)	15.88 (5/8)
	Drain OD(Outside) mm (inch)		21.5 (0.85)	21.5 (0.85)	21.5 (0.85)	21.5 (0.85)
	Type		R32	R32	R32	R32
Refrigerant	Charge at 7.5m g		700	700	1000	1100
	t-CO₂ eq		0.47	0.47	0.68	0.74
	Additional charge g/m		20	20	20	20
	GWP		675	675	675	675
Fan Motor Output	W		43	43	43	85
Compressor Type		Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary	
Net Weight	kg	25.1	25.1	34.4	46.0	
Dimension	mm	717 x 483 x 230	717 x 483 x 230	770 x 545 x 288	870 x 650 x 330	

* This product contains Fluorinated greenhouse gases (R32).


** S : Sleep / L : Low / M : Medium / H : High

*** Specification, design and feature are subject to change without prior notice.


WALL MOUNTED DIMENSIONS

INDOOR UNIT**H09AP.NSM / H12AP.NSM**


(Unit : mm)		
Item No.	Part Name	Remark
1	Front Panel	
2	Air Suction Grille	
3	Knockout Hole	For pipe and cable

AC09BQ.NSJ / AC12BQ.NSJ / AC09SQ.NSJ / AC12SQ.NSJ

(Unit : mm)		
Item No.	Part Name	Remark
1	Front Panel	
2	Display & Signal Receiver	
3	Air Filter	
4	Knockout hole	For pipe and cable



A09FR.NSF/A12FR.NSF

(Unit : mm)		
Item No.	Part Name	Description
1	Refrigerant/Drain pipe and cable routing hole	Knock-out type
2	Terminal Block for Power supply and communication	inside of front panel
3	Corner Cover	-
4	Remote Controller Signal Receiver	for wireless type

AC18BQ.NSK / AC24BQ.NSK / AC18SQ.NSK

(Unit : mm)		
Item No.	Part Name	Remark
1	Front Panel	
2	Display & Signal Receiver	
3	Air Suction Filter	
4	Installation Plate	




WALL MOUNTED DIMENSIONS

INDOOR UNIT**DC09RQ.NSJ / PC12SQ.NSJ / PC09SQ.NSJ / PC12SQ.NSJ / S09EQ.NSJ / S12EQ.NSJ****DC18RQ.NSK / DC24RQ.NSK / PC18SQ.NSK / PC24SQ.NSK / S18EQ.NSK / S24EQ.NSK**

WALL MOUNTED DIMENSIONS

INDOOR UNIT




**AC09BQ.UA3 / AC12BQ.UA3 / AC09SQ.UA3 / AC12SQ.UA3 / DC09RQ.UA3
DC12RQ.UA3 / PC09SQ.UA3 / PC12SQ.UA3 / S09EQ.UA3 / S12EQ.UA3**



(Unit: mm)

Item No.	Part Name
1	Air Outlet
2	Control Box
3	Power and Communication Cable Hole
4	Service Valve Cover
5	Gas Pipe Connection
6	Liquid Pipe Connection



H09AP.U24 / H12AP.U24 / AC24BQ.UL2 / DC24RQ.UL2 / PC24SQ.UL2 / S24EQ.UL2




(Unit: mm)

Item No.	Part Name
1	Air Outlet
2	Control Box
3	Power and Communication Cable Hole
4	Service Valve Cover
5	Gas Pipe Connection
6	Liquid Pipe Connection

AC18BQ.UL2 / AC18SQ.UL2 / DC18RQ.UL2 / PC18SQ.UL2 / S18EQ.UL2



Item No.	Part Name
1	Air Outlet
2	Control Box
3	Power and Communication Cable Hole
4	Service Valve Cover
5	Gas Pipe Connection
6	Liquid Pipe Connection



WALL MOUNTED SPECIFICATION

ACCESSORIES

	PRESTIGE	ARTCOOL GALLERY	ARTCOOL	DELUXE	STANDARD PLUS	STANDARD
Wired Remote Controller	5k				Y	-
	7k			Y	Y	-
	9k	Y	-	Y	Y	-
	12k	Y	-	Y	Y	-
	15k				Y	
	18k			Y	Y	-
	24k			Y	Y	-
PI 485	5k				-	
	7k			-	Y*	-
	9k	-	-	-	Y*	-
	12k	-	-	-	Y*	-
	15k				-	
	18k			-	Y*	-
	24k			-	Y*	-
Dry Contact	5k				Y	
	7k			Y	Y	-
	9k	Y	Y	Y	Y	-
	12k	Y	Y	Y	Y	-
	15k				Y	
	18k			Y	Y	-
	24k			Y	Y	-

* Y: Available

* When connected to Multi 14k & 16k Outdoor units, this may not be supported.

Standard Wired Remote Controller**• Standard III**

PREMTB100 PREMTBB10

• Standard II

PREMTB001 PREMTBB01

MODEL NAME	PREMTB100 PREMTBB10	PREMTB001 PREMTBB01
Operation Mode	On/Off, Fan Speed Control, Temperature Setting	
Mode Change	Cooling / Heating / Auto / Dehumidification / Fan	
Auto Swing / Vane Control	•	•
Reservation	Simple / Sleep / On, Off / Weekly / Holiday	
Time Display	•	•
Electrical Failure Compensation	•	•
Child Lock	•	•
Operation Status LED	•	•
Indoor Temperature Display	•	•
Wireless Remote Controller Receiver	-	•
Size (W x H x D, mm)	120 x 120 x 16	120 x 121 x 16
Backlight	•	•

* Refer to each model PDB for applicable models.

PI 485

PMNFP14A1

Power : Single phase AC 220V 50/60Hz

Max. no. of the indoor units that can be connected: 64 UNITS

Model applied : RAC / Multi / Single / Therma V

* Refer to each product PDB for applicable models

Dry Contact

PDRYCB000



PDRYCB400



PDRYCB300



PDRYCB500

※ Refer to each product PDB for applicable models

MODEL	PDRYCB000	PDRYCB400	PDRYCB300	PDRYCB500
Contact Point	1 Control Point	2 Control Point	8 Control Point	Modbus RTU
Power Input	AC 220V from outside power source	DC 5V & 12V from indoor unit PCB	DC 5V & 12V from indoor unit PCB	DC 5V & 12 V from indoor unit PDB
Voltage / Non Voltage Input		•	•	
On / Off Control	•	•	•	•
Lock / Unlock	•	•	•	•
Fan Speed Setting		•	•	•
Thermo Off		•	•	
Energy Saving		•	•	
Temperature Setting		•	•	•
Error Monitoring	•	•	•	•
Operation Monitoring	•	•	•	•

Remote ControllerPrestige
Artcool
New Deluxe
New Standard Plus
Standard

BUTTON	DISPLAY SCREEN	DESCRIPTION
	-	To turn On / Off the air conditioner.
	88 °F	To adjust the desired room temperature in cooling, heating or auto changeover mode.
COMFORT AIR		To adjust the air flow to deflect wind.
LIGHT OFF	-	To set the brightness of the display on the indoor unit.
		To select the cooling mode.
		To select the heating mode.
MODE		
		To select the dehumidification mode.
		To select the fan mode.
		To select the auto changeover / auto operation mode.
FAN SPEED		To adjust the fan speed.
ENERGY CTRL.		To bring the effect of the power saving.
JET MODE		To change room temperature quickly.
		To adjust the air flow direction vertically or horizontally.
ROOM TEMP		To display the room temperature.
°C ↔ °F [5sec]	°F	To change unit between °C and °F.
SET/ CANCEL	-	To set / cancel the functions and timer.
	-	To adjust time.
	-	To turn on / off air conditioner automatically.
	-	To cancel the timer settings.

MULTI SPLIT



MULTI SPLIT

LINE-UP**R32 INDOOR / OUTDOOR UNIT**

		KBTU/H		5	7	9	12	15	18	24
		KW		1.5	2.1	2.6	3.5	4.2	5.3	7.0
Wall Mounted Unit	ARTCOOL Gallery					A09FR.NSF	A12AR.NSF			
	ARTCOOL Mirror				AM07BPN SJ	AC09BQ.NSJ	AC12BQ.NSJ		AC18BQ.NSK	AM24BPN SK
	ARTCOOL Silver					AC09SQ.NSJ	AC12SQ.NSJ		AC18SQ.NSK	
	Deluxe				DM07RPNSJ	DC09RQ.NSJ	DC12RQ.NSJ		DC18RQ.NSK	DM24RPNSK
	Standard Plus			PM05SP.NSJ	PM07SP.NSJ	PC09SQ.NSJ	PC12SQ.NSJ	PM15SPNSJ	PC18SQ.NSK	PM24SP.NSK
				MJ05PC.NSJ	MJ07PC.NSJ	MJ09PC.NSJ	MJ12PC.NSJ	MJ15PC.NSJ	MJ18PC.NSK	MJ24PC.NSK
Ceiling Mounted Cassette	1 Way Cassette					MT09R.NU1	MT11R.NU1			
	4 Way Cassette			MT06R.NR0	MT08R.NR0	CT09R.NR0	CT12R.NR0		CT18R.NQ0	CT24R.NP0
Ceiling Concealed Duct	Mid / High Static Pressure								CM18R.N10	CM24R.N10
	Low Static Pressure					CL09R.N20	CL12R.N20		CL18R.N20	CL24R.N30
KBTU/H		14	16	18	21	24	27	30		
KW		4.1	4.7	5.3	6.2	7.0	7.9	8.8		
Multi				MU2R15.ULO 2-port	MU2R17.ULO 2-port	MU3R19.UE0 3-port	MU3R21.UE0 3-port	MU4R25U40 4-port	MU4R27U40 4-port	MU5R30.U40 5-port

* ARTCOOL Gallery will be available from May, '19

R410A INDOOR / OUTDOOR UNIT

		KBTU/H		5	7	9	12	15	18	24
		KW		1.5	2.1	2.6	3.5	4.2	5.3	7.0
Ceiling & Floor Convertible						CV09.NE2	CV12.NE2			
Console						CQ09.NAO	CQ12.NAO		CQ18.NAO	
KBTU/H		40		48		57				
KW		11.7		14.1		16.7				
Multi	Multi Piping				MU5M40.U44 5-port					
Distribution Box				FM40AH.U34/FM41AH.U34 7-IDU	FM48AH.U34/FM49AH.U34 8-IDU	FM56AH.U34/FM57AH.U34 9-IDU				

MULTI SPLIT

FEATURE OVERVIEW

Category	R32 MULTI PIPING							R410A DB BOX TYPE			
kBtu/h	14	16	18	21	24	27	30	40	46	48	57
kW	4.1	4.7	5.3	6.2	7.0	7.9	8.8	11.7	13.5	14.1	16.7
Energy Efficiency											
BLDC Comp. & Fan Motor	●	●	●	●	●	●	●	●	●	●	●
Eurovent Certification	●	●	●	●	●	●	●	●	●	●	●
Wide Louver Plus Fin	●	●	●	●	●	●	●	●	●	●	●
Optimised Heat Exchanger Path	●	●	●	●	●	●	●	●	●	●	●
Smart Load Control					●	●	●	●	●	●	●
Peak Current Control	●	●	●	●	●	●	●	●	●	●	●
Standby Mode	●	●	●	●	●	●	●	●	●	●	●
Mode Lock	●	●	●	●	●	●	●	●	●	●	●
Twin Rotary Compressor	●	●	●	●	●	●	●	●	●	●	●
Smart Sensor Pressure Control					●	●	●	●	●	●	●
Ocean Black Fin Heat Exchanger	●	●	●	●	●	●	●	●	●	●	●
Durability											
Fast Cooling & Heating					●	●	●	●	●	●	●
Night Silent Operation	●	●	●	●	●	●	●	●	●	●	●
Wiring Error Check	●	●	●	●	●	●	●	●	●	●	●
Monitoring PCB	●	●	●	●	●	●	●	●	●	●	●
LG MV	●	●	●	●	●	●	●	●	●	●	●
Forced Cooling Operation	●	●	●	●	●	●	●	●	●	●	●
Comfort & Convenience											

MULTI SPLIT

KEY FEATURES

PERFECT SOLUTION FOR MULTIPLE ROOMS



Energy Efficiency | Extreme Durability | Comfort and Convenience

LG Multi split system provides powerful, efficient cooling and heating with two, three, four, or up to nine indoor units operating of a single outdoor unit.

LG's advanced inverter technology brings powerful performance while consuming less energy and it uses less space than installing individual single split systems.

A variety of sleek and elegant indoor units to complement any décor are available in a full range of capacities for all room sizes.

Installation is easy and it offers various convenient functions for easy maintenance.



MULTI SPLIT KEY FEATURES

ENERGY EFFICIENCY




Enhanced Heat exchange by Wide Louver Plus Fin

Wide Louver Plus fin technology increases 11% of full load heating performance and 6% of COP compared to conventional fin. It can slow down frosting of heat exchanger and postpone the start of defrosting operation.

• Heating Operation at Defrost Condition


It can slow down frosting of heat exchanger and postpone the start of defrosting operation





Powerful BLDC (Brushless Direct Current Motor) Compressor

LG air conditioners are equipped with a BLDC Inverter Twin Rotary Compressor that uses a neodymium magnetic core. The compressor has high efficiency and superior reliability, because it is excellent in controlling the operating speed depending on the load. The compressor has improved efficiency compared to standard AC inverter products and optimized for changes of outdoor load. Especially it is optimized for seasonal efficiency.

• Operation Range



• Motor Efficiency




MULTI SPLIT KEY FEATURES

ENERGY EFFICIENCY


Smart Load Control

To save operation energy, it automatically controls the refrigerant temperature according to outside temperature.




• How to set dip switch

To operate smart load control, dip switch setting is needed. It can save energy on real time operation.



• Real Time Energy Saving

■ Smart Load Control
■ Conventional




* Applied models : MU2R15.ULO / MU2R17.ULO / MU3R19.UE0 / MU3R21.UE0 / MU4R25.U40 / MU4R27.U40 / MU5R30.U40 / MU5M40.U44

Peak Current Control


The peak current control function keeps the air conditioner from running at the maximum level while maintaining current system setting, in order to reduce energy consumption. This function allows reducing energy costs during the peak periods of energy use when the energy fee is much higher.

• How to set dip switch


STEP 1 Max power consumption : 1.9 kW



STEP 2 Max power consumption : 1.7 kW




* Full Load consumption : 2.5kW
* 7.0kW model
* LG Internal test result



* When using Peak current control, the cooling capacity may not be sufficient.
* 7.0kW model
* LG Internal test result


MULTI SPLIT KEY FEATURES

EXTREME DURABILITY



Improved BLDC Inverter Twin Rotary Compressor

Parts of BLDC Inverter Twin Rotary Compressor have been improved to allow a longer life span.




Twin Rotary Inverter Compressor

Pressure Control Technology by Smart Sensor


Quicker and more reliable operation is possible from pressure control technology.

- Field Failure Rate of Outdoor unit




Black Fin Heat Exchanger

The black coating with enhanced epoxy resin is applied for strong protection from various corrosive external conditions such as salt contamination and air pollution including fumes from factories. Moreover, the hydrophilic film keeps water from accumulating on the heat exchanger's fin, minimizing moisture buildup and eventually making it even more corrosion resistant.





MULTI SPLIT KEY FEATURES

COMFORT AND CONVENIENCE




Fast Cooling & Heating

Pressure control takes less time to reach the desired temperature up to 30% in cooling and 44% in heating with high level of accuracy and stability.

• Cooling**• Heating**

Night Silent Operation

Night silent operation can reduce noise levels at night time by simply setting the dip switch on the PCB of the outdoor unit.



* This function is only available for Cooling Mode.



* If you want to stop the Night Quiet Mode, Change the Dip Switch.

Wiring Error Check


Installers can check whether the transmission cable has been connected correctly by using the wiring error check function. The wiring error check function can reduce the time taken to check for transmission cable errors.

• LED Result

- If the wiring is correct, the Green LED will light up.
- If the wiring is wrong, display as below
- Red LED : Piping Number
- Green LED : Wiring Number (Room)



Ex) If the Red LED blinks twice and the Green LED blinks 3 times, 2nd pipe is connected to 3rd room




MULTI SPLIT KEY FEATURES

COMFORT AND CONVENIENCE

Monitoring PCB

If there is any problem, without disassembly of chassis, engineers can quickly check air conditioner's error code through 7-segment error indicator



• Displayed Error code

ERROR CODE	CONTENTS	CASE OF ERROR	OUTDOOR STATUS
21	DC Link Peak (IPM Fault)	Over Rated Current	Off
22	CT 2 (Max CT)	Input Over Current	Off
23	DC Link Low Volt.	DC Link Volt is below 140V dc	Off
	DC Link High Volt.	DC Link Volt is above 420V dc	
25	Low Voltage / Over Voltage	Abnormal AC volt Input	Off
26	DC Compressor Position Error	Compressor Starting Fall Error	Off
27	PSC / PFC Fault Error	Over inverter PCB input Current	Off
29	COMP Over Current	Over inverter Compressor Current	Off
...

* Applied models : MU2R15 ULO / MU2R17 ULO / MU3R19 UEO / MU3R21 UEO


LG MV (Monitoring View)

LG MV helps engineers to inspect and monitor air conditioning units easily.



Forced Cooling Operation

The forced cooling operation allows refrigerant to be recharged or pumped down, regardless of the indoor temperature. More importantly this function can be used when indoor units are being moved or repaired.



R32 MULTI SPLIT



R32 MULTI SPLIT OUTDOOR UNITS




RESIDENTIAL

MU2R15
MU2R17



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com



OUTDOOR UNIT		MU2R15.UL0	MU2R17.UL0
Compressor	Type	Twin Rotary	Twin Rotary
Capacity *	Cooling Min / Nom / Max kW	0.9 / 4.1 / 4.7	0.9 / 4.7 / 5.4
	Heating Min / Nom / Max kW	1.0 / 4.7 / 5.4	1.0 / 5.3 / 5.7
Low Temperature Capacity	Heating -7°C Max kW	3.3	3.7
	Cooling Min / Nom / Max kW	0.2 / 1.0 / 1.4	0.2 / 1.3 / 1.7
Power Input *	Heating Min / Nom / Max kW	0.2 / 1.1 / 1.4	0.2 / 1.3 / 1.6
	Cooling Min / Nom / Max A	1.1 / 4.6 / 6.4	1.1 / 5.6 / 7.9
Running Current	Heating Min / Nom / Max A	1.1 / 4.9 / 6.6	1.1 / 5.5 / 7.6
EER		4.14	3.75
COP		4.38	4.22
SEER		8.50	7.80
SCOP		4.20	4.20
Pdesign (@-10°C)	kW	4.10	4.10
Seasonal Energy Label	Cooling / Heating	A+++ (A+++ to D Scale) / A+	A++ (A++ to E Scale) / A+
Annual Energy Consumption	Cooling / Heating	169 / 1,367	210 / 1,367
Airflow Rate	Nom m³/min	28.2	28.2
	Cooling Nom dBA	48	48
Sound Pressure	Heating Nom dBA	51	51
	Cooling Max dBA	61	63
Sound Power		770 x 545 x 288	770 x 545 x 288
Dimensions	W x H x D mm	36	36
Net Weight	Kg	R32	R32
	Type	1.1	1.1
Refrigerant	Charge Kg	20	20
	Additional Charge g/m	675	675
	t-CO₂ eq	0.74	0.74
Operation Range (Outdoor)	Cooling Min / Max °C DB	-10 / 48	-10 / 48
	Heating Min / Max °C WB	-18 / 18	-18 / 18
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable	No. x mm²	3C x 2.5	3C x 2.5
Transmission Cable	No. x mm²	4C x 0.75	4C x 0.75
Circuit Breaker	A	15	15
Piping Length Total	m	30	30
Piping Length per Branch	Max m	20	20
Piping Elevation Difference	IDU - ODU Max m	15	15
	IDU - IDU Max m	7.5	7.5
Piping Connection	Liquid mm (inch) x No.	Ø6.35 (1/4) x 2	Ø6.35 (1/4) x 2
	Gas mm (inch) x No.	Ø9.52 (3/8) x 2	Ø9.52 (3/8) x 2

Notes :


1. Capacities are based on the following conditions:
Cooling : - Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB
Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB
Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.
2. * : See page "Combination Table".
3. Due to our policy of innovation some specifications may be changed without notification.
4. At least two indoor units should be connected
5. Minimum combination ratio should be more than 40%.
6. This product contains fluorinated greenhouse gases (R32)

OUTDOOR UNITS

MU3R19
MU3R21



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com




(Unit : mm)

MU4R25
MU4R27
MU5R30



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com



(Unit : mm)

		OUTDOOR UNIT			MU3R19.UEO	MU3R21.UEO
Compressor	Type	Twin Rotary		Twin Rotary		
Capacity *	Cooling	Min / Nom / Max kW	1.1 / 5.3 / 6.3	1.1 / 6.2 / 7.3		
	Heating	Min / Nom / Max kW	1.2 / 6.3 / 7.3	1.2 / 7.0 / 7.8		
Low Temperature Capacity	Heating -7°C	Max kW	4.4	4.9		
Power Input *	Cooling	Min / Nom / Max kW	0.2 / 1.2 / 1.8	0.2 / 1.4 / 2.1		
	Heating	Min / Nom / Max kW	0.3 / 1.4 / 2.0	0.3 / 1.6 / 2.3		
Running Current	Cooling	Min / Nom / Max A	1.1 / 5.3 / 8.1	1.1 / 6.7 / 9.6		
	Heating	Min / Nom / Max A	1.1 / 6.3 / 9.4	1.1 / 7.4 / 10.6		
EER			4.59	4.27		
COP			4.62	4.42		
SEER			8.50	8.50		
SCOP			4.21	4.21		
Pdesign (@-10°C)	kW		4.90	4.90		
Seasonal Energy Label	Cooling / Heating (A+++ to D Scale)		A+++ / A+	A+++ / A+		
Annual Energy Consumption	Cooling / Heating		217 / 1,629	253 / 1,629		
Airflow Rate	Nom m³/min		50	50		
Sound Pressure	Cooling Nom dBA		49	50		
	Heating Nom dBA		54	54		
Sound Power	Cooling Max dBA		63	64		
Dimensions	W x H x D mm		870 x 655 x 320	870 x 655 x 320		
Net Weight	Kg		44	44		
	Type		R32	R32		
Refrigerant	Charge Kg		1.4	1.4		
	Additional Charge g/m		20	20		
	GWP		675	675		
	t-CO ₂ eq		0.95	0.95		
Operation Range (Outdoor)	Cooling Min / Max °C DB		-10 / 48	-10 / 48		
	Heating Min / Max °C WB		-18 / 18	-18 / 18		
Power Supply	Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50		
Power Supply Cable	No. x mm ²		3C x 2.5	3C x 2.5		
Transmission Cable	No. x mm ²		4C x 0.75	4C x 0.75		
Circuit Breaker	A		20	20		
Piping Length Total	m		50	50		
Piping Length per Branch	Max m		25	25		
Piping Elevation Difference	IDU - ODU Max m		15	15		
	IDU - IDU Max m		7.5	7.5		
Piping Connection	Liquid mm (inch) x No.		Ø6.35 (1/4) x 3	Ø6.35 (1/4) x 3		
	Gas mm (inch) x No.		Ø9.52 (3/8) x 3	Ø9.52 (3/8) x 3		

Notes :

- Capacities are based on the following conditions:
Cooling : - Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB
Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB
Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.
- * : See page "Combination Table".
- Due to our policy of innovation some specifications may be changed without notification.
- At least two indoor units should be connected.
- Minimum combination ratio should be more than 40%.
- This product contains fluorinated greenhouse gases (R32)

Notes :

- Capacities are based on the following conditions:
Cooling : - Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB
Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB
Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.
- * : See page "Combination Table".
- Due to our policy of innovation some specifications may be changed without notification.
- At least two indoor units should be connected.
- Minimum combination ratio should be more than 40%.
- This product contains fluorinated greenhouse gases (R32)



WALL MOUNTED UNITS



	KBTU/H	5	7	9	12	15	18	24
	KW	1.5	2.1	2.6	3.5	4.2	5.3	7.0
Wall Mounted Unit	ARTCOOL Gallery	-	-	A09FR.NSF	A12AR.NSF	-	-	-
	ARTCOOL Mirror	-	-	AM07BPNSJ	AC09BQ.NSJ	AC12BQ.NSJ	AC18BQ.NSK	AM24BPNSK

* ARTCOOL Gallery is available in May, '19

ARTCOOL Gallery

A09FR.NSF				A12FR.NSF			
Capacity	Cooling / Heating	Nom	kW	2.6 / 2.9	3.5 / 3.9		
Power Input		Nom	W	40 x 1	40 x 1		
Running Current		Nom	A	0.1	0.1		
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50		
Air Flow Rate	H / M / L	m³/min		7.7 / 5.9 / 4.4	8.9 / 7.3 / 5.6		
Sound Pressure	Cooling	H / M / L	dB(A)	38 / 32 / 27	44 / 38 / 32		
Sound Power	Cooling		dB(A)	52	54		
Dehumidification Rate		I/h		1.2	1.4		
Dimensions	Body	W x H x D	mm	600 x 600 x 145	600 x 600 x 145		
Net Weight	Body		kg	15.0	15.0		
Piping Connections	Liquid	mm (inch)		Ø 6.35 (1/4)	Ø 6.35 (1/4)		
	Gas	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)		

ARTCOOL Mirror

AM07BP.NSJ					AC09BQ.NSJ	AC12BQ.NSJ	AC18BQ.NSJ	AM24BP.NSJ
Capacity	Cooling / Heating	Nom	kW	2.1 / 2.3	2.5 / 3.2	3.5 / 3.8	5.0 / 5.8	6.6 / 7.5
Power Input		Nom	W	17	18	19	39	45
Running Current		Nom	A	0.14	0.16	0.17	0.28	0.33
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Air Flow Rate	H / M / L	m³/min		8.6 / 7.2 / 5.6	9.2 / 7.4 / 5.6	9.6 / 8.1 / 5.6	14.2 / 11.3 / 9.9	15.2 / 12.7 / 10.2
Sound Pressure	Cooling	H / M / L	dB(A)	35 / 32 / 27	36 / 33 / 27	40 / 35 / 27	44 / 38 / 35	46 / 41 / 36
Sound Power	Cooling		dB(A)	57	57	57	59	65
Dehumidification Rate		I/h		0.9	1.1	1.2	1.9	2.6
Dimension	W x H x D	mm		837 x 308 x 192	837 x 308 x 192	837 x 308 x 192	998 x 345 x 212	998 x 345 x 212
Net weight		kg		9.1	9.9	9.9	13.2	11.6
Piping Connection	Liquid	mm (inch)		Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)
	Gas	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 12.7 (1/2)

	KBTU/H	5	7	9	12	15	18	24
	KW	1.5	2.1	2.6	3.5	4.2	5.3	7.0
Wall Mounted Unit	ARTCOOL Silver	-	-	-	-	-	-	-
	Deluxe	-	-	-	-	-	-	-

NEW Silver Color is available from Mar, '19

ARTCOOL Silver


AC09SQ.NSJ				AC12SQ.NSJ				AC18SQ.NSK			
Capacity	Cooling / Heating	Nom	kW	2.5 / 3.2	3.5 / 3.8	5.0 / 5.8					
Power Input		Nom	W	18	19	39					
Running Current		Nom	A	0.16	0.17	0.28					
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50					
Air Flow Rate	H / M / L	m³/min		9.2 / 7.4 / 5.6	9.6 / 8.1 / 5.6	14.2 / 11.3 / 9.9					
Sound Pressure	Cooling	H / M / L	dB(A)	36 / 33 / 27	40 / 35 / 27	44 / 38 / 35					
Sound Power	Cooling		dB(A)	57	57	57					
Dehumidification Rate		I/h		1.1	1.2	1.9					
Dimension	W x H x D	mm		837 x 308 x 192	837 x 308 x 192	837 x 308 x 192					
Net weight		kg		9.9	9.9	9.9					
Piping Connection	Liquid	mm (inch)		Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)					
	Gas	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)					

DELUXE

DM07RP.NSJ				DC09RQ.NSJ				DC12RQ.NSJ				DC18RQ.NSK				DM24RP.NSK			
Capacity	Cooling / Heating	Nom	kW	2.1 / 2.3	2.5 / 3.2	3.5 / 4.0	5.0 / 5.8	6.6 / 7.5											
Power Input		Nom	W	17	18	19	39	45											
Running Current		Nom	A	0.15	0.16	0.17	0.28	0.33											
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50											
Air Flow Rate	H / M / L	m³/min		7.5 / 6.1 / 4.9	7.7 / 6.4 / 5.0	8.1 / 6.7 / 5.3	14.2 / 11.3 / 9.9	15.2 / 12.7 / 10.2											
Sound Pressure	Cooling	H / M / L	dB(A)	35 / 31 / 26	36 / 32 / 27	38 / 34 / 29	44 / 38 / 34	47 / 41 / 36											
Sound Power	Cooling		dB(A)	56	56	56	60	64											
Dehumidification Rate		I/h		0.9	1.1	1.2	1.9	2.6											
Dimension	W x H x D	mm		837 x 308 x 189	837 x 308 x 189	837 x 308 x 189	998 x 345 x 210	998 x 345 x 210											
Net weight		kg		8.3	8.3	8.3	12.0	12.0											
Piping Connection	Liquid	mm (inch)		Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)											
	Gas	mm (inch)																	

R32 MULTI SPLIT

WALL MOUNTED UNITS

	KBTU/H	5	7	9	12	15	18	24							
	KW	1.5	2.1	2.6	3.5	4.2	5.3	7.0							
Wall Mounted Unit	Standard Plus		PM05SP.NSJ		PM07SP.NSJ		PC09SQ.NSJ		PC12SQ.NSJ		PM15SP.NSJ		PC18SQ.NSK		PM24SP.NSK
			MJ05PC.NSJ		MJ07PC.NSJ		MJ09PC.NSJ		MJ12PC.NSJ		MJ15PC.NSJ		MJ18PC.NSK		MJ24PC.NSK

STANDARD PLUS

		PM05SP.NSJ	PM07SP.NSJ	PC09SQ.NSJ	PC12SQ.NSJ	PM15SP.NSJ	PC18SQ.NSK	PM24SP.NSK		
Capacity	Cooling / Heating	Nom	kW	1.5 / 1.6	2.1 / 2.3	2.5 / 3.2	3.5 / 3.8	4.2 / 5.4	5.0 / 5.8	6.6 / 7.5
Power Input	Nom	W		16	17	18	19	21	39	45
Running Current	Nom	A		0.13	0.14	0.16	0.17	0.18	0.28	0.33
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Air Flow Rate	H / M / L	m³/min		8.3 / 6.7 / 5.6	8.6 / 7.2 / 5.6	9.2 / 7.4 / 5.6	9.6 / 8.1 / 5.6	100/85/6.1	142/113/99	152/127/102
Sound Pressure	H / M / L	dB(A)		34 / 31 / 27	35 / 32 / 27	36 / 33 / 27	40 / 35 / 27	41 / 36 / 29	44 / 38 / 35	46 / 41 / 36
Sound Power		dB(A)		57	57	57	57	57	59	65
Dehumidification Rate		l/h		0.9	0.9	1.1	1.2	1.2	1.9	2.6
Dimension		W x H x D	mm	837 x 308 x 189	998 x 345 x 210	998 x 345 x 210				
Net weight		kg		7.4	7.4	8.7	8.7	8.7	12.0	12.8
Piping Connection	Liquid	mm (inch)		Ø 6.35 (1/4)						
	Gas	mm (inch)		Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 12.7 (1/2)				

		MJ05PC.NSJ	MJ07PC.NSJ	MJ09PC.NSJ	MJ12PC.NSJ	MJ15PC.NSJ	MJ18PC.NSK	MJ24PC.NSK		
Capacity	Cooling / Heating	Nom	kW	1.5 / 1.6	2.1 / 2.3	2.5 / 3.2	3.5 / 3.8	4.2 / 5.4	5.0 / 5.8	6.6 / 7.5
Power Input	Nom	W		16	17	18	19	21	39	45
Running Current	Nom	A		0.13	0.14	0.16	0.17	0.18	0.28	0.33
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Air Flow Rate	H / M / L	m³/min		8.3 / 6.7 / 5.6	8.6 / 7.2 / 5.6	9.2 / 7.4 / 5.6	9.6 / 8.1 / 5.6	10.0 / 8.5 / 6.1	14.2 / 11.3 / 9.9	15.2 / 12.7 / 10.2
Sound Pressure	H / M / L	dB(A)		34 / 31 / 27	35 / 32 / 27	36 / 33 / 27	40 / 35 / 27	41 / 36 / 29	44 / 38 / 35	46 / 41 / 36
Sound Power		dB(A)		57	57	57	57	57	59	65
Dehumidification Rate		l/h		0.9	0.9	1.1	1.2	1.2	1.9	2.6
Dimension		W x H x D	mm	837 x 308 x 189	998 x 345 x 210	998 x 345 x 210				
Net weight		kg		8.7	8.7	8.7	8.7	8.7	12.0	12.8
Piping Connection	Liquid	mm (inch)		Ø 6.35 (1/4)	Ø 6.35 (1/4)					
	Gas	mm (inch)		Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 12.7 (1/2)				

* This product contains Fluorinated greenhouse gases (R32).

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

R32 MULTI SPLIT

CEILING MOUNTED CASSETTE

	KBTU/H	5	7	9	12	15	18	24	
	KW	1.5	2.1	2.6	3.5	4.2	5.3	7.0	
Ceiling Mounted Cassette	1 Way Cassette		-	-	-	-	MT09R.NU1	MT11R.NU1	
	4 Way Cassette		MT06R.NRO	MT08R.NRO	CT09R.NRO	CT12R.NRO	-	CT18R.NQO	CT24R.NPO

1 Way Cassette

	INDOOR	MT09R.NU1	MT11R.NU1			
Capacity	Cooling / Heating	Nom	kW	2.6 / 2.9		3.5 / 3.9
Power Input	Nom	W		20		20
Running Current	Nom	A		0.2		0.2
Power Supply		Ø / V / Hz		1 / 220-240 / 50		1 / 220-240 / 50
Air Flow Rate	H / M / L	m³/min		7.5 / 7.3 / 6.8		8.1 / 7.4 / 7.0
Sound Pressure	Cooling	H / M / L	dBA	36 / 34 / 32		37 / 36 / 33
Sound Power	Cooling	Max	dBA	54		57
Dehumidification Rate		I/h		1.1		1.2
Dimensions	Body	W x H x D	mm	860 x 132 x 450		860 x 132 x 450
Net Weight	Body	kg		13.5		13.5
Piping Connection	Liquid	mm (inch)		Ø 6.35 (1/4)		Ø 6.35 (1/4)
	Gas	mm (inch)		Ø 9.52 (3/8)		Ø 9.52 (3/8)
Model				PT-UUC1		PT-UUC1
Decoration Panel	Color			Morning Fog (RAL120-4)		Morning Fog (RAL120-4)
Dimensions	W x H x D	mm		1,100 x 34 x 500		1,100 x 34 x 500
Weight	kg			4.4		4.4

4 Way Cassette

	MT06R.NRO	MT08R.NRO	CT09R.NRO	CT12R.NRO	CT18R.NQO	CT24R.NPO			
Capacity	Cooling / Heating	Nom	kW	1.5 / 1.6	2.1 / 2.3	2.6 / 2.9	3.5 / 3.9	5.3 / 5.8	6.7 / 7.5

<tbl_r cells

CEILING CONCEALED DUCT



	kBtu/h	05	07	09	12	15	18	24
	kW	1.5	2.1	2.6	3.5	4.2	5.3	7.0
Ceiling Concealed Duct	Mid / High Static Pressure		-	-	-	-	CM18R.N10	CM24R.N10
	Low Static Pressure		-	-	CL09R.N20	CL12R.N20	CL18R.N20	CL24R.N30

Duct (Mid Static)

	CM18R.N10	CM24R.N10
Capacity	Cooling / Heating	Nom kW
Power Input	Nom W	5.3 / 5.8
Running Current	Nom A	160
Power Supply	Ø / V / Hz	0.90
Air Flow Rate	H / M / L m³/min	1 / 220-240 / 50
Sound Pressure	H / M / L dB(A)	16.5 / 14.5 / 13.0
Sound Power	dB(A)	34 / 32 / 30
Dehumidification Rate	I/h	59
Dimension	W x H x D mm	60
Net weight	kg	1.5
Piping Connection	Liquid mm (inch)	2.5
Gas mm (inch)	Ø6.35 (1/4)	
External Static Pressure	Min-Max mmAq (Pa)	Ø12.7 (1/2)
	2-15 (20-147)	Ø12.7 (1/2)
		2-15 (20-147)

Duct (Low Static)

	CL09R.N20	CL12R.N20	CL18R.N20	CL24R.N30
Capacity	Cooling / Heating	Nom kW	2.6 / 2.9	3.5 / 3.9
Power Input	Nom W	100	100	140
Running Current	Nom A	0.80	0.80	0.80
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Air Flow Rate	H / M / L m³/min	10.0 / 8.5 / 7.0	10.0 / 8.5 / 7.0	15.0 / 12.5 / 10.0
Sound Pressure	H / M / L dB(A)	31 / 28 / 27	31 / 28 / 27	36 / 34 / 31
Sound Power	dB(A)	55	55	54
Dehumidification Rate	I/h	0.55	1.11	1.58
Dimension	W x H x D mm	900 x 190 x 700	900 x 190 x 700	900 x 190 x 700
Net weight	kg	24.0	24.0	24.0
Piping Connection	Liquid mm (inch)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)
Gas mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø12.7 (1/2)	Ø12.7 (1/2)
External Static Pressure	Min-Max mmAq (Pa)	0-5 (0-50)	0-5 (0-50)	0-5 (0-50)

R32 MULTI SPLIT

COMBINATION TABLE

MU2R15

Operation	Cooling																
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity			Input(W)								
	UNIT-A		UNIT-B		UNIT-C	UNIT-D		Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5	5	7	7	9	9	12	12	3,000	0.88	5,000	1.47	5,750	1.69	226	381	477
	7	7	9	9	12	12	12	12	4,200	1.23	7,000	2.05	8,050	2.36	303	540	683
	9	9	12	12	12	12	12	12	5,400	1.58	9,000	2.64	10,350	3.03	408	676	864
	12	12	12	12	12	12	12	12	7,200	2.11	12,000	3.52	13,800	4.04	540	926	1,176
2 UNIT	5	5	5	5	7	7	7	7	6,000	1.76	10,000	2.93	11,500	3.37	414	682	889
	5	5	5	5	7	7	7	7	7,200	2.11	12,000	3.52	13,800	4.04	486	833	1,106
	5	5	7	7	9	9	9	9	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	7	7	7	7	9	9	9	9	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	7	7	9	9	9	9	9	9	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	5	12	12	12	12	12	12	12	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	9	9	9	9	9	9	9	9	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	7	12	12	12	12	12	12	12	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	9	12	12	12	12	12	12	12	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376

MU2R17

Operation	Cooling																
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity			Input(W)								
	UNIT-A		UNIT-B		UNIT-C	UNIT-D		Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5	5	7	7	9	9	12	12	3,000	0.88	5,000	1.47	5,750	1.69	226	381	477
	7	7	9	9	9	9	12	12	4,200	1.23	7,000	2.05	8,050	2.36	303	540	683
	9	9	12	12	12	12	12	12	5,400	1.58	9,000	2.64	10,350	3.03	408	676	864
	12	12	12	12	12	12	12	12	7,200	2.11	12,000	3.52	13,800	4.04	540	926	1,176
2 UNIT	5	5	5	5	7	7	7	7	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	5	5	5	5	7	7	7	7	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	7	7	9	9	9	9	9	9	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	7	9	9	9	9	9	9	9	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	5	12	12	12	12	12	12	12	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	9	9	9	9	9	9	9	9	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	7	12	12	12	12	12	12	12	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	9	12	12	12	12	12	12	12	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376
	12	12	12	12	12	12	12	12	8,400	2.46	14,000	4.10	16,100	4.72	583	988	1,376

Operation	Heating																
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity			Input(W)								
	UNIT-A		UNIT-B		UNIT-C	UNIT-D		Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5	5	7	7	9	9	12	12	3,300	0.97	5,500	1.61	6,050	1.77	235	380	472
	7	7	9	9	9	9	12	12	5,040	1.48	8,400	2.46	9,240	2.71	355	604	721
	9	9	12	12	12	12	12	12	6,480	1.90	10,800	3.17	11,880	3.48	454	758	920
	12	12	12	12	12	12	12	12	7,920	2.32	13,200	3.87	14,520	4.26	554	969	1,185
2 UNIT	5	5	5	5	7	7	7	7	6,600	1.93	11,000	3.22	12,100	3.55	408	706	854
	5	5	5	5	7	7	7	7	7,920	2.32	13,200	3.87	14,520	4.26	498	872	1,066
	5	9	9	9	9	9	9	9	9,600	2.81	16,000	4.69	18,400	5.39	613	1,066	1,433
	7	7	9	9	9	9	9	9	9,600	2.81	16,000	4.69	18,400	5.39	613	1,066	1,433
	5	12	12	12	12	12	12	12	9,600	2.81	16,000	4.69	18,400	5.39	613	1,066	1,433
	9	9	9	9	9	9	9	9	9,600	2.81	16,000	4.69	18,400	5.39	613		

R32 MULTI SPLIT

COMBINATION TABLE

MU3R19

Operation	Cooling					Heating										Total Capacity								
	Combination of Indoor Unit (kBtu/h Class)				Total	Total Capacity			Input(W)			Total Capacity										Input(W)		
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max	
1 UNIT	5				5	3,600	1.06	5,000	1.47	6,000	1.76	235	356	527	5	4,000	1.17	5,500	1.61	6,325	1.85	248	368	539
	7				7	4,200	1.23	7,000	2.05	8,400	2.46	257	462	623	7	5,040	1.48	8,400	2.46	9,660	2.83	313	537	680
	9				9	5,400	1.58	9,000	2.64	10,800	3.17	346	580	814	9	6,480	1.90	10,800	3.17	12,420	3.64	401	702	896
	12				12	7,200	2.11	12,000	3.52	14,400	4.22	462	802	1,101	12	7,920	2.32	13,200	3.87	15,180	4.45	491	874	1,121
	15				15	8,520	2.50	14,200	4.16	17,040	4.99	556	983	1,276	15	9,900	2.90	16,500	4.84	18,975	5.56	631	1,105	1,479
	18				18	10,800	3.17	18,000	5.28	21,600	6.33	727	1,282	1,806	18	11,880	3.48	19,800	5.80	22,770	6.67	775	1,376	1,829
	5	5			10	6,000	1.76	10,000	2.93	12,000	3.52	373	620	854	5	7,200	2.11	12,000	3.52	13,800	4.04	424	736	957
	5	7			12	7,200	2.11	12,000	3.52	14,400	4.22	439	762	1,046	5	8,640	2.53	14,400	4.22	16,560	4.85	511	903	1,204
	5	9			14	8,400	2.46	14,000	4.10	16,800	4.92	528	909	1,246	5	9,900	2.90	16,800	4.92	19,320	5.66	622	1,075	1,435
	7	7			14	8,400	2.46	14,000	4.10	16,800	4.92	528	909	1,246	7	10,080	2.95	16,800	4.92	19,320	5.66	622	1,075	1,435
2 UNIT	7	9			16	9,600	2.81	16,000	4.69	19,200	5.63	597	1,061	1,504	7	11,520	3.38	19,200	5.63	22,080	6.47	713	1,255	1,676
	5	12			17	10,200	2.99	17,000	4.98	20,400	5.98	644	1,139	1,644	5	12,240	3.59	20,400	5.98	23,460	6.88	760	1,361	1,801
	9	9			18	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	9	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	7	12			19	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	7	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	5	15			20	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	5	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	9	12			21	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	9	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	7	15			22	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	7	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	5	18			23	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	5	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	9	15			24	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	9	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	12	12			24	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	12	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	7	18			25	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	7	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	9	18			27	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	9	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	12	15			27	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	12	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	12	18			30	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	12	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
	15	15			30	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761	15	12,960	3.80	21,600	6.33	24,840	7.28	807	1,442	2,028
3 UNIT	5	5	5		15	9,000	2.64	15,000	4.40	18,000	5.28	524	935	1,289	5	10,800	3.17	18,000	5.28	20,700	6.07	634	1,118	1,476
	5	5	7		17	10,200	2.99	17,000	4.98	20,400	5.98	611	1,082	1,562	5	12,240	3.59	20,400	5.98	23,460	6.88	722	1,293	1,711
	5	5	9		19	10,800	3.17	18,000	5.28	21,600	6.33	656	1,151	1,668	5	12,960	3.80	21,600	6.33	24,840	7.28	766	1,370	1,944
	5	7	7		19	10,800	3.17	18,000	5.28	21,600	6.33	656	1,151	1,668	5	12,960	3.80	21,600	6.33	24,840	7.28	766	1,370	1,944
	5	7	9		21	10,800	3.17	18,000	5.28	21,600	6.33	656	1,151	1,668										

COMBINATION TABLE

MU3R21

Operation	Cooling											
	Combination of Indoor Unit (kBtu/h Class)				Total Capacity			Input(W)				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	
1 UNIT	5	3,600	1.06	5,000	1.47	6,000	1.76	235	356	527		
	7	4,200	1.23	7,000	2.05	8,400	2.46	257	462	623		
	9	5,400	1.58	9,000	2.64	10,800	3.17	346	580	814		
	12	7,200	2.11	12,000	3.52	14,400	4.22	462	802	1,101		
	15	8,520	2.50	14,200	4.16	17,040	4.99	556	983	1,276		
	18	10,800	3.17	18,000	5.28	21,600	6.33	727	1,282	1,806		
	5	5	10	6,000	1.76	10,000	2.93	12,000	3.52	373	620	854
	5	7	12	7,200	2.11	12,000	3.52	14,400	4.22	439	762	1,046
	5	9	14	8,400	2.46	14,000	4.10	16,800	4.92	528	909	1,246
	7	7	14	8,400	2.46	14,000	4.10	16,800	4.92	528	909	1,246
2 UNIT	7	9	16	9,600	2.81	16,000	4.69	19,200	5.63	597	1,061	1,504
	5	12	17	10,200	2.99	17,000	4.98	20,400	5.98	644	1,139	1,644
	9	9	18	10,800	3.17	18,000	5.28	21,600	6.33	691	1,218	1,761
	7	12	19	11,400	3.34	19,000	5.57	22,800	6.68	714	1,343	1,950
	5	15	20	12,000	3.52	20,000	5.86	23,100	6.77	762	1,436	1,999
	9	12	21	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	7	15	22	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	5	18	23	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	9	15	24	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	12	12	24	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
3 UNIT	7	18	25	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	9	18	27	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	12	15	27	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	12	18	30	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	15	15	30	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	15	18	33	12,600	3.69	21,000	6.15	23,100	6.77	811	1,532	1,999
	5	5	15	9,000	2.64	15,000	4.40	18,000	5.28	524	935	1,289
	5	5	17	10,200	2.99	17,000	4.98	20,400	5.98	611	1,082	1,562
	5	5	19	11,400	3.34	19,000	5.57	22,800	6.68	679	1,276	1,824
	5	7	19	11,400	3.34	19,000	5.57	22,800	6.68	679	1,276	1,824
4 UNIT	5	7	21	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	7	7	21	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	5	22	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	9	23	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	7	7	23	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	7	24	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	7	25	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	7	9	25	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	9	26	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	7	7	26	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
5 UNIT	5	7	27	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	18	28	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	7	9	28	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	9	29	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	12	29	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	7	7	29	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	7	30	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	9	9	30	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	7	9	31	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	7	12	31	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
6 UNIT	5	12	32	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	9	32	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	7	7	32	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	9	9	33	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	9	12	33	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	5	33	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	5	34	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	5	35	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073
	5	5	36	12,600	3.69	21,000	6.15	25,000	7.33	770	1,444	2,073

R32 MULTI SPLIT

COMBINATION TABLE

MU4R25

Operation	Cooling																	
	Combination of Indoor Unit (kBtu/h Class)				Total Capacity			Input(W)										
	UNIT-A		UNIT-B		UNIT-C		UNIT-D		Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5	5	5	5	5	5	5	5	20	12,000	3.52	20,000	5.86	24,000	7.03	680	1,202	1,677
	7	7	5	5	5	5	5	7	22	13,200	3.87	22,000	6.45	26,400	7.74	764	1,317	1,975
	9	9	5	5	5	5	5	9	24	14,400	4.22	24,000	7.03	28,800	8.44	827	1,458	2,274
	12	12	5	5	5	5	5	7	24	14,400	4.22	24,000	7.03	28,800	8.44	827	1,458	2,274
	15	15	5	5	5	5	5	9	26	14,400	4.22	24,000	7.03	28,800	8.44	827	1,458	2,274
	18	18	5	5	5	5	5	7	26	14,400	4.22	24,000	7.03	28,800	8.44	827	1,458	2,274
	24	24	5	5	5	5	5	12	27	14,400	4.22	24,000	7.03	28,800	8.44	827	1,458	2,274
	5	10	6,000	1.76	10,000	2.93	12,000	3.52	378	623	876							
	5	12	7,200	2.11	12,000	3.52	14,400	4.22	444	761	1,066							
	5	9	14,800	2.46	14,000	4.10	16,800	4.92	533	927	1,261							
2 UNIT	7	7	8,400	2.46	14,000	4.10	16,800	4.92	533	927	1,261							
	7	9	16,900	2.81	16,000	4.69	19,200	5.63	601	1,072	1,461							
	5	12	10,200	2.99	17,000	4.98	20,400	5.98	646	1,145	1,578							
	9	9	18,000	3.17	18,000	5.28	21,600	6.33	692	1,220	1,667							
	7	12	11,400	3.34	19,000	5.57	22,800	6.68	715	1,296	1,787							
	5	15	20,000	3.52	20,000	5.86	24,000	7.03	761	1,372	1,878							
	9	12	21,200	3.69	21,000	6.15	24,150	7.08	808	1,449	1,927							
	7	15	22,000	3.87	22,000	6.45	25,300	7.42	855	1,501	2,066							
	5	18	23,800	4.04	23,000	6.74	26,450	7.75	879	1,580	2,261							
	9	15	24,000	4.22	24,000	7.03	28,800	8.44	927	1,675	2,572							
3 UNIT	12	12	24,400	4.22	24,000	7.03	28,800	8.44	927	1,675	2,572							
	7	18	25,000	4.22	24,000	7.03	28,800	8.44	927	1,675	2,572							
	9	18	27,000	4.22	24,000	7.03	28,800	8.44	927	1,675	2,572							
	12	15	27,400	4.22	24,000	7.03	28,800	8.44	927	1,675	2,572							
	5	24	29,000	4.22	24,000	7.03	29,000	8.50	927	1,675	2,626							
	12	15	30,000	4.22	24,000	7.03	29,000	8.50	927	1,675	2,626							
	7	24	31,000	4.22	24,000	7.03	29,000	8.50	927	1,675	2,626							
	9	24	33,000	4.22	24,000	7.03	29,000	8.50	927	1,675	2,626							
	15	18	33,000	4.22	24,000	7.03	29,000	8.50	927	1,675	2,626							
	18	18	36,000	4.22	24,000	7.03	29,000	8.50	927	1,675	2,626							
4 UNIT	12	24	36,000	4.22	24,000	7.03	29,000	8.50	927	1,675	2,626							
	5	5	15,000	2.64	15,000	4.40	18,000	5.28	522	916	1,292							
	5	7	17,000	2.99	17,000	4.98	20,400	5.98	607	1,054	1,483							
	5	9	19,000	3.34	19,000	5.57	22,800	6.68	672	1,194	1,680							
	5	7	19,000	3.34	19,000	5.57	22,800	6.68	672	1,194	1,680							
	5	7	21,000	3.69	21,000	6.15	25,200	7.39	760	1,338	1,942							
	7	7	21,200	3.69	21,000	6.15	25,200	7.39	760	1,338	1,942							
	5	5	22,000	3.87	22,000	6.45	26,400	7.74	804	1,387	2,079							
	5	9	23,800	4.04	23,000	6.74	27,600	8.09	826	1,461	2,278							
	7	7	23,800	4.04	23,000	6.74	27,600	8.09	826	1,461	2,278							
3 UNIT	5	7	24,400	4.22	24,000	7.03	28,800	8.44	871	1,535	2,442							
	5	5	25,000	4.22	24,000	7.03	28,800	8.44	871	1,535	2,442							
	7	9	25,000	4.22	24,000	7.03	28,800	8.44	871	1,535	2,442							
	5	9	26,000	4.22	24,000	7.03	28,800	8.44	871	1,535	2,442							
	7	7	27,000	4.22	24,000	7.03	28,800	8.44	871	1,535	2,442							
	5	9	27,000	4.22	24,000	7.03	28,800	8.44	871	1,535	2,442							
	7	9	28,000	4.22	24,000	7.03	28,800	8.44	871	1,535	2,442							
	5	5	28,000	4.22	24,000	7.03	28,800											

R32 MULTI SPLIT

COMBINATION TABLE

MU4R25

Operation	Heating																	
	Combination of Indoor Unit (kBtu/h Class)				Total Capacity			Input(W)										
	UNIT-A		UNIT-B		UNIT-C		UNIT-D		Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5	5	5	5	5	5	5	5	20	14,400	4.22	24,000	7.03	28,800	8.44	840	1,480	2,100
	7	7	7	7	7	7	7	7	22	15,840	4.64	26,400	7.74	31,680	9.28	927	1,651	2,470
	9	9	9	9	9	9	9	9	24	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	12	12	12	12	12	12	12	12	26	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	15	15	15	15	15	15	15	15	30	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	18	18	18	18	18	18	18	18	33	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	24	24	24	24	24	24	24	24	37	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	5	5	5	5	5	5	5	5	42	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	7	7	7	7	7	7	7	7	45	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	9	9	9	9	9	9	9	9	48	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
2 UNIT	5	5	5	5	5	5	5	5	51	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	7	7	7	7	7	7	7	7	54	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	9	9	9	9	9	9	9	9	57	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	12	12	12	12	12	12	12	12	60	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	15	15	15	15	15	15	15	15	63	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	18	18	18	18	18	18	18	18	66	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	24	24	24	24	24	24	24	24	70	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	5	5	5	5	5	5	5	5	73	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	7	7	7	7	7	7	7	7	76	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	9	9	9	9	9	9	9	9	79	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
3 UNIT	5	5	5	5	5	5	5	5	82	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	7	7	7	7	7	7	7	7	85	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	9	9	9	9	9	9	9	9	88	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	12	12	12	12	12	12	12	12	91	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	15	15	15	15	15	15	15	15	94	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	18	18	18	18	18	18	18	18	97	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	24	24	24	24	24	24	24	24	100	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	5	5	5	5	5	5	5	5	103	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	7	7	7	7	7	7	7	7	106	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	9	9	9	9	9	9	9	9	109	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
4 UNIT	5	5	5	5	5	5	5	5	112	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	7	7	7	7	7	7	7	7	115	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	9	9	9	9	9	9	9	9	118	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	12	12	12	12	12	12	12	12	121	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	15	15	15	15	15	15	15	15	124	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	18	18	18	18	18	18	18	18	127	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	24	24	24	24	24	24	24	24	130	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	5	5	5	5	5	5	5	5	133	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	7	7	7	7	7	7	7	7	136	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517
	9	9	9	9	9	9	9	9	139	17,280	5.06	28,800	8.44	32,000	9.38	1,038	1,826	2,517

Operation	Heating																
Combination of Indoor Unit (kBtu/h Class)				Total Capacity			Input(W)										
UNIT-A		UNIT-B		UNIT-C		UNIT-D		Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max

<tbl_r cells="10

R32 MULTI SPLIT

COMBINATION TABLE

MU4R27

Operation	Cooling																	
	Combination of Indoor Unit (kBtu/h Class)				Total Capacity				Input(W)									
	UNIT-A		UNIT-B		UNIT-C		UNIT-D		Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5	5	5	5	5	5	5	5	20	12,000	3.52	20,000	5.86	24,000	7.03	680	1,202	1,633
	7	7	7	7	7	7	7	7	22	13,200	3.87	22,000	6.45	26,400	7.74	764	1,317	1,923
	9	9	9	9	9	9	9	9	24	14,400	4.22	24,000	7.03	28,800	8.44	827	1,458	2,215
	12	12	12	12	12	12	12	12	24	14,400	4.22	24,000	7.03	28,800	8.44	827	1,458	2,215
	15	15	15	15	15	15	15	15	26	15,600	4.57	26,000	7.62	31,200	9.14	913	1,679	2,520
	18	18	18	18	18	18	18	18	26	15,600	4.57	26,000	7.62	31,200	9.14	913	1,679	2,520
	24	24	24	24	24	24	24	24	27	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	5	5	5	5	5	5	28	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	7	7	7	7	7	28	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	9	9	9	9	9	9	9	9	29	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	12	12	12	12	12	12	12	12	30	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	15	15	15	15	15	15	15	15	30	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	18	18	18	18	18	18	18	18	30	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	24	24	24	24	24	24	24	24	31	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	5	5	5	5	5	5	31	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	7	7	7	7	7	31	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	9	9	9	9	9	9	9	9	32	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	12	12	12	12	12	12	12	12	33	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	15	15	15	15	15	15	15	15	33	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	18	18	18	18	18	18	18	18	33	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	24	24	24	24	24	24	24	24	34	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	5	5	5	5	5	5	34	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	7	7	7	7	7	34	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	9	9	9	9	9	9	9	9	35	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	12	12	12	12	12	12	12	12	35	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	15	15	15	15	15	15	15	15	35	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	18	18	18	18	18	18	18	18	36	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	24	24	24	24	24	24	24	24	36	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	5	5	5	5	5	5	36	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	7	7	7	7	7	36	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	9	9	9	9	9	9	9	9	36	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	12	12	12	12	12	12	12	12	37	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	15	15	15	15	15	15	15	15	37	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	18	18	18	18	18	18	18	18	37	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	24	24	24	24	24	24	24	24	38	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	5	5	5	5	5	5	38	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	7	7	7	7	7	38	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	9	9	9	9	9	9	9	9	38	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	12	12	12	12	12	12	12	12	39	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	15	15	15	15	15	15	15	15	39	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	18	18	18	18	18	18	18	18	40	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	24	24	24	24	24	24	24	24	40	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	5	5	5	5	5	5	40	16,200	4.75	27,000	7.91	32,400	9.50			

R32 MULTI SPLIT

COMBINATION TABLE

MU4R27

Operation	Heating																	
	Combination of Indoor Unit (kBtu/h Class)				Total Capacity			Input(W)										
	UNIT-A		UNIT-B		UNIT-C		UNIT-D		Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5	5	5	5	5,000	1.47	5,500	1.61	6,325	1.85	610	610	610	714				
	7	7	7	7	5,400	1.58	8,400	2.46	9,660	2.83	610	636	825					
	9	9	9	9	6,480	1.90	10,800	3.17	12,420	3.64	610	826	1,077					
	12	12	12	12	7,920	2.32	13,200	3.87	15,180	4.45	583	1,021	1,338					
	15	15	15	15	9,900	2.90	16,500	4.84	18,975	5.56	744	1,279	1,744					
	18	18	18	18	11,880	3.48	19,800	5.80	22,770	6.67	909	1,577	2,133					
	24	24	24	24	15,240	4.47	25,400	7.44	26,670	7.82	1,192	2,077	2,538					
	5	5	10	10	7,200	2.11	12,000	3.52	14,400	4.22	451	773	1,081					
	5	5	12	12	8,640	2.53	14,400	4.22	17,280	5.06	541	940	1,337					
	5	9	14	14	10,080	2.95	16,800	4.92	20,160	5.91	656	1,112	1,571					
2 UNIT	7	7	14	14	10,080	2.95	16,800	4.92	20,160	5.91	656	1,112	1,571					
	7	9	16	16	11,520	3.38	19,200	5.63	23,040	6.75	749	1,289	1,844					
	5	12	17	17	12,240	3.59	20,400	5.98	24,480	7.17	796	1,392	1,968					
	9	9	18	18	12,960	3.80	21,600	6.33	25,920	7.60	844	1,471	2,094					
	7	12	19	19	13,680	4.01	22,800	6.68	27,360	8.02	892	1,577	2,222					
	5	15	20	20	14,400	4.22	24,000	7.03	28,800	8.44	940	1,657	2,352					
	9	12	21	21	15,120	4.43	25,200	7.39	30,240	8.86	989	1,766	2,568					
	7	15	22	22	15,840	4.64	26,400	7.74	31,680	9.28	1,038	1,848	2,811					
	5	18	23	23	16,560	4.85	27,600	8.09	33,120	9.71	1,112	1,960	3,127					
	9	15	24	24	17,280	5.06	28,800	8.44	34,100	9.99	1,100	2,045	3,384					
3 UNIT	12	12	24	24	17,280	5.06	28,800	8.44	34,100	9.99	1,100	2,045	3,384					
	7	18	25	25	18,000	5.28	30,000	8.79	34,100	9.99	1,147	2,194	3,384					
	9	18	27	27	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
	12	15	27	27	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
	5	24	29	29	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
	12	18	30	30	18,600	5.45	31,000	9.09	34,100	9.99	1,100	2,045	3,384					
	15	15	30	30	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
	7	24	31	31	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
	9	24	33	33	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
	15	18	33	33	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
4 UNIT	18	18	36	36	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
	12	24	36	36	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
	15	24	39	39	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384					
	5	5	15	15	18,000	3.17	18,000	5.28	21,600	6.33	660	1,140	1,590					
	5	7	17	17	12,240	3.59	20,400	5.98	24,480	7.17	748	1,309	1,850					
	5	5	19	19	13,680	4.01	22,800	6.68	27,360	8.02	838	1,482	2,089					
	5	7	19	19	13,680	4.01	22,800	6.68	27,360	8.02	838	1,482	2,089					
	5	7	21	21	15,120	4.43	25,200	7.39	30,240	8.86	930	1,660	2,414					
	7	7	21	21	15,120	4.43	25,200	7.39	30,240	8.86	930	1,660	2,414					
	5	5	22	22	15,840	4.64	26,400	7.74	31,680	9.28	976	1,738	2,590					
3 UNIT	5	9	23	23	16,560	4.85	27,600	8.09	33,120	9.71	1,046	1,842	2,767					
	7	9	23	23	16,560	4.85	27,600	8.09	33,120	9.71	1,046	1,842	2,767					
	7	7	24	24	17,280	5.06	28,800	8.44	34,560	10.13	1,093	1,922	2,951					
	5	5	25	25	18,000	5.28	30,000	8.79	34,720	10.18	1,140	2,063	2,998					
	7	9	25	25	18,000	5.28	30,000	8.79	34,720	10.18	1,140	2,063	2,998					
	5	9	26	26	18,720	5.49	31,200	9.14	34,720	10.18	1,188	2,177	2,998					

R32 MULTI SPLIT

COMBINATION TABLE

MU5R30

Operation	Cooling																	
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity			Input(W)									
	UNIT-A		UNIT-B		UNIT-C	UNIT-D		UNIT-E	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5	5	5	5	5	5	5	5	5	4,500	1.32	5,000	1.47	5,000	1.76	416	418	629
	7	7	7	7	7	7	7	7	7	4,800	1.41	7,000	2.05	8,400	2.46	416	494	681
	9	9	9	9	9	9	9	9	9	5,400	1.58	9,000	2.64	10,800	3.17	416	617	884
	12	12	12	12	12	12	12	12	12	7,200	2.11	12,000	3.52	14,400	4.22	494	846	1,184
	15	15	15	15	15	15	15	15	15	8,520	2.50	14,200	4.16	17,040	4.99	592	1,029	1,432
	18	18	18	18	18	18	18	18	18	10,800	3.17	18,000	5.28	21,600	6.33	769	1,328	1,852
	24	24	24	24	24	24	24	24	24	14,400	4.22	24,000	7.03	25,500	7.47	1,029	1,815	2,604
	5	5	5	5	5	5	5	5	5	6,000	1.76	10,000	2.93	12,000	3.52	378	623	876
	5	5	5	5	5	5	5	5	5	7,200	2.11	12,000	3.52	14,400	4.22	444	761	1,066
	5	5	5	5	5	5	5	5	5	8,400	2.46	14,000	4.10	16,800	4.92	533	903	1,261
2 UNIT	7	7	7	7	7	7	7	7	7	8,400	2.46	14,000	4.10	16,800	4.92	533	903	1,261
	7	7	7	7	7	7	7	7	7	9,600	2.81	16,000	4.69	19,200	5.63	601	1,047	1,461
	5	12	5	12	5	12	5	12	5	10,200	2.99	17,000	4.98	20,400	5.98	646	1,121	1,578
	9	9	9	9	9	9	9	9	9	10,800	3.17	18,000	5.28	21,600	6.33	692	1,195	1,667
	7	12	7	12	7	12	7	12	7	11,400	3.34	19,000	5.57	22,800	6.68	715	1,270	1,787
	5	15	5	15	5	15	5	15	5	12,000	3.52	20,000	5.86	24,000	7.03	761	1,347	1,878
	9	12	9	12	9	12	9	12	9	12,600	3.69	21,000	6.15	25,200	7.39	808	1,423	2,066
	7	15	7	15	7	15	7	15	7	13,200	3.87	22,000	6.45	26,400	7.74	855	1,475	2,211
	5	18	5	18	5	18	5	18	5	13,800	4.04	23,000	6.74	27,600	8.09	879	1,554	2,414
	9	15	9	15	9	15	9	15	9	14,400	4.22	24,000	7.03	28,800	8.44	927	1,633	2,572
	12	12	12	12	12	12	12	12	12	14,400	4.22	24,000	7.03	28,800	8.44	927	1,633	2,572
	7	18	7	18	7	18	7	18	7	15,000	4.40	25,000	7.33	30,000	8.79	975	1,755	2,794
	9	18	9	18	9	18	9	18	9	16,200	4.75	27,000	7.91	32,400	9.50	1,047	2,011	3,213
	12	15	12	15	12	15	12	15	12	16,200	4.75	27,000	7.91	32,400	9.50	1,047	2,011	3,213
	5	24	5	24	5	24	5	24	5	17,400	5.10	29,000	8.50	33,000	9.67	1,145	2,284	3,341
	12	18	12	18	12	18	12	18	12	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
	15	15	15	15	15	15	15	15	15	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
	7	24	7	24	7	24	7	24	7	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
	9	24	9	24	9	24	9	24	9	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
	15	18	15	18	15	18	15	18	15	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
	18	18	18	18	18	18	18	18	18	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
	12	24	12	24	12	24	12	24	12	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
	15	24	15	24	15	24	15	24	15	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
	18	24	18	24	18	24	18	24	18	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
	24	24	24	24	24	24	24	24	24	18,000	5.28	30,000	8.79	33,000	9.67	1,195	2,429	3,341
3 UNIT	5	5	5	5	5	5	5	5	5	9,000	2.64	15,000	4.40	18,000	5.28	522	916	1,292
	5	5	5	5	5	5	5	5	5	10,200	2.99	17,000	4.98	20,400	5.98	607	1,054	1,483
	5	5	5	5	5	5	5	5	5	11,400	3.34	19,000	5.57	22,800	6.68	672	1,194	1,680
	5	7	5	7	5	7	5	7	5	11,400	3.34	19,000	5.57	22,800	6.68	672	1,194	1,680
	5	7	5	7	5	7	5	7	5	12,600	3.69	21,000	6.15	25,200	7.39	760	1,338	1,942
	7	7	7	7	7	7	7	7	7	12,600	3.69	21,000	6.15	25,200	7.39	760	1,338	1,942
	5	5	5	5	5	5	5	5	5	13,200	3.87	22,000	6.45	26,400	7.74	804	1,387	2,079
	5	5	5	5	5	5	5	5	5	13,800	4.04	23,000	6.74	27,600	8.09	826	1,461	2,278
	7																	

R32 MULTI SPLIT

COMBINATION TABLE

MU5R30

Operation	Cooling										
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity			Input(W)		
	Min		Rated		Max		Min		Rated		Max
UNIT-A	UNIT-B	UNIT-C	UNIT-D	UNIT-E	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW
5	5	5	5	5	25	15,000	4.40	25,000	7.33	30,000	8.79
5	5	5	5	7	27	16,200	4.75	27,000	7.91	32,400	9.50
5	5	5	5	9	29	17,400	5.10	29,000	8.50	34,800	10.20
5	5	5	7	7	29	17,400	5.10	29,000	8.50	34,800	10.20
5	5	5	7	9	31	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	7	7	31	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	5	12	32	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	9	9	33	18,000	5.28	30,000	8.79	36,000	10.55
5	5	7	7	9	33	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	7	7	33	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	7	12	34	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	5	15	35	18,000	5.28	30,000	8.79	36,000	10.55
5	5	7	9	9	35	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	7	9	35	18,000	5.28	30,000	8.79	36,000	10.55
7	7	7	7	7	35	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	9	12	36	18,000	5.28	30,000	8.79	36,000	10.55
5	5	7	7	12	36	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	7	15	37	18,000	5.28	30,000	8.79	36,000	10.55
5	5	9	9	9	37	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	9	9	37	18,000	5.28	30,000	8.79	36,000	10.55
7	7	7	7	9	37	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	5	18	38	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	7	12	38	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	9	15	39	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	12	12	39	18,000	5.28	30,000	8.79	36,000	10.55
5	5	7	7	15	39	18,000	5.28	30,000	8.79	36,000	10.55
7	7	7	9	9	39	18,000	5.28	30,000	8.79	36,000	10.55
5	7	9	9	9	39	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	7	18	40	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	9	12	40	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	9	12	40	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	12	12	40	18,000	5.28	30,000	8.79	36,000	10.55
5	5	7	7	15	41	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	7	15	41	18,000	5.28	30,000	8.79	36,000	10.55
5	9	9	9	41	41	18,000	5.28	30,000	8.79	36,000	10.55
5	7	9	9	41	41	18,000	5.28	30,000	8.79	36,000	10.55
5	5	9	9	41	41	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	9	18	42	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	12	15	42	18,000	5.28	30,000	8.79	36,000	10.55
5	5	7	7	18	42	18,000	5.28	30,000	8.79	36,000	10.55
5	7	9	9	12	42	18,000	5.28	30,000	8.79	36,000	10.55
5	5	9	9	15	43	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	9	15	43	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	12	12	43	18,000	5.28	30,000	8.79	36,000	10.55
7	7	7	7	15	43	18,000	5.28	30,000	8.79	36,000	10.55
5	9	9	9	9	43	18,000	5.28	30,000	8.79	36,000	10.55
5	5	7	12	15	44	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	5	24	44	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	7	18	44	18,000	5.28	30,000	8.79	36,000	10.55
5	9	9	9	12	44	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	12	12	43	18,000	5.28	30,000	8.79	36,000	10.55
7	7	7	7	15	43	18,000	5.28	30,000	8.79	36,000	10.55
5	9	9	9	9	43	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	12	15	44	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	5	24	44	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	7	18	44	18,000	5.28	30,000	8.79	36,000	10.55
5	9	9	9	12	44	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	12	12	43	18,000	5.28	30,000	8.79	36,000	10.55
7	7	7	7	15	43	18,000	5.28	30,000	8.79	36,000	10.55
5	9	9	9	9	43	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	12	15	42	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	5	18	42	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	9	12	42	18,000	5.28	30,000	8.79	36,000	10.55
5	5	9	9	15	43	18,000	5.28	30,000	8.79	36,000	10.55
5	7	7	7	18	42	18,000	5.28	30,000	8.79	36,000	10.55
5	5	5	9	18	42	18,000	5.28	30,000	8.79	36,000	10.55
5	5	7	7	24							

COMBINATION TABLE

MU5R30

Operation	Heating													
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity			Input(W)					
	Min		Rated		Max		Min		Rated		Max			
UNIT-A	UNIT-B	UNIT-C	UNIT-D	UNIT-E	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW			
3 UNIT	7	18	18	43	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	7	12	24	43	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	5	15	24	44	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	9	18	18	45	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	9	12	24	45	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	12	15	18	45	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	15	15	15	45	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	7	15	24	46	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	5	18	24	47	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	9	15	24	48	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	12	18	18	48	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	12	12	24	48	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	15	15	18	48	20,700	6.07	34,500	10.11	38,640	11.32	1,333	2,566	3,602	
	5	5	5	5	20	14,400	4.22	24,000	7.03	28,800	8.44	840	1,480	2,100
	5	5	5	7	22	15,840	4.64	26,400	7.74	31,680	9.28	927	1,651	2,470
	5	5	5	9	24	17,280	5.06	28,800	8.44	34,560	10.13	1,038	1,826	2,861
	5	5	7	7	24	17,280	5.06	28,800	8.44	34,560	10.13	1,038	1,826	2,861
	5	5	7	9	26	18,720	5.49	31,200	9.14	37,440	10.97	1,128	2,068	3,349
	5	7	7	7	26	18,720	5.49	31,200	9.14	37,440	10.97	1,128	2,068	3,349
	5	5	5	12	27	19,440	5.70	32,400	9.50	38,640	11.32	1,174	2,230	3,524
	5	5	9	9	28	20,160	5.91	33,600	9.85	38,640	11.32	1,220	2,356	3,524
	5	7	7	9	28	20,160	5.91	33,600	9.85	38,640	11.32	1,220	2,356	3,524
	7	7	7	7	28	20,160	5.91	33,600	9.85	38,640	11.32	1,220	2,356	3,524
	5	5	7	12	29	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	5	5	15	30	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	7	9	9	30	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	7	7	7	9	30	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	5	9	12	31	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	7	7	12	31	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	5	7	15	32	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	7	7	9	9	32	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	9	9	9	32	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	5	5	18	33	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	7	9	12	33	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	7	7	7	12	33	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	5	9	15	34	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	5	12	12	34	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	7	9	9	9	34	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	5	18	18	35	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	9	9	12	35	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	7	7	9	12	35	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	7	9	15	36	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	7	12	12	36	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	7	7	7	15	36	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	9	9	9	36	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	5	18	18	37	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	5	12	15	37	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	7	7	18	37	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	7	9	9	12	37	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	9	9	15	38	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,487	3,524
	5	7	12	12	36	20,700	6.07	34,500	10.11	38,640	11.32	1,267	2,48	

R410A MULTI SPLIT



R410A MULTI SPLIT OUTDOOR UNITS






RESIDENTIAL

MU5M40



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com



(Unit : mm)

OUTDOOR			MU5M40.U44
Compressor	Type		R-Scroll
Capacity*	Cooling	Min / Nom / Max kW	1.8 / 11.2 / 14.7
	Heating	Min / Nom / Max kW	2.0 / 12.5 / 15.5
Low Temperature Capacity	Heating -7°C	Max kW	11.0
Power Input*	Cooling	Min / Nom / Max kW	0.8 / 2.8 / 5.0
	Heating	Min / Nom / Max kW	0.8 / 2.9 / 5.2
EER			4.0
COP			4.3
SEER			7.1
SCOP			4.0
Pdesign (@-10°C)		kW	8.8
Season Energy Label	Cooling / Heating (A+++ to E Scale)		A++ / A+
Season Energy Consumption	Cooling / Heating	kWh	552 / 3,080
Airflow Rate	Nom	m³/min	70
Sound Pressure	Cooling	Nom dBA	53
	Heating	Nom dBA	55
Sound Power	Cooling	Max dBA	67
Dimensions	W x H x D	mm	950 x 834 x 330
Net Weight		kg	72
Refrigerant	Type		R410A
	Charge	kg	3.5
	Additional Charge	g/m	20
	GWP		2087.5
	t-CO ₂ eq		9.2
Operation Range (Outdoor)	Cooling	Min / Max °C DB	-10 ~ 48
	Heating	Min / Max °C WB	-18 ~ 18
Power Supply		Ø / V / Hz	1 / 220-240 / 50
Power Supply Cable		No. x mm ²	3C x 4.0
Transmission Cable	ODU-BD	No. x mm ²	4C x 0.75
	BD-IDU	No. x mm ²	4C x 0.75
Circuit Breaker		A	30
Piping Length Total		m	85
Piping Length per Branch	Max	m	25
Piping Elevation Difference	IDU - ODU	m	15
	IDU - IDU	m	7.5
Piping Connection	Liquid	mm (inch) x No.	Ø6.35 (1/4) x 5
	Gas	mm (inch) x No.	Ø9.52 (3/8) x 5

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.
Note : 1. Capacities are based on the following conditions:

Cooling : - Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB
Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB
Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.

2. * : See page "Combination Table".

3. Due to our policy of innovation some specifications may be changed without notification.

4. At least two indoor units should be connected.



5. Minimum combination capacity rate should be more than 40%.

6. This product contains fluorinated greenhouse gases (R410A).

OUTDOOR UNITS

FM40AH**FM48AH****FM56AH**

LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

**FM41AH****FM49AH****FM57AH**

OUTDOOR		FM40AH.U34	FM48AH.U34	FM56AH.U34
Compressor	Type	R-Scroll	R-Scroll	R-Scroll
Capacity*	Cooling	Min / Nom / Max kW	2.4 / 12.3 / 15.4	2.8 / 14.0 / 17.0
	Heating	Min / Nom / Max kW	2.6 / 13.5 / 16.2	3.2 / 16.0 / 17.3
Low Temperature Capacity	Heating -7°C	Max kW	12.0	13.6
Power Input*	Cooling	Min / Nom / Max kW	1.0 / 2.6 / 4.4	1.0 / 3.3 / 5.4
	Heating	Min / Nom / Max kW	1.5 / 2.9 / 4.8	1.5 / 3.8 / 5.8
EER			4.8	4.2
COP			4.7	4.2
SEER			7.3	7.1
SCOP			4.2	4.2
Pdesign (@-10°C)	kW		11.2	11.2
Season Energy Label	Cooling / Heating (A+++ to E Scale)		A++ / A+	A++ / A+
Season Energy Consumption	Cooling / Heating kWh		590 / 3,733	690 / 3,733
Airflow Rate	Nom m³/min		120	120
Sound Pressure	Cooling Nom dBA		53	53
	Heating Nom dBA		55	55
Sound Power	Cooling Max dBA		66	67
Dimensions	W x H x D mm		950 x 1,380 x 330	950 x 1,380 x 330
Net Weight	kg		88	88
Refrigerant			R410A	R410A
Type			4.2	4.2
Charge	kg		20	20
Additional Charge	g/m		2087.5	2087.5
GWP			9.2	9.2
t-CO ₂ eq			2087.5	2087.5
Operation Range (Outdoor)	Cooling Min / Max °C DB		-10 ~ 48	-10 ~ 48
	Heating Min / Max °C WB		-18 ~ 18	-18 ~ 18
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable	No. x mm ²	3C x 4.0	3C x 4.0	3C x 4.0
Transmission Cable	ODU-BD	No. x mm ²	4C x 1.25	4C x 1.25
	BD-IDU	No. x mm ²	4C x 0.75	4C x 0.75
Circuit Breaker	A		40	40
Piping Length Total	m		125	135
Piping Length per Branch	Max m		15	15
Piping Elevation Difference	IDU - ODU Max m		30	30
	IDU - IDU Max m		15	15
Piping Connection	Liquid mm (inch) x No.	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)
	Gas mm (inch) x No.	Ø19.05 (3/4)	Ø19.05 (3/4)	Ø19.05 (3/4)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Capacities are based on the following conditions:

Cooling : Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB

Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB

Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.

2. * : See page "Combination Table".

3. Due to our policy of innovation some specifications may be changed without notification.

4. At least two indoor units should be connected.

5. Minimum combination capacity rate should be more than 40%.

6. This product contains fluorinated greenhouse gases (R410A)

OUTDOOR		FM41AH.U34	FM49AH.U34	FM57AH.U34
Compressor	Type	R-Scroll	R-Scroll	R-Scroll
Capacity*	Cooling	Min / Nom / Max kW	2.8 / 12.3 / 14.7	2.8 / 14.0 / 17.0
	Heating	Min / Nom / Max kW	3.2 / 13.5 / 15.2	3.2 / 16.0 / 17.3
Low Temperature Capacity	Heating -7°C	Max kW	12.0	13.6
Power Input*	Cooling	Min / Nom / Max kW	1.0 / 2.6 / 4.4	1.0 / 3.3 / 5.4
	Heating	Min / Nom / Max kW	1.5 / 2.9 / 4.8	1.5 / 3.8 / 5.8
EER			4.8	4.2
COP			4.7	4.2
SEER			7.3	7.1
SCOP			4.2	4.2
Pdesign (@-10°C)	kW		11.2	11.2
Season Energy Label	Cooling / Heating (A+++ to E Scale)		A++ / A+	A++ / A+
Season Energy Consumption	Cooling / Heating kWh		590 / 3,733	690 / 3,733
Airflow Rate	Nom m³/min		120	120
Sound Pressure	Cooling Nom dBA		53	53
	Heating Nom dBA		55	55
Sound Power	Cooling Max dBA		66	67
Dimensions	W x H x D mm		950 x 1,380 x 330	950 x 1,380 x 330
Net Weight	kg		88	88
Refrigerant			R410A	R410A
Type			4.2	4.2
Charge	kg		20	20
Additional Charge	g/m		2087.5	2087.5
GWP			9.2	9.2
t-CO ₂ eq			2087.5	2087.5
Operation Range (Outdoor)	Cooling Min / Max °C DB		-10 ~ 48	-10 ~ 48
	Heating Min / Max °C WB		-18 ~ 18	-18 ~ 18
Power Supply	Ø / V / Hz	3 / 380-415 / 50	3 / 380-415 / 50	3 / 380-415 / 50
Power Supply Cable	No. x mm ²	5C x 2.5	5C x 2.5	5C x 2.5
Transmission Cable	ODU-BD	No. x mm ²	4C x 1.25	4C x 1.25
	BD-IDU	No. x mm ²	4C x 0.75	4C x 0.75
Circuit Breaker	A		20	20
Piping Length Total	m		125	135
Piping Length per Branch	Max m		15	15
Piping Elevation Difference	IDU - ODU Max m		30	30
	IDU - IDU Max m		15	15
Piping Connection	Liquid mm (inch) x No.	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)
	Gas mm (inch) x No.	Ø19.05 (3/4)	Ø19.05 (3/4)	Ø19.05 (3/4)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Capacities are based on the following conditions:

Cooling : Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB

Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB

Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.

2. * : See page "Combination Table".

3. Due to our policy of innovation some specifications may be changed without notification.

4. At least two indoor units should be connected.

5. Minimum combination capacity rate should be more than 40%.


6. This product contains fluorinated greenhouse gases (R410A)

R410A MULTI SPLIT


CEILING & FLOOR CONVERTIBLE

Flexible Installation

The ceiling and floor models can be installed either on the ceiling or on the floor. This saves space when installed in the shops or offices.




* Ceiling & Floor : CV09 NE2 / CV12 NE2




Airflow Direction Control

Vertical airflow direction can be adjusted using remote controller, and horizontal airflow direction can be adjusted manually.


Horizontal




Vertical



Cooling



Heating



CAPACITY (KW)	2.6	3.5	5.3	7.0
Ceiling & Floor Convertible unit	CV09.NE2	CV12.NE2	-	-

Ceiling & Floor Convertible unit

INDOOR	CV09.NE2	CV12.NE2
Capacity	Cooling / Heating Nom kW	2.6 / 2.9
Power Input	Nom W	30
Running Current	Nom A	0.4
Power Supply	Ø / V / Hz	1 / 220-240 / 50
Air Flow Rate	H / M / L m³/min	7.6 / 6.9 / 6.2
Sound Pressure	Cooling H / M / L dBA	38 / 35 / 32
Sound Power	Cooling Max dBA	52
Dehumidification Rate	I/h	1.2
Dimensions	Body W x H x D mm	900 x 490 x 200
Net Weight	Body kg	13.7
Piping Connection	Liquid mm (inch)	Ø6.35 (1/4)
	Gas mm (inch)	Ø9.52 (3/8)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Capacities are based on the following conditions :

Cooling : - Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB
Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB

Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero

2. Definition of Power Input Nominal conditions - Performance tested under EN14511

3. Due to our policy of innovation some specifications may be changed without notification

4. This product contains fluorinated greenhouse gases (R410A)


* CV09, CV12, CV18, CV24 are compatible between SCAC and MULTI.

R410A MULTI SPLIT

CONSOLE


Optimised Air Flow for Cooling & Heating

During the cooling operation, the vane adjusts upwards to direct the air flow towards the ceiling.
When heating, the vane directs the warm air downwards to balance the room temperature especially for floor.



Quick Floor Heating

Console air conditioners offer a fast and powerful performance. Using the floor heating mode, console air conditioners provide faster floor heating and help to reach the desired temperature quickly.



(Test Condition :Target Temp 23°C, Indoor Room : 13°C~, Outdoor Room : 7°C)

5-Step Vane Control

There are 5 different stages to control air flow direction.



	CAPACITY (kW)	2.6	3.5	5.3
Console		CQ09.NAO	CQ12.NAO	CQ18.NAO

Console

	INDOOR	CQ09.NAO
Capacity	Cooling / Heating Nom kW	2.6 / 2.9
Power Input	Nom W	20
Running Current	Nom A	0.6
Power Supply	Ø / V / Hz	1 / 220-240 / 50
Air Flow Rate	H / M / L m³/min	8.5 / 6.7 / 5.0
Sound Pressure	Cooling H / M / L dBA	38 / 32 / 27
Sound Power	Cooling Max dBA	53
Dehumidification Rate	I/h	1.2
Dimensions	Body W x H x D mm	700 x 600 x 210
Net Weight	Body kg	14.0
Piping Connection	Liquid mm (inch)	Ø6.35 (1/4)
	Gas mm (inch)	Ø9.52 (3/8)

* CQ09, CQ12, CQ18 are compatible between SCAC and MULTI.

	INDOOR	CQ12.NAO	CQ18.NAO
Capacity	Cooling / Heating Nom kW	3.5 / 3.9	5.3 / 5.8
Power Input	Nom W	20	40
Running Current	Nom A	0.6	0.7
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50
Air Flow Rate	H / M / L m³/min	9.0 / 6.9 / 5.2	10.1 / 8.6 / 7.2
Sound Pressure	Cooling H / M / L dBA	39 / 32 / 27	44 / 39 / 35
Sound Power	Cooling Max dBA	56	60
Dehumidification Rate	I/h	1.4	2.3
Dimensions	Body W x H x D mm	700 x 600 x 210	700 x 600 x 210
Net Weight	Body kg	14.0	14.0
Piping Connection	Liquid mm (inch)	Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas mm (inch)	Ø9.52 (3/8)	Ø12.7 (1/2)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Capacities are based on the following conditions :

Cooling :- Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB
Heating :- Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB

Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero

2. Definition of Power Input Nominal conditions - Performance tested under EN14511

3. Due to our policy of innovation some specifications may be changed without notification

4. This product contains fluorinated greenhouse gases (R410A)

MULTI SPLIT ACCESSORIES

LG Wi-Fi MODEM

Control LG air conditioners via using the internet devices as Android or iOS bases smartphones

PWFMD200

Features

- Access LG air conditioner anytime and from anywhere with Wi-Fi equipped device
- LG's exclusive Home Appliances control app(SmartThinQ) is available
- Simple operation for various functions
 - On/Off
 - Fan Speed
 - Energy Monitoring¹⁾
 - Operation Mode
 - Vane Control²⁾
 - Filter Management
 - Current/Set Temperature
 - Reservation (Sleep, Weekly On/Off)
 - Error check

MODEL NAME	PWFMD200
Size (W x H x D, mm)	48 x 68 x 14
Interfaceable Products	Multi Indoor unit ³⁾
Connection Type	Indoor unit 1:1
Communication Frequency	2.4 GHz
Wireless Standards	IEEE 802.11b/g/n
Mobile Application	LG Smart ThinQ (Android v4.1(Jellybean) or higher, iPhone iOS 9.0 or higher)
Optional Extension Cable	PWYREW000 (10m extension)

* Functionality may be different according to each IDU model


* User interface of application shall be revised for its design and contents improvement

* Application is optimized for smartphone use, so it may not be well functioning with tablet devices


1) LG Centralized controller and PDI installation is required for this function

2) Vane Control may not be possible according to the type of Indoor unit

3) For the compatibility with Indoor unit, please contact regional office



Overview



* Search "LG Smart ThinQ" on Google market or Appstore then download the app.
* Internet service with Wi-Fi connection has to be available

MULTI SPLIT ACCESSORIES

ACCESSORIES

Standard Wired Remote Controller

Standard III



PREMTB100

Standard II



PREMTB10

PREMTB001



PREMTB01

Model Name

PREMTB100

PREMTB001

PREMTB01

On/Off, Fan Speed Control, Temperature Setting

Cooling / Heating / Auto / Dehumidification / Fan

*

*

Simple / Sleep / On, Off / Weekly / Holiday

*

*

*

*

*

*

*

*

*

*

*

* Refer to each model PDB for applicable models.

Remote Controller



PQWRHQ0FDB

PI 485



PMNFP14A1

Power : Single phase AC 220V 50/60Hz

Max. no of the indoor units that can be connected: 64 UNITS

Model applied : RAC / Multi / Single / Therma V

* Refer to each product PDB for applicable models

Dry Contact



PDRYCB000



PDRYCB400



* Refer to each product PDB for applicable models

MODEL

PDRYCB000

PDRYCB400

PDRYCB300

PDRYCB500

Contact Point	1 Control Point	2 Control Point	8 Control Point	Modbus RTU
Power Input	AC 220V from outside power source	DC 5V & 12V from indoor unit PCB	DC 5V & 12V from indoor unit PCB	DC 5V & 12V from indoor unit PDB
Voltage / Non Voltage Input				*
On / Off Control	*	*	*	*
Lock / Unlock	*	*	*	*
Fan Speed Setting				*
Thermo Off	*		*	*
Energy Saving	*			*
Temperature Setting	*		*	*
Error Monitoring	*	*	*	*
Operation Monitoring	*	*	*	*

MULTI SPLIT ACCESSORIES

ACCESSORIES

Distributor Box

PMBD3620, PMBD3630, PMBD3640


Easy installation using the range of Distributor Boxes.

For	2 Indoors	3 Indoors	4 Indoors
Distributor			
	PMBD3620	PMBD3630	PMBD3640

Various distributors can make much easier installation for any sites

Features

- Distribution of refrigerant to various indoor units.
- 3 models (2, 3, 4 Indoor Units)
- EEV included
- Controlling PCB inside the unit
- Internally insulated (Prevents any chances of drainage)
- Flare joints for easy and clean installation
- Compact design (Low height)
- Flexible installation



Specification

	PMBD3620	PMBD3630	PMBD3640	
Connectable Indoor Units	Number of Indoor Units	1 ~ 2	1 ~ 3	1 ~ 4
Capacity	5k / 7k / 9k / 12k / 18k / 24k	5k / 7k / 9k / 12k / 18k / 24k	5k / 7k / 9k / 12k / 18k / 24k	5k / 7k / 9k / 12k / 18k / 24k
Power Source	Ø / V / Hz	1 / 220~240 / 50	1 / 200~240 / 50	1 / 200~240 / 50
Power Consumption	W	10	10	10
Running Current	A	0.05	0.05	0.05
Dimensions	W x H x D mm (inch)	302 × 143 × 252 (11.9 × 5.6 × 9.9)	302 × 143 × 252 (11.9 × 5.6 × 9.9)	302 × 143 × 252 (11.9 × 5.6 × 9.9)
Net Weight	kg/lb	4.8 / 10.6	4.9 / 10.8	5 / 11
Piping Connection (To Outdoor Unit)	Liquid mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52(3/8)
	Gas mm (inch)	Ø19.05 (3/4)	Ø19.05 (3/4)	Ø19.05(3/4)
Piping Connection (To Indoor Unit)	Liquid mm (inch)	Ø6.35 (1/4) × 2EA	Ø6.35 (1/4) × 3EA	Ø6.35 (1/4) × 4EA
	Gas mm (inch)	Ø9.52 (3/8) × 2EA	Ø9.52 (3/8) × 3EA	Ø9.52 (3/8) × 4EA
Hanger (Bracket)	EA	4	4	4
Accessories	Screw EA	8	8	8
	Manual EA	1	1	1

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. The piping connection must be suit the piping sizes of the indoor unit which will be connected. (If need, use the connector which is included in the indoor unit)

2. The BD should be installed inside the building.

Y Branch and Branch Kit


PMBL5620 (2 units) / PMBL1203F0 (3 units)






Features

- Y Branch and Branch kit make Multi FDX installation much easier.
- Y Branch and Branch kit for both gas and liquid are provided.
- Insulation material is also provided for covering the branches.

Application



Accessory Model Name

MODEL NAME	NO. OF BRANCH DISTRIBUTION UNITS	APPLICABLE MODEL	SPECIFICATION
			GAS LIQUID
PMBL5620	2 Units	10, 30	 
PMBL1203F0	3 Units	10, 30	 

(Unit : mm)

COMMERCIAL

SINGLE SPLIT



SINGLE SPLIT

LINE-UP**STANDARD INVERTER**

kBtu/h	kW	STANDARD INVERTER (R32)				STANDARD INVERTER (R410A)				
		Ceiling Mounted Cassette	Ceiling Concealed Duct	Ceiling & Floor / Ceiling Suspended	ODU	Ceiling Concealed Duct (High Static)	Ceiling & Floor / Ceiling Suspended	Console / Wall Mounted / Floor Standing	ODU	
					1Ø	3Ø			1Ø	3Ø
9	2.5				CL09R.N20		UU09WR.ULO			CV09.NE2
		CT09R.NR0								CQ09.NAO
										UU09W.ULO
12	3.5				CL12R.N20		UU12WR.ULO			CV12.NE2
		CT12R.NR0								CQ12.NAO
										UU12W.ULO
18	5.0				CL18R.N20		UV18R.N10			UU18WR.U20
		CT18R.NQ0	CM18R.N10	CL18R.N20	UV18R.N10	UU18WR.U20				CQ18.NAO
										UU18W.UE4
24	7.1				CL24R.N30		UV24R.N10			UU24WR.U40
		CT24R.NPO	CM24R.N10	CL24R.N30	UV24R.N10	UU24WR.U40				
30	8.0				UV30R.N10*		UU30WR.U40*			UU30.NV2
		UT30R.NPO*	UM30R.N10*							UU30W.U44
36	10.0				UV36R.N20		UU36WR.U30			UU37WR.U30
		UT36R.NMO	UM36R.N20*							UU36.NV3
										UU36W.U02
42	12.5				UV42R.N20		UU42WR.U30			UU43WR.U30
		UT42R.NMO	UM42R.N20							
48	14.0				UV48R.N20		UU48WR.U30			UU49WR.U30
		UT48R.NMO	UM48R.N30							UP48.NT2
60	15.0				UV60R.N20		UU60WR.U30			UU61WR.U30
		UT60R.NMO	UM60R.N30							
70	20.0									UB70.N94
										UU70W.U34
85	25.0									UB85.N94
										UU85W.U74

* Available from April 2019.

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

SINGLE SPLIT

LINE-UP**COMPACT INVERTER**

kBtu/h	kW	Ceiling Mounted Cassette	Ceiling Concealed Duct		ODU
			Mid / High Static	Low Static	
18	5.0				UU18WCR.ULO
24	7.1				UU24WCR.U20
30	8.0				UU30WCR.U20
36	10.0				UU36WCR.U40*

SINGLE SPLIT



FEATURE OVERVIEW

Category	Standard inverter (R32)									
kBtu/h	9	12	18	24	30	36	42	48	60	
kW	2.5	3.5	5.0	7.1	8.0	10.0	12.5	14.0	15.0	
Energy Efficiency	New Type Scroll Compressor						●	●	●	●
	BLDC Comp. & Fan Motor	●	●	●	●	●	●	●	●	●
	Eurovent Certi.	●	●	●	●	●	●	●	●	●
	Variable Voltage Control		●	●	●	●	●	●	●	●
	Wide Louver Fin	●	●	●	●	●	●	●	●	●
	Optimised Heat Exchanger Path		●	●	●	●	●	●	●	●
	Power Saving Start up	●	●	●	●	●	●	●	●	●
	Quick Operation Response	●	●	●	●	●	●	●	●	●
	Peak Current Control		●	●	●	●	●	●	●	●
	Mode Lock	●**	●**	●	●	●	●	●	●	●
Durability	Standby Mode	●	●	●	●	●	●	●	●	●
	Ocean black fin heat exchanger	●	●	●	●	●	●	●	●	●
	Forced Cooling Operation		●	●	●	●	●	●	●	●
	Night Silent Operation		●	●	●	●	●	●	●	●
	Outdoor Dry Contact					●	●	●	●	●
Smart	LG MV	●	●	●	●	●	●	●	●	●
	Weekly Program*	●	●	●	●	●	●	●	●	●
	PI-485 Connection		●	●	●	●	●	●	●	●
	Wi-Fi Ready***	●	●	●	●	●	●	●	●	●
AHU Solution	Return Air Control		●	●	●	●	●	●	●	●
	0-10V Supply Air Control		●	●	●	●	●	●	●	●

* Weekly program is available with wired remote controller

** With controller PREMTB001 / PREMTBB01 / PREMTB100 / PREMTBB10

*** Available with LG Wi-Fi modem(PWFMDD200) and it is applicable to the indoor unit

Category	COMPACT (R32)					STANDARD INVERTER (R410A)	
kBtu/h	18	24	30	36	70	85	
kW	5.0	7.1	8.0	10.0	20.0	25.0	
Energy Efficiency	New Type Scroll Compressor						
	BLDC Comp. & Fan Motor	●	●	●	●	●	
	Eurovent Certi.	●	●	●	●	●	
	Variable Voltage Control					●	
	Wide Louver Fin	●	●	●	●	●	
	Optimised Heat Exchanger Path	●	●	●	●	●	
	Power Saving Start up	●	●	●	●	●	
	Quick Operation Response	●	●	●	●	●	
	Peak Current Control					●	
	Mode Lock	●	●	●	●	●	
Durability	Standby Mode	●	●	●	●	●	
	Ocean black fin heat exchanger	●	●	●	●	●	
	Forced Cooling Operation					●	
	Night Silent Operation					●	
	Outdoor Dry Contact					●	
Smart	LG MV	●	●	●	●	●	
	Weekly Program*	●**	●**	●	●	●	
	PI-485 Connection					●	
	Wi-Fi Ready***	●	●	●			
AHU Solution	Return Air Control		●	●	●	●	
	0-10V Supply Air Control		●		●	●	

* Weekly program is available with wired remote controller

** With controller PREMTB001 / PREMTBB01

REVOLUTIONARY SCROLL COMPRESSOR

R1 Compressor



* LG Internal test result, Based on single split 10 kW Cassette
** LG Internal test result, Based on conventional compressor (Rotary type GPT442M)


ENERGY EFFICIENCY

Revolutionary Scroll Compressor

Revolutionary Scroll Compressor is applied for high-efficiency and reliability. This type of compressor is more advanced compared to the conventional one, especially tilting motion of scroll has been improved. Further, the operation range is improved compared to the conventional type.

- Scroll compressor with simple structure
- High efficiency (low load at low speed / total efficiency)
- Low noise (high speed possible)
- Improved Tilting Motion of scroll
- 20% weight reduction (vs. conventional compressor)


※ Applied models : UU36WR, UU37WR, UU42WR, UU43WR, UU48WR, UU49WR, UU60WR, UU61WR



• Seasonal energy efficiency


SEER 20%, SCOP 13% improvement (vs. rotary)

* LG Internal test result, Based on single split 10 kW CST



• Wide Operation Range


- Optimized for various cooling & heat load operation
- World best compressor speed (up to 150 Hz)
- Optimized for even low load operation (down to 10 Hz)
(Efficiency increases / Improved comfort)




ENERGY EFFICIENCY

Power Saving Start Up

LG commercial air conditioners will automatically alter the temperature of discharge air by controlling their refrigerant temperature based on the difference between the indoor temperature and the target indoor temperature. During cooling operation, evaporating temperature will increase if the temperature difference reduces. This leads to extremely comfortable indoor air whilst minimizing energy consumption.




Quick Operating Response




Peak Current Control

The peak current control function prevents the air conditioner from running at the maximum level while maintaining current system settings, in order to reduce energy consumption. This function helps minimize energy costs during the peak periods of energy use when the energy billing is much higher.




Mode Lock

Set the operation mode to either cooling-only or heating-only; either by adjusting the wired remote controller or setting the DIP switch to avoid combined use of cooling and heating. (Some models need wired remote controller for mode lock function according to feature overview table)



Standby Mode

Standard Inverter can minimise power consumption by turning power off on the PCB except for the MICOM which receives signals.




※ The applicable products can be found in the 'Feature Overview'

SINGLE SPLIT KEY FEATURES

DURABILITY

Ocean Black Fin

LG's exclusive "Ocean Black Fin" heat exchanger is designed for improved corrosion resistance.



• Certified protection



- Test Method B of ISO21207, 6.2 & Annex A
- Test condition: Salt contaminated condition
+ severe industrial/traffic environment(NO_2/SO_2)



* Based on 1,500 UL test hours

SINGLE SPLIT KEY FEATURES

FAST COOLING & HEATING

Forced Cooling Operation

This function allows the refrigerant to be recharged or pumped down, regardless of the indoor temperature. Note that this function can be used when indoor units are being moved or repaired.





※ The applicable products can be found in the 'Feature Overview'

SINGLE SPLIT KEY FEATURES

COMFORT**Night Silent Operation**

This function enables noise reduction during night time by simply setting the dip switch on the PCB of the outdoor unit.



* This function is only available for Cooling Mode.


* If you want to stop the Night Quiet Mode, Change the Dip Switch.

* LG Internal test result, based on UU37WR


SINGLE SPLIT KEY FEATURES

SMART**Outdoor Dry Contact**

Air conditioners can be turned ON/OFF at the same time using the ON/OFF dry contact function that outdoor units have. (Models capacity over 10 kW).

**LG MV (Monitoring View)**

LG MV helps engineers to inspect and monitor air conditioning units conveniently. Instructions are provided with the product type. (SINGLE Split & MULTI Split)



LG MV displays cycle info represented by diagrams . It assists the user to check for data that is concentrated on a graph. A technician can easily obtain info about the error status by looking up the Error Indicator table. (Troubleshooting guide)

• Error Indicator


ERROR CODE	CONTENTS
01	Air temperature sensor of indoor unit
02	Inlet pipe temperature sensor of indoor unit
03	Communication error : Wired Remote Controller ↔ Indoor Unit
...	

SMART

Weekly Program


You can allot 2 reservations for one day, and up to 14 reservations for a week.

Program 1



Program 2

Program 3




Program 4



Wi-fi

Control your air conditioners via using the smart internet devices as Android or iOS based smartphones. Wi-Fi modem (PWFMD200) is required by option.


- Access your air conditioner anytime and from anywhere



- Simple operation for various functions


- ON/OFF
- Mode Selection
- Current temperature
- Set temperature
- Vane Control
- Reservation
- Energy Monitoring
- Filter Management

※ Search "LG Smart ThinQ" on Google market or Appstore then download the app.




PERFORMANCE

Wide Operation Range



Stable Operation


High and stable cooling performance at low temperatures.



QUIET OPERATION

Advanced Grille & Fan

The improved grille shape design on the outdoor unit helps to distribute air more efficiently which improves heat exchange and reduces the noise level. The new axial Fan has a thick front edge and a smooth rear edge, thus providing not only high efficiency, low noise, wide fan, but also improving the air flow rate.



CEILING MOUNTED CASSETTE



SINGLE SPLIT KEY FEATURES

CEILING MOUNTED CASSETTE

COMMERCIAL

Compact Size


The indoor unit with slim and compact dimensions allows successful installation by easily accommodating it in limited space.



Standard Inverter	Height
7.1 ~ 8.0kW	204mm
10.0kW	246mm
12.5 ~ 15kW	288mm


620 Panel – Compact and Stylish Design

- New 4 way cassette panel adapted unibody shape and matching with into the ceiling
- Panel size is fit into the ceiling tile




High Ceiling Mode

High ceiling mode provides powerful cooling and heating up to 4.2m in height, from ceiling to floor.




CEILING MOUNTED CASSETTE

Human detection sensor & humidity sensor



- Human detection sensor (PTVSMA0)
- Apply human detection sensor
- Apply vision sensor
- Saving energy
- Supply comfortable air flow
- The sensor is an optional accessory that can only be applied on PT-MCHW0



- Comfortable and Power Saving Control based on Humidity
- Apply humidity sensor
- Saving energy
- To apply humidity sensor, new remote controller, PREMTB100 or PREMTBB10 is needed

• Detection


Motion sensors detect the activity of people per 20seconds



20seconds



• Detection range



Height 3.2 (15 x 8m)





Height 3.5 (16 x 10m)



A sensor is installed 90°rotation
12 x 6m → 6 x 12m detecting

950/620 Panel – Wide Jet Air Flow

Improved vanes reduce the curved area and provide even distribution.




Independent Vane Operation

The independent vane operation feature uses separate motors, making it possible to control all four vanes independently.

All Vane Operation



Independent Vane Control




SINGLE SPLIT KEY FEATURES

CEILING MOUNTED CASSETTE


Convenient Panel Installation

The detachable corner design makes it convenient to adjust the hanger during installation and to check for leakages in the drain connection pipe.



Auto Elevation Grille

Easy filter cleaning by using the elevation grill.



* Operating with wired remote controller PREMTB100, PREMTB001 and wireless remote controller included in PTEGM0.

* Applied to cassette panel PT-UMC1

SINGLE SPLIT SPECIFICATION

CEILING MOUNTED CASSETTE



STANDARD INVERTER (R32)

CT09R
CT12R
CT18R
CT24R
UT30R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
: www.eurovent-certification.com

UU09WR
UU12WR

UU18WR

UU24WR
UU30WR



	INDOOR	CT09R.NRO	CT12R.NRO	CT18R.NQ0	CT24R.NPO	UT30R.NPO*
Capacity	Cooling Min / Nom / Max kW Heating Min / Nom / Max kW	1.0 / 2.5 / 2.8 1.2 / 3.2 / 3.4	1.4 / 3.4 / 3.9 1.6 / 4.0 / 4.6	2.0 / 5.0 / 5.7 2.2 / 5.8 / 6.8	2.84 / 6.8 / 7.8 3.2 / 8.0 / 8.8	3.2 / 8.0 / 8.8 3.6 / 9.0 / 9.9
Low Temperature Capacity	Heating -7°C Max kW	2.7	3.6	4.9	7.2	8.1
Power Input (Set)	Cooling Nom kW Heating Nom kW	0.63 0.75	0.97 1.12	1.56 1.66	1.94 2.00	2.39 2.65
Power Input (Indoor)	Min / Nom / Max W	10 / 20 / 20	10 / 20 / 20	10 / 30 / 40	20 / 50 / 60	30 / 70 / 80
Running Current	Cooling / Heating Nom A	2.7 / 3.5	4.3 / 5.0	7.1 / 7.5	8.6 / 8.8	10.6 / 11.8
Power Supply		Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER			4.00	3.51	3.21	3.51
COP			4.00	3.58	3.49	4.00
SEER			6.77	6.58	6.25	7.70
SCOP			4.36	4.40	4.25	4.60
Pdesign (@-10°C)						
Seasonal Energy Label	Cooling / Heating kW					
Annual Energy Consumption	Cooling / Heating kWh	129 / 963	181 / 955	280 / 1,351	309 / 1,765	400 / 2,100
Piping Connection	Liquid mm (inch) Gas mm (inch) Drain O.D. / I.D. mm	Ø 6.35 (1/4) Ø 9.52 (3/8) 32 / 25	Ø 6.35 (1/4) Ø 9.52 (3/8) 32 / 25	Ø 6.35 (1/4) Ø 12.7 (1/2) 32 / 25	Ø 9.52 (3/8) Ø 15.88 (5/8) 32 / 25	Ø 9.52 (3/8) Ø 15.88 (5/8) 32.0 / 25.0
Air Flow Rate	High / Medium / Low m³/min	8.5 / 7.0 / 6.0	9.5 / 8.0 / 7.0	13.0 / 12.0 / 11.0	17.0 / 15.0 / 13.0	19.0 / 17.0 / 15.0
Sound Pressure	Cooling High / Medium / Low dBA	36 / 33 / 30	38 / 35 / 32	41 / 39 / 36	38 / 36 / 34	40 / 37 / 35
Sound Power	Cooling Max dBA	52	52	57	57	58
Dehumidification Rate	I/h	0.9	1.4	2.0	2.7	2.5
Dimensions	Body W x H x D mm	570 x 214 x 570	570 x 214 x 570	570 x 256 x 570	840 x 204 x 840	840 x 204 x 840
Net Weight	Body kg	14.0	14.0	14.3	20.5	20.5
Model	PT-QCHW0	PT-QCHW0	PT-QCHW0	PT-MCHW0	PT-MCHW0	
Decoration Panel	Color Morning Fog	620 x 20 x 620	620 x 20 x 620	620 x 20 x 620	950 x 35 x 950	950 x 35 x 950
	Dimensions W x H x D mm	3.0	3.0	3.0	6.3	6.3
	Weight kg					

	OUTDOOR	UU09WR.ULO	UU12WR.ULO	UU18WR.U20	UU24WR.U40	UU30WR.U40*
Compressor	Type	Twin Rotary				
Airflow Rate	Nom m³/min	32	32	50	58	58
Sound Pressure	Cooling Nom dBA	47	49	47	48	48
Sound Power	Heating Nom dBA	50	52	52	52	52
Dimensions	Cooling Max dBA	65	65	63	67	68
Net Weight	W x H x D mm	770 x 545 x 288	770 x 545 x 288	870 x 650 x 330	950 x 834 x 330	950 x 834 x 330
Refrigerant	kg	33.8	33.8	44.8	56.1	58.0
	Type R32	R32	R32	R32	R32	R32
	Charge g	900	900	1,100	1,600	1,900
	Additional Charge (after 7.5m) g/m	20	20	20	35	35
	GWP 675	675	675	675	675	675
	TCO _{eq} 0.61	0.61	0.74	1.08	1.28	
Operation Range (Outdoor)	Cooling Min / Max °C DB	-15 / 48	-15 / 48	-15 / 48	-15 / 48	-15 / 48
	Heating Min / Max °C WB	-18 / 18	-18 / 18	-18 / 18	-18 / 18	-18 / 18
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable	No. x mm² 3C x 2.5	3C x 2.5	3C x 2.5	3C x 2.5	3C x 2.5	3C x 2.5
Transmission Cable	No. x mm² 4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker	A 15	15	20	25	25	25
Piping Length Total	Min / Max m	5 / 20	5 / 20	5 / 30	5 / 50	5 / 50
Piping Elevation Difference	IDU - ODU Max m	15	15	30	30	30
Piping Connection	Liquid mm (inch) Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas mm (inch) Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)

* Available from April 2019.

** For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notice.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R32)

CEILING MOUNTED CASSETTE



STANDARD INVERTER (R32)

UT36R
UT42R
UT48R
UT60R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU36WR / UU42WR
UU48WR / UU60WR



STANDARD INVERTER (R32)

UT36R
UT42R
UT48R
UT60R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU37WR / UU43WR
UU49WR / UU61WR



	INDOOR			UT36R.NMO	UT42R.NMO	UT48R.NMO	UT60R.NMO
Capacity	Cooling	Min / Nom / Max	kW	4.5 / 9.5 / 13.0	5.0 / 12.0 / 14.5	5.5 / 13.4 / 16.0	5.9 / 14.6 / 16.3
	Heating	Min / Nom / Max	kW	5.0 / 10.8 / 13.7	5.5 / 13.5 / 16.5	6.1 / 15.5 / 18.0	6.8 / 16.9 / 18.7
Low Temperature Capacity	Heating -7°C	Max	kW	9.8	12.5	14.3	15.2
Power Input (Set)	Cooling	Nom	kW	2.47	3.50	4.35	5.38
	Heating	Nom	kW	2.80	3.75	4.82	5.60
Power Input (Indoor)	Min / Nom / Max	W		40 / 190 / 210	40 / 190 / 210	40 / 190 / 210	40 / 190 / 210
Running Current	Cooling / Heating	Nom	A	10.7 / 12.2	15.2 / 16.3	18.9 / 21.0	23.4 / 24.3
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER				3.85	3.43	3.08	2.71
COP				3.86	3.60	3.22	3.02
SEER				6.50	6.10	5.87	5.57
SCOP				4.30	4.10	4.04	3.92
Pdesign (@-10°C)		kW		8.05	8.05	9.30	9.30
Seasonal Energy Label	Cooling / Heating			A++ / A+	A++ / A+	-	-
Annual Energy Consumption	Cooling / Heating		kWh	512 / 2,605	689 / 2,732	1,370 / 3,223	1,573 / 3,321
Piping Connection	Liquid		mm (inch)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas		mm (inch)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)
	Drain	O.D. / I.D.	mm	32 / 25	32 / 25	32 / 25	32 / 25
Air Flow Rate	High / Medium / Low	m³/min		30.0 / 25.0 / 20.0	33.0 / 28.0 / 22.0	33.0 / 28.0 / 22.0	33.0 / 28.0 / 22.0
Sound Pressure	Cooling	High / Medium / Low	dBA	46 / 43 / 40	47 / 44 / 41	47 / 44 / 41	47 / 44 / 41
Sound Power	Cooling	Max	dBA	62	64	64	66
Dehumidification Rate		l/h		2.7	4.2	5.2	6.2
Dimensions	Body	W x H x D	mm	840 x 288 x 840			
Net Weight	Body		kg	24.6	24.6	24.6	24.6
Model				PT-MCHW0	PT-MCHW0	PT-MCHW0	PT-MCHW0
Color				Morning Fog	Morning Fog	Morning Fog	Morning Fog
Decoration Panel	Dimensions	W x H x D	mm	950 x 35 x 950			
	Weight		kg	6.3	6.3	6.3	6.3

	OUTDOOR			UU36WR.U30	UU42WR.U30	UU48WR.U30	UU60WR.U30
Compressor	Type			R-Scroll	R-Scroll	R-Scroll	R-Scroll
Airflow Rate	Nom	m³/min		110	110	110	110
Sound Pressure	Cooling	Nom	dBA	52	52	52	52
	Heating	Nom	dBA	54	54	54	54
Sound Power	Cooling	Max	dBA	66	67	68	68
Dimensions	W x H x D		mm	950 x 1,380 x 330			
Net Weight		kg		87.5	87.5	87.5	87.5
	Type			R32	R32	R32	R32
Refrigerant	Charge	g		3,000	3,000	3,000	3,000
	Additional Charge (after 7.5m)	g/m		40	40	40	40
	GWP			675	675	675	675
	TCO _{eq}			2.03	2.03	2.03	2.03
Operation Range (Outdoor)	Cooling	Min / Max	°C DB	-15 / 48	-15 / 48	-15 / 48	-15 / 48
	Heating	Min / Max	°C WB	-27 / 18	-27 / 18	-27 / 18	-27 / 18
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable		No. x mm²		3C x 6.0	3C x 6.0	3C x 6.0	3C x 6.0
Transmission Cable		No. x mm²		4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker		A		40	40	40	40
Piping Length Total		Min / Max	m	5 / 85	5 / 85	5 / 85	5 / 85
Piping Elevation Difference	IDU - ODU	Max	m	30	30	30	30
Piping Connection	Liquid	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas	mm (inch)		Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R32)

	INDOOR			UT36R.NMO	UT42R.NMO	UT48R.NMO	UT60R.NMO
Capacity	Cooling	Min / Nom / Max	kW	4.5 / 9.5 / 13.0	5.0 / 12.0 / 14.5	5.5 / 13.4 / 16.0	5.9 / 14.6 / 16.3
	Heating	Min / Nom / Max	kW	5.0 / 10.8 / 13.7	5.5 / 13.5 / 16.5	6.1 / 15.5 / 18.0	6.8 / 16.9 / 18.7
Low Temperature Capacity	Heating -7°C	Max	kW	9.8	12.5	14.3	15.2
Power Input (Set)	Cooling	Nom	kW	2.47	3.50	4.35	5.38
	Heating	Nom	kW	2.80	3.75	4.82	5.60
Power Input (Indoor)	Min / Nom / Max	W		40 / 190 / 210	40 / 190 / 210	40 / 190 / 210	40 / 190 / 210
Running Current	Cooling / Heating	Nom	A	10.7 / 12.2	15.2 / 16.3	18.9 / 21.0	23.4 / 24.3
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER				3.85	3.43	3.08	2.71
COP				3.86	3.60	3.22	3.02
SEER				6.50	6.18	5.87	5.57
SCOP				4.30	4.17	4.04	3.92
Pdesign (@-10°C)		kW		8.05	8.05	9.30	9.30
Seasonal Energy Label	Cooling / Heating			A++ / A+	A++ / A+	-	-
Annual Energy Consumption	Cooling / Heating		kWh	512 / 2,605	689 / 2,732	1,370 / 3,223	1,573 / 3,321
Piping Connection	Liquid		mm (inch)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas		mm (inch)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)
	Drain	O.D. / I.D.	mm	32 / 25	32 / 25	32 / 25	32 / 25
Air Flow Rate	High / Medium / Low	m³/min		30.0 / 25.0 / 20.0	33.0 / 28.0 / 22.0	33.0 / 28.0 / 22.0	33.0 / 28.0 / 22.0
Sound Pressure	Cooling	High / Medium / Low	dBA	46 / 43 / 40	47 / 44 / 41	47 / 44 / 41	47 / 44 / 41
Sound Power							

CEILING CONCEALED DUCT




SINGLE SPLIT KEY FEATURES

CEILING CONCEALED DUCT

COMMERCIAL



E.S.P. (External Static Pressure) Control

This function easily controls volume of the air by a remote controller. The BLDC motor can control fan speed and air volume regardless of the external static pressure. Additional accessories are not required to control air flow.



High Head Drain Pump


High head drain pump automatically drains water up to a height of 200mm of drain-head height. It provides the perfect solution for draining of water. (Standard Inverter : Accessory (ABDPG) / Low-Static Duct : Included)



CEILING CONCEALED DUCT

Two Thermistors Control

The indoor temperature can be checked using the thermistors in the remote controller as well as from the indoor unit. There may be a significant difference between ceiling and floor air temperature. Two thermistors can optimise indoor air temperature for a more comfortable environment.





Compares temperatures sensed from different positions, and automatically selects the optimum temperature for users

Operation for Multiple Rooms

Using a spiral duct (Embedded or flexible type) and stream chamber, it is possible to operate cooling / heating for several rooms simultaneously. Also, zone control is available with zone controller accessory (ABZCA)


Zone control features

- Controls different zones (up to 4 zones) by external thermostat (AC 24V)
- Maintain proper air volume of each zone
- Auto variation of dampers
- Auto control of fan speed and On / Off operation




Minimized Height

New high static ducts provide ideal solution for installation in limited space.




Wide Operation Range



Easy Service & Maintenance

Users are not required to disassemble the whole panel for maintenance; since panel is divided into 2 components; one for heat exchanger and the other for fan/motor. The user can easily detach and re-attach the filter in the available limited space.




SINGLE SPLIT KEY FEATURES

CEILING CONCEALED DUCT (LOW STATIC PRESSURE)

Quiet Operation

The noise level of low static ducts have been reduced, even though ESP has been increased.

	CL09R N20	CL12R N20	CL18R N20	CL24R N30
Sound Pressure (High / Medium / Low) dB (A)	31 / 28 / 27	31 / 28 / 27	36 / 34 / 31	39 / 35 / 32




Flexible Installation

Standard Inverter low static duct allows the air intake at the rear or bottom under installation condition.


Conventional

Air intake at the only rear



Standard Inverter Low Static Duct

Air intake at the rear or bottom



SINGLE SPLIT SPECIFICATION

CEILING CONCEALED DUCT



COMMERCIAL

STANDARD INVERTER (R32)

HIGH STATIC PRESSURE

- CM18R / CM24R / UM30R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU18WR

UU24WR
UU30WR



	INDOOR	CM18R.N10	CM24R.N10	UM30R.N10*
Capacity	Cooling Min / Nom / Max kW Heating Min / Nom / Max kW	1.8 / 5.0 / 6.0 2.2 / 6.0 / 7.2	2.8 / 6.8 / 7.8 3.2 / 7.5 / 8.3	3.2 / 7.8 / 8.8 3.6 / 9.0 / 9.9
Low Temperature Capacity	Heating -7°C Max kW	5.4	7.2	8.1
Power Input (Set)	Cooling Nom kW Heating Nom kW	1.46 1.60	2.03 2.20	2.31 2.62
Power Input (Indoor)	Min / Max (ESP 2.5mmAq) W Min / Max (ESP 8.0mmAq) W	50 / 80 90 / 160	50 / 90 100 / 180	90 / 150 160 / 240
Running Current	Cooling / Heating Nom A	6.5 / 7.1	9.0 / 9.8	10.1 / 10.7
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER		3.42	3.35	3.37
COP		3.74	3.40	3.44
SEER		6.30	6.81	6.20
SCOP		4.15	4.01	4.00
Pdesign (@-10°C)	kW	4.1	5.4	6.3
Seasonal Energy Label	Cooling / Heating	A++ / A+	A++ / A+	A++ / A+
Annual Energy Consumption	Cooling / Heating kWh	278 / 1,383	350 / 1,890	440 / 2,205
Piping Connection	Liquid mm (inch) Gas mm (inch) Drain O.D. / I.D. mm	Ø 6.35 (1/4) Ø 2.7 (1/2) 32.0 / 25.0	Ø 9.52 (3/8) Ø 15.88 (5/8) 32.0 / 25.0	Ø 9.52 (3/8) Ø 15.88 (5/8) 32.0 / 25.0
Air Flow Rate	High / Medium / Low m³/min	16.5 / 14.5 / 13.0	18.0 / 16.5 / 14.5	22.0 / 20.0 / 18.0
Sound Pressure	Cooling High / Medium / Low dBA Cooling Max dBA	34 / 32 / 30 59	35 / 34 / 32 60	37 / 35 / 34 62
Sound Power		1.5	2.5	2.8
Dehumidification Rate	l/h			
Dimensions	Body W x H x D mm	900 x 270 x 700	900 x 270 x 700	900 x 270 x 700
Net Weight	Body kg	26.5	26.5	25.3
External Static Pressure	Min / Max mmAq (Pa)	2.5 / 15 (25 / 147)	2.5 / 15 (25 / 147)	2.5 / 15 (25 / 147)

	OUTDOOR	UU18WR.U20	UU24WR.U40	UU30WR.U40*
Compressor	Type	Twin Rotary	Twin Rotary	Twin Rotary
Airflow Rate	Nom m³/min	50	58	58
Sound Pressure	Cooling dBA Heating dBA	47 52	48 52	48 52
Sound Power	Cooling Max dBA	63	67	68
Dimensions	W x H x D mm	870 x 650 x 330	950 x 834 x 330	950 x 834 x 330
Net Weight	kg	44.8	56.1	58.0
Refrigerant	Type R32 Charge g	R32 1,100	R32 1,600	R32 1,900
	Additional Charge (after 7.5m) g/m	20	35	35
	GWP 675	675	675	675
	TCO ₂ eq 0.74	0.74	1.08	1.28
Operation Range (Outdoor)	Cooling Min / Max °C DB Heating Min / Max °C WB	-15 / 48 -18 / 18	-15 / 48 -18 / 18	-15 / 48 -18 / 18
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable	No. x mm² 3C x 2.5	3C x 2.5	3C x 2.5	3C x 2.5
Transmission Cable	No. x mm² 4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker	A 20	25	25	25
Piping Length Total	Min / Max m	5 / 30	5 / 50	5 / 50
Piping Elevation Difference	IDU - ODU Max m	30	30	30
Piping Connection	Liquid mm (inch) Gas mm (inch)	Ø 6.35 (1/4) Ø 12.7 (1/2)	Ø 9.52 (3/8) Ø 15.88 (5/8)	Ø 9.52 (3/8) Ø 15.88 (5/8)

* Available from April 2019.

** For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R32)

SINGLE SPLIT SPECIFICATION

CEILING CONCEALED DUCT



STANDARD INVERTER (R32)

HIGH STATIC PRESSURE

- UM36R / UM42R / UM48R / UM60R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU36WR / UU42WR
UU48WR / UU60WR



STANDARD INVERTER (R32)

HIGH STATIC PRESSURE

- UM36R / UM42R / UM48R / UM60R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU37WR / UU43WR
UU49WR / UU61WR



		INDOOR			
		UM36R.N20	UM42R.N20	UM48R.N30	UM60R.N30
Capacity	Cooling	Min / Nom / Max	kW	4.5 / 9.5 / 13.0	5.1 / 12.0 / 14.5
	Heating	Min / Nom / Max	kW	5.0 / 10.8 / 13.7	5.5 / 13.5 / 16.5
Low Temperature Capacity	Heating -7°C	Max	kW	10.0	12.5
Power Input (Set)	Cooling	Nom	kW	2.43	3.45
	Heating	Nom	kW	2.85	3.65
Power Input (Indoor)	Min / Max (ESP 5.0mmAq)	W		120 / 210	140 / 260
	Min / Max (ESP 15.0mmAq)	W		200 / 360	230 / 380
Running Current	Cooling / Heating	Nom	A	10.6 / 12.4	15.0 / 15.9
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50
EER				3.91	3.48
COP				3.79	3.70
SEER				5.62	5.50
SCOP				4.04	4.00
Pdesign (@-10°C)			kW	8.05	8.05
Seasonal Energy Label	Cooling / Heating		A+ / A+	-	-
Annual Energy Consumption	Cooling / Heating		kWh	594 / 2,800	764 / 2,800
	Liquid	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)
Piping Connection	Gas	mm (inch)		Ø 15.88 (5/8)	Ø 15.88 (5/8)
	Drain	O.D. / I.D.	mm	32 / 25	32 / 25
Air Flow Rate	High / Medium / Low	m³/min		32.0 / 28.0 / 24.0	38.0 / 33.0 / 28.0
Sound Pressure	Cooling	High / Medium / Low	dBA	36 / 34 / 33	38 / 36 / 34
Sound Power	Cooling	Max	dBA	60	62
Dehumidification Rate			l/h	2.6	3.6
Dimensions	Body	W x H x D	mm	1,250 x 270 x 700	1,250 x 270 x 700
Net Weight	Body		kg	38.5	38.5
External Static Pressure		Min / Max	mmAq (Pa)	4 / 15 (39 / 147)	5 / 15 (49 / 147)

		OUTDOOR			
		UU36WR.U30	UU42WR.U30	UU48WR.U30	UU60WR.U30
Compressor	Type	R-Scroll	R-Scroll	R-Scroll	R-Scroll
Airflow Rate	Nom	m³/min	110	110	110
Sound Pressure	Cooling	Nom	dBA	52	52
	Heating	Nom	dBA	54	54
Sound Power	Cooling	Max	dBA	66	67
Dimensions	W x H x D	mm	950 x 1,380 x 330	950 x 1,380 x 330	950 x 1,380 x 330
Net Weight		kg	87.5	87.5	87.5
	Type		R32	R32	R32
Refrigerant	Charge	g	3,000	3,000	3,000
	Additional Charge (after 7.5m)	g/m	40	40	40
	GWP		675	675	675
	TCO _{eq}		2.03	2.03	2.03
Operation Range (Outdoor)	Cooling	Min / Max	°C DB	-15 / 48	-15 / 48
	Heating	Min / Max	°C WB	-27 / 18	-27 / 18
Power Supply		Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable		No. x mm²	3C x 6.0	3C x 6.0	3C x 6.0
Transmission Cable		No. x mm²	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker			A	40	40
Piping Length Total		Min / Max	m	5 / 85	5 / 85
Piping Elevation Difference	IDU - ODU	Max	m	30	30
Piping Connection	Liquid	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas	mm (inch)		Ø 15.88 (5/8)	Ø 15.88 (5/8)

		INDOOR			
		UM36R.N20	UM42R.N20	UM48R.N30	UM60R.N30
Capacity	Cooling	Min / Nom / Max	kW	4.5 / 9.5 / 13.0	5.1 / 12.0 / 14.5
	Heating	Min / Nom / Max	kW	5.0 / 10.8 / 13.7	5.5 / 13.5 / 16.5
Low Temperature Capacity	Heating -7°C	Max	kW	10.0	12.5
Power Input (Set)	Cooling	Nom	kW	2.43	3.45
	Heating	Nom	kW	2.85	3.65
Power Input (Indoor)	Min / Max (ESP 5.0mmAq)	W		120 / 210	140 / 260
	Min / Max (ESP 15.0mmAq)	W		200 / 360	230 / 380
Running Current	Cooling / Heating	Nom	A	3.5 / 4.1	5.0 / 5.3
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50
EER				3.91	3.48
COP				3.79	3.70
SEER				5.60	5.50
SCOP				4.00	4.00
Pdesign (@-10°C)			kW	8.05	8.05
Seasonal Energy Label	Cooling / Heating		A+ / A+	A / A+	-
Annual Energy Consumption	Cooling / Heating		kWh	594 / 2,800	764 / 2,800
	Liquid	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)
Piping Connection	Gas	mm (inch)		Ø 15.88 (5/8)	Ø 15.88 (5/8)
	Drain	O.D. / I.D.	mm	32 / 25	32 / 25
Air Flow Rate	High / Medium / Low	m³/min		32.0 / 28.0 / 24.0	38.0 / 33.0 / 28.0
Sound Pressure	Cooling	High / Medium / Low	dBA	36 / 34 / 33	38 / 36 / 34
Sound Power	Cooling	Max	dBA	60	62
Dehumidification Rate			l/h	2.6	3.6
Dimensions	Body	W x H x D	mm	1,250 x 270 x 700	1,250 x 270 x 700
Net Weight	Body		kg	38.5	38.5
External Static Pressure		Min / Max	mmAq (Pa)	4 / 15 (39 / 147)	5 / 15 (49 / 147)

		OUTDOOR			
		UU37WR.U30	UU43WR.U30	UU49WR.U30	UU61WR.U30
Compressor	Type	R-Scroll	R-Scroll	R-Scroll	R-Scroll
Airflow Rate	Nom	m³/min	110	110	110
Sound Pressure	Cooling	Nom	dBA	52	52
	Heating	Nom	dBA	54	54
Sound Power	Cooling	Max	dBA	66	67
Dimensions	W x H x D	mm	950 x 1,380 x 330	950 x 1,380 x 330	950 x 1,380 x 330
Net Weight		kg	87.5	87.5	87.5
	Type		R32	R32	R32
Refrigerant	Charge	g	3,000	3,000	3,000
	Additional Charge (after 7.5m)	g/m	40	40	40
	GWP		675	675	675
	TCO _{eq}		2.03	2.03	2.03
Operation Range (Outdoor)	Cooling	Min / Max	°C DB	-15 / 48	-15 / 48
	Heating	Min / Max	°C WB	-27 / 18	-27 / 18
Power Supply		Ø / V / Hz	3 / 380-415 / 50	3 / 380-415 / 50	3 / 380-415 / 50
Power Supply Cable		No. x mm²	5C x 2.5	5C x 2.5	5C x 2.5
Transmission Cable		No. x mm²	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker			A	20	20
Piping Length Total		Min / Max	m</td		

CEILING CONCEALED DUCT



STANDARD INVERTER (R32)

LOW STATIC PRESSURE

- CL09R / CL12R / CL18R / CL24R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU09WR
UU12WR

UU18WR

UU24WR



		INDOOR		CL09R.N20	CL12R.N20	CL18R.N20	CL24R.N30
Capacity	Cooling	Min / Nom / Max	kW	1.1 / 2.5 / 3.2	1.4 / 3.4 / 3.9	2.0 / 5.0 / 6.0	4.0 / 7.1 / 7.7
	Heating	Min / Nom / Max	kW	1.2 / 3.2 / 3.6	1.6 / 4.0 / 4.7	2.2 / 6.0 / 7.2	2.0 / 7.5 / 8.2
Low Temperature Capacity	Heating -7°C	Max	kW	3.5	4.4	6.7	8.2
Power Input (Set)	Cooling	Nom	kW	0.64	0.99	1.52	2.15
	Heating	Nom	kW	0.74	1.00	1.76	2.06
Power Input (Indoor)	Min / Max (ESP 2.5mmAq)	W		80 / 95	80 / 95	95 / 120	90 / 150
	Min / Max (ESP 5.0mmAq)	W		80 / 100	80 / 100	100 / 140	110 / 160
Running Current	Cooling / Heating	Nom	A	2.8 / 3.2	4.2 / 4.6	6.8 / 7.8	9.5 / 9.1
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER				3.90	3.42	3.30	3.30
COP				4.30	4.00	3.41	3.65
SEER				6.28	6.28	6.30	6.60
SCOP				4.00	4.00	3.95	4.20
Pdesign (@-10°C)			kW	3.0	3.0	4.1	5.4
Seasonal Energy Label	Cooling / Heating			A++ / A+	A++ / A+	A++ / A	A++ / A+
Annual Energy Consumption	Cooling / Heating		kWh	139 / 1,050	189 / 1,050	278 / 1,453	377 / 1,798
Piping Connection	Liquid		mm (inch)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas		mm (inch)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 15.88 (5/8)
	Drain	O.D. / I.D.	mm	32.0 / 25.0	32.0 / 25.0	32.0 / 25.0	32.0 / 25.0
Air Flow Rate	High / Medium / Low	m³/min		10.0 / 8.5 / 7.0	10.0 / 8.5 / 7.0	15.0 / 12.5 / 10.0	20.0 / 16.0 / 12.0
Sound Pressure	Cooling	High / Medium / Low	dBA	31 / 28 / 27	31 / 28 / 27	36 / 34 / 31	39 / 35 / 32
Sound Power	Cooling	Max	dBA	55	55	54	58
Dehumidification Rate			l/h	0.5	1.1	1.6	2.6
Dimensions	Body	W x H x D	mm	900 x 190 x 700	900 x 190 x 700	900 x 190 x 700	1,100 x 190 x 700
Net Weight	Body		kg	24.0	24.0	24.0	27.0
External Static Pressure		Min / Max	mmAq (Pa)	0 / 5 (0 / 49)	0 / 5 (0 / 49)	0 / 5 (0 / 49)	0 / 5 (0 / 49)

		OUTDOOR		UU09WR.ULO	UU12WR.ULO	UU18WR.U20	UU24WR.U40
Compressor	Type		Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary
Airflow Rate	Nom	m³/min	32	32	50	58	58
Sound Pressure	Cooling	Nom	dBA	47	49	47	48
	Heating	Nom	dBA	50	52	52	52
Sound Power	Cooling	Max	dBA	65	65	63	67
Dimensions	W x H x D		mm	770 x 545 x 288	770 x 545 x 288	870 x 650 x 330	950 x 834 x 330
Net Weight		kg		33.8	33.8	44.8	56.1
Refrigerant	Type		R32	R32	R32	R32	R32
	Charge	g	900	900	1,100	1,600	1,600
	Additional Charge (after 7.5m)	g/m	20	20	20	35	35
	GWP		675	675	675	675	675
	TCO _{eq}		0.61	0.61	0.74	1.08	1.28
Operation Range (Outdoor)	Cooling	Min / Max	°C DB	-15 / 48	-15 / 48	-15 / 48	-15 / 48
	Heating	Min / Max	°C WB	-18 / 18	-18 / 18	-18 / 18	-18 / 18
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable		No. x mm²		3C x 2.5	3C x 2.5	3C x 2.5	3C x 2.5
Transmission Cable		No. x mm²		4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker		A		15	15	20	25
Piping Length Total		Min / Max	m	5 / 20	5 / 20	5 / 30	5 / 50
Piping Elevation Difference	IDU - ODU	Max	m	10	10	30	30
Piping Connection	Liquid	mm (inch)		Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 15.88 (5/8)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R32)

COMPACT INVERTER (R32)

HIGH STATIC PRESSURE

- CM18R / CM24R / UM30R / UM36R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU18WCR
UU24WCR

UU30WCR
UU36WCR



		INDOOR		CM18R.N10	CM24R.N10	UM30R.N10	UM36R.N20*
Capacity	Cooling	Min / Nom / Max	kW	1.8 / 5.0 / 5.3	2.7 / 6.8 / 7.4	3.0 / 7.5 / 8.2	4.5 / 9.5 / 13.0
	Heating	Min / Nom / Max	kW	1.7 / 5.2 / 6.0	1.9 / 7.5 / 8.2	2.0 / 8.0 / 8.4	5.0 / 10.8 / 13.7
Low Temperature Capacity	Heating -7°C	Max	kW	3.9	5.7	7.0	8.7
Power Input (Set)	Cooling	Nom	kW	1.67	2.27	2.34	3.35
	Heating	Nom	kW	1.58	2.40	2.28	2.93
Power Input (Indoor)	Min / Max (ESP 2.5mmAq)	W		50 / 80	50 / 90	90 / 150	120 / 210
	Min / Max (ESP 8.0mmAq)	W		90 / 160	100 / 180	160 / 240	200 / 360
Running Current	Cooling / Heating	Nom	A	7.4 / 7.0	10.2 / 10.6	10.6 / 10.0	14.9 / 13.0
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER				2.99	3.00	3.21	2.84
COP				3.29	3.13	3.51	3.69
SEER				5.60	5.60	5.88	5.90
SCOP				3.80	3.80	3.90	3.90
Pdesign (@-10°C)			kW	2.9	4.0	4.0	5.5
Seasonal Energy Label	Cooling / Heating			A+ / A	A+ / A	A+ / A	A+ / A
Annual Energy Consumption	Cooling / Heating		kWh	313 / 1,066	425 / 1,474	446 / 1,436	563 / 1,974
Piping Connection	Liquid		mm (inch)	Ø 6.35 (1/4)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas		mm (inch)	Ø 12.7 (1/2)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)
	Drain	O.D. / I.D.	mm	32.0 / 25.0	32.0 / 25.0	32.0 / 25.0	32.0 / 25.0
Air Flow Rate	High / Medium / Low</						

SINGLE SPLIT SPECIFICATION

CEILING CONCEALED DUCT



STANDARD INVERTER (R410A)

HIGH STATIC PRESSURE

- UB70 / UB85



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU70W UU85W



	INDOOR			UB70.N94	UB85.N94
Capacity	Cooling	Min / Nom / Max	kW	7.6 / 19.0 / 20.9	9.2 / 23.0 / 25.3
	Heating	Min / Nom / Max	kW	9.0 / 22.4 / 24.6	10.8 / 27.0 / 29.7
Low Temperature Capacity	Heating -7°C	Max	kW	18.0	24.0
Power Input (Set)	Cooling	Nom	kW	6.69	8.19
	Heating	Nom	kW	6.4	8.31
Power Input (Indoor)	Min / Max (Nom ESP) W			550 / 760	610 / 920
Running Current	Cooling / Heating	Nom	A	11.5 / 10.7	13.5 / 13.6
Power Supply	Ø / V / Hz			1 / 220-240 / 50	1 / 220-240 / 50
EER				2.84	2.81
COP				3.50	3.25
SEER				4.60	4.80
SCOP				3.53	3.51
Pdesign (@ -10°C)		kW		13.4	18.5
Seasonal Energy Label	Cooling / Heating			-	-
Annual Energy Consumption	Cooling / Heating	kWh		-	-
Piping Connection	Liquid	mm (inch)		Ø9.52 (3/8)	Ø12.7 (1/2)
	Gas	mm (inch)		Ø25.4 (1/1)	Ø22.2 (7/8)
	Drain	O.D. / I.D.	mm	32 / 25	32 / 25
Air Flow Rate	High / Medium / Low	m³/min		70.0 / 65.0 / 60.0	80.0 / 72.0 / 64.0
Sound Pressure	Cooling	High / Medium / Low	dBA	43 / 41 / 40	43 / 41 / 40
Sound Power	Cooling	Max	dBA	73	75
Dehumidification Rate		l/h		1.81 (4.2)	5.14 (11.9)
Dimensions	Body	W x H x D	mm	1,563 x 460 x 688	1,563 x 460 x 688
Net Weight	Body	kg		90.0	90.0
External Static Pressure	Min / Max	mmAq (Pa)		6 / 25 (60 / 250)	6 / 25 (60 / 250)

	OUTDOOR			UU70W.U34	UU85W.U74
Compressor	Type			Hermetically Sealed Scroll	Hermetically Sealed Scroll
Airflow Rate	Nom	m³/min		110	190
Sound Pressure	Cooling	Nom	dBA	55	59
	Heating	Nom	dBA	58	60
Sound Power	Cooling	Max	dBA	75	75
Dimensions	W x H x D	mm		950 x 1,380 x 330	1,090 x 1,625 x 380
Net Weight	kg			110	144.0
Refrigerant	Type	-		R410A	R410A
	Charge	g		5,200	5,500
	Additional Charge	g/m		70	70
	GWP	-		2087.5	2087.5
	TCO ₂ eq	-		10.9	11.5
Operation Range (Outdoor)	Cooling	Min / Max	°C DB	-20 / 48	-20 / 48
	Heating	Min / Max	°C WB	-18 / 18	-18 / 18
Power Supply	Ø / V / Hz			3 / 380-415 / 50	3 / 380-415 / 50
Power Supply Cable	No. x mm ²			5C x 2.5	5C x 2.5
Transmission Cable	No. x mm ²			4C x 1.0	4C x 1.0
Circuit Breaker	A			30	30
Piping Length Total	Min / Max	m		5 / 75	5 / 75
Piping Elevation Difference	IDU - ODU	Max	m	30	30
Piping Connection	Liquid	mm (inch)		Ø9.53 (3/8)	Ø12.7 (1.2)
	Gas	mm (inch)		Ø25.4 (1/1)	Ø22.2 (7/8)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R410A)


CEILING & FLOOR CONVERTIBLE CEILING SUSPENDED UNIT




CEILING & FLOOR CONVERTIBLE

Flexible Installation

The ceiling and floor models can be installed either on the ceiling or on the floor, thus saving on space while being installed in commercial premises.







* Ceiling & Floor : CV09 NE2 / CV12 NE2



Airflow Direction Control

Vertical airflow direction can be adjusted using the remote controller, while horizontal airflow direction can be adjusted manually.



CEILING SUSPENDED UNIT

Differentiated Design

With its stunning V-shaped design and black vane, LG's new ceiling-suspended air conditioner portrays elegance and sophistication appropriate for any space. This attractive aesthetics of the air conditioner qualified it for the iF Design Award.




Powerful Cooling & Heating

The new LG Ceiling Suspended Unit is remarkably efficient for using in large areas due to its powerful cooling and heating operation. The powerful air speed and high volume features enhance the flow of air to reach up to 15m away from the air conditioner.




With enlarged outlet space, optimized the Air flow Path and improved Heat Exchanger's performance

• Outlet Space



115% ENLARGED

• Optimized the Air flow Path




105% IMPROVED

SINGLE SPLIT KEY FEATURES

CEILING SUSPENDED UNIT


One Touch & 2 Piece Filter

Easy IN/OUT filter structure in addition to an easy-to-use two-piece filter, which slides out for easy cleaning and maintenance.




Two Thermistors Control

Users can purchase an optional control panel that includes a second thermistor that allows checking of temperature from multiple locations.



Easy installation

Installation speed and ease is improved by reducing the total number of screws used and placing the screws on the easily accessible front panel.



SINGLE SPLIT SPECIFICATION

CEILING SUSPENDED UNIT



STANDARD INVERTER (R32)

UV18R / UV24R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
: www.eurovent-certification.com

UU18WR



UU24WR UU30WR



	INDOOR	UV18.R.N10	UV24.R.N10	UV30.R.N10*
Capacity	Cooling Min / Nom / Max kW Heating Min / Nom / Max kW	1.9 / 5.0 / 6.0 2.0 / 5.2 / 6.3	2.8 / 6.8 / 7.5 3.0 / 7.5 / 8.3	3.0 / 7.6 / 8.4 3.4 / 8.2 / 9.2
Low Temperature Capacity	Heating -7°C Max kW	4.6	6.9	7.5
Power Input (Set)	Cooling Nom kW Heating Nom kW	1.38 1.52	1.97 2.20	2.30 2.52
Power Input (Indoor)	Min / Max W	20 / 25	40 / 60	40 / 60
Running Current	Cooling / Heating Nom A	6.1 / 6.7	8.7 / 9.8	10.2 / 11.1
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER		3.62	3.45	3.30
COP		3.42	3.40	3.25
SEER		6.50	7.10	6.60
SCOP		4.30	4.30	4.10
Pdesign (@-10°C)	kW	4.1	5.4	5.8
Seasonal Energy Label	Cooling / Heating	A++ / A+	A++ / A+	A++ / A+
Annual Energy Consumption	Cooling / Heating kWh	269 / 1,335	335 / 1,758	403 / 2,030
Piping Connection	Liquid mm (inch) Gas mm (inch)	Ø 6.35 (1/4) Ø 12.7 (1/2)	Ø 9.52 (3/8) Ø 15.88 (5/8)	Ø 9.52 (3/8) Ø 15.88 (5/8)
Air Flow Rate	Drain O.D. / I.D. mm	21.5 / 16.0	21.5 / 16.0	21.5 / 16.0
Sound Pressure	Cooling High / Medium / Low dBa	42 / 40 / 39	44 / 43 / 41	44 / 43 / 41
Sound Power	Cooling Max dBa	55	61	61
Dehumidification Rate	I/h	1.9	3.0	3.0
Dimensions	Body W x H x D mm	1,200 x 235 x 690	1,200 x 235 x 690	1,200 x 235 x 690
Net Weight	Body kg	27.3	28.0	28.0

	OUTDOOR	UU18WR.U20	UU24WR.U40	UU30WR.U40*
Compressor	Type	Twin Rotary	Twin Rotary	Twin Rotary
Airflow Rate	Nom m³/min	50	58	58
Sound Pressure	Cooling Nom dBa Heating Nom dBa	47 52	48 52	48 52
Sound Power	Cooling Max dBa	63	67	68
Dimensions	W x H x D mm	870 x 650 x 330	950 x 834 x 330	950 x 834 x 330
Net Weight	kg	44.8	56.1	58.0
Refrigerant	Type R32 Charge g Additional Charge (after 10m) g/m	R32 1,100 20	R32 1,600 35	R32 1,900 35
GWP	675	675	675	675
TCO _{eq}	0.74	1.08	1.08	1.28
Operation Range (Outdoor)	Cooling Min / Max °C DB Heating Min / Max °C WB	-15 / 48 -18 / 18	-15 / 48 -18 / 18	-15 / 48 -18 / 18
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable	No. x mm² 3C x 2.5	3C x 2.5	3C x 2.5	3C x 2.5
Transmission Cable	No. x mm² 4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker	A 20	25	25	25
Piping Length Total	Min / Max m	5 / 30	5 / 50	5 / 50
Piping Elevation Difference	IDU - ODU Max m	30	30	30
Piping Connection	Liquid mm (inch) Gas mm (inch)	Ø 6.35 (1/4) Ø 12.7 (1/2)	Ø 9.52 (3/8) Ø 15.88 (5/8)	Ø 9.52 (3/8) Ø 15.88 (5/8)

* Available from April 2019.

† For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R32)

SINGLE SPLIT SPECIFICATION

CEILING SUSPENDED UNIT



STANDARD INVERTER (R32)

UV36R / UV42R / UV48R / UV60R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU36WR / UU42WR
UU48WR / UU60WR



STANDARD INVERTER (R32)

UV36R / UV42R / UV48R / UV60R



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU37WR / UU43WR
UU49WR / UU61WR



INDOOR		UV36R.N20	UV42R.N20	UV48R.N20	UV60R.N20
Capacity	Cooling	Min / Nom / Max	kW	4.5 / 9.5 / 13.0	5.0 / 12.0 / 14.5
	Heating	Min / Nom / Max	kW	5.0 / 10.8 / 13.7	5.5 / 13.5 / 16.5
Low Temperature Capacity	Heating -7°C	Max	kW	9.4	12.5
Power Input (Set)	Cooling	Nom	kW	2.30	3.65
	Heating	Nom	kW	2.75	4.00
Power Input (Indoor)	Min / Max	W		30 / 180	30 / 180
Running Current	Cooling / Heating	Nom	A	10.0 / 12.0	16.9 / 16.0
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50
EER				4.13	3.28
COP				3.93	3.37
SEER				5.62	5.5
SCOP				4.04	4.0
Pdesign (@-10°C)		kW		8.05	8.05
Seasonal Energy Label	Cooling / Heating			A+ / A+	A / A+
Annual Energy Consumption	Cooling / Heating	kWh		594 / 2,800	764 / 2,800
Piping Connection	Liquid	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas	mm (inch)		Ø 15.88 (5/8)	Ø 15.88 (5/8)
	Drain	O.D. / I.D.	mm	21.5 / 16.0	21.5 / 16.0
Air Flow Rate	High / Medium / Low	m³/min		28.0 / 24.0 / 20.0	28.0 / 24.0 / 20.0
Sound Pressure	Cooling	High / Medium / Low	dBA	46 / 43 / 40	46 / 43 / 40
Sound Power	Cooling	Max	dBA	63	63
Dehumidification Rate		l/h		3.8	5.8
Dimensions	Body	W x H x D	mm	1,600 x 690 x 235	1,600 x 690 x 235
Net Weight	Body		kg	36.5	36.5

OUTDOOR		UU36WR.U30	UU42WR.U30	UU48WR.U30	UU60WR.U30
Compressor	Type	R-Scroll	R-Scroll	R-Scroll	R-Scroll
Airflow Rate	Nom	m³/min	110	110	110
Sound Pressure	Cooling	Nom	dBA	52	52
	Heating	Nom	dBA	54	54
Sound Power	Cooling	Max	dBA	66	67
Dimensions	W x H x D	mm	950 x 1,380 x 330	950 x 1,380 x 330	950 x 1,380 x 330
Net Weight		kg	87.5	87.5	87.5
Refrigerant	Type	R32	R32	R32	R32
	Charge	g	3,000	3,000	3,000
	Additional Charge (after 7.5m)	g/m	40	40	40
	GWP		675	675	675
	TCO _{eq}		2.03	2.03	2.03
Operation Range (Outdoor)	Cooling	Min / Max	°C DB	-15 / 48	-15 / 48
	Heating	Min / Max	°C WB	-27 / 18	-27 / 18
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable		No. x mm²		3C x 6.0	3C x 6.0
Transmission Cable		No. x mm²		4C x 0.75	4C x 0.75
Circuit Breaker		A		20	40
Piping Length Total	Min / Max	m	5 / 85	5 / 85	5 / 85
Piping Elevation Difference	IDU - ODU	Max	m	30	30
Piping Connection	Liquid	mm (inch)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas	mm (inch)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)

INDOOR		UV36R.N20	UV42R.N20	UV48R.N20	UV60R.N20
Capacity	Cooling	Min / Nom / Max	kW	4.5 / 9.5 / 13.0	5.0 / 12.0 / 14.5
	Heating	Min / Nom / Max	kW	5.0 / 10.8 / 13.7	5.5 / 13.5 / 16.5
Low Temperature Capacity	Heating -7°C	Max	kW	9.4	12.5
Power Input (Set)	Cooling	Nom	kW	2.30	3.65
	Heating	Nom	kW	2.75	4.00
Power Input (Indoor)	Min / Max	W		30 / 180	30 / 180
Running Current	Cooling / Heating	Nom	A	3.3 / 4.0	5.6 / 5.3
Power Supply		Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50
EER				4.13	3.21
COP				3.93	3.37
SEER				5.60	5.5
SCOP				4.00	4.0
Pdesign (@-10°C)		kW		8.05	8.05
Seasonal Energy Label	Cooling / Heating			A+ / A+	A / A+
Annual Energy Consumption	Cooling / Heating	kWh		594 / 2,800	764 / 2,800
Piping Connection	Liquid	mm (inch)		Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas	mm (inch)		Ø 15.88 (5/8)	Ø 15.88 (5/8)
	Drain	O.D. / I.D.	mm	21.5 / 16.0	21.5 / 16.0
Air Flow Rate	High / Medium / Low	m³/min		28.0 / 24.0 / 20.0	28.0 / 24.0 / 20.0
Sound Pressure	Cooling	High / Medium / Low	dBA	46 / 43 / 40	46 / 43 / 40
Sound Power	Cooling	Max	dBA	63	63
Dehumidification Rate		l/h		3.8	5.8
Dimensions	Body	W x H x D	mm	1,600 x 690 x 235	1,600 x 690 x 235
Net Weight	Body		kg	36.5	36.5

OUTDOOR		UU37WR.U30	UU43WR.U30	UU49WR.U30	UU61WR.U30
Compressor	Type	R-Scroll	R-Scroll	R-Scroll	R-Scroll
Airflow Rate	Nom	m³/min	110	110	110
Sound Pressure	Cooling	Nom	dBA	52	52
	Heating	Nom	dBA	54	54
Sound Power	Cooling	Max	dBA	66	67
Dimensions	W x H x D	mm	950 x 1,380 x 330	950 x 1,380 x 330	950 x 1,380 x 330
Net Weight		kg	87.5	87.5	87.5
Refrigerant	Type	R32	R32	R32	R32
	Charge	g	3,000	3,000	3,000
	Additional Charge (after 7.5m)	g/m	40	40	40
	GWP		675	675	675
	TCO _{eq}		2.03	2.03	2.03
Operation Range (Outdoor)	Cooling	Min / Max	°C DB	-15 / 48	-15 / 48
	Heating	Min / Max	°C WB	-27 / 18	-27 / 18
Power Supply		Ø / V / Hz		3 / 380-415 / 50	3 / 380-415 / 50
Power Supply Cable		No. x mm²		5C x 2.5	5C x 2.5
Transmission Cable		No. x mm²		4C x 0.75	4C x 0.75
Circuit Breaker		A		20	20
Piping Length Total	Min / Max	m	5 / 85	5 / 85	5 / 85
Piping Elevation Difference	IDU - ODU	Max	m	30	30
Piping Connection	Liquid	mm (inch)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas	mm (inch)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R32)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

SINGLE SPLIT SPECIFICATION

CEILING & FLOOR CONVERTIBLE



STANDARD INVERTER (R410A)

CV09
CV12



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU09W / UU12W



INDOOR			CV09.NE2	CV12.NE2
Capacity	Cooling	Min / Nom / Max kW	1.0 / 2.5 / 2.8	1.3 / 3.3 / 3.6
	Heating	Min / Nom / Max kW	1.2 / 3.0 / 3.3	1.5 / 3.8 / 4.2
Low Temperature Capacity	Heating -7°C	Max kW	3.1	3.4
Power Input (Set)	Cooling Nom	kW	0.75	1.09
	Heating Nom	kW	0.83	1.18
Power Input (Indoor)	Nom W		30	40
Running Current	Cooling / Heating Nom A		3.26 / 3.61	4.74 / 5.13
Power Supply	Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50
EER			3.33	3.03
COP			3.61	3.22
SEER			5.11	5.31
SCOP			3.81	3.81
Pdesign (@ -10°C)	kW		3.0	3.0
Seasonal Energy Label	Cooling / Heating (A++ to E Scale)		A / A	A / A
Annual Energy Consumption	Cooling / Heating kWh		172 / 1,102	218 / 1,102
Piping Connection	Liquid mm (inch)		Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas mm (inch)		Ø9.52 (3/8)	Ø9.52 (3/8)
	Drain O.D. / I.D. mm		21.5 / 16.0	21.5 / 16.0
Air Flow Rate	High / Medium / Low m³/min		7.6 / 6.9 / 6.2	9.2 / 7.6 / 6.6
Sound Pressure	Cooling High / Medium / Low dBA		38 / 35 / 32	40 / 36 / 31
Sound Power	Cooling Max dBA		52	56
Dehumidification Rate	l/h		1.2	1.2
Dimensions	Body W x H x D mm		900 x 490 x 200	900 x 490 x 200
Net Weight	Body kg		13.7	13.7

OUTDOOR			UU09W.UL0	UU12W.UL0
Compressor	Type		Rotary	Rotary
Airflow Rate	Nom m³/min		32	32
Sound Pressure	Cooling dBA		47	47
	Heating dBA		48	48
Sound Power	Cooling dBA		56	57
Dimensions	W x H x D mm		770 x 540 x 245	770 x 540 x 245
Net Weight	kg		32.0	32.0
Refrigerant	Type	-	R410A	R410A
	Charge g		1,000	1,000
	Additional Charge g/m		20	20
	GWP	-	2,087.5	2087.5
	TCO,eq	-	2.1	2.1
Operation Range (Outdoor)	Cooling Min / Max °C DB		-10 / 43	-10 / 43
	Heating Min / Max °C WB		-18 / 18	-18 / 18
Power Supply	Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable	No. x mm²		3C x 2.5	3C x 2.5
Transmission Cable	No. x mm²		4C x 0.75	4C x 0.75
Circuit Breaker	A		15	15
Piping Length Total	Min / Max m		5 / 15	5 / 15
Piping Elevation Difference	IDU - ODU Max m		10	10
Piping Connection	Liquid mm (inch)		Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas mm (inch)		Ø9.52 (3/8)	Ø9.52 (3/8)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R410A)

CONSOLE




CONSOLE

Optimised Air Flow for Cooling & Heating

During the cooling operation, the vane adjusts upwards to direct the air flow towards the ceiling.

When heating, the vane directs the warm air downwards to balance out the room temperature especially towards the floor.

It is controlled by wireless remote controller which is included indoor unit product



Quick Floor Heating


Console air conditioners portray high speed and powerful performance. Using the floor heating mode, console air conditioners provides floor heating at a faster pace and helps to reach the desired temperature quickly.

	Company A	Electric Heater	LG	LG Floor Heating Mode
27°C Vertical				
15°C Horizontal				
Lead Time for Heating (13°C - 21°C)	12 minutes 30 seconds	50 minutes	9 minutes 30 seconds	8 minutes 40 seconds

(Test Condition :Target Temp 23°C, Indoor Room : 13°C~, Outdoor Room : 7°C)


5-Step Vane Control

There are 5 different stages to control air flow direction.




Easy Installation and Service

6 Different Ways to Install Piping



Easy Slide-type PCB



CONSOLE



STANDARD INVERTER (R410A)

CQ09
CQ12
CQ18



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
: www.eurovent-certification.com

UU09W
UU12W



UU18W



	INDOOR	CQ09.NAO	CQ12.NAO	CQ18.NAO
Capacity	Cooling Min / Nom / Max kW Heating Min / Nom / Max kW	1.3 / 2.6 / 3.4 1.4 / 3.1 / 4.2	1.4 / 3.5 / 3.7 1.6 / 4.0 / 4.4	2.2 / 5.0 / 5.6 2.2 / 4.8 / 5.8
Low Temperature Capacity	Heating -7°C Max kW	3.4	3.6	4.9
Power Input (Set)	Cooling Nom kW Heating Nom kW	0.64 0.74	1.06 1.08	1.55 1.50
Power Input (Indoor)	Nom W	20	30	40
Running Current	Cooling / Heating Nom A	3.42 / 3.87	5.02 / 5.03	7.0 / 6.9
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER		3.98	3.30	3.23
COP		4.19	3.70	3.20
SEER		5.11	5.31	6.2
SCOP		3.81	3.81	3.81
Pdesign (@ -10°C)	kW	2.8	3.0	3.8
Seasonal Energy Label	Cooling / Heating (A++ to E Scale)	A / A	A / A	A++ / A
Annual Energy Consumption	Cooling / Heating kWh	172 / 1,032	231 / 1,105	282 / 1,396
Piping Connection	Liquid mm (inch) Gas mm (inch)	Ø6.35 (1/4) Ø9.52 (3/8)	Ø6.35 (1/4) Ø12.7 (1/2)	Ø6.35 (1/4) Ø12.7 (1/2)
Air Flow Rate	Drain O.D. / I.D. mm	21.5 / 16.0	21.5 / 16.0	21.5 / 16.0
Sound Pressure	Cooling High / Medium / Low m³/min	8.5 / 6.7 / 5.0	9.0 / 6.9 / 5.2	10.1 / 8.6 / 7.2
Sound Power	Cooling Max dBA	38 / 32 / 27	39 / 32 / 27	44 / 39 / 35
Dehumidification Rate	Cooling l/h	53	56	60
Dimensions	Body W x H x D mm	700 x 600 x 210	700 x 600 x 210	700 x 600 x 210
Net Weight	Body kg	14.0	14.0	14.0

	OUTDOOR	UU09W.ULO	UU12W.ULO	UU18W.UE4
Compressor	Type	Rotary	Rotary	Twin Rotary
Airflow Rate	Nom m³/min	32	32	50
Sound Pressure	Cooling Nom dBA	47	47	47
Sound Power	Heating Nom dBA	48	48	52
Dimensions	Cooling Max dBA	56	57	63
Net Weight	W x H x D mm	770 x 540 x 245	770 x 540 x 245	870 x 655 x 320
Refrigerant	kg	32.0	32.0	44.6
Operation Range	Type	R410A	R410A	R410A
Power Supply	Charge g	1,000	1,000	1,300
Transmission Cable	Additional Charge g/m	20	20	20
Circuit Breaker	GWP -	2,087.5	2087.5	2087.5
Piping Length Total	Min / Max °C DB	-10 / 43	-10 / 43	-15 / 48
Piping Elevation Difference	Heating Min / Max °C WB	-18 / 18	-18 / 18	-18 / 18
Piping Connection	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
	No. x mm²	3C x 2.5	3C x 2.5	3C x 2.5
	No. x mm²	4C x 0.75	4C x 0.75	4C x 0.75
	A	15	15	20
	m	5 / 15	5 / 15	5 / 30
	IDU - ODU Max m	10	10	30
	Liquid mm (inch)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø12.7 (1/2)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R410A)

FLOOR STANDING UNIT



COMMERCIAL

SINGLE SPLIT KEY FEATURES

FLOOR STANDING UNIT

Stylish Design



The new LG floor standing air conditioner which is Red Dot design award winner 2013, is ideal for modern interiors in your home or office.



reddot design award
winner 2013

Quick Response

Offering powerful cooling, the commercial air conditioning system can reach a set temperature in a shorter period of time. Meanwhile, the Power Heating function provides the optimal airflow angle, guaranteeing a faster heating performance.



Powerful Air Flow

The new LG floor standing air conditioner is efficient for using in large areas due to its powerful cooling and heating operation. The powerful air speed and volume means the air flow can reach up to 20m away from the air conditioner.



SINGLE SPLIT SPECIFICATION

FLOOR STANDING UNIT



STANDARD INVERTER (R410A)

UP48



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
: www.eurovent-certification.com

UU48W



STANDARD INVERTER (R410A)

UP49



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
: www.eurovent-certification.com

UU49W



COMMERCIAL

INDOOR			
Capacity	Cooling	Min / Nom / Max	kW
	Heating	Min / Nom / Max	kW
Low Temperature Capacity	Heating -7°C	Max	kW
	Cooling	Nom	kW
Power Input (Set)	Heating	Nom	kW
Power Input (Indoor)	Nom	W	
Running Current	Cooling / Heating	Nom	A
Power Supply		Ø / V / Hz	
EER		1 / 220-240 / 50	
COP		3.21	
SEER		3.41	
SCOP		5.05	
Pdesign (@ -10°C)		3.51	
Seasonal Energy Label	Cooling / Heating	kW	
Annual Energy Consumption	Cooling / Heating	kWh	
	Liquid	mm (inch)	
Piping Connection	Gas	mm (inch)	
	Drain	O.D. / I.D.	mm
Air Flow Rate	High / Medium / Low	m³/min	
Sound Pressure	Cooling	High / Medium / Low	dBA
Sound Power	Cooling	Max	dBA
Dehumidification Rate		I/h	
Dimensions	Body	W x H x D	mm
Net Weight	Body	kg	

OUTDOOR			
Compressor	Type		
Airflow Rate	Nom	m³/min	
Sound Pressure	Cooling	Nom	dBA
	Heating	Nom	dBA
Sound Power	Cooling	Max	dBA
Dimensions	W x H x D	mm	
Net Weight	kg		
	Type	-	
Refrigerant	Charge	g	
	Additional Charge	g/m	
	GWP	-	
	TCO ₂ eq	-	
Operation Range (Outdoor)	Cooling	Min / Max	°C DB
	Heating	Min / Max	°C WB
Power Supply		Ø / V / Hz	
Power Supply Cable		No. x mm²	
Transmission Cable		No. x mm²	
Circuit Breaker		A	
Piping Length Total	Min / Max	m	
Piping Elevation Difference	IDU - ODU	Max	m
Piping Connection	Liquid	mm (inch)	
	Gas	mm (inch)	

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R410A)

INDOOR			
Capacity	Cooling	Min / Nom / Max	kW
	Heating	Min / Nom / Max	kW
Low Temperature Capacity	Heating -7°C	Max	kW
	Cooling	Nom	kW
Power Input (Set)	Heating	Nom	kW
Power Input (Indoor)	Nom	W	
Running Current	Cooling / Heating	Nom	A
Power Supply		Ø / V / Hz	
EER		1 / 220-240 / 50	
COP		3.21	
SEER		3.41	
SCOP		5.05	
Pdesign (@ -10°C)		3.51	
Seasonal Energy Label	Cooling / Heating	kW	
Annual Energy Consumption	Cooling / Heating	kWh	
	Liquid	mm (inch)	
Piping Connection	Gas	mm (inch)	
	Drain	O.D. / I.D.	mm
Air Flow Rate	High / Medium / Low	m³/min	
Sound Pressure	Cooling	High / Medium / Low	dBA
Sound Power	Cooling	Max	dBA
Dehumidification Rate		I/h	
Dimensions	Body	W x H x D	mm
Net Weight	Body	kg	

OUTDOOR			
Compressor	Type		
Airflow Rate	Nom	m³/min	
Sound Pressure	Cooling	Nom	dBA
	Heating	Nom	dBA
Sound Power	Cooling	Max	dBA
Dimensions	W x H x D	mm	
Net Weight	kg		
	Type	-	
Refrigerant	Charge	g	
	Additional Charge	g/m	
	GWP	-	
	TCO ₂ eq	-	
Operation Range (Outdoor)	Cooling	Min / Max	°C DB
	Heating	Min / Max	°C WB
Power Supply		Ø / V / Hz	
Power Supply Cable		No. x mm²	
Transmission Cable		No. x mm²	
Circuit Breaker		A	
Piping Length Total	Min / Max	m	
Piping Elevation Difference	IDU - ODU	Max	m
Piping Connection	Liquid	mm (inch)	
	Gas	mm (inch)	

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R410A)

WALL MOUNTED UNIT




SINGLE SPLIT KEY FEATURES

WALL MOUNTED UNIT

COMMERCIAL

Wide Operation Range


Ideal and comprehensive solution for server rooms, machine rooms and kitchens.



Easy Installation


Detachable Bottom Cover

The bottom cover is detachable when needed, making installation easier. Disassembly or additional support of the unit is unnecessary. Installation can be completed by one individual with LG's patented support tool.



Installation Support Clip

A support clip creates adequate space between the wall and the unit for easier installation.



SINGLE SPLIT KEY FEATURES


WALL MOUNTED UNIT

High Energy Efficiency

New wall mounted units provide good seasonal energy efficiency connected with Standard Inverter outdoor units.


	8.0kW	10kW
SEER	6.1 (A++)	5.4 (A)
SCOP	3.9 (A)	3.8 (A)

Powerful Cooling & Heating



Optimised Airflow

Direction of horizontal vane can be adjusted from step 1 to step 6 with full auto swing. This function can cool and heat specific areas much faster.



Quick Cooling & Heating

Jet cooling and heating disperses air evenly at high speed to secure an optimally cooled or heated room in just 3 minutes.



SINGLE SPLIT SPECIFICATION

WALL MOUNTED UNIT



STANDARD INVERTER (R410A)

UJ30 / UJ36



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
www.eurovent-certification.com

UU30W

UU36W
UU37W



COMMERCIAL

	INDOOR	UJ30.NV2	UJ36.NV3	UJ36.NV3
Capacity	Cooling Min / Nom / Max kW Heating Min / Nom / Max kW	3.5 / 7.8 / 8.5 4.0 / 8.4 / 9.2	4.0 / 9.5 / 10.5 4.4 / 10.5 / 11.5	4.0 / 9.5 / 10.5 4.4 / 10.5 / 11.5
Low Temperature Capacity	Heating -7°C Max kW	7.5	9.4	9.4
Power Input (Set)	Cooling Nom kW Heating Nom kW	2.29 2.46	2.79 3.08	2.79 3.08
Power Input (Indoor)	Nom W	140	160	160
Running Current	Cooling / Heating Nom A	10.0 / 10.7	12.1 / 13.4	4.0 / 4.4
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER		3.41	3.41	3.41
COP		3.41	3.41	3.41
SEER		6.11	5.41	5.41
SCOP		3.91	3.81	3.81
Pdesign (@ -10°C)	kW	6.3	7.6	7.6
Seasonal Energy Label	Cooling / Heating (A++ to E Scale)	A++ / A	A / A	A / A
Annual Energy Consumption	Cooling / Heating kWh	448 / 2,262	615 / 2,793	615 / 2,793
Piping Connection	Liquid mm (inch) Gas mm (inch)	Ø9.52 (3/8) Ø15.88 (5/8)	Ø9.52 (3/8) Ø15.88 (5/8)	Ø9.52 (3/8) Ø15.88 (5/8)
Air Flow Rate	Drain O.D. / I.D. mm	21.5 / 16.0	21.5 / 16.0	21.5 / 16.0
Sound Pressure	Cooling High / Medium / Low dBa	45 / 42 / 40	48 / 45 / 41	48 / 45 / 41
Sound Power	Cooling Max dBa	61	63	63
Dehumidification Rate	l/h	3.0	3.4	3.4
Dimensions	Body W x H x D mm	1,190 x 346 x 265	1,190 x 346 x 265	1,190 x 346 x 265
Net Weight	Body kg	15.7	16.0	16.0

	OUTDOOR	UU30W.U44	UU36W.UO2	UU37W.UO2
Compressor	Type	Twin Rotary	Twin Rotary	Twin Rotary
Airflow Rate	Nom m³/min	58	90	90
Sound Pressure	Cooling Nom dBa Heating Nom dBa	48 52	53 54	53 54
Sound Power	Cooling Max dBa	68	66	66
Dimensions	W x H x D mm	950 x 834 x 330	950 x 1,170 x 330	950 x 1,170 x 330
Net Weight	kg	58.0	81.0	85.0
Refrigerant	Type	R410A	R410A	R410A
	Charge g	2,000	2,800	2,800
	Additional Charge g/m	40	40	40
	GWP -	2087.5	2087.5	2087.5
	TCO ₂ eq -	4.2	5.8	5.8
Operation Range (Outdoor)	Cooling Min / Max °C DB Heating Min / Max °C WB	-15 / 48 -18 / 18	-15 / 48 -18 / 18	-15 / 48 -18 / 18
Power Supply	Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	3 / 380-415 / 50
Power Supply Cable	No. x mm²	3C x 2.5	3C x 5.0	5C x 2.5
Transmission Cable	No. x mm²	3C x 2.5	4C x 0.75	4C x 0.75
Circuit Breaker	A	4C x 0.75	40	20
Piping Length Total	Min / Max m	25	5 / 50	5 / 50
Piping Elevation Difference	IDU - ODU Max m	30	30	30
Piping Connection	Liquid mm (inch) Gas mm (inch)	Ø9.52 (3/8) Ø15.88 (5/8)	Ø9.52 (3/8) Ø15.88 (5/8)	Ø9.52 (3/8) Ø15.88 (5/8)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB

Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R410A)

AHU SOLUTION



COMMERCIAL

SINGLE SPLIT AHU SOLUTION AHU COMBINATION


Air Handling Applications

Economically feasible solution for pair application with air handling units.

Return / Room Air Temperature Control

• Temp. Sensors
 • Comm. Line
 • Central Comm. Line to ODU
 • Ref. Pipe


 T_E = Evaporator Temperature (Liquid Pipe / Gas Pipe)
 T_R = Return Air Temperature
 T_{ROOM} = Room Air Temperature



Discharge Air Temperature Control

• Temp. Sensors
 • Comm. Line
 • Central Comm. Line to ODU
 • Ref. Pipe

 T_E = Evaporator Temperature (Liquid Pipe / Gas Pipe)
 T_D = Discharge Air Temperature
 T_{ROOM} = Room Air Temperature



1) PI485(PMNFP14A1) is required for using centralized controller

2) In case of applying DDC with contact signal, discharge air temperature should be measured and controlled by DDC

3) For more detail, please refer to the PDB of AHU Communication Kit

SINGLE SPLIT AHU SOLUTION

AHU COMMUNICATION KITS

COMMUNICATION KIT

NEW! PAHCMR000
NEW! PAHCMS000



Specifications

MODEL	COMBINATION		DESCRIPTION	DIMENSIONS (MM)		
	OUTDOOR UNIT	CENTRALIZED CONTROLLER		W	H	D
PAHCMR000	Single Split	.	Return / Room air temperature control by DDC or LG individual / centralized controller	300	300	155
PAHCMS000	Single Split	.	Discharge air temperature control by DDC or LG individual / centralized controller	380	300	155

Function list for Communication kit

FUNCTION LIST*	PAHCMR000	PAHCMS000	NOTE
Comm. Kit Operation	On / Off	On / Off	
Operation Mode ¹⁾	Cooling / Heating	Cooling / Heating	
Return (room) Air Temperature	16~30°C	-	
Control Discharge Air Temperature ²⁾	-	16~30°C	Available in case of using DDC with Modbus or LG Control system
Fan Speed ³⁾	Low / Middle / High	Low / Middle / High	It may not be possible depending on the particular condition
Forced Thermal On / Off	On / Off	-	Available in case of using DDC with contact signal
Capacity Control	-	-	Available in case of using DDC with Modbus or contact signal
Comm. Kit Operation	On / Off	On / Off	
Operation Mode ¹⁾	Cooling / Heating	Cooling / Heating	Available in case of using DDC with Modbus or LG Control system
Monitor Fan Speed	Low / Middle / High	Low / Middle / High	
Error Alarm	-	-	
Compressor On / Off	On / Off	On / Off	Available in case of using DDC with Modbus or LG individual controller PAHCMR000 doesn't provide this in case of using DDC with contact signal

1) Available operation mode can be varied depending on the setting of AHU Communication Kit.

2) This range may differ depending on the type of controller

3) To control and monitor the fan speed, DO ports for the fan speed status have to be connected with the fan unit

* Some of functions may not be possible depending on the setting of AHU Communication Kit. For more details of condition, please refer to the product data book

Combination Table

STANDARD INVERTER (1-phase)

	UU18WR.U20	UU24WR.U40	UU30WR.U40	UU36WR.U30	UU42WR.U30	UU48WR.U30	UU60WR.U30	
Capacity	Cooling kW	4.7	7.7	8.0	10.0	12.5	13.9	14.6
	Heating kW	5.5	8.0	9.0	11.0	14.0	15.4	16.9

AHU Kit	PAHCMR000
	PAHCMS000	.	.	.	-	-	-

STANDARD INVERTER (3-phase)

	UU37WR.U30	UU43WR.U30	UU49WR.U30	UU61WR.U30	UU70W.U34	UU85W.U74	
Capacity	Cooling kW	10.0	12.5	13.9	14.6	19.0	23.0
	Heating kW	11.0	14.0	15.4	16.9	22.4	27.0

AHU Kit	PAHCMR000
	PAHCMS000	-	-	-	-	-

ACCESSORIES



SINGLE SPLIT ACCESSORIES

LG Wi-Fi MODEM

Control LG air conditioners via using the internet devices as Android or iOS bases smartphones

PWFMD200

Features

- Access LG air conditioner anytime and from anywhere with Wi-Fi equipped device
- LG's exclusive Home Appliances control app(SmartThinQ) is available
- Simple operation for various functions
 - On/Off
 - Fan Speed
 - Energy Monitoring¹⁾
 - Operation Mode
 - Vane Control²⁾
 - Filter Management
 - Current/Set Temperature
 - Reservation (Sleep, Weekly On/Off)
 - Error check

MODEL NAME	PWFMD200
Size (W x H x D, mm)	48 x 68 x 14
Interfaceable Products	Single Indoor unit ³⁾
Connection Type	Indoor unit 1:1
Communication Frequency	2.4 GHz
Wireless Standards	IEEE 802.11b/g/n
Mobile Application	LG Smart ThinQ (Android v4.1(Jellybean) or higher, iPhone iOS 9.0 or higher)
Optional Extension Cable	PWYREW000 (10m extension)

* Functionality may be different according to each IDU model


* User interface of application shall be revised for its design and contents improvement

* Application is optimized for smartphone use, so it may not be well functioning with tablet devices


1) LG Centralized controller and PDI installation is required for this function

2) Vane Control may not be possible according to the type of Indoor unit

3) For the compatibility with Indoor unit, please contact regional office



Overview



* Search "LG Smart ThinQ" on Google market or Appstore then download the app.
* Internet service with Wi-Fi connection has to be available

SINGLE SPLIT ACCESSORIES

ACCESSORIES

Standard Wired Remote Controller

Standard III



PREMTB100

Standard II



PREMTB001



PREMTBB01

Model Name

PREMTB100
PREMTB001On/Off; Fan Speed Control,
Temperature Setting

Mode Change

Cooling / Heating / Auto /
Dehumidification / Fan

Auto Swing / Vane Control

•

•

Reservation

Simple / Sleep / On, Off / Weekly / Holiday

Time Display

•

•

Electrical Failure Compensation

•

•

Child Lock

•

•

Operation Status LED

•

•

Indoor Temperature Display

•

•

Wireless Remote Controller

- •

Receiver

- •

Size (W x H x D, mm)

120 x 120 x 16

120 x 121 x 16

Backlight

•

•


* Refer to each model PDB for applicable models.

Remote Controller



PQWRHQ0FDB

PI 485



PMNFP14A1

Power : Single phase AC 220V 50/60Hz

Max. no of the indoor units that can be connected: 64 UNITS

Model applied : RAC / Multi / Single / Therma V

※ Refer to each product PDB for applicable models

Dry Contact



※ Refer to each product PDB for applicable models

MODEL	PDRYCB000	PDRYCB400	PDRYCB300	PDRYCB500
Contact Point	1 Control Point	2 Control Point	8 Control Point	Modbus RTU
Power Input	AC 220V from outside power source	DC 5V & 12V from indoor unit PCB	DC 5V & 12V from indoor unit PCB	DC 5V & 12 V from indoor unit PDB
Voltage / Non Voltage Input			•	•
On / Off Control	•	•	•	•
Lock / Unlock	•	•	•	•
Fan Speed Setting			•	•
Thermo Off			•	•
Energy Saving			•	•
Temperature Setting		•	•	•
Error Monitoring	•	•	•	•
Operation Monitoring	•	•	•	•


SINGLE SPLIT DIMENSIONS

CEILING CASSETTE

CT09R.NR0 / CT12R.NR0

(Unit : mm)


	Part Name
1	Gas Pipe Connection
2	Liquid Pipe Connection
3	Drain Pipe Connection
4	Power and Communication cable routing hole
5	Wired remote controller wire routing hole
6	Air Intake
7	Air Outlet
8	Decoration Panel (PT-QCHWO)
9	Decoration Corner Cover
10	Decoration Coner Display Cover
11	Flexible Drain Hose
12	Fresh air Intake Hole



CT18R.NQ0

(Unit : mm)

	Part Name
1	Gas Pipe Connection
2	Liquid Pipe Connection
3	Drain Pipe Connection
4	Power and Communication cable routing hole
5	Wired remote controller wire routing hole
6	Air Intake
7	Air Outlet
8	Decoration Panel (PT-QCHWO)
9	Decoration Corner Cover
10	Decoration Coner Display Cover
11	Flexible Drain Hose
12	Fresh air Intake Hole




SINGLE SPLIT DIMENSIONS

CEILING CASSETTE

CT24R.NPO

(Unit : mm)


	Part Name
1	Gas Pipe Connection
2	Liquid Pipe Connection
3	Drain Pipe Connection
4	Power and Communication cable routing hole
5	Wired remote controller wire routing hole
6	Air Inlet
7	Air Outlet
8	Decoration Panel (PT-MCHWO)
9	Decoration Corner Cover
10	Flexible Drain Hose
11	Fresh air Intake Hole



UT36R.NMO / UT42R.NMO / UT48R.NMO / UT60R.NMO

(Unit : mm)

	Part Name
1	Gas Pipe Connection
2	Liquid Pipe Connection
3	Drain Pipe Connection
4	Power and Communication cable routing hole
5	Wired remote controller wire routing hole
6	Air Inlet
7	Air Outlet
8	Decoration Panel (PT-MCHWO)
9	Decoration Corner Cover
10	Flexible Drain Hose
11	Fresh air Intake Hole




SINGLE SPLIT DIMENSIONS

CEILING CONCEALED DUCT

CM18R.N10 / CM24R.N10

(Unit : mm)


	Part Name
1	Gas pipe connection
2	Liquid pipe connection
3	Drain pipe connection
4	Power and Communication Cable Routing Hole
5	Wired Remote Controller Wire Routing Hole
6	Air Inlet Vent
7	Air Outlet Vent
8	Air Filter
9	Control Cover



UM36R.N20 / UM42R.N20

(Unit : mm)


	Part Name
1	Gas pipe connection
2	Liquid pipe connection
3	Drain pipe connection
4	Power and Communication Cable Routing Hole
5	Remote Controller Cable Hole
6	Air Inlet
7	Air Outlet
8	Air Filter
9	Control Cover



UM48R.N30 / UM60R.N30

(Unit : mm)

	Part Name
1	Refrigerant pipe connection
2	Drain pipe connection
3	Power and communication Cable Hole
4	Remote Controller Cable Hole
5	Air Inlet
6	Air Outlet
7	Air Filters
8	Control Cover



SINGLE SPLIT DIMENSIONS


CEILING CONCEALED DUCT

CL09R.N20 / CL12R.N20 / CL18R.N20 / CL24R.N30

(Unit : mm)

		Part Name	
1	Liquid pipe connection		
2	Gas pipe connection		
3	Drain pipe connection		
4	Power supply connection		
5	Air discharge		
6	Air suction		


Chassis	A	B	C	D
CB09L	774	700	733	660
CB12L				
CB18L				
CL09R	974	900	933	860
CL12R				
CL18R				
CB24L				
CL24R	1,174	1,100	1,133	1,060



UB70.N94 / UB85.N94

(Unit : mm)


		Part Name	
1	Air suction flange		
2	Air discharge flange		
3	Control Box		
4	Gas piping connection		
5	Liquid pipe connection		
6	Drain pipe connection		
7	Drain pump (Option)		




SINGLE SPLIT DIMENSIONS

CEILING SUSPENDED UNIT

UV18R.N10 / UV24R.N10




UV36R.N20 / UV42R.N20 / UV48R.N20 / UV60R.N20



SINGLE SPLIT DIMENSIONS

CEILING & FLOOR CONVERTIBLE


CV09.NE2 / CV12.NE2



SINGLE SPLIT DIMENSIONS

CONSOLE

CQ09.NA0 / CQ12.NA0 / CQ18.NA0




SINGLE SPLIT DIMENSIONS

WALL MOUNTED

UJ30.NV2 / UJ36.NV3

(Unit : mm)

	Part Name
1	Front Panel
2	Display & Signal Receiver
3	Air Suction Grille
4	Installation Plate




SINGLE SPLIT DIMENSIONS

FLOOR STANDING

UP48.NT2

(Unit : mm)

	Part Name
1	Front air discharge grille
2	Display & Single receiver
3	Air suction grille




SINGLE SPLIT DIMENSIONS

UNIVERSAL OUTDOOR


UU09WR.UL0 / UU12WR.UL0

(Unit : mm)

	Part Name
1	Air Outlet
2	Control cover & SVC valve cover
3	Power and communication cable connection
4	Gas Pipe connection
5	Liquid Pipe connection
6	Power and communication cable routing hole
7	Refrigerant pipe routing hole
8	Handle
9	Intake air temperature sensor cover




3D View




UU18WR.U20

(Unit : mm)

	Part Name
1	Air Outlet
2	Control cover & SVC valve cover
3	Power and communication cable connection
4	Gas Pipe Connection
5	Liquid Pipe Connection
6	Handle
7	Intake air temperature sensor cover



3D View




SINGLE SPLIT DIMENSIONS

UNIVERSAL OUTDOOR

UU24WR.U40

(Unit : mm)


	Part Name
1	Air Outlet
2	Power and communication cable Hole
3	Gas Pipe Connection
4	Liquid Pipe Connection
5	Handle
6	Pipe routing hole (front)
7	Pipe routing hole (side)
8	Pipe routing hole (back)



UU36WR.U30 / UU37WR.U30 / UU42WR.U30 / UU43WR.U30 UU48WR.U30 / UU49WR.U30 / UU60WR.U30 / UU61WR.U30

(Unit : mm)


	Part Name
1	Air Outlet
2	Power and communication cable hole
3	Gas Pipe Connection
4	Liquid Pipe Connection
5	Handle
6	Pipe routing hole (front)
7	Pipe routing hole (side)
8	Pipe routing hole (back)




SINGLE SPLIT DIMENSIONS

UNIVERSAL OUTDOOR

UU70W.U34



UU85W.U74



HEATING

MONOBLOC (MID TEMPERATURE)

SPLIT (HIGH TEMPERATURE)

DOMESTIC HOT WATER TANK

SPLIT (LOW TEMPERATURE)

SPLIT (DHW TANK INTEGRATED)

ACCESSORIES



WHAT IS THERMA V




What is LG THERMA V?

THERMA V is LG's Air to Water Heat Pump system, especially designed for new and renovated housings. It is an in-house design by LG's advanced heating technology consuming less energy.

THERMA V can be used as a multi-purpose heating Solution ranging from floor heating to hot water supply using various heat sources.

Energy Efficient Application

THERMA V offers the best solution for home heating and hot water supply with LG's inverter technology. It is 4 times more energy efficient than the traditional boiler system by absorbing energy from the outdoor environment.



Optimal Application

Advanced model selection software enables designers to choose optimal THERMA V model based on the location and environmental factors.


- Model selection screen




- Monthly energy simulation



- Heat load & heat pump capacity




- System comparison chart



Reliable Application

Heating range for outdoor temperature is down to -20°C and leaving water temperature can reach max. 57°C



* In case of Split models

Various Application

Various kinds of application is possible with THERMA V units including new house also renovation house.


- New House

With low temp. monobloc & split model, heating and cooling can be ensured.



- Renovation House

THERMA V can be connected to existing boiler system to optimize energy efficiency and heating capacity for renovation house. Also THERMA V High Temperature can provide equivalent water heating to a boiler of up to 80°C.



THERMA V

LINE-UP


THERMA V

TYPE	PHASE	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	3Ø	3Ø	3Ø	
	KW	5	7	9	12	14	16	12	14	16	
Monobloc Type		NEW	HM051M.U43	HM071M.U43	HM091M.U43						
		NEW				HM121M.U33	HM141M.U33	HM161M.U33	HM123M.U33	HM143M.U33	HM163M.U33
Split Type			HN1616.NK3	HN1616.NK3	HN1616.NK3						
			HU051.U43	HU071.U43	HU091.U43						
						HN1616.NK3	HN1616.NK3	HN1616.NK3	HN1639.NK3	HN1639.NK3	HN1639.NK3
						HU121.U33	HU141.U33	HU161.U33	HU123.U33	HU143.U33	HU163.U33

Type	Phase	1Ø KW	1Ø 5	1Ø 7	1Ø 9	1Ø 12	1Ø 14	1Ø 16	3Ø 12	3Ø 14	3Ø 16
Split DHW Tank Integrated Type					HU1616T.NB0						
					HU091.U43						
						HN1616T.NB0	HN1616T.NB0	HN1616T.NB0	HN1616T.NB0	HN1616T.NB0	HN1616T.NB0
						HU121.U33	HU141.U33	HU161.U33	HU123.U33	HU143.U33	HU163.U33
Split High Temp. Type								HN1610H.NK2			
								HU161H.U32			

* A+++ label is available from 26, Sep. 2019 and should be considered as A++ label until that time.

LG THERMA V



Why LG THERMA V?

The LG THERMA V is designed to provide reasonable benefits such as like energy saving, comforts, easy controls and services by applying the advanced technologies.

The LG Inverter Technology provides excellent energy efficiency with optimal components such as water pump, heat exchanger and fan motor. Moreover, the pressure control technology provides stable heating capacity at a low temperature and reaches target performance without difficulties.

Additionally, the amalgamated model where all-in-one features are combined such as gold-fin and users-oriented functions. This has resulted in boosting professional reputation and enhancing end-user's experience in the form of LG's full line-up from 5kW to 16kW in heating capacity.

MONOBLOC



THERMA V KEY FEATURES


MONOBLOC

R1 Scroll Compressor

Revolutionary Scroll Compressor is applied for high-efficiency and reliability. This type of compressor is more advanced compressor compared to the conventional scroll compressor, especially tilting motion of scroll has been improved. Further, compressor operation range is improved compared to previous model.

• Revolutionary Scroll Compressor

- Scroll compressor with simple structure
- High efficiency (low load at low speed / total efficiency)
- Low noise (high speed possible)
- Improved Tilting Motion of scroll
- 20% weight reduction (vs. conventional compressor)




Flash Gas Injection

In case of R32 Refrigerant, it is very important to control discharge temperature of compressor properly. In the R32 Monobloc, Flash Gas Injection technology is applied to control discharge temperature of compressor efficiently. As a result of this technology, heating operation range is expanded and heating performance at low ambient temperature is enhanced.


• Vapor Injection

- Discharge Temperature of Compressor is very high (160°C)
- Failure of Injection Cycle and compressor operation under protection logic



• Flash Gas Injection

- Discharge Temperature of Compressor is below 110°C
- Good Operation of Injection Cycle



MONOBLOC

Intuitive Interface

The R32 Monobloc system is upgraded with new remote controller.




Premium Design

New Modern design 4.3 inch color LCD display
Capacitive touch button (especially on/off button turn on LED)

User Friendly Interface

Information displayed with simple graphic, icon & text
Navigation button, easy to use



More energy contents

Auto controlled by weather and time


Convenient Functions

Optimize schedule setting logic
• Set the period, date, on/off time, operation mode, target temp
Easy installation setting (as-is : numeric code, to-be : word)

Seasonal Auto Mode

In this mode, the target temperature will vary according to the outdoor temperature automatically.
This mode adds the cooling season function to the conventional weather dependent operation mode.

	Auto-Adjustable Target Temp.	Leaving Water Temp.	Outdoor Air Temp.	
Heating	Water 1 Heat	15 ~ 57	Outdoor 1 Heat	-15 ~ 24
	Water 2 Heat	15 ~ 57	Outdoor 2 Heat	-15 ~ 24
Cooling	Water 3 Cool	5 ~ 25	Outdoor 3 Cool	10 ~ 43
	Water 4 Cool	5 ~ 25	Outdoor 4 Cool	10 ~ 43




Various Temperature Control Options

Various Temperature Control Options are possible for the User's comfort and convenience. Especially for European life style where thermal comfort is preferred, Simultaneous Control of Room Air and Water Temp. function is added.

① Control of Leaving Water Temperature


② Control of Entering Water Temperature

- Thermo On : When Satisfied both Room Air Temp. Condition and Water Temp. Condition
- Thermo Off : When Satisfied Room Air Temp. Condition or Water Temp. Condition



③ Control of Room Air Temperature

④ Simultaneous Control of Room Air and Water Temp.



Ocean Black Fin

'Ocean Black Fin' heat exchanger is highly corrosion resistant, designed to perform in corrosive environment such as contaminated and humid conditions.



Longer Lifespan,
Lower Operational Costs



Strengthened corrosion
resistant coating


Hydrophilic Film (Water Flow)

The Hydrophilic coating minimizes moisture buildup on the fin.

Epoxy Resin (Corrosion resistant)

The Black coating provides strong protection from corrosion

Aluminum Fin



Ocean
Black Fin


Easy Installation

All-in-one Concept

- LG provides fully packaged THERMA V Monobloc that additional water side components are included in the package.
- No need to work refrigerant piping, easier and quicker installation.



Water side Items included in the Monobloc



MONOBLOC

HM051M.U43 / HM071M.U43 / HM091M.U43



		DESCRIPTION	UNIT	HM051M.U43	HM071M.U43	HM091M.U43
		SEASONAL ENERGY				
Space Heating (According to EN14825)	Average Climate water outlet 35°C	SCOP		4.45	4.45	4.45
	Rated heat output (Prated)		kWh	6	6	6
	Seasonal space heating efficiency (ηs) %			175	175	175
	Seasonal space heating eff. Class			A+++	A+++	A+++
	Annual energy consumption		kWh	2,551	2,668	2,784
	SCOP			3.12	3.12	3.12
	Rated heat output (Prated)		kWh	6	6	6
	Seasonal space heating efficiency (ηs) %			122	122	122
	Seasonal space heating eff. Class			A+	A+	A+
	Annual energy consumption		kWh	3,638	3,638	3,638
PRODUCT SPECIFICATION						
Nominal Capacity	OAT	LWT				
	7°C	35°C	kW	5.50	7.00	9.00
	Heating	7°C	55°C	5.50	5.50	5.50
	2°C	35°C	kW	3.30	4.20	5.40
Nominal Power Input	Cooling	35°C	18°C	kW	5.50	7.00
	35°C	7°C	kW	5.50	7.00	9.00
	Heating	7°C	35°C	kW	1.22	1.56
	2°C	55°C	kW	2.04	2.04	2.04
COP	Heating	7°C	35°C	kW	0.94	1.20
	2°C	35°C	kW	1.20	1.56	1.54
	Cooling	35°C	18°C	kW	1.20	1.56
	35°C	7°C	kW	1.96	2.59	3.46
EER	Heating	7°C	35°C	W/W	4.50	4.50
	2°C	55°C	W/W	2.70	2.70	2.70
	Cooling	35°C	18°C	W/W	4.60	4.50
	35°C	7°C	W/W	2.80	2.70	2.60
Operation range	Water Side Min - Max (outlet)	°C		15 ~ 65		
	Air Side Min-Max	°C		-25 ~ 35		
	Cooling	Water Side Min - Max (outlet)	°C	5 ~ 27		
	Air Side Min-Max	°C		5 ~ 48		
Refrigerant	Domestic Hot Water	Water Side Min - Max (outlet)	°C	15 ~ 80		
	Type			R32		
	GWP (Global Warming Potential)			675		
	Charge	kg	tCO ₂ eq	1.4		
Compressor	Quantity			0.95		
	Type			1		
Water Flow Rate	Min.	LPM		Scroll		
Piping Connections	Water Circuit	Inlet	mm(in)			
	Circuit	Outlet	mm(in)	Male PT 25(1)		
Dimensions	Unit	W x H x D	mm	Male PT 25(1)		
Net Weight	Unit		kg	1,239 x 834 x 330		
Sound Pressure Level (at 1m)	Heating	Rated	dBA	91		
Sound power level	Heating	Rated	dBA	50		
Power supply	Phase / Frequency / Voltage	Ø / Hz / V		1 / 50 / 220-240		
	Maximum Running Current	A		23		

- Note
 1. A+++ label is available from 26, Sep. 2019 and should be considered as A++ label until that time.
 2. Due to our policy of innovation some specifications may be changed without notification.
 3. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
 4. Sound pressure level is measured on the rated condition in the anechoic rooms by ISO 3745 standard. Sound power level is measured on the rated condition in the reverberation rooms by ISO 3741 standard. Therefore, these values can be increased owing to ambient conditions during operation.
 5. Performances are accordance with EN14511. 6. This product contains Fluorinated greenhouse gases. 7. LWT : Leaving Water Temperature, OAT : Outdoor Air Temperature

HM121M.U33 / HM141M.U33 / HM161M.U33
HM123M.U33 / HM143M.U33 / HM163M.U33

		DESCRIPTION	UNIT	HM121M.U33	HM141M.U33	HM161M.U33	HM123M.U33	HM143M.U33	HM163M.U33
		SEASONAL ENERGY							
Space Heating (According to EN14825)	Average Climate water outlet 35°C	SCOP		4.45	4.45	4.45	4.45	4.45	4.45
	Rated heat output (Prated)		kWh	10	11	10	11	11	11
	Seasonal space heating efficiency (ηs) %			175	175	175	175	175	175
	Seasonal space heating eff. Class			A+++	A+++	A+++	A+++	A+++	A+++
	Annual energy consumption		kWh	4,642	4,875	5,103	4,642	4,875	5,103
	SCOP			3.18	3.18	3.18	3.18	3.18	3.18
	Rated heat output (Prated)		kWh	12	12	12	12	12	12
	Seasonal space heating efficiency (ηs) %			124	124	124	124	124	124
	Seasonal space heating eff. Class			A+	A+	A+	A+	A+	A+
	Annual energy consumption		kWh	7,795	7,795	7,795	7,795	7,795	7,795
		PRODUCT SPECIFICATION							
Nominal Capacity	OAT	LWT							
	7°C	35°C	kW	12.00	14.00	16.00	12.00	14.00	16.00
	Heating	7°C	55°C	12.00	12.00	12.00	12.00	12.00	12.00
	2°C	35°C	kW	11.00	12.00	13.80	11.00	12.00	13.80
Nominal Power Input	Cooling	35°C	18°C	kW	14.00	14.00	16.00	14.00	16.00
	35°C	7°C	kW	14.00	14.00	16.00	14.00	16.00	16.00
	Heating	7°C	35°C	kW	2.61	3.11	4.00	2.61	3.11
	2°C	55°C	kW	4.29	4.29	4.29	4.29	4.29	4.29
COP	Cooling	35°C	18°C	kW	3.04	3.26	4.00	3.04	3.26
	35°C	7°C	kW	5.19	5.38	6.40	5.19	5.38	6.40
	Heating	7°C	35°C	W/W	4.60	4.50	4.00	4.60	4.50
	2°C	55°C	W/W	2.80	2.80	2.80	2.80	2.80	2.80
EER	Cooling	35°C	18°C	W/W	4.60	4.30	4.00	4.60	4.30
	35°C	7°C	W/W	2.70	2.60	2.50	2.70	2.60	2.50
	Heating	Water Side Min - Max (outlet)	°C	15 ~ 65			15 ~ 65		
	Air Side Min-Max	°C		-25 ~ 35			-25 ~ 35		
Operation range	Cooling	Water Side Min - Max (outlet)	°C	5 ~ 27			5 ~ 27		
	Air Side Min-Max	°C		5 ~ 48			5 ~ 48		
	Domestic Hot Water	Water Side Min - Max (outlet)	°C	15 ~ 80			15 ~ 80		
	Type			R32			R32		
Refrigerant	GWP (Global Warming Potential)			675			675		
	Charge	kg	tCO ₂ eq	1.4			2.4		
Compressor	Quantity			0.95			1.62		
	Type			1			1		
Water Flow Rate	Min.	LPM		Scroll			Scroll		
Piping Connections	Water Circuit	Inlet	mm(in)				20		
	Circuit	Outlet	mm(in)	Male PT 25(1)			Male PT 25(1)		
Dimensions	Unit	W x H x D	mm	Male PT 25(1)			1,239 x 1,380 x 330		
Net Weight	Unit		kg	91			125		
Sound Pressure Level (at 1m)	Heating	Rated	dBA	50			52		
Sound power level	Heating	Rated	dBA	60			63		
Power supply	Phase / Frequency / Voltage	Ø / Hz / V		1 / 50 / 220-240			1 / 50 / 220-240		
	Maximum Running Current	A		23			35		

- Note
 1. Due to our policy of innovation some specifications

SPLIT




THERMA V KEY FEATURES

SPLIT


BLDC (Brushless Direct Current Motor) Compressor

THERMA V is equipped with a BLDC compressor that uses a strong neodymium magnet. The compressor has improved efficiency compared to standard AC inverter product and it is optimized for seasonal efficiency.

- Minimized oil circulation
- High efficiency motor
- Optimized compression
- Optimized vibration, noise
- High reliability



Power input saving
by High efficient A-Class water pump





* Condition : 12 hours x 30 days x 5 month (estimated value)

SPLIT

Reliability at Low Temperature

Pressure control reinforces heating performance by operating in stable condition at low ambient temperature.



Emergency Operation

Even in case of sudden product error, THERMA V ensures stable heating operation by applying 2 steps of emergency control.



Easy Commissioning

• Pre-Installation Setting

- Based on installation site information, installers can prepare presetting with LG Heating Configurator and save data into memory card from office.
- At the site, then installers can simply insert memory card at the back of remote controller to activate configuration data.



Easy & Quick Maintenance

• Data Logging

- The remote controller can store up to 50 history items, making it possible to easily identify cause of malfunctioning or faults using the history data and prompt solution



- Date and time
- Operation mode (Cooling, Heating, Hot Water, Auto)
- Setting temperature
- Inlet / Outlet temperature
- Room air temperature
- DHW (Operation status / Target temperature / current temperature)
- ODU operation status
- Error status & code

HN1616.NK3 / HU051.U43, HU071.U43, HU091.U43



LG participates in the ECP programme for EUROVENT EURO-HP program.
Check ongoing validity of certification :
www.eurovent-certification.com



	DESCRIPTION		ODU	HU051.U43	HU071.U43	HU091.U43
	IDU			HU1616.NK3		
SEASONAL ENERGY						
Space Heating (According to EN14825)	Average Climate water outlet 35°C	SCOP Rated heat output (Prated) Seasonal space heating efficiency (η_s) %	4.52 6 178	4.45 6 175	4.34 7 171	
	Annual energy consumption kWh	A+++ 2,512	2,783	3,093		
	Average Climate water outlet 55°C	SCOP Rated heat output (Prated) Seasonal space heating efficiency (η_s) %	3.23 6 126	3.23 6 126	3.23 6 126	
	Annual energy consumption kWh	A++ 3,581	3,581	3,581		

	PRODUCT SPECIFICATION		OAT	LWT							
	Nominal Capacity	Heating	7°C 2°C -2°C -7°C	35°C 35°C 50°C 35°C	kW	5.00 4.30 6.24 4.23	7.00 5.97 6.68 5.88	9.00 7.30 7.08 7.53			
Nominal Power Input	Cooling	35°C 7°C -2°C -7°C	18°C 35°C 35°C 35°C	kW	5.00 1.01 3.52 2.78	7.00 1.59 1.70 2.14	9.00 2.05 2.09 2.74				
COP	Heating	2°C -2°C -7°C	35°C 50°C 35°C	W/W	4.93 1.95 2.78	4.80 2.00 2.75	4.40 2.00 2.75				
EER	Cooling	35°C Heating	35°C Min. ~ Max.	W/W	4.60	4.50	3.80				
Operation Range (Outdoor Air)	Heating	35°C Cooling	18°C Min. ~ Max.	°C DB °C DB	-20 ~ 35						
GWP (Global Warming Potential)	Type	-	R410A	2,088							
Refrigerant	Charge	kg	tCO ₂ eq	1.8							
	Chargeless Pipe Length	m		3.76							
	Additional Charging Volume	g/m		7.5							
Compressor	Quantity	EA		40							
Refrigerant Piping Connection	Type	Rotary		1							
	Outer Dia.	Liquid	mm(in)	Ø 9.52 (3/8)							
		Gas	mm(in)	Ø 15.88 (5/8)							
	Length	Min.	m	3							
	Max.	m		7.5							
	Level Difference (ODU - IDU)	Max.	m	50							
Dimensions	Unit	W x H x D	mm	950 x 834 x 330							
Weight	Unit	kg		59							
Sound Power Level	Heating	Rated	dB(A)	65							
Power Supply	Phase / Frequency / Voltage	Ø / Hz / V		1 / 50 / 220-240							
	Maximum Running Current	A		19.0							
	Recommended Circuit Breaker	A		30							

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.

3. Sound Level Values are measured at Anechoic chamber. Therefore, these values depend on the ambient conditions and values are normally higher in actual operation.

4. Performances are based on that Interconnected Pipe Length is standard length and difference of Elevation (Outdoor ~ Indoor Unit) is Zero.

5. This product contains Fluorinated greenhouse gases. 6. LWT : Leaving Water Temperature, OAT : Outdoor Air Temperature

	DESCRIPTION		UNIT	HN1616.NK3
	Operation Range (Leaving Water)	Heating	°C	15 ~ 57
	Cooling	For Fan Coil Unit For under floor	°C	6 ~ 30 16 ~ 30
	Power supply	Phase / Frequency / Voltage	Ø / Hz / V	1 / 50 / 220-240
Electric Heater	Number of Heating Coil	EA		2
	Capacity	kW		3 + 3
	Maximum Running Current	A		32
Water Flow Rate	Min.	LPM		15
Piping Connections	Water Circuit	Inlet Outlet	mm(in)	Male PT 25(1) Male PT 25(1)
	Refrigerant Circuit	Gas Liquid	mm(in)	Ø 15.88 (5/8) Ø 9.52 (3/8)
Dimensions	Body	W x H x D	mm	490 x 850 x 315
Net Weight	Body	kg		43
Sound power level	Heating	Rated	dBA	44

HN1616.NK3 / HU121.U33, HU141.U33, HU161.U33
HN1639.NK3 / HU123.U33, HU143.U33, HU163.U33

LG participates in the ECP programme for EUROVENT EURO-HP program.
Check ongoing validity of certification :
www.eurovent-certification.com



	DESCRIPTION		ODU	HU121.U33	HU141.U33	HU161.U33	HU123.U33	HU143.U33	HU163.U33
	IDU			HU1616.NK3	HU1616.NK3	HU1616.NK3	HU1639.NK3	HU1639.NK3	HU1639.NK3
SEASONAL ENERGY									
Space Heating (According to EN14825)	Average Climate water outlet 35°C	SCOP Rated heat output (Prated) Seasonal space heating efficiency (η_s) %	4.45 9 175	4.45 10 169	4.30 10 175	4.45 9 175	4.45 10 169	4.45 10 175	4.30 10 169
	Annual energy consumption kWh	A+++ 4,177	4,408	4,802	4,177	4,408	4,802	4,802	4,802
	Average Climate water outlet 55°C	SCOP Rated heat output (Prated) Seasonal space heating efficiency (η_s) %	3.32 10 130						
	Annual energy consumption kWh	A++ 6,154	6,154	6,154	6,154	6,154	6,154	6,154	6,154

	PRODUCT SPECIFICATION		OAT	LWT						
	Nominal Capacity	Heating	7°C 2°C -2°C -7°C	35°C 35°C 50°C 35°C	kW	12.00 10.33 11.89 11.00	14.00 10.83 11.89 12.50	12.00 10.33 11.89 12.50	14.00 11.95 11.89 13.50	16.00 11.95 11.89 13.50
Nominal Power Input	Cooling	35°C 7°C -2°C -7°C	18°C 35°C 35°C 35°C	kW	2.64 2.93 5.25 3.14	3.17 3.09 5.25 4.35	3.76 3.41 5.25 3.73	3.17 3.41 5.25 4.35	3.76 3.41 5.25 4.35	3.76 3.41 5.25 4.35
COP	Heating	2°C -2°C -7°C	50°C 35°C 35°C	W/W	2.60 4.55 4.41	3.08 4.55 4.41	3.60 4.55 4.41	3.60 4.55 4.41		

DHW TANK INTEGRATED



THERMA V KEY FEATURES

SPLIT DHW TANK INTEGRATED


Save space & Save time

Compared with conventional system, easy & quick installation is possible and smaller spaces are required for installation.

Conventional	New (DHW tank integrated type)
 <ul style="list-style-type: none"> Buffer Tank AWHP Indoor Unit Water Tank Water Pipe 	<ul style="list-style-type: none"> - Enough rooms for product installation - Need to secure the space for water tank - More water piping work & More installation time <p>All in one Small space for product installation</p>

2nd Heating Circuit



Possible heating individually through separate heating circuits with a controller and a mixing valve.



With the circuit extension module, **max 4 heating circuits** to control individually (Optional)

Controller for convenient control

Easy & convenient setting room temperature!



SPLIT DHW TANK INTEGRATED



HN1616T.NBO

HN1616T.NBO / HU091.U43, HU121.U33, HU141.U33, HU161.U33,
HU123.U33, HU143.U33, HU163.U33

DESCRIPTION		UNIT	HN1616T.NBO		
PRODUCT SPECIFICATION					
Operation Range (Leaving Water)	Heating	°C	25 ~ 58		
	Cooling	°C	7 ~ 25		
	Domestic Hot Water	°C	10 ~ 60		
	Power supply	Phase / Frequency / Voltage	Ø / Hz / V	1 / 50 / 220-240	1 / 50 / 220-240
	Number of Heating Coil	EA		3 / 50 / 380-415	1
Electric Heater	Capacity	kW	2	2	2
	Maximum Running Current	A	2 + 2	2 + 2 + 2	11.1
	Recommended Circuit Breaker	A	16	20	11.1
Water Flow Rate	Min.	LPM	13		
	Water Circuit	Inlet	mm(in)	Male PT 25(1)	
		Outlet	mm(in)	Male PT 25(1)	
Piping Connections	Refrigerant Circuit	Gas	mm(in)	Ø 15.88 (5/8)	
		Liquid	mm(in)	Ø 9.52 (3/8)	
	DHW Tank Water Circuit	Cold Inlet	mm(in)	Male PT 19.05 (3/4)	
		Hot Outlet	mm(in)	Male PT 25 (1)	
		Recirculation	mm(in)	Male PT 19.05 (3/4)	
	Type		Hydro module with integrated boiler		
	Material	-	Enamelled steel		
DHW Tank	Water Volume	Rated	ℓ	200	
	Internal Thermal Protect limit		°C	95	
	Maximum water pressure limit		bar	10	
	Material	-		Polyurethane foam	
	Insulation	Thickness		50	
	Heat loss (for 24hr)	kWh		1.67	
Buffer Tank	Water Volume	Rated	ℓ	40	
	Material	-		Steel powder coated	
	Insulation Material	-		Closed cell foamed rubber	
Dimensions	Body	W x H x D	mm	607 x 2,079 x 725	
Net Weight	Body		kg	228	
Sound power level	Heating	Rated	dBA	36	

Notes

1. Indoor unit is include integrated electrical heater

SPLIT (OUTDOOR)			ODU	HU091.U43	HU121.U33	HU141.U33	HU161.U33	HU123.U33	HU143.U33	HU163.U33	
PRODUCT SPECIFICATION			IDU	HN1616T.NBO							
Nominal Capacity	Heating	OAT	LWT								
	Cooling	7°C	35°C	kW	9.0	12.0	14.0	16.0	12.0	14.0	
Nominal Power Input	Heating	35°C	18°C	kW	9.0	10.4	11.0	12.0	10.4	11.0	
	Cooling	7°C	35°C	kW	2.23	2.78	3.43	4.18	2.78	3.43	
COP	Heating	35°C	18°C	kW/W	2.88	3.30	3.53	4.00	3.30	3.53	
EER	Cooling	35°C	18°C	W/W	4.04	4.32	4.08	3.83	4.32	4.08	
Operation Range (Outdoor Air)	Heating	Min. ~ Max.	°C DB								
	Cooling	Min. ~ Max.	°C DB								
	Type	-									
Refrigerant	GWP (Global Warming Potential)	-									
	Charge	kg	1.8	2.3	2.3	2.3	2.3	2.3	2.3	2.3	
	Chargeless Pipe Length	tCO ₂ eq	3.76	4.8	4.8	4.8	4.8	4.8	4.8	4.8	
Compressor	Additional Charging Volume	m									
	Quantity	g/m									
	Type	EA									
Refrigerant Piping Connection	Outer Dia.	Liquid	mm(in)								
		Gas	mm(in)								
	Length	Min.	m								
		Standard	m								
	Level Difference	Max.	m								
Dimensions	Unit	W x H x D	mm	950x84x330	950x1,380x330	950x1,380x330	950x1,380x330	950x1,380x330	950x1,380x330	950x1,380x330	
Weight	Unit	kg		59	94	94	94	94	94	94	
Sound Power Level	Heating	Rated	dB(A)	65	66	66	66	66	66	66	
	Phase / Frequency / Voltage	Ø / Hz / V	1 / 50 / 220-240	1 / 50 / 220-240	1 / 50 / 220-240	1 / 50 / 220-240	1 / 50 / 220-240	3 / 50 / 380-415	3 / 50 / 380-415	3 / 50 / 380-415	
Power Supply	Maximum Running Current	A		19	25	25	25	16.1	16.1	16.1	
	Recommended Circuit Breaker	A		30	40	40	40	20	20	20	
Modbus Converter (*Required purchase separately)	Type	-						Gateway PI485			
	Model	-						PP485B00K			
SEASONAL ENERGY											
Space heating	Average climate water outlet 55°C (A++ to G Scale)	General	SCOP	2.88	3	3	3	3	3	3	
			Ƞs (Seasonal space heating % efficiency)	112	117	117	117	117	117	117	
			Seasonal space heating eff. Class	A+							
	Average climate water outlet 35°C (A++ to G Scale)	General	SCOP	4.04	4.2	4.15	4.15	4.2	4.15	4.15	
			Ƞs (Seasonal space heating % efficiency)	159	165	163	163	165	163	163	
			Seasonal space heating eff. Class	A++							
Domestic Hot Water Heating	General	Declared load profile	XL	XL	XL	XL	XL	XL	XL	XL	
	Average climate (A to G Scale)	Ƞwh (water heating efficiency) %	98	89	89	89	89	89	89	89	89
		Water heating energy efficiency class	A	A	A	A	A	A	A	A	

Note

1. Due to our policy of innovation some specifications may be changed without notification.
2. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
3. Sound Level Values are measured at Anechoic chamber. Therefore, these values depend on the ambient conditions and values are normally higher in actual operation.
4. Performances are based on that Interconnected Pipe Length is standard length and difference of Elevation (Outdoor ~ Indoor Unit) is Zero.
5. This product contains Fluorinated greenhouse gases.
6. LWT : Leaving Water Temperature, OAT : Outdoor Air Temperature

DHW TANK INTEGRATED





THERMA V KEY FEATURES

HIGH TEMPERATURE

Quick Defrosting

Through R134A compressor controlling technology, necessary time for defrost operation has been minimized effectively. (LG Patent)


As compared to normal reverse cycle defrost, 25% reduction in defrost time, and 10% increase of integrated heating capacity is achieved using hybrid defrosting.




Higher Energy Efficiency

By applying efficient compressor and optimally designed structure, the more energy saving, the lower operating cost make sooner return on initial investment.

Heating COP at -7°C Outdoor Temperature




Heating COP at -7°C Outdoor Temperature



Low Noise Level


Through cutting edge technology for DC inverter compressor, operating noise level of indoor & outdoor unit has been reduced and serves more comfort.



HIGH TEMPERATURE


Enhanced Efficiency & Performance

THERMA V high temp. can produce Max. 80°C hot water with high efficiency (Max. COP 4.06 at 24°C ODT & 40/45 EWT/LWT) through cascade 2 stage compression technology.




Cascade 2 Stage Compression Technology

Max. 80°C hot water can be generated through Cascade R410A to R134a BLDC compressor technology and is applicable for existing old boiler heating system which demands hot water supply.



Low Maximum Current Level

LG High Temperature THERMA V can be easily installed without any incurring any additional costs to the electric connections.



HIGH TEMPERATURE



HN1610H.NK2
HU161H.U32



LG participates in the ECP programme for EUROVENT EURO-HP program.
Check ongoing validity of certification :
www.eurovent-certification.com



HEATING

Product Specification

	DESCRIPTION	OUTDOOR UNIT	HU161H.U32
		INDOOR UNIT	HN1610H.NK2
Nominal Capacity	Heating OAT 7°C LWT 65°C kW		16.00
Nominal Power Input	Heating 7°C 65°C kW		6.13
COP	Heating 7°C 65°C W/W		2.61
Operation Range (Outdoor Air)	Heating Min. ~ Max. °C DB Cooling Min. ~ Max. °C DB		-20 ~ 35 N/A
Type	-		R410A
GWP (Global Warming Potential)	-		2,088
Refrigerant	Charge kg tCO ₂ eq		3.5
Compressor	Chargeless Pipe Length m Additional Charging Volume g/m Quantity EA Type -		7.3 10 60 1
Refrigerant Piping Connection	Outer Dia. Liquid mm(in) Gas mm(in) Min. m Length Standard m Max. m		Ø 9.52 (3/8) Ø 15.88 (5/8) 5 7.5 50
Dimensions	Level Difference (ODU ~ IDU) Max. m		30
Weight	Unit W x H x D mm		950 x 1,380 x 330
Sound Power Level	Unit kg		105
Power Supply	Heating Rated dB(A) Phase / Frequency / Voltage Φ / Hz / V Maximum Running Current A Recommended Circuit Breaker A		5 1 / 50 / 220-240 19 25

Note :

1. Capacities and power inputs are based on the following conditions:
 - Piping Length : Interconnected Pipe Length = 7.5m
 - Difference Limit of Elevation (Outdoor ~ Indoor Unit) is Zero.
2. Wiring cable size must comply with the applicable local and national codes.

3. Due to our policy of innovation some specifications may be changed without notification.

4. Sound Level Values are measured at Anechoic chamber. Therefore, these values can be increased owing to ambient conditions during operation.

5. This product contains Fluorinated Greenhouse Gases.

6. LWT : Leaving Water Temperature, OAT : Outdoor Air Temperature

Indoor Unit Specification

	DESCRIPTION	UNIT	HN1610H.NK2
Operation Range(Leaving Water)	Heating °C		25 ~ 80
Refrigerant	Type R134a		R134a
	GWP (Global Warming Potential) -		1,430
	Charge kg tCO ₂ eq		2.3
Compressor	Quantity EA		3.3
Water Flow Rate	Min. LPM		1
Piping Connections	Water Circuit Inlet mm(in) Refrigerant Circuit Outlet mm(in) Gas Liquid mm(in)		Rotary 15
Dimensions	Body W x H x D mm		Male PT 25(1)
Net Weight	Body kg		Male PT 25(1)
Sound Pressure Level	Heating Rated dB(A) Phase / Frequency / Voltage Φ / Hz / V		Ø 15.88 (5/8)
Power Supply	Maximum Running Current A Recommended Circuit Breaker A		Ø 9.52 (3/8)

Note :

1. Wiring cable size must comply with the applicable local and national codes.
2. Due to our policy of innovation some specifications may be changed without notification.

3. Sound Level Values are measured at Anechoic chamber. Therefore, these values can be increased owing to ambient conditions during operation.

4. This product contains Fluorinated Greenhouse Gases (R134a).

ACCESSORIES



THERMA V SPECIFICATION

ELECTRIC BACK UP HEATER

HA031M.E1
HA061M.E1



HEATING

	Electrical Specification	HM031M.E1	HA061M.E1
Backup Heater	Type	Sheath	Sheath
	Number of Heating Coil	EA	1
	Capacity Combination	kW	3.0
	Operation		Automatic
	Heating Steps	Step	1
	Power Supply	V, Ø, Hz	220-240, 1, 50
Wiring Connections	Maximum Current	A	12.0
	Power Cable (included Earth, H07RN-F)	No. x mm ²	3 x 1.5
	Communication Cable (H07RN-F)	No. x mm ²	4 x 0.75

Note

1. Due to our policy of innovation some specifications may be changed without notification.
2. Wiring cable size must comply with the applicable local and national codes.

DOMESTIC HOT WATER TANK

OSHW-200F
OSHW-300F
OSHW-500F
OSHW-300FD



Domestic Hot Water Tank – Double Coil

DOMESTIC HOT WATER TANK		OSHW-200F	OSHW-300F	OSHW-500F	OSHW-300FD
PRODUCT SPECIFICATION					
General Characteristics	Water Volume	L	200	300	500
	Diameter	mm	640	640	640
	Height	mm	1,350	1,850	1,900
	Empty Weight	kg	61	100	146
	Tank Materials		STS:F18	STS:F18	STS:F18
Specification of Electric Back-up	Color		Grey	Grey	Grey
	Additional Electric Heater	W	2,400	2,400	2,400
	Power Supply	Φ / V / Hz	1 / 230 / 50(60)	1 / 230 / 50(60)	1 / 230 / 50(60)
Specification of Heat Exchanger	Adjustable Thermostat	°C	0 - 90	0 - 90	0 - 90
	Exchanger Type		Single	Single	Single
	Material Exchanger		STS:F18	STS:F18	STS:F18
	Maximum Water Temp	°C	90	90	90
Water Connections	Coil Surface	m ²	2.3	3.1	4.8
	Heat Pump Inlet	inch	1 BSP Female	1 BSP Female	1 1/4 BSP Female
					3/4 BSP Female (Upper Coil)
	Heat Pump Outlet	inch	1 BSP Female	1 BSP Female	1 1/4 BSP Female
					3/4 BSP Female (Upper Coil)
	Solar Inlet	inch	-	-	-
	Solar Outlet	inch	-	-	-
Energy Efficiency Class	City Water Inlet	inch	3/4 BSP Male	3/4 BSP Male	1 BSP Male
	Hot Water Outlet	inch	3/4 BSP Female	1 BSP Female	1 BSP Female
			B	B	B
Standing Heat Loss		W	61	70	83
MANDATORY ACCESSORIES					
Domestic Hot Water Tank Installation Kit		PHLTA/PHLTB/PHLTC	PHLTA/PHLTB/PHLTC	PHLTA/PHLTB/PHLTC	PHLTA/PHLTB/PHLTC
OPTIONAL ACCESSORIES					
Mixing Valve (3/4" dn20)		OSHA-MV	OSHA-MV	OSHA-MV	OSHA-MV
Mixing Valve (1"dn25)		OSHA-MV1	OSHA-MV1	OSHA-MV1	OSHA-MV1
3-Way Valve		OSHA-3V	OSHA-3V	OSHA-3V	OSHA-3V

LG Wi-Fi MODEM

Control LG THERMA V via using the internet devices as Android or iOS bases smartphones

PWFMD200



Features


- Access LG THERMA V anytime and from anywhere with Wi-Fi equipped device
- LG's exclusive Home Appliances control app(SmartThinQ) is available
- Simple operation for various functions
 - On/Off
 - Operation Mode
 - Current/Set Temperature

MODEL NAME	PWFMD200
Size (W x H x D, mm)	48 x 68 x 14
Interfaceable Products	THERMA V Split Indoor unit
Connection Type	Indoor unit 1:1
Communication Frequency	2.4 GHz
Wireless Standards	IEEE 802.11b/g/n
Mobile Application	LG Smart ThinQ (Android v4.1(Jellybean) or higher, iPhone iOS 9.0 or higher)
Optional Extension Cable	PWYREW000 (10m extension)

- * Functionality may be different according to each IDU model (Monobloc and Split only available)
- * User interface of application shall be revised for its design and contents improvement
- * Application is optimized for smartphone use, so it may not be well functioning with tablet devices
- 1) Vane Control may not be possible according to the type of Indoor unit
- 2) For the compatibility with Indoor unit, please contact regional office



Overview



* Search "LG Smart ThinQ" on Google market or Appstore then download the app.
* Internet service with Wi-Fi connection has to be available

ACCESSORIES

Accessories Provided by LG

ACCESSORY	FEATURE
Domestic Hot Water Tank	 <p>OSHW-200F 200 LITRES OSHW-300F 300 LITRES OSHW-500F 500 LITRES</p> <p>Single Coil</p>
	 <p>OSHW-300FD 300 LITRES</p> <p>Double Coil</p>
	 <p>OSHA-3V 3-Way Valve OSHA-MV Mixing Valve</p>
Domestic Hot Water Tank Kit	<ul style="list-style-type: none"> • PHLTA (1Ø, Split) • PHLTC (3Ø, Split) • PHLTB (Monobloc) <p>Features Easy to install the domestic hot water for monobloc. There is a MCCB to protect the product. Dimension (mm) (H x W x D) : 250 x 170 x 110 Weight (kg) : 2.1</p> <p>To extend THERMA V functionality in generating domestic hot water.</p>   <p>* PHLTA, PHLTC is required only when you want to use the electric heater function at the sanitary tank. If not, it's not necessary. THERMA V indoor unit it self already has electric heater(back up heating) function.</p> <p>* The sensor (PHRSTAO) can be purchased separately in case of using other brand's Domestic tank.</p>
Remote Temperature Sensor	<ul style="list-style-type: none"> • PQRSTAO <p>Features It can help to detect the exact room temperature. Applied to ceiling cassette, ceiling concealed duct, AWHP and Hydro Kit.</p> <p>Parts Included Remote temperature sensor / Extension cable (15m) / Manual</p> 
Solar Thermal Kit	<ul style="list-style-type: none"> • PHLLA <p>Features To interface solar-thermal system with THERMA V and double coil Domestic tank. Installed at the water pipe, between Domestic tank and solar-thermal system. Dimension (mm) (H x W x D) : 110 x 55 x 22</p> 
Dry Contact	<ul style="list-style-type: none"> • PDRYCB000 <p>Features For connection with boiler (Bivalent scene)</p> 
Drain Pan	<ul style="list-style-type: none"> • PHDPB <p>Features Collects condensate water (When dropping to the base is not possible) and drains the water to a pipe</p> 

Recommended Optional Accessories

NO.	ACCESSORY	PICTURE	PURPOSE	SPECIFICATION
1	Domestic Hot Water Tank		Store and provide hot water for sanitation	Volume : 200 - 400 l Enameld or stainless-steel tank / Insulating foam (e.g. PUR - polyurethane) heat-exchanger surface $\geq 3\text{ m}^2$
2	3-Way-Valve		Switch between heating and domestic hot water circuit	230V AC SPDT (Single Pole Double Throw) / opening time 30 - 90 sec / final position switch Internal leakage rate < 0,1%
3	Electrical Tank Heater		Supports heating of domestic hot water, when heat pump is blocked or capacity is limited	2 - 6 kW Connector dimension suitable for DHW tank
4	Buffer Tank		Prevents cycling, when water volume is low and / or heating demand is low; secures enough heat for defrosting cycle	Insulating foam (e.g. PUR - polyurethane) Volume : 100 - 200 l (Installation in series with heat pump) 500 ~ 1,000 l (Installation in parallel with heat pump)
5	Bypass Valve		Ensures minimum water flow rate, when flow through heating circuits is limited due to closed valves	Dimensioning according manufacturer adjustable opening pressure
6	2-Way-Valve		Blocks heating circuits, that are not suitable for cooling during cooling operation	230V AC NO or NC type final position switch
7	Expansion Vessel		Absorption of pressure differences in the heating circuits due to temperature increase / decrease of the water	Dimensioning on-site required
8	Strainer		Protects plate-heat-exchanger from blocking particles	1inch / 25.4mm, Mesh size ~ 1 x 1mm for HM03M1.U42 only (other models are included)
9	Heating Cable		Prevents the condensate pan and the drainage pipe from icing	Thermostatic control depending on outdoor temperature All models do have electric heating cable for prevent frost from condensing water at the condensing pan except 3kW capacity.
10	Antifreeze		Prevents the heating water from freezing, when heat pump is out of order	Monoethyleneglycole Concentration according to lowest possible outdoor temperature
11	Noise Damper		Prevents that structure-born noise is transported via the water piping	EPDM; Operating temperature according climate region (at least -10 ~ + 90°C)
12	Anti-Noise Sockets		Prevents that structure-born noise is transported to the base or to the brackets	Dimensioning on-site required
13	Thermostat		When thermostatic room temperature control is preferred by costumer	230V AC When heat pumps operates in heating and cooling mode : thermostat with mode selection
14	Refrigerant Tubes		Pre-fabricated double-pipe to connect split indoor and outdoor unit	Diameter : Please refer to Specification
15	Water Tubes		Pre-fabricated double-pipe to connect monobloc outdoor unit with heating system	When heat pump is used for cooling : diffusion-resistant tubes
16	Bushing Sleeve		Protecting the building against pressing water coming through the duct of the heating tubes	Dimensioning on-site required
17	Insulation Material		Mandatory when heat pump is used for cooling; prevents condensate water on cold pipes and assemblies	Diffusion-resistant

LG LATS THERMA V

THERMA V Selection Program

LATS THERMA V simulates quick and easy result of THERMA V's economic benefits. By specifying a number of parameters, this program shows annual energy cost compared with conventional heating system and CO₂ annual amount, monthly energy amount and cost, total amount of thermal energy in kWh as the outside temperature.

