QUOTE	ORDER
-------	-------



QUOTES - T: 01933 685747 F: 01933 678872

ALUMINIUM A	ALUK I	F82 BI-FOLDING D	E: quot ORDERS - F: 0193	ies@emplas.co.uk 33 678635 ers@emplas.co.uk
Company Name:		Contact Name:	Date Ordered:	
, , , , , , , , , , , , , , , , , , , ,		Email address:	Delivery Date:	
		Phone Number:	Reference:	Reference:
			PLEASE MANUFACTURE THIS ORDEF WITH YOUR TERMS AND CO	
OPDED FORM (VIEWE	D EDOM OI	ITCIDE)	***PLEASE FILL OUT ALL FIEL	DS***
ORDER FORM (VIEWE	ow 'E'Toughoned A	200 (4/16/16 0)	Give as much information as pos ed to comply with SBD, Clear Low'E'Toughened	
28mm Double Glazed Units v	with Black Warm Ed	ge Spacer Bar 28mm Argon Filled Double Glazed	d Units with Black Warm Edge Spacer Bar	Unglazed
Folding Options	Qty:	Location:		
N		Width:	82 18 46 18	20mm add on
U 110		(inc add-ons if required)	U61631 Profile length (	(m) 6.5
220*	211	Height:  (inc cill and add-ons if required)		
<b>W</b> 220	ΨŲ ···	Door Type: (Viewed Outside)	U61632	
330	321		Profile langth (	m) 6.5
444	Ψν.	Leafs Fold Left Fold Rig		Head detail
440*	431	Open In Open O		showing 40mm extender. (needed
	W.	Standard Door Colour:	000	for trickle vents)
422*		Grey 7016M White 9910H	dG	
MYN	MM1.	Black Grey 7016M (OUT) White 9910HG (IN)	82	
550		Deep Black 9005M (out) White HG 9910	(in)	
<b>TTT</b> 532		Special Colours: Extra Costs App	ply	47mm Standard
WW "		Single RAL:		threshold detail showing optional
651		Dual RAL: In: Out:	11-	external cill. (Open out
		Traffic and 'Pop Out'T Hand (Has to be same colour internally / Externally)		configuration)
660*		White Black Silver	121.5	
MMM1	MMM	Hinge Colour	29.5	
761	WWW	Black (to match up with gasket)  To Match Handle Colour (White, Black, S	Tihor	40
Additional Comments / Diagram		as selected above)	190	25 (C)
Additional Comments / Diagram		Cill Type: None 190		, Only
		Drainage: Concealed F	Face SMALL OUTER FRAME	
		Frame Extenders:	(No Warranty, internal use only)	-2 -1
		20mm (U61631) 40mm (U616	i32)	
		TOP / BOTTOM / LEFT / RIGHT  Trickle Vents*: Yes	No J	29.5
		4000 (2500EA) Number Req		
		* Please note that a 40mm add-on must be used to	. 82	

Threshold:

STANDARD (SBD)

SMALL OUTER FRAME (No Warranty, internal use only)

\* Please Note: Styles 220 - 440 - 422 - 660 do not have a single prime door. Two leafs need to be operated together - No external handle available.