

# **ChannelPlus XL Series 2**

## **Electronic Programmers**



A range of electronic programmers that offer up to four independent channels and feature a large, easily read display and simple menu driven programming. Three and four channel models are made for multiple zone control with single and two channel models used with combi boiler systems and stored hot water systems.

- 1, 2, 3 or 4 channels
- 24 hour or 7 day
- Back-lit LCD display
- Simplified menu driven programming
- Advance and boost on each channel
- Preset clock
- Automatic Winter / Summer time changes
- 5 year warranty











### **CHANNELPLUS H47XL**

Programmer with 7 day setting over four independent channels. Designed for use with fully pumped central heating systems using four separate zone valves in addition to many other applications.

#### **CHANNELPLUS H37XL**

Programmer with 7 day setting over three independent channels. Designed for use with fully pumped central heating systems using three separate zone valves. Meets zoning requirements of Part L1 of the Building Regulations.

#### **CHANNELPLUS H37VXL**

The same as the H<sub>37</sub>XL but with volt free contacts

#### **CHANNELPLUS H27ZXL**

Two channel with 7 day programming and independent timing of zone 1 and zone 2.

#### **CHANNELPLUS H27XL**

Two channel with 7 day programming and independent timing of heating and hot water.

#### CHANNELPLUS H21XL

Two channel with 24 hour programming and independent timing of heating and hot water.

## **CHANNELPLUS H17XL**

Single channel time switch with full 7 day programming

#### **CHANNELPLUS H11XL**

Single channel time switch with 24 hour programming.

Voltage free contacts make both the H11 and H17 units ideal for combi boilers.

## **Specification**

CONTACT RATING

CONTACT TYPE

SUPPLY POLLUTION DEGREE

CLASS A SOFTWARE ENCLOSURE PROTECTIONS DOUBLE INSULATED

OPERATING TEMPERATURE

BATTERY LIFE CASE MATERIAL

DIMENSIONS DISPLAY CLOCK

DISPLAYED TIME **ADJUSTMENTS SWITCHED TIME** ADJUSTMENTS

PROGRAMME OPTIONS

OPERATING PERIODS

PER DAY OVERRIDE (EACH CHANNEL) 1 or 2 hour boost

3 (1) Amps 230V AC Micro-disconnection

Voltage free (not 230V 50 Hz Degree 2 IP30

o° C to +40 °c

Thermoplastic flame retardant 101 x 163 x 37 mm Back lit liquid crystal 24 hour or 12 hour

AM/PM

1 minute steps

10 minute steps ON, OFF, All Day, Auto & Holiday

3 for each channel

1 or 2 hour extension to ON period Instant advance

9 pin wall fixing plate

