

asbestos essentials

Non-licensed tasks

This information will help employers and the self-employed to comply with the Control of Asbestos Regulations 2012.

It is also useful for trade union and employee safety representatives.

Asbestos fibres can cause lung cancer and lung diseases.

The sheet covers the points you need to follow to reduce exposure to an adequate level.


It can act as a risk assessment for asbestos if it matches what you plan to do.

Follow all the points, or use equally effective measures.

Only carry out this work if you are properly trained and have the right equipment.

Main points

- Asbestos fibres can kill.
- Keep exposures low using all the controls in this sheet.
- Also follow sheet a0 and equipment and method (em) sheets; see 'Essential information'.



Cleaning inside the tube fitting with a Class H vacuum cleaner

Cleaning light fittings attached to asbestos insulating board (AIB)

What this sheet covers

This sheet describes good practice when you need to clean a contaminated light fitting attached to AIB, eg to change a bulb or tube.

This sheet is NOT appropriate where the AIB is damaged, or may be damaged eg by 'rocking' the screws during cleaning. Use an HSE-licensed contractor for such work.

See sheet em4 Using a Class H vacuum cleaner for asbestos when removing a screwed in fitting, and sheet a6 for minor damage repair.

Preparing the work area

- Ensure safe access.
- Restrict access minimise the number of people present.
- Close doors. Use tape and notices to warn others.
- Ensure adequate lighting.

Equipment

- 500-gauge polythene sheeting and duct tape;
- warning tape and notices;
- Class H vacuum cleaner (BS 8520) see sheet em4;
- bucket of water and rags;
- asbestos waste container, eg labelled polythene sack; and
- clear polythene sack.

Personal protective equipment (PPE) - see sheet em6

- Provide:
 - disposable overalls fitted with a hood;
 - boots without laces (laced boots are hard to decontaminate); and
 - respiratory protective equipment.

Procedure

- Isolate the power supply use a competent electrician.
- Protect nearby surfaces from contamination. Cover with 500-gauge polythene sheeting and fix with duct tape to non-asbestos surfaces.
- Avoid removing the light fitting this may disturb the AIB.
- Clean the light fitting exterior with the Class H vacuum cleaner.
- Place easily removable sections on the polythene sheeting, for cleaning on the floor.
- Open the light fitting carefully. Insert the Class H vacuum cleaner hose, and clean inside the fitting.
- Complete the cleaning with the Class H vacuum cleaner.



MORE HELP

More asbestos pictures www.hse.gov.uk/asbestos/gallery.htm

Help to decide if work is licensed www.hse.gov.uk/asbestos/licensing/ index.htm

■ For information about health and safety, or to report inconsistencies or inaccuracies in this guidance, visit www.hse.gov.uk/. You can view HSE guidance online or order priced publications from the website. HSE priced publications are also available from bookshops.

These task (a) sheets and equipment and method (em) sheets can be downloaded free from www.hse.gov.uk/asbestos/ essentials/index.htm

See sheet a0 for details of more guidance.

ESSENTIAL INFORMATION

Download and follow these advice sheets from www.hse.gov.uk /asbestos/essentials/index.htm:

em1 What to do if you uncover or damage materials that could contain asbestos

em2 Training

em4 Using a Class H vacuum cleaner for asbestos

em6 Personal protective equipment (PPE)

em7 Using damp rags to clean surfaces of minor asbestos contamination

em8 Personal decontamination

em9 Disposal of asbestos waste

a5

Cleaning and disposal

- Clean the area with damp rags.
- Put debris, used rags, polythene sheeting and other waste in the asbestos waste container and tape it closed.
- Put the asbestos waste container in a clear polythene sack and tape it closed.
- Disposal see sheet em9.

Personal decontamination

See sheet em8.

Clearance and checking off

- Visually inspect the area to make sure that it has been cleaned properly.
- Clearance air sampling is not normally required.
- Get the premises owner, duty-holder or client to check off the job.

OTHER HAZARDS

Work at height - see www.hse.gov.uk/falls/index.htm. Take precautions to avoid falls. Must you work from a ladder? Where necessary, erect an access platform.

Electrical hazards - see www.hse.gov.uk/electricity/ index.htm. Get a competent electrician to isolate and reconnect electricity supply.

There may also be other hazards you need to consider them all.

This guidance is issued by the Health and Safety Executive. Following the guidance is not compulsory and you are free to take other action. But if you do follow the guidance you will normally be doing enough to comply with the law. Health and safety inspectors seek to secure compliance with the law and may refer to this guidance as illustrating good practice.

SAFETY CHECKLIST

- Can you avoid disturbing asbestos by doing the job in some other way?
- Do you need a licence for the work?
- Always follow all legal requirements.
- ✓ Follow the task guidance sheet.
- ✓ Use an asbestos waste container.
- Dispose at a licensed disposal site.

Caution:

- Don't sweep up dust or debris use a Class H vacuum cleaner or damp rags.
- Don't take used overalls home.
- Don't reuse disposable PPE.
- Don't smoke.
- Don't eat or drink in the work area.

This document is available at www.hse.gov.uk/asbestos/essentials/index.htm

© Crown copyright If you wish to reuse this information visit www.hse.gov.uk/copyright for details. First published as part of Asbestos Essentials Task Manual 2001.

Published by the Health and Safety Executive 04/12