

Best spill control Best value Reduced waste



Enviro Pad®

The spill pad that doesn't leak when it rains

- The original and best smart polymer spill pad
- Turns oil leaks and fuel spills into solid rubber so they can't escape
- Can be safely stored/carried upright & jet washed
- 5 sizes to minimise over-spend
- Best oil retention rates









Cost per litre of oil absorbed:

	EnviroPad®	Nearest Competitor	Nearest Competitor + Liner	
Small	£13	£53	£28	
Medium	£12	£12 £42		
Large	£12	-	-	
XL	£12	-	-	
XXL	£8	£25	£15	

Based on average prices from six leading stockists (March 2020).

Best spill control. Best value.

- EnviroPad® has the lowest cost per litre of oil absorbed. And it doesn't leak!
- Can be used inside and outdoors
- Doesn't need sidewalls or a liner
- Reduces the volume of waste you produce because contaminated water doesn't pool inside

A better fit for your plant and machinery ...and your budget!











EnviroPad® I S4 Small I Up to 4.5L I

EnviroPad® M10 Medium Up to 10.5L

EnviroPad® L20 Large Up to 20.2L

EnviroPad® XL30
Up to 30.4L

EnviroPad® XXL40 Up to 44.3L



Best spill control Best value Reduced waste

COMPLIANT



EnviroHorn Drain Filter

Prevents sediment and contaminants from your site entering the drainage system

- Oil & Sediment and Sediment only filters
- Retains up to 21kg of sediment
- Removes sediment particles down to 100µm
- Simply empty and reuse
- Oil & Sediment model retains 1L hydrocarbon sheen
- Install in 5 minutes

Oil & Sediment Dewatering Filters Stay compliant and on schedule with

our robust and reusable filters

- Save £000s no vacuum tankering required
- Different sizes and grades (see table)
- Easy to attach, use and empty
- ■Integral hydrocarbon detector indicates when oil & sediment filter needs replacing
- Reuse up to 20 times*
- Manifold for attaching up to eight filters

Product	Sediment	oil	Reuse	Size	Flow Rate	Usage
Budget Filter	20Kg	-	-	100µm	450L/Min	Single use/One day
Sediment Filter	20Kg	-	20x	150µm	450L/Min	All scenarios
Sediment XL Filter	40Kg	-	20x	150µm	800L/Min	All scenarios
Oil & Sediment Filter	20Kg	2.5L sheen	20x*	150µm	300L/Min	Hydrocarbons present
Low-gauge Oil & Sediment Filter (Camlock)	20Kg	2.5L sheen	20x*	1µm	300L/Min	Specialist areas/high pressure/hydrocarbons
Low-gauge Oil & Sediment Filter (Collar)	20Kg	2.5L sheen	20x*	1µm	300L/Min	Specialist areas/high pressure/hydrocarbons
Manifold (for 4, 6 or 8 filters)	80-320Kg	10-20L sheen	Unlimited			For when a sediment tank impractical/too expensive/overkill













Oil Retention Pillows

Quick & reactive pollution response

- Contains our proprietary polymer which turns oils and fuels into solid rubber
- Captured contaminants cannot leak out
- Remove a sheen from pooled water
- Reduce a slick to enable dewatering with filters where vacuum tankering would otherwise be required