

LEWIS BULK-BAG"

Hi-Capacity, Heavy-Duty, 3000 lbs.

Providing 47 cubic feet of secure storage for your valuable Thread Protectors.

Lewis Bulk-Bag[™] is ideal for securely storing your Drill Pipe and Casing thread protectors.



2" Rim Web Reinforcement

The bag keeps your valuable gear organized and helps to reduce thread protectors trip hazards. Also it is excellent for debris removal or storage.

For More Info call:


Toll-Free 888-398-4719



Can be moved with a forklift thus reducing lifting & back injuries.



- Heavy-Duty 22 oz. Vinyl-Coated Nylon
- 3000 lbs. Max Load Capacity
- Bag measures 44" x 44" x 42" high with a volume of 47 cubic feet or 1.74 cubic yards
- 24" high, 4" Wide High-Strength Nylon Webbing Lifting and Support Straps
- 2" Top Rim High-Strength Nylon Web Reinforcement
- Double-Layered Bottom for extra strength
- NOT for use with liquids



High-Strength 4" Wide Reinforced Lifting Straps

AWARNING

READ THIS DOCUMENT & PRODUCT WARNING BEFORE USINGINFORMATION ON USE, INSPECTION & MAINTENANCE OF LEWIS BULK-BAG

- 1. STAY CLEAR WHEN TRANSPORTING A LOADED BULK BAG.
- 2. Do not allow personnel or equipment beneath the bulk bag at any time, this is a DROP/CRUSH HAZARD.
- 3. Do not alter, cut or modify this bulk bag in any way.
- 4. Do not use the bulk bag for hoisting personnel. This is **NOT A PERSONNEL LIFT** device.
- 5. Carefully inspect the straps and nylon material before each use for any signs of wear.
- 6. Do not place sharp objects in bulk bag.
- 7. Remove the bulk bag from service immediately if it has any rips or tears or if it has torn seams.
- 8. All Support / Lifting straps must be on the outside of bag before use.
- 9. Do not expose the bulk bag to any heat source. This bag is not fire proof.
- **10.** Do not transport liquids, as the bag is not watertight, and not made for this operation.
- 11. If you do not understand how to properly use this bulk bag, ask your supervisor or

Contact Lewis Mfg. Co. (USA) Call Toll-Free 888-398-4719





Lewis Canvas Products

3601 S. Byers ◆ Oklahoma City, OK 73129 ◆ Toll-Free 888-398-4719



